Package 'BiocWorkflowTools'

November 11, 2026

Title Tools to aid the development of Bioconductor Workflow packages

Version 1.38.0

Encoding UTF-8

Description Provides functions to ease the transition between Rmarkdown and LaTeX documents when authoring a Bioconductor Workflow.

License MIT + file LICENSE

Depends R (>= 3.4)

Imports BiocStyle, bookdown, git2r, httr, knitr, rmarkdown, rstudioapi, stringr, tools, utils, usethis

NeedsCompilation no

VignetteBuilder knitr

biocViews Software, ReportWriting

RoxygenNote 7.1.0

Collate 'createBiocWorkflow.R' 'f1000_article.R' 'uploadToOverleaf.R' 'utils.R'

git_url https://git.bioconductor.org/packages/BiocWorkflowTools

git_branch RELEASE_3_23

git_last_commit 584e3e4

git_last_commit_date 2026-04-28

Repository Bioconductor 3.23

Date/Publication 2026-11-11

Author Mike Smith [aut, cre], Andrzej Oleś [aut]

Maintainer Mike Smith <grimbough@gmail.com>

Contents

createBiocWorkflow 2
f1000_article 2
uploadToOverleaf 4

Index **5**

`createBiocWorkflow` *Create a New Bioconductor Workflow Package*

Description

Uses `create_package` to set up a skeleton for a new Bioconductor workflow package.

Usage

```
createBiocWorkflow(
  path,
  description = getOption("devtools.desc"),
  rstudio = TRUE,
  open = rstudio
)
```

Arguments

`path`	location to create new package. The last component of the path will be used as the package name.
`description`	list of description values to override default values or add additional values.
`rstudio`	if `TRUE`, creates an RStudio project file.
`open`	if `TRUE`, opens the project in a new RStudio session.

Value

File path to the R Markdown vignette (invisibly).

Examples

```
createBiocWorkflow(file.path(tempdir(), "MyWorkflow"), open = FALSE)
```

`f1000_article` *F1000Research article format*

Description

Format for creating F1000Research software tool articles.

Usage

```
f1000_article(
  toc = FALSE,
  number_sections = FALSE,
  fig_width = 5.67,
  fig_height = fig_width,
  fig_align = "center",
  keep_tex = TRUE,
  citation_package = "natbib",
  md_extensions = "+link_attributes",
  pandoc_args = "--wrap=preserve",
  ...
)
```

Arguments

toc	TRUE to include a table of contents in the output
number_sections	TRUE to number section headings
fig_width	Default width (in inches) for figures
fig_height	Default height (in inches) for figures
fig_align	Default alignment of figures. Possible values are "center" (default) "left" and "right".
keep_tex	Keep the intermediate tex file used in the conversion to PDF
citation_package	The LaTeX package to process citations, natbib or biblatex. Use none if neither package is to be used.
md_extensions	Markdown extensions to be added or removed from the default definition or R Markdown. See the rmarkdown_format for additional details.
pandoc_args	Additional command line options to pass to pandoc
...	Arguments to pdf_document

Details

Creates LaTeX sources which can be submitted to F1000Research through Overleaf.

Value

R Markdown output format to pass to render

Citations

R Markdown supports automatic generation of citations. You can find more information on the markdown citation syntax in the Bibliographies and Citations article in the R Markdown online documentation.

A bibliography file can be specified using the bibliography metadata field in the document's YAML header. Metadata variables for customizing citation style include:

`biblio-style` Bibliography style (e.g. "unsrtnat", "plainnat")

`natbiboptions` Options to `natbib` LaTeX package (e.g. "number", "super", "round")

`biblatexoptions` Options to `biblatex` LaTeX package

Examples

```
## Not run:

rmarkdown::draft("MyArticle.Rmd", template="f1000_article", package="BiocWorkflowTools")

## End(Not run)
```

`uploadToOverleaf` *Upload a LaTeX project to Overleaf*

Description

Upload a LaTeX project to Overleaf

Usage

```
uploadToOverleaf(path)
```

Arguments

`path`	File path to a directory or a single zip file to be uploaded.

Value

Does not return any value. The Overleaf project page will automatically open in the default browser.

Examples

```
## Not run:
## don't run this code chunk in the example as we don't want to spam Overleaf
uploadToOverleaf(files = 'MyWorkflow', openInBrowser = TRUE)

## End(Not run)
```

Index

create_package, *2*
createBiocWorkflow, 2

f1000_article, 2

pdf_document, *3*

render, *3*
rmarkdown_format, *3*

uploadToOverleaf, 4