Package 'DEGseq'

November 11, 2026

Title Identify Differentially Expressed Genes from RNA-seq data

Version 1.66.0

Author Likun Wang <wanglk@pku.edu.cn>, Xiaowo Wang <xwwang@tsinghua.edu.cn> and Xuegong Zhang

<zhangxg@tsinghua.edu.cn>.

Description DEGseq is an R package to identify differentially expressed genes from RNA-Seq data.

Maintainer Likun Wang <wanglk@pku.edu.cn>

Depends R (>= 2.8.0), qvalue, methods

Imports graphics, grDevices, methods, stats, utils

License LGPL (>=2)

Collate AllClasses.R AllGenerics.R Bind.R methodPlots.R NormMethods.R functions.R IdentifyDiffExpGenes.R MainFunction.R MainFunctionWrap.R MainFunction2.R

LazyLoad yes

biocViews RNASeq, Preprocessing, GeneExpression, DifferentialExpression, ImmunoOncology

git_url https://git.bioconductor.org/packages/DEGseq

git_branch RELEASE_3_23

git_last_commit c6b49c5

git_last_commit_date 2026-04-28

Repository Bioconductor 3.23

Date/Publication 2026-11-11

Contents

DEGexp 2
DEGexp2 5
DEGseq 8
GeneExpExample1000 11

GeneExpExample5000 11
getGeneExp 12
kidneyChr21.bed 13
kidneyChr21Bowtie 13
liverChr21.bed 14
liverChr21Bowtie 14
readGeneExp 15
refFlatChr21 16

Index **17**

`DEGexp` *DEGexp: Identifying Differentially Expressed Genes from gene expression data*

Description

This function is used to identify differentially expressed genes when users already have the gene expression values (or the number of reads mapped to each gene).

Usage

```
DEGexp(geneExpMatrix1, geneCol1=1, expCol1=2, depth1=rep(0, length(expCol1)), groupLabel1="group1",
     geneExpMatrix2, geneCol2=1, expCol2=2, depth2=rep(0, length(expCol2)), groupLabel2="group2",
       method=c("LRT", "CTR", "FET", "MARS", "MATR", "FC"),
       pValue=1e-3, zScore=4, qValue=1e-3, foldChange=4,
     thresholdKind=1, outputDir="none", normalMethod=c("none", "loess", "median"),
     replicateExpMatrix1=NULL, geneColR1=1, expColR1=2, depthR1=rep(0, length(expColR1)), replicateLa
     replicateExpMatrix2=NULL, geneColR2=1, expColR2=2, depthR2=rep(0, length(expColR2)), replicateLa
```

Arguments

`geneExpMatrix1`	gene expression matrix for replicates of sample1 (or replicate1 when `method="CTR"`).
`geneCol1`	gene id column in geneExpMatrix1.
`expCol1`	expression value *columns* in geneExpMatrix1 for replicates of sample1 (numeric vector). *Note*: Each column corresponds to a replicate of sample1.
`depth1`	the total number of reads uniquely mapped to genome for each replicate of sample1 (numeric vector), default: take the total number of reads mapped to all annotated genes as the depth for each replicate.
`groupLabel1`	label of group1 on the plots.
`geneExpMatrix2`	gene expression matrix for replicates of sample2 (or replicate2 when `method="CTR"`).
`geneCol2`	gene id column in geneExpMatrix2.
`expCol2`	expression value *columns* in geneExpMatrix2 for replicates of sample2 (numeric vector). *Note*: Each column corresponds to a replicate of sample2.

depth2 — the total number of reads uniquely mapped to genome for each replicate of sample2 (numeric vector),
default: take the total number of reads mapped to all annotated genes as the depth for each replicate.

groupLabel2 — label of group2 on the plots.

method — method to identify differentially expressed genes. Possible methods are:

- "LRT": Likelihood Ratio Test (Marioni et al. 2008),
- "CTR": Check whether the variation between Technical Replicates can be explained by the random sampling model (Wang et al. 2009),
- "FET": Fisher's Exact Test (Joshua et al. 2009),
- "MARS": MA-plot-based method with Random Sampling model (Wang et al. 2009),
- "MATR": MA-plot-based method with Technical Replicates (Wang et al. 2009),
- "FC" : Fold-Change threshold on MA-plot.

pValue — pValue threshold (for the methods: LRT, FET, MARS, MATR).
only used when thresholdKind=1.

zScore — zScore threshold (for the methods: MARS, MATR).
only used when thresholdKind=2.

qValue — qValue threshold (for the methods: LRT, FET, MARS, MATR).
only used when thresholdKind=3 or thresholdKind=4.

thresholdKind — the kind of threshold. Possible kinds are:

- 1: pValue threshold,
- 2: zScore threshold,
- 3: qValue threshold (Benjamini et al. 1995),
- 4: qValue threshold (Storey et al. 2003),
- 5: qValue threshold (Storey et al. 2003) and Fold-Change threshold on MA-plot are both required (can be used only when method="MARS").

foldChange — fold change threshold on MA-plot (for the method: FC).

outputDir — the output directory.

normalMethod — the normalization method: "none", "loess", "median" (Yang et al. 2002).
recommend: "none".

replicateExpMatrix1 — matrix containing gene expression values for replicate batch1 (only used when method="MATR").
Note: replicate1 and replicate2 are two (groups of) technical replicates of a sample.

geneColR1 — gene id column in the expression matrix for replicate batch1 (only used when method="MATR").

expColR1 — expression value *columns* in the expression matrix for replicate batch1 (numeric vector) (only used when method="MATR").

depthR1 the total number of reads uniquely mapped to genome for each replicate in replicate batch1 (numeric vector),
default: take the total number of reads mapped to all annotated genes as the depth for each replicate (only used when method="MATR").

replicateLabel1
label of replicate batch1 on the plots (only used when method="MATR").

replicateExpMatrix2
matrix containing gene expression values for replicate batch2 (only used when method="MATR").
Note: replicate1 and replicate2 are two (groups of) technical replicates of a sample.

geneColR2 gene id column in the expression matrix for replicate batch2 (only used when method="MATR").

expColR2 expression value *columns* in the expression matrix for replicate batch2 (numeric vector) (only used when method="MATR").

depthR2 the total number of reads uniquely mapped to genome for each replicate in replicate batch2 (numeric vector),
default: take the total number of reads mapped to all annotated genes as the depth for each replicate (only used when method="MATR").

replicateLabel2
label of replicate batch2 on the plots (only used when method="MATR").

rawCount a logical value indicating the gene expression values are based on raw read counts or normalized values.

References

Benjamini,Y. and Hochberg,Y (1995). Controlling the false discovery rate: a practical and powerful approach to multiple testing. *J. R. Stat. Soc. Ser. B* **57**, 289-300.

Jiang,H. and Wong,W.H. (2008) Statistical inferences for isoform expression in RNA-seq. *Bioinformatics*, **25**, 1026-1032.

Bloom,J.S. et al. (2009) Measuring differential gene expression by short read sequencing: quantitative comparison to 2-channel gene expression microarrays. *BMC Genomics*, **10**, 221.

Marioni,J.C. et al. (2008) RNA-seq: an assessment of technical reproducibility and comparison with gene expression arrays. *Genome Res.*, **18**, 1509-1517.

Storey,J.D. and Tibshirani,R. (2003) Statistical significance for genomewide studies. *Proc. Natl. Acad. Sci.* **100**, 9440-9445.

Wang,L.K. and et al. (2010) DEGseq: an R package for identifying differentially expressed genes from RNA-seq data, *Bioinformatics* **26**, 136 - 138.

Yang,Y.H. et al. (2002) Normalization for cDNA microarray data: a robust composite method addressing single and multiple slide systematic variation. *Nucleic Acids Research*, **30**, e15.

See Also

DEGexp2, DEGseq, getGeneExp, readGeneExp, GeneExpExample1000, GeneExpExample5000.

Examples

```
## kidney: R1L1Kidney, R1L3Kidney, R1L7Kidney, R2L2Kidney, R2L6Kidney
## liver: R1L2Liver, R1L4Liver, R1L6Liver, R1L8Liver, R2L3Liver

geneExpFile <- system.file("extdata", "GeneExpExample5000.txt", package="DEGseq")
cat("geneExpFile:", geneExpFile, "\n")
outputDir <- file.path(tempdir(), "DEGexpExample")
geneExpMatrix1 <- readGeneExp(file=geneExpFile, geneCol=1, valCol=c(7,9,12,15,18))
geneExpMatrix2 <- readGeneExp(file=geneExpFile, geneCol=1, valCol=c(8,10,11,13,16))
geneExpMatrix1[30:32,]
geneExpMatrix2[30:32,]
DEGexp(geneExpMatrix1=geneExpMatrix1, geneCol1=1, expCol1=c(2,3,4,5,6), groupLabel1="kidney",
    geneExpMatrix2=geneExpMatrix2, geneCol2=1, expCol2=c(2,3,4,5,6), groupLabel2="liver",
       method="LRT", outputDir=outputDir)
cat("outputDir:", outputDir, "\n")
```

DEGexp2 *DEGexp2: Identifying Differentially Expressed Genes from gene expression data*

Description

This function is another (old) version of DEGexp. It takes the gene expression files as input instead of gene expression matrixs.

Usage

```
DEGexp2(geneExpFile1, geneCol1=1, expCol1=2, depth1=rep(0, length(expCol1)), groupLabel1="group1",
     geneExpFile2, geneCol2=1, expCol2=2, depth2=rep(0, length(expCol2)), groupLabel2="group2",
       header=TRUE, sep="", method=c("LRT", "CTR", "FET", "MARS", "MATR", "FC"),
         pValue=1e-3, zScore=4, qValue=1e-3, foldChange=4,
     thresholdKind=1, outputDir="none", normalMethod=c("none", "loess", "median"),
     replicate1="none", geneColR1=1, expColR1=2, depthR1=rep(0, length(expColR1)), replicateLabel1="r
     replicate2="none", geneColR2=1, expColR2=2, depthR2=rep(0, length(expColR2)), replicateLabel2="r
```

Arguments

geneExpFile1	file containing gene expression values for replicates of sample1 (or replicate1 when method="CTR").
geneCol1	gene id column in geneExpFile1.
expCol1	expression value *columns* in geneExpFile1 for replicates of sample1 (numeric vector). *Note*: Each column corresponds to a replicate of sample1.
depth1	the total number of reads uniquely mapped to genome for each replicate of sample1 (numeric vector), default: take the total number of reads mapped to all annotated genes as the depth for each replicate.

groupLabel1 — label of group1 on the plots.

geneExpFile2 — file containing gene expression values for replicates of sample2 (or replicate2 when method="CTR").

geneCol2 — gene id column in geneExpFile2.

expCol2 — expression value *columns* in geneExpFile2 for replicates of sample2 (numeric vector).
Note: Each column corresponds to a replicate of sample2.

depth2 — the total number of reads uniquely mapped to genome for each replicate of sample2 (numeric vector),
default: take the total number of reads mapped to all annotated genes as the depth for each replicate.

groupLabel2 — label of group2 on the plots.

header — a logical value indicating whether geneExpFile1 and geneExpFile2 contain the names of the variables as its first line. See ?read.table.

sep — the field separator character. If sep = "" (the default for read.table) the separator is *white space*, that is one or more spaces, tabs, newlines or carriage returns. See ?read.table.

method — method to identify differentially expressed genes. Possible methods are:

- "LRT": Likelihood Ratio Test (Marioni et al. 2008),
- "CTR": Check whether the variation between Technical Replicates can be explained by the random sampling model (Wang et al. 2009),
- "FET": Fisher's Exact Test (Joshua et al. 2009),
- "MARS": MA-plot-based method with Random Sampling model (Wang et al. 2009),
- "MATR": MA-plot-based method with Technical Replicates (Wang et al. 2009),
- "FC" : Fold-Change threshold on MA-plot.

pValue — pValue threshold (for the methods: LRT, FET, MARS, MATR).
only used when thresholdKind=1.

zScore — zScore threshold (for the methods: MARS, MATR).
only used when thresholdKind=2.

qValue — qValue threshold (for the methods: LRT, FET, MARS, MATR).
only used when thresholdKind=3 or thresholdKind=4.

thresholdKind — the kind of threshold. Possible kinds are:

- 1: pValue threshold,
- 2: zScore threshold,
- 3: qValue threshold (Benjamini et al. 1995),
- 4: qValue threshold (Storey et al. 2003),
- 5: qValue threshold (Storey et al. 2003) and Fold-Change threshold on MA-plot are both required (can be used only when method="MARS").

foldChange — fold change threshold on MA-plot (for the method: FC).

outputDir — the output directory.

normalMethod — the normalization method: "none", "loess", "median" (Yang et al. 2002). recommend: "none".

replicate1 — file containing gene expression values for replicate batch1 (only used when method="MATR").
Note: replicate1 and replicate2 are two (groups of) technical replicates of a sample.

geneColR1 — gene id column in the expression file for replicate batch1 (only used when method="MATR").

expColR1 — expression value *columns* in the expression file for replicate batch1 (numeric vector) (only used when method="MATR").

depthR1 — the total number of reads uniquely mapped to genome for each replicate in replicate batch1 (numeric vector),
default: take the total number of reads mapped to all annotated genes as the depth for each replicate (only used when method="MATR").

replicateLabel1 — label of replicate batch1 on the plots (only used when method="MATR").

replicate2 — file containing gene expression values for replicate batch2 (only used when method="MATR").
Note: replicate1 and replicate2 are two (groups of) technical replicates of a sample.

geneColR2 — gene id column in the expression file for replicate batch2 (only used when method="MATR").

expColR2 — expression value *columns* in the expression file for replicate batch2 (numeric vector) (only used when method="MATR").

depthR2 — the total number of reads uniquely mapped to genome for each replicate in replicate batch2 (numeric vector),
default: take the total number of reads mapped to all annotated genes as the depth for each replicate (only used when method="MATR").

replicateLabel2 — label of replicate batch2 on the plots (only used when method="MATR").

rawCount — a logical value indicating the gene expression values are based on raw read counts or normalized values.

References

Benjamini,Y. and Hochberg,Y (1995). Controlling the false discovery rate: a practical and powerful approach to multiple testing. *J. R. Stat. Soc. Ser. B* **57**, 289-300.

Jiang,H. and Wong,W.H. (2008) Statistical inferences for isoform expression in RNA-seq. *Bioinformatics*, **25**, 1026-1032.

Bloom,J.S. et al. (2009) Measuring differential gene expression by short read sequencing: quantitative comparison to 2-channel gene expression microarrays. *BMC Genomics*, **10**, 221.

Marioni,J.C. et al. (2008) RNA-seq: an assessment of technical reproducibility and comparison with gene expression arrays. *Genome Res.*, **18**, 1509-1517.

Storey,J.D. and Tibshirani,R. (2003) Statistical significance for genomewide studies. *Proc. Natl. Acad. Sci.* **100**, 9440-9445.

Wang,L.K. and et al. (2010) DEGseq: an R package for identifying differentially expressed genes from RNA-seq data, *Bioinformatics* **26**, 136 - 138.

Yang,Y.H. et al. (2002) Normalization for cDNA microarray data: a robust composite method addressing single and multiple slide systematic variation. *Nucleic Acids Research*, **30**, e15.

See Also

DEGexp, DEGseq, getGeneExp, readGeneExp, GeneExpExample1000, GeneExpExample5000.

Examples

```
## kidney: R1L1Kidney, R1L3Kidney, R1L7Kidney, R2L2Kidney, R2L6Kidney
## liver: R1L2Liver, R1L4Liver, R1L6Liver, R1L8Liver, R2L3Liver

geneExpFile <- system.file("extdata", "GeneExpExample5000.txt", package="DEGseq")
outputDir <- file.path(tempdir(), "DEGexpExample")
exp <- readGeneExp(file=geneExpFile, geneCol=1, valCol=c(7,9,12,15,18))
exp[30:35,]
exp <- readGeneExp(file=geneExpFile, geneCol=1, valCol=c(8,10,11,13,16))
exp[30:35,]
DEGexp2(geneExpFile1=geneExpFile, geneCol1=1, expCol1=c(7,9,12,15,18), groupLabel1="kidney",
     geneExpFile2=geneExpFile, geneCol2=1, expCol2=c(8,10,11,13,16), groupLabel2="liver",
        method="MARS", outputDir=outputDir)
cat("outputDir:", outputDir, "\n")
```

DEGseq *DEGseq: Identify Differentially Expressed Genes from RNA-seq data*

Description

This function is used to identify differentially expressed genes from RNA-seq data. It takes uniquely mapped reads from RNA-seq data for the two samples with a gene annotation as input. So users should map the reads (obtained from sequencing libraries of the samples) to the corresponding genome in advance.

Usage

```
DEGseq(mapResultBatch1, mapResultBatch2, fileFormat="bed", readLength=32,
       strandInfo=FALSE, refFlat, groupLabel1="group1", groupLabel2="group2",
       method=c("LRT", "CTR", "FET", "MARS", "MATR", "FC"),
       pValue=1e-3, zScore=4, qValue=1e-3, foldChange=4, thresholdKind=1,
       outputDir="none", normalMethod=c("none", "loess", "median"),
       depthKind=1, replicate1="none", replicate2="none",
       replicateLabel1="replicate1", replicateLabel2="replicate2")
```

Arguments

`mapResultBatch1`
: vector containing uniquely mapping result files for technical replicates of sample1 (or replicate1 when `method="CTR"`).

`mapResultBatch2`
: vector containing uniquely mapping result files for technical replicates of sample2 (or replicate2 when `method="CTR"`).

`fileFormat`
: file format: `"bed"` or `"eland"`.
example of `"bed"` format: `chr12 7 38 readID 2 +`
example of `"eland"` format: `readID chr12.fa 7 U2 F`
Note: The field separator character is `TAB`. And the files must follow the format as one of the examples.

`readLength`
: the length of the reads (only used if `fileFormat="eland"`).

`strandInfo`
: whether the strand information was retained during the cloning of the cDNAs.
  - `"TRUE"` : retained,
  - `"FALSE"`: not retained.

`refFlat`
: gene annotation file in UCSC refFlat format.
See http://genome.ucsc.edu/goldenPath/gbdDescriptionsOld.html#RefFlat.

`groupLabel1`
: label of group1 on the plots.

`groupLabel2`
: label of group2 on the plots.

`method`
: method to identify differentially expressed genes. Possible methods are:
  - `"LRT"`: Likelihood Ratio Test (Marioni et al. 2008),
  - `"CTR"`: Check whether the variation between two Technical Replicates can be explained by the random sampling model (Wang et al. 2009),
  - `"FET"`: Fisher's Exact Test (Joshua et al. 2009),
  - `"MARS"`: MA-plot-based method with Random Sampling model (Wang et al. 2009),
  - `"MATR"`: MA-plot-based method with Technical Replicates (Wang et al. 2009),
  - `"FC"` : Fold-Change threshold on MA-plot.

`pValue`
: pValue threshold (for the methods: `LRT`, `FET`, `MARS`, `MATR`).
only used when `thresholdKind=1`.

`zScore`
: zScore threshold (for the methods: `MARS`, `MATR`).
only used when `thresholdKind=2`.

`qValue`
: qValue threshold (for the methods: `LRT`, `FET`, `MARS`, `MATR`).
only used when `thresholdKind=3` or `thresholdKind=4`.

`thresholdKind`
: the kind of threshold. Possible kinds are:
  - `1`: pValue threshold,
  - `2`: zScore threshold,
  - `3`: qValue threshold (Benjamini et al. 1995),
  - `4`: qValue threshold (Storey et al. 2003),

- 5: qValue threshold (Storey et al. 2003) and Fold-Change threshold on MA-plot are both required (can be used only when method="MARS").

foldChange — fold change threshold on MA-plot (for the method: FC).

outputDir — the output directory.

normalMethod — the normalization method: "none", "loess", "median" (Yang,Y.H. et al. 2002). recommend: "none".

depthKind — 1: take the total number of reads uniquely mapped to genome as the depth for each replicate,
0: take the total number of reads uniquely mapped to all annotated genes as the depth for each replicate.
We recommend taking depthKind=1, especially when the genes in annotation file are part of all genes.

replicate1 — files containing uniquely mapped reads obtained from replicate batch1 (only used when method="MATR").

replicate2 — files containing uniquely mapped reads obtained from replicate batch2 (only used when method="MATR").

replicateLabel1 — label of replicate batch1 on the plots (only used when method="MATR").

replicateLabel2 — label of replicate batch2 on the plots (only used when method="MATR").

References

Benjamini,Y. and Hochberg,Y. (1995) Controlling the false discovery rate: a practical and powerful approach to multiple testing. *J. R. Stat. Soc. Ser. B* **57**, 289-300.

Jiang,H. and Wong,W.H. (2009) Statistical inferences for isoform expression in RNA-seq. *Bioinformatics*, **25**, 1026-1032.

Bloom,J.S. et al. (2009) Measuring differential gene expression by short read sequencing: quantitative comparison to 2-channel gene expression microarrays. *BMC Genomics*, **10**, 221.

Marioni,J.C. et al. (2008) RNA-seq: an assessment of technical reproducibility and comparison with gene expression arrays. *Genome Res.*, **18**, 1509-1517.

Storey,J.D. and Tibshirani,R. (2003) Statistical significance for genomewide studies. *Proc. Natl. Acad. Sci.* **100**, 9440-9445.

Wang,L.K. and et al. (2010) DEGseq: an R package for identifying differentially expressed genes from RNA-seq data, *Bioinformatics* **26**, 136 - 138.

Yang,Y.H. et al. (2002) Normalization for cDNA microarray data: a robust composite method addressing single and multiple slide systematic variation. *Nucleic Acids Research*, **30**, e15.

See Also

DEGexp, getGeneExp, readGeneExp, kidneyChr21.bed, liverChr21.bed, refFlatChr21.

Examples

```
kidneyR1L1 <- system.file("extdata", "kidneyChr21.bed.txt", package="DEGseq")
liverR1L2  <- system.file("extdata", "liverChr21.bed.txt", package="DEGseq")
refFlat    <- system.file("extdata", "refFlatChr21.txt", package="DEGseq")
mapResultBatch1 <- c(kidneyR1L1)  ## only use the data from kidneyR1L1 and liverR1L2
mapResultBatch2 <- c(liverR1L2)
outputDir <- file.path(tempdir(), "DEGseqExample")
DEGseq(mapResultBatch1, mapResultBatch2, fileFormat="bed", refFlat=refFlat,
       outputDir=outputDir, method="LRT")
cat("outputDir:", outputDir, "\n")
```

GeneExpExample1000 *GeneExpExample1000*

Description

GeneExpExample1000.txt includes the first 1000 lines in SupplementaryTable2.txt which is a supplementary file for Marioni,J.C. et al. (2008) (http://genome.cshlp.org/content/18/9/1509/suppl/DC1).

References

Marioni,J.C. et al. (2008) RNA-seq: an assessment of technical reproducibility and comparison with gene expression arrays. *Genome Res.*, **18**, 1509-1517.

See Also

DEGexp, getGeneExp, readGeneExp, GeneExpExample5000.

GeneExpExample5000 *GeneExpExample5000*

Description

GeneExpExample5000.txt includes the first 5000 lines in SupplementaryTable2.txt which is a supplementary file for Marioni,J.C. et al. (2008) (http://genome.cshlp.org/content/18/9/1509/suppl/DC1).

References

Marioni,J.C. et al. (2008) RNA-seq: an assessment of technical reproducibility and comparison with gene expression arrays. *Genome Res.*, **18**, 1509-1517.

See Also

DEGexp, getGeneExp, readGeneExp, GeneExpExample1000.

getGeneExp *getGeneExp: Count the number of reads and calculate the RPKM for each gene*

Description

This function is used to count the number of reads and calculate the RPKM for each gene. It takes uniquely mapped reads from RNA-seq data for a sample with a gene annotation file as input. So users should map the reads (obtained from sequencing library of the sample) to the corresponding genome in advance.

Usage

```
getGeneExp(mapResultBatch, fileFormat="bed", readLength=32, strandInfo=FALSE,
       refFlat, output=paste(mapResultBatch[1],".exp",sep=""), min.overlapPercent=1)
```

Arguments

`mapResultBatch`	vector containing uniquely mapping result files for a sample. *Note*: The sample can have multiple technical replicates.
`fileFormat`	file format: `"bed"` or `"eland"`. example of `"bed"` format: `chr12 7 38 readID 2 +` example of `"eland"` format: `readID chr12.fa 7 U2 F` *Note*: The field separator character is `TAB`. And the files must follow the format as one of the examples.
`readLength`	the length of the reads (only used if `fileFormat="eland"`).
`strandInfo`	whether the strand information was retained during the cloning of the cDNAs. • `"TRUE"` : retained, • `"FALSE"`: not retained.
`refFlat`	gene annotation file in UCSC refFlat format. See http://genome.ucsc.edu/goldenPath/gbdDescriptionsOld.html#RefFlat.
`output`	the output file.
`min.overlapPercent`	the minimum percentage of the overlapping length for a read and an exon over the length of the read itself, for counting this read from the exon. should be <=1. `0`: at least 1 bp overlap between a read and an exon.

Note

This function sums up the numbers of reads coming from all exons of a specific gene (according to the known gene annotation) as the gene expression value. The exons may include the 5'-UTR, protein coding region, and 3'-UTR of a gene. All introns are ignored for a gene for the sequenced reads are from the spliced transcript library. If a read falls in an exon (usually, a read is shorter than an exon), the read count for this exon plus 1. If a read is crossing the boundary of an exon, users can tune the parameter `min.overlapPercent`, which is the minimum percentage of the overlapping length for a read and an exon over the length of the read itself, for counting this read from the exon. The method use the union of all possible exons for calculating the length for each gene.

References

Mortazavi,A. et al. (2008) Mapping and quantifying mammalian transcriptomes by RNA-seq. *Nat. Methods*, **5**, 621-628.

See Also

DEGexp, DEGseq, readGeneExp, kidneyChr21.bed, liverChr21.bed, refFlatChr21.

Examples

```
kidneyR1L1 <- system.file("extdata", "kidneyChr21.bed.txt", package="DEGseq")
refFlat    <- system.file("extdata", "refFlatChr21.txt", package="DEGseq")
mapResultBatch <- list(kidneyR1L1)
output <- file.path(tempdir(), "kidneyChr21.bed.exp")
exp <- getGeneExp(mapResultBatch, refFlat=refFlat, output=output)
write.table(exp[30:35,], row.names=FALSE)
cat("output: ", output, "\n")
```

---

kidneyChr21.bed *kidneyChr21.bed*

Description

The reads uniquely mapped to human chromosome 21 obtained from the kidney sample sequenced in Run 1, Lane 1.

References

Marioni,J.C. et al. (2008) RNA-seq: an assessment of technical reproducibility and comparison with gene expression arrays. *Genome Res.*, **18**, 1509-1517.

See Also

DEGexp, DEGseq, getGeneExp, readGeneExp, liverChr21.bed, refFlatChr21.

---

kidneyChr21Bowtie *kidneyChr21Bowtie*

Description

The reads uniquely mapped to human chromosome 21 obtained from the kidney sample sequenced in Run 1, Lane 1.

References

Marioni,J.C. et al. (2008) RNA-seq: an assessment of technical reproducibility and comparison with gene expression arrays. *Genome Res.*, **18**, 1509-1517.

See Also

DEGexp, DEGseq, getGeneExp, readGeneExp, liverChr21.bed, refFlatChr21.

`liverChr21.bed` *liverChr21.bed*

Description

The reads uniquely mapped to human chromosome 21 obtained from the liver sample sequenced in Run 1, Lane 2.

References

Marioni,J.C. et al. (2008) RNA-seq: an assessment of technical reproducibility and comparison with gene expression arrays. *Genome Res.*, **18**, 1509-1517.

See Also

DEGexp, DEGseq, getGeneExp, readGeneExp, kidneyChr21.bed, refFlatChr21.

`liverChr21Bowtie` *liverChr21Bowtie*

Description

The reads uniquely mapped to human chromosome 21 obtained from the liver sample sequenced in Run 1, Lane 2.

References

Marioni,J.C. et al. (2008) RNA-seq: an assessment of technical reproducibility and comparison with gene expression arrays. *Genome Res.*, **18**, 1509-1517.

See Also

DEGexp, DEGseq, getGeneExp, readGeneExp, kidneyChr21.bed, refFlatChr21.

readGeneExp *readGeneExp: read gene expression values to a matrix*

Description

This method is used to read gene expression values from a file to a matrix in R workspace. So that the matrix can be used as input of other packages, such as *edgeR*. The input of the method is a file that contains gene expression values.

Usage

```
readGeneExp(file, geneCol=1, valCol=2, label = NULL, header=TRUE, sep="")
```

Arguments

file	file containing gene expression values.
geneCol	gene id column in file.
valCol	expression value *columns* to be read in the file.
label	label for the columns.
header	a logical value indicating whether the file contains the names of the variables as its first line. See ?read.table.
sep	the field separator character. If sep = "" (the default for read.table) the separator is *white space*, that is one or more spaces, tabs, newlines or carriage returns. See ?read.table.

See Also

getGeneExp, GeneExpExample1000, GeneExpExample5000.

Examples

```
## If the data files are collected in a zip archive, the following
## commands will first extract them to the temporary directory.

geneExpFile <- system.file("extdata", "GeneExpExample1000.txt", package="DEGseq")
exp <- readGeneExp(file=geneExpFile, geneCol=1, valCol=c(7,9,12,15,18,8,10,11,13,16))
exp[30:35,]
```

refFlatChr21 *refFlatChr21*

Description

The gene annotation file includes the annotations of genes on chromosome 21, and is in UCSC refFlat format. See http://genome.ucsc.edu/goldenPath/gbdDescriptionsOld.html#RefFlat.

See Also

DEGseq, DEGexp, kidneyChr21.bed, liverChr21.bed.

Index

∗ **datasets**
GeneExpExample1000, 11
GeneExpExample5000, 11
kidneyChr21.bed, 13
kidneyChr21Bowtie, 13
liverChr21.bed, 14
liverChr21Bowtie, 14
refFlatChr21, 16
∗ **methods**
DEGexp, 2
DEGexp2, 5
DEGseq, 8
getGeneExp, 12
readGeneExp, 15

DEGexp, 2, *8*, *10, 11*, *13, 14*, *16*
DEGexp2, *4*, 5
DEGseq, *4*, *8*, 8, *13, 14*, *16*

GeneExpExample1000, *4*, *8*, *11*, 11, *15*
GeneExpExample5000, *4*, *8*, *11*, 11, *15*
getGeneExp, *4*, *8*, *10, 11*, 12, *13–15*

kidneyChr21.bed, *10*, *13*, 13, *14*, *16*
kidneyChr21Bowtie, 13

liverChr21.bed, *10*, *13, 14*, 14, *16*
liverChr21Bowtie, 14

readGeneExp, *4*, *8*, *10, 11*, *13, 14*, 15
refFlatChr21, *10*, *13, 14*, 16