Package 'DMRScan'

November 11, 2026

Title Detection of Differentially Methylated Regions

Version 1.34.0

Description This package detects significant differentially methylated regions (for both qualitative and quantitative traits), using a scan statistic with underlying Poisson heuristics. The scan statistic will depend on a sequence of window sizes (# of CpGs within each window) and on a threshold for each window size. This threshold can be calculated by three different means: i) analytically using Siegmund et.al (2012) solution (preferred), ii) an important sampling as suggested by Zhang (2008), and a iii) full MCMC modeling of the data, choosing between a number of different options for modeling the dependency between each CpG.

biocViews Software, Technology, Sequencing, WholeGenome

Depends R (>= 3.6.0)

Imports Matrix, MASS, RcppRoll,GenomicRanges, IRanges, Seqinfo, methods, mvtnorm, stats, parallel

License GPL-3

LazyData true

Author Christian M Page [aut, cre],
Linda Vos [aut],
Trine B Rounge [ctb, dtc],
Hanne F Harbo [ths],
Bettina K Andreassen [aut]

Maintainer Christian M Page <page.ntnu@gmail.com>

RoxygenNote 6.1.1

Suggests knitr, rmarkdown, BiocStyle, BiocManager

VignetteBuilder knitr

URL https://github.com/christpa/DMRScan

BugReports https://github.com/christpa/DMRScan/issues

PackageStatus Active

git_url https://git.bioconductor.org/packages/DMRScan

git_branch RELEASE_3_23
git_last_commit 6ec615b
git_last_commit_date 2026-04-28
Repository Bioconductor 3.23
Date/Publication 2026-11-11

Contents

dmrscan 2
DMRScan.methylationData 3
DMRScan.phenotypes 4
DMRScan_package 4
estimateThreshold 6
makeCpGgenes 7
makeCpGregions 8
manyWindowSizeScanner 9
oneWindowSizeScanner 9

Index **11**

`dmrscan` *DMR Scan function*

Description

DMR Scan function

Usage

```
dmrscan(observations, windowSize, windowThreshold = NULL, chr = NULL,
  pos = NULL, maxGap = 500, ...)
```

Arguments

`observations`	An object of either; `GRangesList` made by `makeCpGregions`, a vector of the test statistic, a `GRanges` object, or a "minfi" object (soon to be supported).
`windowSize`	A sequence of windowSizes for the slidingWindow. Must be an integer vector, with equal length as the number of windows.
`windowThreshold`	Optional argument with corresponding cut-off for each window. Will be estimated if not supplied.
`chr`	A vector of chromosomal position. Only used when the observations vector is a matrix of test statistic.
`pos`	A vector of genomic coordinates for the CpGs to match the chr argument
`maxGap`	The maximum allowed gap between two CpGs within the same region.
`...`	Optional arguments to be passed to `estimateThreshold`, if no grid is specified.

Value

An object of type GRanges with significantly differentially

Examples

```
## methylation data from chromosome 22
data(DMRScan.methylationData)
## phenotype (end-point for methylation data)

data(DMRScan.phenotypes)

## Test for an association between phenotype and methylation
test.statistics <- apply(DMRScan.methylationData,1,function(x,y)
  summary(glm(y ~ x, family = binomial(link = "logit")))$coefficients[2,3],
                                                    y = DMRScan.phenotypes)
## Set chromosomal position to each test-statistic
positions <- data.frame(matrix(as.integer(unlist(strsplit(names(test.statistics),
                               split="chr|[.]"))), ncol = 3, byrow = TRUE))[,-1]
## Set clustering features
min.cpg <- 4  ## Minimum number of CpGs in a tested cluster
## Maximum distance (in base-pairs) within a cluster
## before it is broken up into two separate cluster
max.gap <- 750

## Identify all clusters, and generate a list for each cluster
regions <- makeCpGregions(observations = test.statistics,
                          chr = positions[,1], pos = positions[,2],
                          maxGap = max.gap, minCpG = min.cpg)
## Number of CpGs in the slidingWindows, can be either a single number
## or a sequence of windowSizes
windowSizes <- 3:7
nCpG        <- sum(sapply(regions,length)) ## Number of CpGs to be tested

# Estimate the windowThreshold, based on the number of CpGs and windowSizes
windowThresholds <- estimateWindowThreshold(nProbe = nCpG,
               windowSize = windowSizes, method = "sampling", mcmc = 10000)
## Run the slidingWindow
DMRScanResults   <- dmrscan(observations = regions,
                            windowSize = windowSizes,
                            windowThreshold = windowThresholds)
## Print the result
print(DMRScanResults)
```

Description

Bi-sulfite sequencing data from all known CpG islands at chromosome 22 from 100 the Finish teens study, sampled from extreme BMI quantiles. The data set is reduced to 25139 sites on chromosome 22. See "Genome-wide DNA methylation in saliva and body size of adolescent girls", TB Rounge, CM Page, M Lepisto, E Pekka, and BK Andreassen and E Weiderpass, _Epigenomics_ 8.11 (2016): 1495-1505 for a full overview of the data set.

Examples

```
data(DMRScan.methylationData)
head(DMRScan.methylationData)
```

`DMRScan.phenotypes` *DMRScan*

Description

Accompanying phenotypes for the methylation data, indicating case- control status for the BMI quantiles. See "Genome-wide DNA methylation in saliva and body size of adolescent girls", TB Rounge, CM Page, M Lepisto, E Pekka, and BK Andreassen and E Weiderpass, _Epigenomics_ 8.11 (2016): 1495-1505 for a full description of the phenotypes.

Examples

```
data(DMRScan.phenotypes)
table(DMRScan.phenotypes)
```

`DMRScan_package` *DMRScan: An R-package for identification of Differentially Metylated Regions*

Description

DMRScan: An R-package for identification of Differentially Metylated Regions

Arguments

`observations`	An object of type GRangesList from makeCpGregions
`windowSize`	A sequence of windowSizes for the slidingWindow, must be an integer
`windowThreshold`	Optional argument with corresponding cut-off for each window. Will be estimated if not supplied.
`...`	Optional arguments to be pased to `estimateThreshold`, if no grid is specified.

Value

An object of type GRanges with signficantly differentially

Author(s)

Christian Page, <page.ntnu@gmail.com>

References

Not Published yet (Under revision)

Examples

```
## nProbeoad methylation data from chromosome 22
data(DMRScan.methylationData)
## nProbeoad phenotype (end-point for methylation data)
data(DMRScan.phenotypes)

## Test for an association between phenotype and Methylation
test.statistics <- apply(DMRScan.methylationData,1,function(x,y)
  summary(glm(y ~ x, family = binomial(link = "logit")))$coefficients[2,3],
                                                    y = DMRScan.phenotypes)
## Set chromosomal position to each test-statistic
positions <- data.frame(matrix(as.integer(unlist(strsplit(names(test.statistics), split="chr|[.]"))), ncol = 3, b
## Set clustering features
min.cpg <- 4  ## Minimum number of CpGs in a tested cluster
## Maxium distance (in base-pairs) within a cluster
## before it is broken up into two seperate cluster
max.gap <- 750

## Identify all clusters, and generate a list for each cluster
regions <- makeCpGregions(observations = test.statistics,
                          chr = positions[,1], pos = positions[,2],
                          maxGap = max.gap, minCpG = min.cpg)
## Number of CpGs in the slidingWindows, can be either a single number
## or a sequence of windowSizes
windowSizes <- 3:7
nCpG        <- sum(sapply(regions, length)) ## Number of CpGs to be tested

# Estimate the windowThreshold, based on the number of CpGs and windowSizes
windowThresholds <- estimateWindowThreshold(nProbe = nCpG,
               windowSize = windowSizes, method = "sampling", mcmc = 10000)
## Run the slidingWindow
DMRScanResults   <- dmrscan(observations = regions,
                            windowSize = windowSizes,
                            windowThreshold = windowThresholds)
## Print the result
print(DMRScanResults)
```

`estimateThreshold` *EstimateWindowThresholds*

Description

Estimate window thresholds for sliding window, one unique value for each window size

Usage

```
estimateWindowThreshold(nProbe, windowSize, method = "siegmund",
  mcmc = 1000, nCPU = 1, submethod = "ar", ...)
```

Arguments

`nProbe`	The number of probes (CpGs) in the study.
`windowSize`	The different window sizes to be tested. Must be either one, or an ordered sequence of integers.
`method`	Gives the method by which the threshold is calculated. Can be either an analytical solution "siegmund", provided by Siegnumd et.al (2012), or an iterative process; either importance sampling "sampling", as suggested by Zhang (2012) or a full MCMC model "mcmc" which can account for any dependency structure, wich is pass to arima.sim, with ...
`mcmc`	The number of MCMC iterations to be used, when using either Important Sampling ("zhang") or MCMC estimation of the threshold.
`nCPU`	When calculating the thresholds on a cluster, how many CPUs should be used. This option is only compatible with the 'mcmc' method.
`submethod`	A character string indicating if an AR(5) or ARIMA model should be used. In the AR(5), the index runs from -2 to 2. A regular AR(p) model can be obtaine using ARIMA(p,0,0) instead.
`...`	Optinal parameters pased on to `arima`, when simulating data using the mcmc option, see arima.sim()

Value

Returns a vector of the threshold for each window size

Examples

```
thresholdGrid <- estimateWindowThreshold(nProbe = 1000,
                                  windowSize = 3:8, method = "siegmund")
```

makeCpGgenes *Cluster*

Description

Cluster CpGs together in genes based on annotation

Usage

```
makeCpGgenes(observations, chr, pos, gene, minCpG = 2)
```

Arguments

observations	Vector of corresponding observed T-value for each CpG, must be ordered in the same way as chr and pos
chr	Vector of chromosome location for each CpG
pos	Vector giving base pair position for each CpG If unsorted, use order(chr,pos) to sort the genomic positions within each chromosome.
gene	A vector asigning each probe to a gene.
minCpG	Minimum number of CpGs allowed in each region to be considered. Default is set to at least 2 CpGs within each region.

Value

The suplied observations ordered into into a list, with one entry for each CpG region.

Examples

```
data(DMRScan.methylationData) ## Load methylation data from chromosome 22
data(DMRScan.phenotypes) ## Load phenotype (end-point for methylation data)

## Test for an association between phenotype and Methylation
testStatistics <- apply(DMRScan.methylationData,1,function(x,y)
 summary(glm(y ~ x, family = binomial(link = "logit")))$coefficients[2,3],
  y = DMRScan.phenotypes)

## Set chromosomal position to each test-statistic
pos <- data.frame(matrix(as.integer(unlist(strsplit(names(testStatistics),
 split="chr|[.]"))), ncol = 3, byrow = TRUE))[,-1]

## Set clustering features
minCpG   <- 3  ## Minimum number of CpGs in a tested cluster
gene     <- sample(paste("Gene",1:100,sep=""),
                          length(testStatistics),replace=TRUE)
regions  <- makeCpGgenes(observations = testStatistics,
                         chr = pos[,1], pos = pos[,2],
                         gene = gene, minCpG = minCpG)
```

makeCpGregions *Cluster*

Description

Cluster CpGs together in regions based on proximity

Usage

```
makeCpGregions(observations, chr, pos, maxGap = 500, minCpG = 2)
```

Arguments

observations	Vector of corresponding observed T-value for each CpG, must be ordered in the same way as chr and pos
chr	Vector of chromosome location for each CpG
pos	Vector giving base pair position for each CpG If unsorted, use order(chr,pos) to sort the genomic positions within each chromosome.
maxGap	Maximum allowed base pair gap within a cluster. Default is set to 500.
minCpG	Minimum number of CpGs allowed in each region to be considered. Default is set to at least 2 CpGs within each region.

Value

The suplied observations ordered into into a GRangesList object. To be parsed further into dmrscan

Examples

```
data(DMRScan.methylationData) ## Load methylation data from chromosome 22
data(DMRScan.phenotypes) ## Load phenotype (end-point for methylation data)

## Test for an association between phenotype and Methylation
testStatistics <- apply(DMRScan.methylationData,1,function(x,y)
 summary(glm(y ~ x, family = binomial(link = "logit")))$coefficients[2,3],
 y = DMRScan.phenotypes)

## Set chromosomal position to each test-statistic
pos<- data.frame(matrix(as.integer(unlist(strsplit(names(testStatistics),
split="chr|[.]"))), ncol = 3, byrow = TRUE))[,-1]

## Set clustering features
minCpG <- 3  ## Minimum number of CpGs in a tested cluster
## Maxium distance (in base-pairs) within a cluster before it is
## broken up into two seperate cluster
maxGap <- 750
regions <- makeCpGregions(observations = testStatistics, chr = pos[,1],
                          pos = pos[,2], maxGap = maxGap, minCpG = minCpG)
```

manyWindowSizeScanner *Method Fixed window size scan for a sequence of window sizes*

Description

Method Fixed window size scan for a sequence of window sizes

Usage

```
manyWindowSizeScanner(region, windowThreshold, windowSize)

## S4 method for signature 'GRangesList'
manyWindowSizeScanner(region, windowThreshold,
  windowSize)

## S4 method for signature 'GRanges'
manyWindowSizeScanner(region, windowThreshold,
  windowSize)
```

Arguments

region	Object of type GRanges
windowThreshold	Vector of window thresholds
windowSize	Vector of window sizes to be tested on regions

Value

A list of the windows that are significant

Examples

```
## Not run
```

oneWindowSizeScanner *Method Fixed window size scan for one window size*

Description

Method Fixed window size scan for one window size

Usage

```
oneWindowSizeScanner(region, windowThreshold, windowSize)

## S4 method for signature 'GRangesList'
oneWindowSizeScanner(region, windowThreshold,
  windowSize)

## S4 method for signature 'GRanges'
oneWindowSizeScanner(region, windowThreshold,
  windowSize)
```

Arguments

region	Object of type GRanges
windowThreshold	Vector of window thresholds
windowSize	Vector of window sizes to be tested on regions

Value

A list of the windows that are significant

Examples

```
## Not run
```

Index

∗ **CpG**
  makeCpGgenes, 7
  makeCpGregions, 8
∗ **DMR,**
  DMRScan_package, 4
∗ **DMRScan**
  dmrscan, 2
  DMRScan_package, 4
∗ **Regions**
  makeCpGgenes, 7
  makeCpGregions, 8
∗ **datasets**
  DMRScan.methylationData, 3
∗ **dataset**
  DMRScan.phenotypes, 4

arima, *6*

dmrscan, 2, *8*
DMRScan.methylationData, 3
DMRScan.phenotypes, 4
DMRScan_package, 4
DMRScan_package-package
  *(*DMRScan_package*)*, 4

estimateThreshold, *2*, *4*, 6
estimateWindowThreshold
  *(*estimateThreshold*)*, 6

GRanges, *2, 3*, *5*
GRangesList, *2*

makeCpGgenes, 7
makeCpGregions, *2*, 8
manyWindowSizeScanner, 9
manyWindowSizeScanner,GRanges-method
  *(*manyWindowSizeScanner*)*, 9
manyWindowSizeScanner,GRangesList-method
  *(*manyWindowSizeScanner*)*, 9

oneWindowSizeScanner, 9
oneWindowSizeScanner,GRanges-method
  *(*oneWindowSizeScanner*)*, 9
oneWindowSizeScanner,GRangesList-method
  *(*oneWindowSizeScanner*)*, 9

Rt *(*oneWindowSizeScanner*)*, 9
Rt,GRanges-method
  *(*oneWindowSizeScanner*)*, 9
Rt,GRangesList-method
  *(*oneWindowSizeScanner*)*, 9

St *(*manyWindowSizeScanner*)*, 9