Package 'DuplexDiscovereR'

November 11, 2026

Title Analysis of the data from RNA duplex probing experiments

Description DuplexDiscovereR is a package designed for analyzing data from RNA cross-linking and proximity ligation protocols such as SPLASH, PARIS, LIGR-seq, and others.
DuplexDiscovereR accepts input in the form of chimerically or split-aligned reads. It includes procedures for alignment classification, filtering, and efficient clustering of individual chimeric reads into duplex groups (DGs). Once DGs are identified, the package predicts RNA duplex formation and their hybridization energies. Additional metrics, such as p-values for random ligation hypothesis or mean DG alignment scores, can be calculated to rank final set of RNA duplexes.
Data from multiple experiments or replicates can be processed separately and further compared to check the reproducibility of the experimental method.

License GPL-3

URL https://github.com/Egors01/DuplexDiscovereR/

BugReports https://github.com/Egors01/DuplexDiscovereR/issues/

Encoding UTF-8

NeedsCompilation no

Version 1.6.0

Roxygen list(markdown = TRUE)

RoxygenNote 7.3.3

BiocType Software

biocViews Sequencing, Transcriptomics, StructuralPrediction, Clustering, SplicedAlignment

Imports Gviz, Biostrings, rtracklayer, GenomicAlignments, GenomicRanges, GenomeInfoDb, ggsci, igraph, rlang, scales, stringr, dplyr, tibble, tidyr, purrr, methods, grDevices, stats, utils, vctrs

Depends R (>= 4.5), InteractionSet

LazyData false

Suggests knitr, UpSetR, BiocStyle, rmarkdown, testthat (>= 3.0.0)

VignetteBuilder knitr

VignetteEngine knitr

Config/testthat/edition 3

git_url https://git.bioconductor.org/packages/DuplexDiscovereR

git_branch RELEASE_3_23

git_last_commit 6f2f2e9

git_last_commit_date 2026-04-28

Repository Bioconductor 3.23

Date/Publication 2026-11-11

Author Egor Semenchenko [aut, cre, cph] (ORCID:
<https://orcid.org/0009-0007-5306-076X>),
Volodymyr Tsybulskyi [ctb] (ORCID:
<https://orcid.org/0009-0002-4141-6291>),
Irmtraud M. Meyer [aut, cph] (ORCID:
<https://orcid.org/0000-0002-4048-3479>)

Maintainer Egor Semenchenko <yegor.smb@gmail.com>

Contents

.addDGidsForTmpDGs . . . 3
.addGeneCounts . . . 4
.annotateCisTrans . . . 5
.compute_clusters_comp . . . 5
.DGIdToDuplexId . . . 6
.getStartEndOvl . . . 6
.gv_plotboxes . . . 7
.gv_updatepars . . . 7
annotateGI . . . 8
availableDisplayPars . . . 9
calculateLigationPvalues . . . 10
classifyTwoArmChimeras . . . 12
clusterDuplexGroups . . . 13
collapseIdenticalReads . . . 15
collapseSimilarChimeras . . . 16
collapse_duplex_groups . . . 17
col_check_rename . . . 18
compareMultipleInteractions . . . 19
computeGISelfOverlaps . . . 21
convert_gi_to_ranges . . . 21
dd_get_chimeric_reads . . . 22
dd_get_chimeric_reads_stats . . . 23
dd_get_duplex_groups . . . 24
dd_get_reads_classes . . . 25
dd_get_run_stats . . . 26
drawGD,DuplexTrack-method . . . 27

DuplexDiscovereR . . . 27
DuplexDiscovererResults-class . . . 28
DuplexTrack . . . 29
getChimericJunctionTypes . . . 32
getRNAHybrids . . . 33
getSpliceJunctionChimeras . . . 34
get_arm_a . . . 35
get_arm_b . . . 35
get_char_count_cigar . . . 36
get_chimeric_junctions_onestrand . . . 36
get_colnames_and_types_for_input . . . 37
makeDfFromGi . . . 37
makeGiFromDf . . . 38
preproc_chim_junction_out_pe . . . 39
preproc_chim_junction_out_se . . . 39
preproc_generic . . . 40
preproc_generic_gi . . . 41
refresh_gi . . . 41
RNADuplexesGeneCounts . . . 42
RNADuplexesRawBed . . . 42
RNADuplexesRawChimSTAR . . . 43
RNADuplexSampleClustReads . . . 43
RNADuplexSampleDGs . . . 44
RNADuplexSampleGI . . . 45
runDuplexDiscoPreproc . . . 46
runDuplexDiscoverer . . . 47
SampleGeneAnnoGR . . . 50
SampleSmallGI . . . 51
SampleSpliceJncGR . . . 51
show,DuplexDiscovererResults-method . . . 52
show,DuplexTrack-method . . . 53
subset_gi . . . 54
trimAroundJunction . . . 54
writeGiToSAMfile . . . 55

Index **57**

`.addDGidsForTmpDGs` *Helper function to add ids to the duplex groups missed during global clustering*

Description

Check if there are a temporary duplex records with `duplex_id`, which consist of more than one read `n_reads` > 1 , but does not have assigned any `dg_id` as the duplex group (DG) index. Creates new `dg_id` if `n_reads` > 1

Usage

```
.addDGidsForTmpDGs(gi_input)
```

Arguments

gi_input	**GInteractions** with the dg_id, duplex_id and n_reads column

Details

Meant to be used in the situations when previous collapsing steps merged two or more reads to the temporary DG with duplex_id, but global clustering has not identified any overlap between this temporary group and other duplexes, resulting in undefined dg_id. This function looks up for these cases and creates new dg_id for temporary DGs, marking them as the final DGs. New dg_id values are unique and allocated sequentially after the maximum value of dg_id

Value

GInteractions object with new dg_id for rows with n_reads > 1

.addGeneCounts *Helper function to add count data to metadata of* GInteractions

---

Description

Merges the count dataframe and interactions metadata by id_col If key is not found, in metadata throws error

Usage

```
.addGeneCounts(gi, df_counts, id_col = "gene_id")
```

Arguments

gi	GInteractions
df_counts	dataframe with read counts
id_col	key to use in merge

Value

GInteractions with added counts

.annotateCisTrans *Annotate RNA-RNA interactions as cis- and trans-*

Description

Annotated each entry gi object as cis, if the .A and .B arms correspond to the same feature (i.e transcript_id or gene_id) If the values are are equal, then annotated with value: `cis` = 1, If not equal or `NA`: `cis` = 0

Usage

```
.annotateCisTrans(gi, id_col_base = "gene_id")
```

Arguments

`gi`	`GInteractions` object containing two metadata columns as feature annotation
`id_col_base`	base name of the feature id columns to use. Function will look for <id_col_base>.A and <id_col_base>.B columns and compare them

Value

gi `GInteractions` object containing `cis` field with 0/1 values

.compute_clusters_comp *Helper function to call clustering on each component*

Description

Helper function to call clustering on each component

Usage

```
.compute_clusters_comp(graph, index)
```

Details

Call clustering on each independent graph component. Used when decompose==TRUE

Value

sub-graph with clusters labelled with sample-wise unique ids (cluster_group)

.DGIdToDuplexId *Accessor for mapping between temporary and final cluster ids*

Description

Accessor for mapping between temporary and final cluster ids

Usage

```
.DGIdToDuplexId(gi)
```

Arguments

gi

Value

tibble

.getStartEndOvl *Helper func for calculating one-side overlap of SJ and junctions of gi*

Description

Helper func for calculating one-side overlap of SJ and junctions of gi

Usage

```
.getStartEndOvl(gi, gr_chim_c, gr_sj_c, tol = 3)
```

Arguments

gi	GInteractions object
gr_chim_c	GRanges object with chimeric junctions of gi
gr_sj_c	GRanges with chimeric junctions
tol	overlap tolerance

Value

Granges object with the left (A) region

.gv_plotboxes *Plots distributed boxes*

Description

Non-exported from Gviz, contains logic for calcualting boxes alignment on plot

Usage

```
.gv_plotboxes(box, lwd, lty, alpha)
```

Value

pushes boxes to the viewport

.gv_updatepars *Set Gviz graphical parameters*

Description

Set Gviz graphical parameters

Usage

```
.gv_updatepars(x, class)
```

Details

Non-exported from Gviz. Uses the same procedure as in AnnotationTrack to set defaults.

Value

set default values inside class upon calling withn class constructor

annotateGI *Annotate RNA duplexes with features*

Description

Overlays RNA duplexes with GRanges annotation object.

Usage

```
annotateGI(
  gi,
  anno_gr,
  keys = c("gene_name", "gene_type", "gene_id"),
  ambig_key = keys[1],
  save_ambig = TRUE,
  order_key = NULL,
  order_vec = NULL
)
```

Arguments

gi	GInteraction object to annotate
anno_gr	GRanges object with the keys columns in the metadata
keys	vectors with the names of the features to use for annotation.
ambig_key	a which feature to use for recording the annotation ambiguity. Determines the values in ambig_list.A and ambig_list.B.
save_ambig	When RNA duplex overlaps multiple features, ambiguous annotation for a single key can be stored in ambig_list.A and ambig_list.B. ambig.A and 'ambig.B' fields will be added as the 0/1 label
order_key	Experimental. In case RNA duplex overlaps multiple features, this key will be used to sort the overlapping features.
order_vec	Experimental. An ordered vector of values in order_key annotation feature, which sets the priority in case of feature overlap.

Details

For each annotation feature in keys, i.e if keys=c(keyname1), then <keyname1>.A, <keyname1>.B annotation fields will be created, containing the names of overlapping features If no overlap is found for the feature, then filed will have NA

Value

GInteractions object with new fields

Examples

```
data("RNADuplexesSampleData")
annotateGI(gi = RNADuplexSampleDGs, anno_gr = SampleGeneAnnoGR)

# Prioritisation of the snRNA and lncRNA before mRNA if genes overlap
annotateGI(
    gi = RNADuplexSampleDGs, anno_gr = SampleGeneAnnoGR,
    keys = c("gene_id", "gene_name", "gene_type"),
    order_key = "gene_type",
    order_vec = c("snRNA", "lncRNA", "protein_coding"),
    save_ambig = TRUE
)
```

---

availableDisplayPars *The default display parameters for a* DuplexTrack *object*

Description

DuplexTrack inherits from [Gviz::Annotaiontrack()] and its Gviz parents. Most likely, user doesn't need all dioplay pars for the parents, so only parameters relevant to the DuplexTrack are returned by default.

Usage

```
availableDisplayPars(class)
```

Arguments

class	DuplexTrack track object This function allows user to display the default display parameters for the DuplexTrack class.

Value

list of the default display parameters.

Examples

```
library(InteractionSet)
anchor1 <- GRanges(
    seqnames = "chr1",
    ranges = IRanges(
        start = c(100, 600, 1100, 1600, 2100),
        end = c(200, 700, 1200, 1700, 2200)
    ),
    strand = "+"
)
anchor2 <- GRanges(
    seqnames = "chr1",
    ranges = IRanges(
```

```
        start = c(300, 800, 1300, 1800, 2300),
        end = c(400, 900, 1400, 1900, 2400)
    ),
    strand = "+"
)

interactions <- GInteractions(anchor1, anchor2, mode = "strict")
gr_region <- range(anchor1, anchor2)
a <- DuplexTrack(interactions, gr_region = gr_region, stacking = "dense")
availableDisplayPars("DuplexTrack")
DuplexDiscovereR::availableDisplayPars(a)
```

`calculateLigationPvalues` *Calculate ligation-based significance statistics for RNA duplexes*

Description

Calculates significance statistics for each gene/transcript pair represented in a `GInteractions` object. Two optional models are supported:

Usage

```
calculateLigationPvalues(
  gi,
  df_counts,
  id_col = "gene_id",
  compute_binom = TRUE,
  compute_odds = FALSE
)
```

Arguments

`gi`	`GInteractions` object annotated with gene/transcript names.
`df_counts`	`data.frame`. A two-column data frame with gene/transcript counts. The first column should match the `<id_col>.A` / `<id_col>.B` identifiers in `gi`. The second column is the corresponding count.
`id_col`	`character(1)`. Prefix for gene/transcript metadata fields in `gi`. Two fields, `<id_col>.A` and `<id_col>.B`, are expected.
`compute_binom`	`logical(1)`. Whether to compute the binomial random-ligation test. Default is `TRUE`.
`compute_odds`	`logical(1)`. Whether to compute the odds-ratio / Fisher exact test. Default is `TRUE`.

Details

1. A binomial random-ligation model, where pair probability is derived from per-gene/transcript counts and tested using the right-tail binomial test.
2. An odds-ratio / Fisher exact test based on a 2x2 contingency table using chimeric counts and singleton counts. This test is used in RBP-dependent and RNA probing methods like RIL-seq

The function also outputs abundance fractions for each duplex pair and counts of other RNA duplexes formed by either or neither gene/transcript in the pair.

Binomial model

Null hypothesis: an observed duplex is generated by random ligation.

Alternative hypothesis: the duplex is enriched above the random-ligation expectation.

The random-ligation probability $P(a, b)$ is defined as:

$$P(a,b) \propto \begin{cases} 2 \cdot P(a) \cdot P(b) & \text{if } a:b \text{ is observed and } a \neq b \\ P(a)^2 & \text{if } a:b \text{ is observed and } a = b \\ 0 & \text{otherwise} \end{cases}$$

where:

$$P(a) = \frac{\text{N reads}(a)}{\text{total N reads}}$$

The observed-pair probabilities are renormalized to sum to one and the p-value is computed from the right tail of the binomial distribution.

Odds-ratio / Fisher model

For a pair `(A, B)`, the contingency table is:

	B present	B absent
A present	C1	C2
A absent	C3	C4

with:

- `C1`: chimeric fragments containing both `A` and `B`
- `C2`: fragments containing `A` but not `B`
- `C3`: fragments containing `B` but not `A`
- `C4`: fragments containing neither `A` nor `B`

A one-sided Fisher exact test (`alternative = "greater"`) is used.

Value

`GInteractions` object with added metadata columns.

Examples

```
data("RNADuplexesSampleData")
gi <- calculateLigationPvalues(
  RNADuplexSampleDGs,
  df_counts = RNADuplexesGeneCounts
)
hist(gi$p.adj, breaks = 20)
```

`classifyTwoArmChimeras` *Wrapper for classification of the 2arm chimeric reads*

Description

Wraps two procedures for different types of classification for read alignment:

overlap type test if chimeric junction map to two non-overlapped regions or shorter than defined minimum distance

splice junction test if chimeric junction is also a splice junction

Usage

```
classifyTwoArmChimeras(
  gi,
  min_junction_len = 4,
  junctions_gr,
  max_sj_shift = 4
)
```

Arguments

`gi`	`GInteractions` object
`min_junction_len`	minimum allowed distance between two chimeric arms
`junctions_gr`	`Granges` object with the splice junctions coordinates
`max_sj_shift`	maximum shift between either donor and acceptor splice sites and corresponding chimreic junction coordinates to count chimeric junction as splice junction

Details

Calls detection of the chimeric junction type, annotates short junctions on same chromosome an strand as 'short'. Compares chimeric junctions with splice junctions. Adds results as the new metadata fields parallel to the input.

Value

GInteractions object object of the same size with new columns:

splicejnc filled with 0 or 1

junction_type factor for the junction types

See Also

DuplexDiscovereR::getChimericJunctionTypes(), DuplexDiscovereR::getSpliceJunctionChimeras()

Examples

```
data("RNADuplexesSampleData")
head(RNADuplexSampleGI)
# remove all metadata
mcols(RNADuplexSampleGI) <- NULL
gi <- classifyTwoArmChimeras(RNADuplexSampleGI,
    min_junction_len = 5,
    junctions_gr = SampleSpliceJncGR, max_sj_shift = 10
)
table(gi$splicejnc)
table(gi$junction_type)
```

---

clusterDuplexGroups *Cluster RNA duplexes in* GInteractions *object*

Description

Main method to find duplex groups from the individual interactions

Usage

```
clusterDuplexGroups(
  gi,
  graphdf = NULL,
  maxgap = 40,
  minoverlap = 10,
  id_column = "duplex_id",
  weight_column = "weight",
  fast_greedy = FALSE,
  decompose = FALSE,
  id_columns_grapdf = paste(id_column, c(1, 2), sep = "."),
  min_arm_ratio = 0.3,
  dump_graph = FALSE,
  dump_path = ""
)
```

Arguments

gi	GInteractions object
graphdf	Optional. Dataframe representing connection edges between entries in gi If not provided, graphdf is created inside the function
maxgap	For graph creation only. Max shift between arms starts and ends for pair of overlapping reads
minoverlap	For graph creation only. Minimum required overlap between either arm for pair of overlapping reads Other optional arguments, which are not relevant, unless user want to modify clustering weights or modify clustering in some other way
id_column	Optional. Column name in the GInteractions metadata, which was used to index temporary duplex groups, if they are present
weight_column	Optional. If graphdf is provided, field to use for weight overlaps
fast_greedy	Optional. Run the fast_greedy algorithm instead of Louvain. Can speed up calcualtion for the large graphs.
decompose	Decompose graph into separate sub-graphs before clustering.
id_columns_grapdf	Column in the graph dataframe, which was used for index
min_arm_ratio	For graph creation only. Span-to-overlap ratio threshold. If smaller than this value, then edge is not drawn
dump_graph	For debug. Export the graph elements. not used
dump_path	For debug. PArt to export the graph elements. not used

Details

Accepts or creates the connections graphdf dataframe, creates graph with igraph package, uses community detection algoritm to call clusters. New field dg_id is added to label the clusters (duplex groups). If no community is found for the read, dg_id is NA

Value

GInteractions object with new dg_id column

Examples

```
data("RNADuplexesSampleData")
# run preprocessing and filtering
preproc_df <- runDuplexDiscoPreproc(RNADuplexesRawBed, table_type = "bedpe")
preproc_gi <- makeGiFromDf(preproc_df)
preproc_gi <- classifyTwoArmChimeras(preproc_gi,
    min_junction_len = 5,
    junctions_gr = SampleSpliceJncGR, max_sj_shift = 10
)
# collapse duplicates
gi <- collapseIdenticalReads(preproc_gi)$gi
# run global clustering
gi <- clusterDuplexGroups(gi)
# check dg_ids
table(is.na(gi$dg_id))
```

collapseIdenticalReads *Collapses identical interactions*

Description

Two entries (reads) are considered identical if they share start, end, strand and score vales Identical entries are collapsed into the single one.

Usage

```
collapseIdenticalReads(gi)
```

Arguments

gi	GInteractions(mode='strict') object with chromA, strandA, startA, endA, chromB, strandB, startB, endB, score columns Optionally cigar_alnA, cigar_alnB columns are also considered for collapsing 'read_id' column used as the index in the initial objects. Created, if not exists

Details

Adds columns to the collapsed object duplex_id (int) unique record id n_reads (int) number of entries collapsed

Value

result_list object with keys ' gi_collapsed': New collapsed GInteraction object ' stats_df': tibble with the mapping of the original entries to the new duplex_id

Examples

```
# load data
data("RNADuplexesSmallGI")
res_collapse <- collapseIdenticalReads(SampleSmallGI)
gi_new <- res_collapse[["gi_collapsed"]]
# keeps the mapping of the colapsed object to new
read_stats_df <- res_collapse[["stats_df"]]
```

collapseSimilarChimeras *Call clustering multiple times to collapse similar reads into duplex groups*

Description

Function calls clustering algorithm several times and collapses highly similar reads to the temporary duplex groups (DGs).

Usage

```
collapseSimilarChimeras(
  gi,
  read_stats_df,
  maxgap = 5,
  niter = 2,
  minoverlap = 10,
  min_nodes = 10
)
```

Arguments

gi	GInteractions object
read_stats_df	tibble with the mapping 'read_id' and 'duplex_id' fields 'read_id' refers to the unique read, 'duplex_id' refers to the entry collapsed identical reads i.e two identical reads will will correspond to two unique read_id and the single duplex_id with n_reads=2
maxgap	Maximum relative shift between the overlapping read arms
niter	Number of times clustering will be called
minoverlap	Minimum required overlap between either read arm
min_nodes	Minimum count of nodes to finish the interaction merging

Details

Calling this procedure before global read clustering substantially reduces time required for calling DGs. Collapsed duplex groups are aggregated only from the reads which are shifted by only a few nucleotides from each other. These DGs are temporary until full library clustering is called. To keep track of the mapping of the temprary DGs to the input, dedicated dataframe is returned. The 'duplex_id' column will be added or updated as identifier for the temporary duplex group. The number of reads under single 'duplex_id' is recorded in the 'n_reads' fields

Value

a list with the following keys

gi_updated `GInteractions` object with both collapsed duplex groups and not-collapsed unchanged reads

stats_df `tibble` With the mapping from the unique read - with the the infromation about time and memory reaquired for the function call

---

`collapse_duplex_groups` *Collapse the reads into the duplex groups after clustering*

Description

Collapse each interaction in the input to the duplex group based on the pre-computed dg_id

Usage

```
collapse_duplex_groups(
  gi,
  return_unclustered = FALSE,
  return_collapsed = TRUE,
  keep_meta = TRUE
)
```

Arguments

`gi`	`GInteractions` with the 'dg_id' metadata field
`return_unclustered`	add unclustered reads to output
`return_collapsed`	add duplex groups, which were created as temporary with n_reads > 1 but was not clustered to the DG golabally. This parameter is used internally and should be kept default in most situations.
`keep_meta`	whether to keep metadata, which only unclustered reads have, in case of a mixed output

Details

'dg_id' is used as the identifier for the duplex group Reads belonging to the same duplex group are collapsed into a single entry with start and end are set as min() and max() coordinate of the reads in within the duplex group. The 'score' column is averaged across the duplex group reads is calculated and put as the 'score' for the collapsed duplex group Behavior in case 'dg_id' = NA: Option '`return_unclustered`' - whether unclustered reads with should be added to the output gi

return_unclustered == FALSE Interaction is not returned in the output. Default.

return_unclustered == TRUE Interaction is returned in the output, output is mixed duplex groups and individual reads

Internally used argument #'

return_collapsed == FALSE In case interaction already collapsed and n_read > 1, interaction will not be returned as duplex group

return_collapsed == TRUE In case interaction has n_read > 1, interaction will be treated as duplex group

Value

`GInteractions` object with collapsed duplex groups

Examples

```
# load example of clustered data
data("RNADuplexesSampleData")
# some reads assigned to DG, some are not
table(is.na(RNADuplexSampleGI$dg_id))
# Return only DGs
gicollapsed <- collapse_duplex_groups(RNADuplexSampleGI, return_unclustered = FALSE)
# Return DGs and unclustered reads as well
gimixed <- collapse_duplex_groups(RNADuplexSampleGI, return_unclustered = TRUE)

# load small sample GInteractions and process it manually
data("RNADuplexesSmallGI")
# First, collapse duplicated reads. This adds n_reads and duplex ids
ginodup <- collapseIdenticalReads(SampleSmallGI)$gi_collapsed
# Second, run clustering, get DG ids
ginodup <- clusterDuplexGroups(ginodup)
# Return all DGs result in n=3 DGS, one of them formed by
# identical duplicated alignments
collapse_duplex_groups(ginodup, return_collapsed = TRUE)
# Return DGs, but drop duplicated returns n=2 DGs
collapse_duplex_groups(ginodup, return_collapsed = FALSE)
```

---

col_check_rename *Check the column names and types in read dataframe*

Description

Function to check the correct column names and types in dataframe input. Tries to guess the column names, if colnames are not provided, but the types are correct

Usage

```
col_check_rename(df, table_type = "STAR")
```

Arguments

df	input
table_type	one in c("STAR","bedpe")

Details

- Expected column names for bedpe file c("chromA","startA",'endA',"chromB", 'startB','endB','readname','
- Expected colnames for STAR Chimeric junction input:
- For the 'old' chimeric detection scheme: c("chr_donorA","brkpt_donorA","strand_donorA","chr_acceptorB","
- For the 'new' chimeric detection scheme c("chr_donorA","brkpt_donorA", "strand_donorA","chr_acceptorB", "brkpt_acceptorB","strand_acceptorB", "junction_type","repeat_left_lenA", "repeat_right_lenB","r "start_alnA","cigar_alnA", "start_alnB","cigar_alnB")

Value

dataframe with the properly formatted columns

---

compareMultipleInteractions

Compare multiple RNA-RNA interactions sets

Description

Combines all interaction into single superset by clustering & collapsing. Then compares every input entry with the superset. Overlaps between superset and inputs are recorded in a table as 0/1

Usage

```
compareMultipleInteractions(
  gi_samples_list,
  min_ratio = 0.3,
  minoverlap = 5,
  maxgap = 50,
  niter = 3,
  gi_superset = NULL,
  anno_gr = NULL
)
```

Arguments

gi_samples_list	anmes list with the GInteractions entries list('sample1'=gi1,'sample2'='gi2)
min_ratio	If the overlap-to-span ratio for either arm (A or B) for pair of chimeric reads is less than min_arm_ratio, then the total overlap for this pair is set to zero. Relevant to comparison of superset vs individual samples

minoverlap	Parameter for read clustering to create a superset. Minimum required overlap to for either arm (A or B) for pair of entries.
maxgap	Parameter for read clustering. Minimum required shift between start and end coordinates of arms for pair of overlapping entries.. If the shift is longer than max_gap for either arm, then total read overlap between those reads is zero.
niter	Internal parameter for debugging. Number of cluster& collapse iterations to find superset
gi_superset	Optional. Superset defining the space (all) of the interactions, against which inputs from the list will be compared.
anno_gr	Optional. Granges to annotate superset.

Value

dataframe recodding the overlaps between samples and supeset

Examples

```
# Create test set of RNA interactions
chrom <- "chr1"
start1 <- c(1, 11, 21, 31, 41, 51, 61, 71, 81, 91)
end1 <- start1 + 9
start2 <- c(101, 111, 121, 131, 141, 151, 161, 171, 181, 191)
end2 <- start2 + 9

anchor1 <- GRanges(seqnames = chrom, ranges = IRanges(start = start1, end = end1))
anchor2 <- GRanges(seqnames = chrom, ranges = IRanges(start = start2, end = end2))

interaction <- GInteractions(anchor1, anchor2)

# Ensure some overlaps
n <- length(interaction)
group_size <- ceiling(n / 2)
group_indices1 <- sort(sample(seq_len(n), group_size))
group_indices2 <- sort(sample(seq_len(n), group_size))
group_indices3 <- sort(sample(seq_len(n), group_size))

# Create separate GInteractions objects for each group
group1 <- interaction[group_indices1]
group2 <- interaction[group_indices2]
group3 <- interaction[group_indices3]

# format input and call comparison
a <- list("sample1" = group1, "sample2" = group2, "sample3" = group3)
res <- compareMultipleInteractions(a)
# comparison result
head(res$dt_upset)
# superset
res$gi_all
# dataframe for the Upset plot
res$dt_upset
```

computeGISelfOverlaps *Find overlaps between entries in* GInteractions

Description

Utility function to find overlapping reads in the input and calculate overlap scores. Removes self-hits. Computes overlap/span ratios for each interaction arm. Sum of the scores is recorded in 'weight' field

Usage

```
computeGISelfOverlaps(
  gi,
  id_column = "duplex_id",
  maxgap = 40,
  minoverlap = 10
)
```

Arguments

gi	input gi object
id_column	column which use for using as ids for entries
maxgap	parameter for call of InteractionSet::findOverlaps()
minoverlap	parameter for call InteractionSet::findOverlaps()

Value

dataframe with indexes of pairwise overlapsin input and columns for span, overlap, ratios of either read arm

Examples

```
data("RNADuplexesSmallGI")
computeGISelfOverlaps(SampleSmallGI)
```

convert_gi_to_ranges *Convert* GInteractions *object to* Granges

Description

Creates the 'long' GRanges by stacking the A and B arms one 'on top' of the other. Adds id and group fields as indicators of original index and interaction arm (A- left arm, B- right arm)

Usage

```
convert_gi_to_ranges(gi)
```

Arguments

gi	GInteractions

Value

GRanges twice the length of the input

Examples

```
data("RNADuplexesSmallGI")
convert_gi_to_ranges(SampleSmallGI)
```

---

dd_get_chimeric_reads *Accessor for* chimeric_reads *Slot*

Description

Retrieves the value of the chimeric_reads slot in a DuplexDiscovererResults object.

Usage

```
dd_get_chimeric_reads(object)

## S4 method for signature 'DuplexDiscovererResults'
dd_get_chimeric_reads(object)
```

Arguments

object	A DuplexDiscovererResults object.

Value

GInteractions object from the chimeric_reads slot.

Examples

```
# load example input
data("RNADuplexesSmallGI")
data("RNADuplexesSampleData")
# run whole pipeline
result <- runDuplexDiscoverer(
    data = SampleSmallGI,
    junctions_gr = SampleSpliceJncGR,
    anno_gr = SampleGeneAnnoGR,
    sample_name = "run_example",
    lib_type = "SE",
    table_type = "STAR"
)
# access results
```

```
show(result)
gi_clusters <- dd_get_duplex_groups(result)
gi_reads <- dd_get_chimeric_reads(result)
df_reads <- dd_get_reads_classes(result)
dd_get_reads_classes(result)
dd_get_run_stats(result)
```

`dd_get_chimeric_reads_stats` *Accessor for* `chimeric_reads_stats` *Slot*

Description

Retrieves the value of the `chimeric_reads_stats` slot in a `DuplexDiscovererResults` object.

Usage

```
dd_get_chimeric_reads_stats(object)

## S4 method for signature 'DuplexDiscovererResults'
dd_get_chimeric_reads_stats(object)
```

Arguments

`object`	A `DuplexDiscovererResults` object.

Value

`tibble` from the `chimeric_reads_stats` slot.

Examples

```
# load example input
data("RNADuplexesSmallGI")
data("RNADuplexesSampleData")
# run whole pipeline
result <- runDuplexDiscoverer(
    data = SampleSmallGI,
    junctions_gr = SampleSpliceJncGR,
    anno_gr = SampleGeneAnnoGR,
    sample_name = "run_example",
    lib_type = "SE",
    table_type = "STAR"
)
# access results
show(result)
gi_clusters <- dd_get_duplex_groups(result)
gi_reads <- dd_get_chimeric_reads(result)
df_reads <- dd_get_reads_classes(result)
dd_get_reads_classes(result)
dd_get_run_stats(result)
```

dd_get_duplex_groups *Accessor for* duplex_groups *slot*

Description

Retrieves the value of the duplex_groups slot in a DuplexDiscovererResults object.

Usage

```
dd_get_duplex_groups(object)

## S4 method for signature 'DuplexDiscovererResults'
dd_get_duplex_groups(object)
```

Arguments

object	A DuplexDiscovererResults object.

Value

GInteractions object from the duplex_groups slot.

Examples

```
# load example input
data("RNADuplexesSmallGI")
data("RNADuplexesSampleData")
# run whole pipeline
result <- runDuplexDiscoverer(
    data = SampleSmallGI,
    junctions_gr = SampleSpliceJncGR,
    anno_gr = SampleGeneAnnoGR,
    sample_name = "run_example",
    lib_type = "SE",
    table_type = "STAR"
)
# access results
show(result)
gi_clusters <- dd_get_duplex_groups(result)
gi_reads <- dd_get_chimeric_reads(result)
df_reads <- dd_get_reads_classes(result)
dd_get_reads_classes(result)
dd_get_run_stats(result)
```

dd_get_reads_classes *Accessor for* reads_classes *Slot*

Description

Retrieves the value of the reads_classes slot in a DuplexDiscovererResults object.

Usage

```
dd_get_reads_classes(object)

## S4 method for signature 'DuplexDiscovererResults'
dd_get_reads_classes(object)
```

Arguments

object	A DuplexDiscovererResults object.

Value

tibble from the reads_classes slot.

Examples

```
# load example input
data("RNADuplexesSmallGI")
data("RNADuplexesSampleData")
# run whole pipeline
result <- runDuplexDiscoverer(
    data = SampleSmallGI,
    junctions_gr = SampleSpliceJncGR,
    anno_gr = SampleGeneAnnoGR,
    sample_name = "run_example",
    lib_type = "SE",
    table_type = "STAR"
)
# access results
show(result)
gi_clusters <- dd_get_duplex_groups(result)
gi_reads <- dd_get_chimeric_reads(result)
df_reads <- dd_get_reads_classes(result)
dd_get_reads_classes(result)
dd_get_run_stats(result)
```

dd_get_run_stats *Accessor for* run_stats *Slot*

Description

Retrieves the value of the run_stats slot in a DuplexDiscovererResults object.

Usage

```
dd_get_run_stats(object)

## S4 method for signature 'DuplexDiscovererResults'
dd_get_run_stats(object)
```

Arguments

object	A DuplexDiscovererResults object.

Value

tibble from the run_stats slot.

Examples

```
# load example input
data("RNADuplexesSmallGI")
data("RNADuplexesSampleData")
# run whole pipeline
result <- runDuplexDiscoverer(
    data = SampleSmallGI,
    junctions_gr = SampleSpliceJncGR,
    anno_gr = SampleGeneAnnoGR,
    sample_name = "run_example",
    lib_type = "SE",
    table_type = "STAR"
)
# access results
show(result)
gi_clusters <- dd_get_duplex_groups(result)
gi_reads <- dd_get_chimeric_reads(result)
df_reads <- dd_get_reads_classes(result)
dd_get_reads_classes(result)
dd_get_run_stats(result)
```

drawGD,DuplexTrack-method *Draw method for DuplexTrack*

Description

Gviz::AnnotationTrack stacking algorithm is used to calculate vertical distribution of boxes for the interactions. Boxes coordinates are later imported for placing labels and arcs

Usage

```
## S4 method for signature 'DuplexTrack'
drawGD(GdObject, minBase, maxBase, prepare = FALSE, subset = TRUE, ...)
```

Value

pushes boxes, arcs and labels to viewport

DuplexDiscovereR *Analysis of the data from RNA duplex probing experiments*

Description

DuplexDiscovereR is a package for analysing data from RNA cross-linking and proximity ligation protocols such as SPLASH, PARIS, LIGR-seq and others, which provide information about intra-molecular RNA-RNA interactions through chimeric RNA-seq reads. Chimerically aligned fragments in these experiments correspond to the base-paired stretches (RNA duplexes) of RNA molecules . DuplexDiscovereR takes input in the form of chimericly or split -aligned reads, It implements procedures for alignment classification, filtering and efficient clustering of individual chimeric reads into duplex groups (DGs). Once DGs are found, RNA duplex formation and their hybridization energies are predicted. Additional metrics, such as p-values or mean DG alignment scores, can be calculated to rank and analyse the final set of RNA duplexes. Data from multiple experiments or replicates can be processed separately and further compared to check the reproducibility of the experimental method.

Details

DuplexDiscovereR

Author(s)

Egor Semenchenko

See Also

DuplexDiscovereR vignette

DuplexDiscovererResults-class
DuplexDiscovererResults

Description

A helper S4 class to store the results of the full DuplexDiscovereR analysis. This class contains the following output:

- `duplex_groups`: clustered duplex groups.
- `chimeric_reads`: individual two-regions chimeric reads. Contains both clustered and unclustered reads. Clustered reads are linked to the duplex groups though 'dg_id' field in metadata
- `reads_classes`: dataframe parallel to the the input containing classification result and detected mapping type for each entry in the input
- `chimeric_reads_stats`: dataframe containing read type classification statistics
- `run_stats`: data frame containing statistics about the time and memory used by the pipeline

Usage

```
DuplexDiscovererResults(
  duplex_groups,
  chimeric_reads,
  reads_classes,
  chimeric_reads_stats,
  run_stats
)
```

Arguments

`duplex_groups`	**GInteractions** object with duplex groups
`chimeric_reads`	**GInteractions** object with chimeric reads
`reads_classes`	`tibble` (tbl_df) with read classification data.
`chimeric_reads_stats`	`tibble` (tbl_df) read type statistics.
`run_stats`	`tibble` (tbl_df) runtime and memory info

Details

Each output type has a corresponding accessor:

- `dd_get_duplex_groups()`
- `dd_get_chimeric_reads()`
- `dd_get_reads_classes()`
- `dd_get_chimeric_reads_stats()`
- `dd_get_run_stats()`

Value

A DuplexDiscovererResults object.

Slots

duplex_groups **GInteractions** object with duplex groups

chimeric_reads **GInteractions** object with chimeric reads

reads_classes tibble (tbl_df) with read classification data.

chimeric_reads_stats tibble (tbl_df) read type statistics.

run_stats tibble (tbl_df) runtime and memory info

See Also

dd_get_duplex_groups(), dd_get_chimeric_reads(), dd_get_reads_classes(), dd_get_chimeric_reads_stats()
, dd_get_run_stats()

Examples

```
# load example input
data("RNADuplexesSmallGI")
data("RNADuplexesSampleData")
# run whole pipeline
result <- runDuplexDiscoverer(
    data = SampleSmallGI,
    junctions_gr = SampleSpliceJncGR,
    anno_gr = SampleGeneAnnoGR,
    sample_name = "run_example",
    lib_type = "SE",
    table_type = "STAR"
)
# access results
show(result)
gi_clusters <- dd_get_duplex_groups(result)
gi_reads <- dd_get_chimeric_reads(result)
df_reads <- dd_get_reads_classes(result)
dd_get_reads_classes(result)
dd_get_run_stats(result)
```

DuplexTrack *class for the visualization of RNA duplexes*

Description

Inherits the Gviz::AnnotationTrack, plots interaction ranges as boxes. Arguments from Gviz::AnnotationTrack, as stacking which set boxes layout are accepted. Parent aesthetics for labels are overwritten with Display parameters of this class. Accepts GInteractions object to plot and GRanges to define plot region

Duplexes which can be displayed on the plot range are connected with arcs. Duplexes which are partially outside of the range are displayed without arcs. Labeles and appearance can be controlled with display parameters

Arguments

gi	An GInteractions object
gr_region	GRanges region for plotting
from	Integer start coordinate of subset region. Used if gr_region is not provided
to	Integer end coordinate of subset region. Used if gr_region is not provided
chromosome	Chromosome of subset region. Used if gr_region is not provided
strand	Used if gr_region is not provided
fill.column	used for fill. Default is "" (empty) and triggers IGV color pallete. **Display parameters**

arcs.color Character. Color of the arcs. Default is "black".

arc.location Character in c('inner','outer','midpoint'). Location of the arcs in X axis relative to range. Default is "inner"

labels.v.offset.base Numeric. Base vertical offset for the labels. Default is 0.2. Other offesets are added to it.

labels.v.offset.trans Numeric. Vertical offset for trans labels. Applied when one part of the duplex is outside of the plot. Recommended ranges are in -0.5 to 0.5 Default is 0.0.

labels.h.offset.trans Numeric. Horizontal offset for trans labels. Applied when one part of the duplex is outside of the plot Value is in nucleotide units. Default is 0.0.

labels.v.offset.cis Numeric. Vertical offset for cis labels. Recommended ranges are in -0.5 to 0.5 Default is 0.0. Default is 0.0.

labels.h.offset.cis Numeric. Horizontal offset for cis labels. Value is in nucleotide units. Default is 0.0.

labels.fontsize Numeric. Font size of the labels. Default is 18.

label.cis.above Logical. Whether the cis labels should be above. When set to FALSE, labels are plot for each box separately. Default is TRUE

annotation.column1 Character. First annotation column to use for labels. Default is "group" and generated internally.

annotation.column2 Character. Second annotation column to use for labels. Default is "" (empty).

fill.column Character. Column used for fill. Default is "" (empty) and triggers IGV color pallete.

labels.color Character. Color of the labels. Default is 'black'.

labels.align Character. Alignment of the labels. Default is 'center'. Possible values are in c('left','right','center)

arcConstrain Numeric. Minimum gap distance between arms of the interaction to draw arcs

Examples

```
library(InteractionSet)
library(Gviz)
# generate input
anchor1 <- GRanges(
    seqnames = "chr1",
    ranges = IRanges(
        start = c(100, 600, 1100, 1600, 2100, 150, 400),
        end = c(200, 700, 1200, 1700, 2200, 250, 500)
    ),
    strand = "+"
)
anchor2 <- GRanges(
    seqnames = "chr1",
    ranges = IRanges(
        start = c(300, 800, 1300, 1800, 2300, 1500, 1700),
        end = c(400, 900, 1400, 1900, 2400, 1600, 1800)
    ),
    strand = "+"
)

interactions <- GInteractions(anchor1, anchor2, mode = "strict")
# define plotting range
gr_region <- range(anchor1, anchor2)
interactions$anno_A <- sample(LETTERS, length(interactions))
interactions$anno_B <- interactions$anno_A
a <- DuplexTrack(interactions, gr_region = gr_region, stacking = "dense")
plotTracks(a, stacking = "dense")
plotTracks(a, stacking = "squish", annotation.column1 = "anno_A")

# add interactions which are not fully in plot range: outside the range or on different chromosome()

# one left (A) interaction arm outside of the plot, other on different chromosome
new_anchor1 <- GRanges(
    seqnames = c("chr1", "chr2"),
    ranges = IRanges(
        start = c(10, 600),
        end = c(90, 700)
    ),
    strand = "+"
)
new_anchor2 <- GRanges(
    seqnames = c("chr1", "chr1"),
    ranges = IRanges(
        start = c(1500, 1000),
        end = c(1600, 1200)
    ),
    strand = "+"
)

new_interactions <- GInteractions(new_anchor1, new_anchor2)
new_interactions$anno_A <- c("A.out", "A.out_chr")
```

```
new_interactions$anno_B <- c("B.in", "B.in")
all_interactions <- c(interactions, new_interactions)

b <- DuplexDiscovereR::DuplexTrack(all_interactions,
    gr_region = gr_region,
    annotation.column1 = "anno_A",
    annotation.column2 = "anno_B"
)

plotTracks(b)

# to customize plot, one can call, to see options
DuplexDiscovereR::availableDisplayPars(b)
```

`getChimericJunctionTypes` *Classify chimeric junctions of two-arm reads into types*

Description

Chimeric reads which can be represented ans two-arm interactions can be divided into several categories based on the distance between the chimeric fragments and existence of the overlap between these fragments.

Usage

```
getChimericJunctionTypes(gi, normal_gap_threshold = 10)
```

Arguments

`gi`	`GInteractions` object
`normal_gap_threshold`	minimum allowed distance between chimeric arms

Details

Takes `GInteractions` object and classifies junctions into following categories

2arm normal chimeric read

2arm_short normal chimeric read with junction < *normal_gap_threshold*

self_ovl arms overlap

antisense_ovl arms overlap on the opposite strand

Value

gi object of the same size with the 'junction_type' field added

Examples

```
data("RNADuplexesSampleData")
preproc_df <- runDuplexDiscoPreproc(RNADuplexesRawBed, table_type = "bedpe")
preproc_gi <- makeGiFromDf(preproc_df)
preproc_gi <- getChimericJunctionTypes(preproc_gi)
table(preproc_gi$junction_type)
```

`getRNAHybrids` *Run prediciton of RNA hybridization*

Description

Calls RNAduplex from ViennaRNA to find base-pairs for every entry in the input, throws a message and system warning if it is not installed

Usage

```
getRNAHybrids(gi, fafile)
```

Arguments

`gi`	`Ginteraction` with pairs of regions
`fafile`	path to the .fasta file with genome

Value

object parallel to input with added energy GC content, dot-format base-pairings and lenghts of RNA hybrids will return the input, if RNAhybrids cannot be run

Examples

```
sequence <- paste0(
    "AGCUAGCGAUAGCUAGCAUCGUAGCAUCGAUCGUAAGCUAGCUAGCUAGCAUCGAUCGUAGCUAGCAUCGAU",
    "CGUAGCAUCGUAGCUAGCUAGCUAUGCGAUU"
)

# Save the sequence to a temp fasta file
fasta_file <- tempfile(fileext = ".fa")
chrom <- "test_chrA"
writeLines(c(">test_chrA", sequence), con = fasta_file)

# Create the GInteraction object
# Define start and end positions for the base-pairing regions
regions <- data.frame(
    start1 = c(1, 11, 21, 31, 41),
    end1 = c(10, 20, 30, 40, 50),
    start2 = c(91, 81, 71, 61, 51),
    end2 = c(100, 90, 80, 70, 60)
)
```

```
# GRanges objects for the anchors
anchor1 <- GRanges(seqnames = chrom, ranges = IRanges(start = regions$start1, end = regions$end1))
anchor2 <- GRanges(seqnames = chrom, ranges = IRanges(start = regions$start2, end = regions$end2))
interaction <- GInteractions(anchor1, anchor2)
# predict hybrids
# In case ViennaRNA is installed
## Not run:
gi_with_hybrids <- getRNAHybrids(interaction, fasta_file)

## End(Not run)
```

`getSpliceJunctionChimeras` *Identify chimeric junctions coinciding with the splice junctions*

Description

Marks interactions which starts/ends within specified shift from the known splice junctions.

Usage

```
getSpliceJunctionChimeras(
  gi,
  sj_gr,
  sj_tolerance = 20,
  sj_tolerance_strict = 10
)
```

Arguments

`gi`	**GInteractions** object
`sj_gr`	**Granges** object with the splice junctions data
`sj_tolerance`	maximum shift between either donor and acceptor splice sites and corresponding chimreic junction coordinates to count chimeric junction as splice junction
`sj_tolerance_strict`	maximum shift between either donor and acceptor splice sites irrespective of the particular splice junction. If both chimeric junction start and end correspond to donor or acceptor of any known junction, it is marked as splice junction. Used to catch novel combinations of known 3' and 5' sites

Value

gi object with added 'splicejnc' and field Additionally 'splicejnc_donor' 'splicejnc_acceptor' fields are added

Examples

```
data("RNADuplexesSampleData")
gi <- getSpliceJunctionChimeras(RNADuplexSampleGI, SampleSpliceJncGR)
table(gi$splicejnc)
table(gi$splicejnc_acceptor, gi$splicejnc_donor)
```

`get_arm_a` *Get left arm of GInteraction*

Description

Get left arm of GInteraction

Usage

```
get_arm_a(gi)
```

Arguments

`gi`	GInteractions object

Value

Granges object with the left (A) region

`get_arm_b` *Get right arm of GInteraction*

Description

Get right arm of GInteraction

Usage

```
get_arm_b(gi)
```

Arguments

`gi`	GInteractions object

Value

Granges object with the right (B) region

get_char_count_cigar *Count the length of the key type in CIGAR string*

Description

Takes CIGAR operands i.e M,N,S and sums the associated blocks length It is vectorized. i.e supports vector with CIGAR strings

Usage

```
get_char_count_cigar(strings, s)
```

Arguments

strings	CIGAR string vector
s	CIGAR operands

Value

vector with length values

Examples

```
# From a vector
get_char_count_cigar(c("4S18M22S", "25S26M"), "S")
get_char_count_cigar(c("18M22S", "20M20S"), "M")
```

get_chimeric_junctions_onestrand *Get chimeric junctions*

Description

Returns chimeric junction defined as range distance between the end and the start of the first and second range respectively

Usage

```
get_chimeric_junctions_onestrand(gi_intra)
```

Details

If the pair of interacting ranges is not on the same strand and chromosome, returns error

Value

Granges object with the

get_colnames_and_types_for_input *Get colnames for expected data types*

Description

Get colnames for expected data types

Usage

```
get_colnames_and_types_for_input(nameset)
```

Arguments

nameset	name of the table

Value

character vector

makeDfFromGi *Convert GInteractions to tibble*

Description

Converts GInteractions to tibble, preserves metadata

Usage

```
makeDfFromGi(gi)
```

Arguments

gi	GInteracttions

Details

Following naming conventions is used for region coordinates: c('chromA','startA','endA','strandA', 'chromB','startB','endB','strandB')

Value

tibble preserving metadata columns

See Also

makeGiFromDf()

Examples

```
data(RNADuplexesSmallGI)
converted_to_df <- makeDfFromGi(SampleSmallGI)
converted_to_gi <- makeGiFromDf(converted_to_df)
```

`makeGiFromDf` *Convert Dataframe to GInteractions*

Description

Converts dataframe-like object to the `GInteractions`.

Usage

```
makeGiFromDf(df)
```

Arguments

`df`	dataframe-like object. Should be convertable to tibble::tibble()

Details

arms will be consistent between different objects of same reference Following columns are looked up in input dataframe to parse region coordinates: c("chromA','startA','endA','strandA',"chromB",'startB','endB','strandB') `GInteractions(mode='strict')` is enforced, to ensure that the order of the regions Extra columns are stored as metadata fields

Value

GInteractions(mode='strict')

See Also

`makeDfFromGi()`

Examples

```
# load example GInteractions
data(RNADuplexesSmallGI)

converted_to_df <- makeDfFromGi(SampleSmallGI)
converted_to_gi <- makeGiFromDf(converted_to_df)
```

preproc_chim_junction_out_pe

Processing of of the STAR PE Chimeric.junction.out

Description

Calculates alignment coordinates and returns reads with categories

Usage

```
preproc_chim_junction_out_pe(dt, keep_all_columns = FALSE)
```

Arguments

dt	Chimeric.out.junction with the correct column names
keep_all_columns	• TRUE or FALSE. Keep CIGAR strings and junction coordinate columns

Details

#'

multimap multi-mapped read

multigap more than one junction (more than two 'N' in CIGAR string)

bad junction Artifacts. I.e alignments for both arms are continious, but with 'backward' chimeric junction was wrongly put

Value

tibble with annotated reads

preproc_chim_junction_out_se

Processing of of the STAR SE Chimeric.junction.out

Description

Calculates alignment coordinates and returns reads with categories

Usage

```
preproc_chim_junction_out_se(dt, keep_all_columns = FALSE)
```

Arguments

dt	Chimeric.out.junction with the correct column names
keep_all_columns	• TRUE or FALSE. Keep CIGAR strings and junction coordinate columns

Details

#'

multimap multi-mapped read

multigap more than one junction (more than two 'N' in CIGAR string)

bad junction Artifacts. I.e alignments for both arms are continious, but with 'backward' chimeric junction was wrongly put

Value

tibble with annotated reads

See Also

col_check_rename()

---

preproc_generic *Preprocess .bedpe input*

Description

Searches for the multi-mapped and bad reads (overlapping arms) Adds 'multimap', 'bad_junction' columns filled with 0 or 1 and 'multigap' = 0 for consistency with other pre-processing methods

Usage

```
preproc_generic(dt, keep_all_columns = TRUE)
```

Arguments

dt	dataframe with reads aligned to strictly two loci
keep_all_columns	keeep columns apart form the required from .bedpe format

Value

pre-processed dataframe

preproc_generic_gi *Preprocess GInteractions input*

Description

Searches for the multi-mapped reads (overlapping arms) Adds 'multimap', 'bad_junction' columns filled with 0/1 and 'multigap' = 0 for consistency with other pre-processing methods.

Usage

```
preproc_generic_gi(gi_raw, keep_all_columns = TRUE)
```

Arguments

gi_raw	GInteractions with inpit RNA interactions
keep_all_columns	keep columns apart from those required by .bedpe format

Value

pre-processed dataframe

refresh_gi *Refresh the* GInteractions *object*

Description

Sub-setting the GInteractions object does not reduce its ranges container For some applications, to save memory, we can safely reduce the size of the object by re-creating it. Also, it can be used to ensure the 'strict' mode of the regions in ranges

Usage

```
refresh_gi(gi)
```

Arguments

gi	GInteractions object

Value

GInteractions object with new ranges attribute

RNADuplexesGeneCounts *Gene counts on human chromosome 22, embryonic stem cells*

Description

File generated by mapping with STAR using `--quantMode GeneCounts` see `system.file("extdata/scripts", "DD_data_generation.R", package = "DuplexDiscovereR")` for details on the pre-processing and sub-setting the

Usage

```
data(RNADuplexesSampleData)
```

Format

An object of class `spec_tbl_df` (inherits from `tbl_df`, `tbl`, `data.frame`) with 1445 rows and 2 columns.

Value

`tibble` with columns of Chimeric.junction.out

Source

SequenceReadArcive

RNADuplexesRawBed *Chimeric reads of SPLASH converted to .bedpe fromat*

Description

A Chimeric.out.Junction file with a subset of chr 22 Chimeric reads detected by SPLASH protocol in Human embryonic stem cells.

Usage

```
data(RNADuplexesSampleData)
```

Format

An object of class `spec_tbl_df` (inherits from `tbl_df`, `tbl`, `data.frame`) with 2040 rows and 10 columns.

Value

`tibble` with columns of bedpe format

Source

SequenceReadArcive Reads were aligned with STAR and filtered to contain only reads which could be represented as 2-arm chimeric alignments. Converted to the bedpe format see `system.file("extdata/scripts", "DD_data_generation.R", package = "DuplexDiscovereR")` for details on the pre-processing and sub-setting the data

---

RNADuplexesRawChimSTAR

Chimeric reads of SPLASH

Description

A Chimeric.out.Junction file with a subset of chr 22 Chimeric reads detected by SPLASH protocol in Human embryonic stem cells.

Usage

```
data(RNADuplexesSampleData)
```

Format

An object of class `tbl_df` (inherits from `tbl`, `data.frame`) with 5000 rows and 21 columns.

Value

`tibble` with columns of Chimeric.junction.out

Source

SequenceReadArcive Reads were aligned with STAR see `system.file("extdata/scripts", "DD_data_generation.R", package = "DuplexDiscovereR")` for details on the pre-processing and sub-setting the data

---

RNADuplexSampleClustReads

RNA duplex reads of SPLASH, clustered and assigned to duplex groups

---

Description

`GInteractions` read-level object containing processed reads,annotated with duplex group ids, read types gene names and p-values

Usage

```
data(RNADuplexesSampleData)
```

Format

An object of class `StrictGInteractions` of length 2090.

Value

`GInteractions` with

- `n_reads_dg` : number of reads in the duplex group (DG)
- `duplex_id` : temporary id for RNA duplexes which could be found before clustering (duplicated or shifted by couple of nt)
- `dg_id` :id of the duplex group
- `score` : median alignment score in duplex group
- other columns inherited from the STAR Chimeric.out.Junction

Source

SequenceReadArcive Reads were aligned with STAR and duplex groups were identified see `system.file("extdata/script "DD_data_generation.R", package = "DuplexDiscovereR")` for details on the data generation proccedure.

RNADuplexSampleDGs *RNA duplex reads of SPLASH, clustered and collapsed to duplex groups*

Description

`GInteractions` duplex group -level object containing detected duplex groups, annotated with duplex group ids, gene_names and p-values

Usage

```
data(RNADuplexesSampleData)
```

Format

An object of class `StrictGInteractions` of length 79.

Value

`GInteractions` with

- `n_reads` : number of reads in the duplex group (DG)
- `dg_id` :id of the duplex group
- `p_val` : BH adjusted p-value of testing to reject hypothesis of DG arising from random ligation
- `score` : median alignment score in duplex group
- other columns with `.A` and `.B` annotating to which genes either arm of the DG maps

Source

SequenceReadArcive Reads were aligned with STAR and duplex groups were identified see `system.file("extdata/script "DD_data_generation.R", package = "DuplexDiscovereR")` for details on the data generation procedure.

`RNADuplexSampleGI` *RNA duplex reads of SPLASH derived from chimeric alignments*

Description

`GInteractions` read-level object containing two-arm chimeric reads extracted from mapping output and which can be represented in the `GInteraction` object

Usage

```
data(RNADuplexesSampleData)
```

Format

An object of class `StrictGInteractions` of length 2090.

Details

see `system.file("extdata/scripts", "DD_data_generation.R", package = "DuplexDiscovereR")` for details on the data generation proccedure.

Value

`GInteractions` with

- `readname` : read name
- `map_type` : type of the mapped read (2arm by design of pre-filtering)
- `junction_type` : if read jucntion is too short, or it not a 'true' ligated reads because of the jucntoin coincides with splice junction
- cigar_aln* columns inherited from the STAR Chimeric.out.Junction output

Source

SequenceReadArcive

`runDuplexDiscoPreproc` *Run pre-processing of chimeric reads input*

Description

Imports dataframe with reads (*.bedpe* or *Chimeric.out.junction*) or `GInteractions` object. Checks column names or tries to quess them if not provided. Adds necessary annotation depending on the input type, For *STAR* input, calculates length of the alignments and marks unique 2-arm alignments. For the *.bedpe* or `GInteractions` input, all entries are already represented as reads with two different aligned parts (2-arm), so only check for unique readname is performed.

Usage

```
runDuplexDiscoPreproc(
  data,
  table_type,
  library_type = "SE",
  keep_metadata = TRUE,
  return_gi = FALSE,
  min_arm_len = 15
)
```

Arguments

`data`	Either dataframe-like object: *Chimeric.out.junction* from *STAR* or *.bedpe* - formatted or `GInteractions` object from **InteractionSet** package
`table_type`	in `c("STAR","bedpe")` for Chimeric.out.Junction or generic input
`library_type`	`c("SE","PE")` for pair- or single- end input
`keep_metadata`	`c(TRUE,FALSE)` Whether extra fields like CIGAR strings and junction coordinates should be kept
`return_gi`	if the return object should be `GInteractions`
`min_arm_len`	minimum allowed length of the alignment arm. Read will be dropped if either arm is shorter

Details

If not existed, adds fields required for the downstream steps: 'readname', 'map_type', 'score', 'n_reads'. 'map_type' field determines the type of the chimeric read:

multimap multi-mapped read

multigap more than one junction (more than two 'N' in CIGAR string)

bad junction Artifacts or possibly unaccounted types. I.e alignments for both arms are continuous, but with 'backward' chimeric junction was wrongly introduced in the mapping

Value

tibble with new metadata fields OR GInteractions if `return_gi` is set to TRUE

Examples

```
# load data
data(RNADuplexesSampleData)
# with bedpe input
preproc_reads <- runDuplexDiscoPreproc(RNADuplexesRawBed, table_type = "bedpe")
# with STAR input
preproc_reads_star <- runDuplexDiscoPreproc(RNADuplexesRawChimSTAR,
    table_type = "STAR",
    keep_metadata = FALSE
)
```

`runDuplexDiscoverer` *Executes all steps of DuplexDiscovereR pipeline*

Description

Generates GInteractions object with duplex groups from the STAR Chimeric.out.junction or bedpe file. Classifies reads, annotates reads by overlap with the gene or transcript features, calculates p-values and hybridization energies. Additionally, returns mappings from duplex groupd back to genes.

Usage

```
runDuplexDiscoverer(
  data,
  table_type = "",
  junctions_gr = NULL,
  anno_gr = NULL,
  anno_gr_keys = c("gene_id", "gene_name", "gene_type"),
  fafile = NULL,
  df_counts = NULL,
  sample_name = "sample",
  lib_type = "SE",
  min_junction_len = 5,
  max_gap = 50,
  min_arm_ratio = 0.1,
  min_overlap = 10,
  max_sj_shift = 10,
  gap_collapse_similar = 2,
  collapse_n_inter = 5,
  trim_alignments = FALSE,
  trim_length = 40,
  min_arm_len = 9,
```

```
  compute_p_values = TRUE,
  compute_odds_test_p_values = FALSE
)
```

Arguments

data	dataframe-like object with the split reads. Output of Chimeric.out.junction or dataframe with fileds defined by bedpe format: c("chromA","startA",'endA',"chromB",'startB','endB','rea ...) Alternatively, `GInteractions` object
table_type	one in c("STAR","bedpe") Defines the type of the input dataframe. ignored if input data is `GInteractions`
junctions_gr	**GRanges** object with the splice junction coordinates
anno_gr	**GRanges** object to use for the annotation of the interactions. Optional
anno_gr_keys	c() vector with names of metadata fields in anno_gr which will be used for the annotation. Argument passed to `annotateGI()` function. The c('gene_id','gene_name','gene_type') columns in anno_gr are used by default.
fafile	path to the genome .fasta file. Used to calculate hybridization energy with *RNADuplex*. Sequence names should correspond to the sequences from which the mapping index was created. Optional
df_counts	A two- column dataframe with counts. Counts are used for p-value calculation. The first column should match the 'gene_id' feature in anno_gr. The second column is the respective count. Optional
sample_name	A name of the sample, used for assembling the analysis statistics dataframe
lib_type	one in c('SE','PE'). Type of the seqeuncing library. Default is 'SE'
min_junction_len	a minimum allowed distance between chimeric arms for the read input. Reads with the junction closer than `min_junction_len` are annotated as '2arm_shot' and not clustered to duplex groups
max_gap	Parameter for read clustering. Minimum required shift between start and end coordinates of arms for pair of overlapping chimeric reads. If the shift is longer than `max_gap` for either arm, then total read overlap between those reads is zero.
min_arm_ratio	Parameter for read clustering. If the overlap-to-span ratio for either arm (A or B) for pair of chimeric reads is less than `min_arm_ratio`, then the total overlap for this pair is set to zero.
min_overlap	Parameter for read clustering. Minimum required overlap to for either arm (A or B) for pair of chimeric reads.
max_sj_shift	Maximum shift between either donor and acceptor splice sites and chimeric junction coordinates to count chimeric junction as splice junction
gap_collapse_similar	Parameter for read clustering (iterative step). Analogous to the max_gap, but applied `collapse_n_inter` times during the iterative merging step. Reduce this to 1 or 2 to lower RAM usage for clustering the library with many similar reads.

`collapse_n_inter`
: Parameter for read clustering (iterative step). Number of iterations to repeat step of collapsing of the highly similar chimeric reads. Increasing this from i.e 0 to 5 reduces clustering time and memory for the libraries with many overlapping reads.

`trim_alignments`
: TRUE or FALSE. Whether to trim arms alignments to 'trim_length' nucleotide around chimeric junction

`trim_length`
: target size of trimmed alignment

`min_arm_len`
: minimum allowed length of the alignment arm. Read will be dropped if either arm is shorter

`compute_p_values`
: TRUE or FALSE. whether to calcualte random ligation test with binominal ligation model

`compute_odds_test_p_values`
: TRUE or FALSE. Whether to calcualte odds-ratio random ligation test.

Details

This is a main function to do the initial discovery of the RNA duplexes after the chimeric read mapping. It wraps following procedures:

- Classifies the input reads by the mapping type. Keeps 2-arm chimeric reads for downstream analysis
- Compares 2arm duplex reads against provided splice junctions
- Classifies 2arm duplexes into spurious self-overlapping, splice junction categoris
- Performs clustering of the remaining reads into duplex groups
  - Collapses identically mapped reads
  - Collapses closely located reads, almost identical reads
  - Finds duplex groups throughout whole data set
- Annotates duplex groups with genomic features if annotation is provided
- Calculates p-values if gene counts and annotation are provided
- Calculates hybridization energies if path to the .fasta file is provided

Value

a list with the following keys

`duplex_groups` `GInteractions` object with chimeric reads clustered duplex groups

`chimeric_reads` `GInteractions` object with non-collapsed chimeric reads

`reads_classes` `tbl_df` dataframe parallel to the the input dataframe, annotated with read categories and duplex groups

`chimeric_reads_stats` `tbl_df` dataframe containing read type classification statistics

`run_stats` `tbl_df` dataframe with the time and memory info about the run

See Also

DuplexDiscovererResults()

Examples

```
library(DuplexDiscovereR)
# load data
data("RNADuplexesSampleData")
result <- runDuplexDiscoverer(
    data = RNADuplexesRawChimSTAR,
    junctions_gr = SampleSpliceJncGR,
    anno_gr = SampleGeneAnnoGR,
    df_counts = RNADuplexesGeneCounts,
    sample_name = "test clustering",
    fafile = NULL,
    collapse_n_inter = 3,
    lib_type = "SE",
    table_type = "STAR"
)
# see results object
print(result)
# duplex groups
dd_get_duplex_groups(result)
# individual chimeric reads
dd_get_chimeric_reads(result)
# counts of detected read tyoes
dd_get_chimeric_reads_stats(result)
```

SampleGeneAnnoGR *Gene coordinates on human chromosome 22*

Description

Granges containing gene coordinates of human chromosome 22 obtained from GENCODEv44 annotaion

Usage

```
data(RNADuplexesSampleData)
```

Format

An object of class GRanges of length 1445.

Details

see `system.file("extdata/scripts", "DD_data_generation.R", package = "DuplexDiscovereR")` for details

Value

statdatd GENCODE gtf fields

Source

GENCODEv44

SampleSmallGI *RNA duplex reads of SPLASH derived from chimeric alignments*

Description

GInteractions object containing two-arm chimeric reads extracted from mapping output and which can be represented in the GInteraction object and subset to chr22: 23877144-45562960 '*'

Usage

```
data(RNADuplexesSmallGI)
```

Format

An object of class StrictGInteractions of length 14.

Details

see `system.file("extdata/scripts", "DD_data_generation.R", package = "DuplexDiscovereR")` for details on the data generation procedure.

Source

SequenceReadArcive

SampleSpliceJncGR *Gene coordinates on human chromosome 22*

Description

Granges containing coordinates of splice junctions human chromosome 22 obtained from GENCODEv44 annotaion

Usage

```
data(RNADuplexesSampleData)
```

Format

An object of class GRanges of length 8465.

Details

see system.file("extdata/scripts", "DD_data_generation.R", package = "DuplexDiscovereR") for details

Value

statdatd GENCODE gtf fields

Source

GENCODEv44

---

show,DuplexDiscovererResults-method

Show Method for DuplexDiscovererResults class

Description

This method provides a summary of the DuplexDiscovererResults object. It prints chimeric_reads_stats followed by the run_stats.

Usage

```
## S4 method for signature 'DuplexDiscovererResults'
show(object)
```

Arguments

object	A DuplexDiscovererResults object.

Value

None. Prints a formatted summary.

show,DuplexTrack-method *Show method for DuplexTrack*

Description

Show method for DuplexTrack

Usage

```
## S4 method for signature 'DuplexTrack'
show(object)
```

Arguments

object	DuplexTrack.

Value

class representation

Examples

```
library(InteractionSet)
anchor1 <- GRanges(
    seqnames = "chr1",
    ranges = IRanges(
        start = c(100, 600, 1100, 1600, 2100),
        end = c(200, 700, 1200, 1700, 2200)
    ),
    strand = "+"
)
anchor2 <- GRanges(
    seqnames = "chr1",
    ranges = IRanges(
        start = c(300, 800, 1300, 1800, 2300),
        end = c(400, 900, 1400, 1900, 2400)
    ),
    strand = "+"
)

interactions <- GInteractions(anchor1, anchor2, mode = "strict")
gr_region <- range(anchor1, anchor2)
a <- DuplexTrack(interactions, gr_region = gr_region, stacking = "dense")
show(a)
```

subset_gi *Subset the* GInteractions *object to single interaction*

Description

Sub-setting the GInteractions object does not reduce its ranges container This function selects Ginteraction by index and reduces the ranges

Usage

```
subset_gi(gi, k)
```

Arguments

gi	GInteractions object

Value

GInteractions with the range atribure reduced to single interaction

trimAroundJunction *Extract regions around chimeric junction*

Description

Trim alignements to contain only 'extract len' nucleotides adajcent to the chimeric junction

Usage

```
trimAroundJunction(dt, extract_len = 30)
```

Arguments

dt	table with the
extract_len	the length of the seqeunce to trim

Details

In case of the long alignemtns, it may be necessary trim chimeric alignments to identify RNA duplex. If 'extract_len' is longer than the read alignemnt length, then no trimming is performed

Value

dataframe with the trimmed alignments

Examples

```
data("RNADuplexesSampleData")
dt_preproc <- runDuplexDiscoPreproc(RNADuplexesRawChimSTAR,
    table_type = "STAR", library_type = "SE"
)
trimAroundJunction(dt_preproc, 40)
```

`writeGiToSAMfile` *Write reads to sam file*

Description

Writes interactions to the sam file for visualization in extrnal browsers. Takes input as GInteractions object containing reads or duplex groups.

Usage

```
writeGiToSAMfile(
  gi_coords,
  file_out,
  distance_chim_junction = 10000,
  read_name_column = "readname",
  id_column = "dg_id",
  genome = "",
  sample_name = "noname_sample"
)
```

Arguments

`gi_coords`	input Ginteraction object
`file_out`	path to write output file
`distance_chim_junction`	maximum distance between input duplex groups/reads, which will be represented as the single-line in .sam file. Junction will be output as N- gap. For the interactions with longer distances, chimeric junction will be represented as MR:Z:i tag
`read_name_column`	character field, pointing out to read names. Read names are generated automatically if not provided.
`id_column`	character name of the field containing integer duplex group ids. NA are replaced with zeros
`genome`	character. Genome version. Required for the retrieval of sequence lengths for sam file header- SQ and SN tags. For convenience, hg38 and hg19 chromosome lengths will be assigned automatically. If the value is not in c('hg38','hg19'), seqlengths will be looked for be in attribute in seqlengths() of regions(gi_coords)
`sample_name`	name to use in RG SAM tag in header

Value

no object is returned

Examples

```
# Load test data
data("RNADuplexesSampleData")
# if the input is read-based, it should have integer duplex group ids
# here, we have 2090 reads
length(RNADuplexSampleGI)
# among them 300 reads does not belong to any DG
# missing ids will be converted to 0
table(is.na(RNADuplexSampleGI$dg_id))
tmpf <- tempfile(".sam")
writeGiToSAMfile(
    gi_coords = RNADuplexSampleGI,
    id_column = "dg_id",
    file_out = tmpf,
    distance_chim_junction = 1e5,
    genome = "hg38"
)
```

Index

∗ **datasets**
RNADuplexesGeneCounts, 42
RNADuplexesRawBed, 42
RNADuplexesRawChimSTAR, 43
RNADuplexSampleClustReads, 43
RNADuplexSampleDGs, 44
RNADuplexSampleGI, 45
SampleGeneAnnoGR, 50
SampleSmallGI, 51
SampleSpliceJncGR, 51
∗ **interal**
preproc_chim_junction_out_se, 39
∗ **internal**
.DGIdToDuplexId, 6
.annotateCisTrans, 5
.compute_clusters_comp, 5
.getStartEndOvl, 6
.gv_plotboxes, 7
.gv_updatepars, 7
col_check_rename, 18
drawGD,DuplexTrack-method, 27
get_arm_a, 35
get_arm_b, 35
get_chimeric_junctions_onestrand, 36
get_colnames_and_types_for_input, 37
preproc_chim_junction_out_pe, 39
preproc_generic, 40
preproc_generic_gi, 41
refresh_gi, 41
subset_gi, 54
.DGIdToDuplexId, 6
.addDGidsForTmpDGs, 3
.addGeneCounts, 4
.annotateCisTrans, 5
.compute_clusters_comp, 5
.getStartEndOvl, 6
.gv_plotboxes, 7
.gv_updatepars, 7

annotateGI, 8
availableDisplayPars, 9

calculateLigationPvalues, 10
classifyTwoArmChimeras, 12
clusterDuplexGroups, 13
col_check_rename, 18
col_check_rename(), *40*
collapse_duplex_groups, 17
collapseIdenticalReads, 15
collapseSimilarChimeras, 16
compareMultipleInteractions, 19
computeGISelfOverlaps, 21
convert_gi_to_ranges, 21

dd_get_chimeric_reads, 22
dd_get_chimeric_reads(), *28, 29*
dd_get_chimeric_reads,DuplexDiscovererResults-method (dd_get_chimeric_reads), 22
dd_get_chimeric_reads_stats, 23
dd_get_chimeric_reads_stats(), *28, 29*
dd_get_chimeric_reads_stats,DuplexDiscovererResults-method (dd_get_chimeric_reads_stats), 23
dd_get_duplex_groups, 24
dd_get_duplex_groups(), *28, 29*
dd_get_duplex_groups,DuplexDiscovererResults-method (dd_get_duplex_groups), 24
dd_get_reads_classes, 25
dd_get_reads_classes(), *28, 29*
dd_get_reads_classes,DuplexDiscovererResults-method (dd_get_reads_classes), 25
dd_get_run_stats, 26
dd_get_run_stats(), *28, 29*
dd_get_run_stats,DuplexDiscovererResults-method (dd_get_run_stats), 26
drawGD,DuplexTrack-method, 27
DuplexDiscovereR, 27

DuplexDiscovereR-package (DuplexDiscovereR), 27
DuplexDiscovereR::getChimericJunctionTypes(), 13
DuplexDiscovereR::getSpliceJunctionChimeras(), 13
DuplexDiscovererResults (DuplexDiscovererResults-class), 28
DuplexDiscovererResults(), 50
DuplexDiscovererResults-class, 28
DuplexTrack, 29

get_arm_a, 35
get_arm_b, 35
get_char_count_cigar, 36
get_chimeric_junctions_onestrand, 36
get_colnames_and_types_for_input, 37
getChimericJunctionTypes, 32
getRNAHybrids, 33
getSpliceJunctionChimeras, 34

InteractionSet::findOverlaps(), 21

makeDfFromGi, 37
makeDfFromGi(), 38
makeGiFromDf, 38
makeGiFromDf(), 37

preproc_chim_junction_out_pe, 39
preproc_chim_junction_out_se, 39
preproc_generic, 40
preproc_generic_gi, 41

refresh_gi, 41
RNADuplexesGeneCounts, 42
RNADuplexesRawBed, 42
RNADuplexesRawChimSTAR, 43
RNADuplexSampleClustReads, 43
RNADuplexSampleDGs, 44
RNADuplexSampleGI, 45
runDuplexDiscoPreproc, 46
runDuplexDiscoverer, 47

SampleGeneAnnoGR, 50
SampleSmallGI, 51
SampleSpliceJncGR, 51
show,DuplexDiscovererResults-method, 52
show,DuplexTrack-method, 53
subset_gi, 54
trimAroundJunction, 54
writeGiToSAMfile, 55