Package 'InteractiveComplexHeatmap'

November 12, 2026

Type Package

Title Make Interactive Complex Heatmaps

Version 1.20.0

Date 2025-01-30

Depends R (>= 4.0.0), ComplexHeatmap (>= 2.11.0)

Imports grDevices, stats, shiny, grid, GetoptLong, S4Vectors (>= 0.26.1), digest, IRanges, kableExtra (>= 1.3.1), utils, svglite, htmltools, clisymbols, jsonlite, RColorBrewer, fontawesome

Suggests knitr, rmarkdown, testthat, EnrichedHeatmap, GenomicRanges, data.table, circlize, GenomicFeatures, tidyverse, tidyHeatmap, cluster, org.Hs.eg.db, simplifyEnrichment, GO.db, SC3, GOexpress, SingleCellExperiment, scater, gplots, pheatmap, airway, DESeq2, DT, cola, BiocManager, gridtext, HilbertCurve (>= 1.21.1), shinydashboard, SummarizedExperiment, pkgndep, ks

VignetteBuilder knitr

Description This package can easily make heatmaps which are produced by the ComplexHeatmap package into interactive applications. It provides two types of interactivities:
1. on the interactive graphics device, and 2. on a Shiny app. It also provides functions for integrating the interactive heatmap widgets for more complex Shiny app development.

biocViews Software, Visualization, Sequencing

URL https://github.com/jokergoo/InteractiveComplexHeatmap

BugReports https://github.com/jokergoo/InteractiveComplexHeatmap/issues

License MIT + file LICENSE

git_url https://git.bioconductor.org/packages/InteractiveComplexHeatmap

git_branch RELEASE_3_23

git_last_commit 9ffb2b9

git_last_commit_date 2026-04-28

Repository Bioconductor 3.23

Date/Publication 2026-11-11

Author Zuguang Gu [aut, cre] (ORCID: <https://orcid.org/0000-0002-7395-8709>)

Maintainer Zuguang Gu <guzuguang@suat-sz.edu.cn>

Contents

all_column_indices . . . 2
all_row_indices . . . 3
getPositionFromBrush . . . 3
getPositionFromClick . . . 4
getPositionFromDblclick . . . 5
getPositionFromHover . . . 5
HeatmapInfoOutput . . . 6
htPositionsOnDevice . . . 7
htShiny . . . 8
htShinyExample . . . 11
ht_shiny . . . 11
interactivate . . . 12
interactivate.DESeqDataSet . . . 13
interactivate.kde . . . 13
interactivateDensity2D . . . 14
InteractiveComplexHeatmapModal . . . 15
InteractiveComplexHeatmapOutput . . . 17
InteractiveComplexHeatmapWidget . . . 19
is_in_sub_heatmap . . . 21
makeInteractiveComplexHeatmap . . . 21
originalHeatmapOutput . . . 23
rand_mat . . . 24
record_observation . . . 25
selectArea . . . 26
selectPosition . . . 27
subHeatmapOutput . . . 28

Index **29**

`all_column_indices` *Get all column indicies from the selected data frame*

Description

Get all column indicies from the selected data frame

Usage

```
all_column_indices(df)
```

Arguments

df	The selected data frame.

Examples

```
# There is no example
NULL
```

---

all_row_indices *Get all row indicies from the selected data frame*

Description

Get all row indicies from the selected data frame

Usage

```
all_row_indices(df)
```

Arguments

df	The selected data frame.

Examples

```
# There is no example
NULL
```

---

getPositionFromBrush *Get the position of the brushed area on the heatmap image*

Description

Get the position of the brushed area on the heatmap image

Usage

```
getPositionFromBrush(brush, ratio = 1)
```

Arguments

brush	The input brush object. Assume heatmap_brush is the ID set to argument brush in plotOutput, then the value here is input$heatmap_brush.
ratio	The relative resolution. The value should the ratio between res set in makeInteractiveComplexHeatmap and 72 (res/72).

Value

A list of length two. The two elements correspons to the coordinates of the two diagonal points.

See Also

getPositionFromClick, getPositionFromHover, getPositionFromDblclick.

Examples

```
# There is no example
NULL
```

---

getPositionFromClick *Get the position of clicked point on the heatmap image*

Description

Get the position of clicked point on the heatmap image

Usage

```
getPositionFromClick(click, ratio = 1)
```

Arguments

click	The input click object. Assume heatmap_click is the ID set to argument click in plotOutput, then the value here is input$heatmap_click.
ratio	The relative resolution. The value should the ratio between res set in makeInteractiveComplexHeatmap and 72 (res/72).

Value

A unit object of length two which are the coordinates of the clicked points.

See Also

getPositionFromBrush, getPositionFromHover, getPositionFromDblclick.

Examples

```
# There is no example
NULL
```

getPositionFromDblclick *Get the position of double clicked point on the heatmap image*

Description

Get the position of double clicked point on the heatmap image

Usage

```
getPositionFromDblclick(dblclick, ratio = 1)
```

Arguments

dblclick	The input dblclick object. Assume heatmap_dblclick is the ID set to argument dblclick in plotOutput, then the value here is input$heatmap_dblclick.
ratio	The relative resolution. The value should the ratio between res set in makeInteractiveComplexHeatmap and 72 (res/72).

Value

A unit object of length two which are the coordinates of the double clicked points.

Examples

```
# There is no example
NULL
```

getPositionFromHover *Get the position of hovered point on the heatmap image*

Description

Get the position of hovered point on the heatmap image

Usage

```
getPositionFromHover(hover, ratio = 1)
```

Arguments

hover	The input hover object. Assume heatmap_hover is the ID set to argument hover in plotOutput, then the value here is input$heatmap_hover.
ratio	The relative resolution. The value should the ratio between res set in makeInteractiveComplexHeatmap and 72 (res/72).

Value

A unit object of length two which are the coordinates of the hover points.

Examples

```
# There is no example
NULL
```

HeatmapInfoOutput *UI for the output*

Description

UI for the output

Usage

```
HeatmapInfoOutput(heatmap_id, title = NULL, width = 400,
    output_ui = default_output_ui(heatmap_id),
    output_ui_float = FALSE, action = NULL, response = NULL, internal = FALSE)
```

Arguments

heatmap_id	ID of the plot.
title	Title of the output.
width	Width of the output div.
output_ui	A htmlOutput or other *Output object (defined in shiny or other related packages).
output_ui_float	Whether the UI defined by output_ui floats at the mouse positions.
action	It is only used when output_ui_float = TRUE to properly bind the floating frame to the event on heatmap (i.e. click, hover or dblclick). If HeatmapInfoOutput is executed after originalHeatmapOutput, the value for it is automatically decided
response	It is only used when output_ui_float = TRUE and response = "brush" or response = "brush-output", so that single clicking or hovering won't have any effect, in other word, there is only response from brushing. If HeatmapInfoOutput is executed after originalHeatmapOutput, the value for it is automatically decided
internal	Internally used.

See Also

originalHeatmapOutput, subHeatmapOutput.

Examples

```
# See examples on the help page of originalHeatmapOutput()
```

---

htPositionsOnDevice *Get heatmap positions on the graphics device*

Description

Get heatmap positions on the graphics device

Usage

```
htPositionsOnDevice(ht_list = get_last_ht(), unit = "inch", valueOnly = FALSE,
    include_annotation = FALSE, calibrate = TRUE)
```

Arguments

ht_list	A HeatmapList-class object returned by draw,Heatmap-method or draw,HeatmapList-method. If it is omitted, it uses the last generated heatmap.
unit	The unit.
valueOnly	Whether only return the numeric values.
include_annotation	Internally used.
calibrate	Internally used.

Details

ht_list must have been already updated by draw() function. The function needs to be executed under a graphics device where the heatmap is written.

Value

It returns a DataFrame object of the position of every heatmap slice.

Examples

```
if(dev.interactive()) {
    m = matrix(rnorm(100), 10)
    ht = Heatmap(m, row_km = 2, column_km = 2)
    ht = draw(ht)
    pos = htPositionsOnDevice(ht)

    InteractiveComplexHeatmap:::redraw_ht_vp(pos)
}
```

htShiny *Interactive heatmaps as a Shiny app*

Description

Interactive heatmaps as a Shiny app

Usage

```
htShiny(ht_list = get_last_ht(), title = NULL,
    description = NULL, hline = TRUE, html = NULL,

    # parameters passed to InteractiveComplexHeatmapOutput()
   heatmap_id = NULL, title1 = "Original heatmap", title2 = "Selected sub-heatmap",
    width1 = ifelse(layout == "1|(2-3)", 800, 450),
    height1 = ifelse(layout == "1-(2|3)", 700, 350),
    width2 = 400,
    height2 = 350,
    width3 = ifelse(layout == "(1-2)|3", 800, 400),
    layout = ifelse("brush" %in% response, "(1-2)|3", "1-3"), compact = FALSE,
    action = "click", cursor = TRUE, response = c(action, "brush"),
    brush_opt = list(stroke = "#f00", opacity = 0.6),
    output_ui_float = FALSE,

    # specific for sub-heatmap
    show_cell_fun = TRUE, show_layer_fun = TRUE,

    save = NULL, app_options = list())
```

Arguments

ht_list	A Heatmap-class or a HeatmapList-class object. If it is not specified, the last generated heatmap is used. The heatmap object should better be already updated by draw() function.
title	Title of the app.
description	Description of the app. The content will be wrapped by a p tag and inserted before the interactive heatmap widget.
hline	Whether to add the horizontal line (by hr tag) after description.
html	HTML fragment inserted below the heatmap. The value can be a string or be wrapped by HTML.
heatmap_id	Pass to InteractiveComplexHeatmapOutput.
title1	Pass to InteractiveComplexHeatmapOutput.
title2	Pass to InteractiveComplexHeatmapOutput.
width1	Pass to InteractiveComplexHeatmapOutput.

height1	Pass to InteractiveComplexHeatmapOutput.
width2	Pass to InteractiveComplexHeatmapOutput.
height2	Pass to InteractiveComplexHeatmapOutput.
width3	Pass to InteractiveComplexHeatmapOutput.
layout	Pass to InteractiveComplexHeatmapOutput.
compact	Pass to InteractiveComplexHeatmapOutput.
action	Pass to InteractiveComplexHeatmapOutput.
cursor	Pass to InteractiveComplexHeatmapOutput.
response	Pass to InteractiveComplexHeatmapOutput.
brush_opt	Pass to InteractiveComplexHeatmapOutput.
output_ui_float	Pass to InteractiveComplexHeatmapOutput.
show_cell_fun	Whether show graphics made by cell_fun on the main heatmap?
show_layer_fun	Whether show graphics made by cell_fun on the main heatmap?
save	The value can be set to a folder name so that the shiny app is saved into several files.
app_options	All pass to the options argument in shinyApp.

Details

With any Heatmap/HeatmapList object, directly send to htShiny() to create a Shiny app for the heatmap(s):

```
htShiny(ht_list)
```

If the heatmaps are already drawn, ht_list can be omitted and the last heatmap object is retrieved automatically:

```
Heatmap(...) + other_heatmaps_or_annotations # or other functions that internally use Heatmap()
  htShiny()
```

Value

A Shiny app object.

See Also

- https://jokergoo.shinyapps.io/interactive_complexheatmap/
- https://jokergoo.shinyapps.io/interactive_complexheatmap_vertical/
- https://jokergoo.shinyapps.io/interactive_densityheatmap/
- https://jokergoo.shinyapps.io/interactive_oncoprint/
- https://jokergoo.shinyapps.io/interactive_enrichedheatmap/
- https://jokergooo.shinyapps.io/interactive_upsetp/

- https://jokergooo.shinyapps.io/interactive_pheatmap/
- https://jokergooo.shinyapps.io/interactive_heatmap/
- https://jokergooo.shinyapps.io/interactive_heatmap_2/
- https://jokergooo.shinyapps.io/interactive_tidyheatmap/

There are also many examples that can be get with htShinyExample.

Examples

```
# use last generated heatmap
if(interactive() && dev.interactive()) {
    m = matrix(rnorm(100), 10)
    Heatmap(m)
    htShiny()
}

# by providing a heatmap/heatmap list
if(interactive()) {
    m = matrix(rnorm(100), 10)
    rownames(m) = 1:10
    colnames(m) = 1:10

    ht = Heatmap(m)
    ht = draw(ht)
    htShiny(ht)
}

# vertical heatmap list
if(interactive()) {
    m1 = matrix(rnorm(100), 10)
    rownames(m1) = 1:10
    colnames(m1) = 1:10
    ht1 = Heatmap(m1, row_km = 2, column_km = 2)

    m2 = matrix(sample(letters[1:10], 100, replace = TRUE), 10)
    ht2 = Heatmap(m2)

    ht_list = draw(ht1 + ht2)
    htShiny(ht_list)

    ht_list = ht1 %v% ht2
    htShiny(ht_list)
}

# compact mode
if(interactive()) {
    m = matrix(rnorm(100), 10)
    Heatmap(m)
    htShiny(compact = TRUE)
}
```

htShinyExample *Examples of interactive complex heatmaps*

Description

Examples of interactive complex heatmaps

Usage

```
htShinyExample(which)
```

Arguments

which	An index of which example to use. The list of all examples can be obtained by executing htShinyExample with no argument.

Details

In every example, there is a Shiny app opened, which also includes source code that generates this app.

Value

A Shiny app object.

Examples

```
# list all examples
htShinyExample()

if(interactive()) {
    htShinyExample(4.2)
}
```

ht_shiny *Interactive heatmaps as a Shiny app*

Description

Interactive heatmaps as a Shiny app

Usage

```
ht_shiny(...)
```

Arguments

...	All goes to htShiny.

Value

A Shiny app object.

Examples

```
# There is no example
NULL
```

`interactivate` *Generic function for interactivate an object in an interactive Shiny app*

Description

Generic function for interactivate an object in an interactive Shiny app

Usage

```
interactivate(x, ...)
```

Arguments

x	An object.
...	Other arguments.

Examples

```
# There is no example
NULL
```

`interactivate.DESeqDataSet` *Visualize DESeq2 result in an interactive Shiny app*

Description

Visualize DESeq2 result in an interactive Shiny app

Usage

```
## S3 method for class 'DESeqDataSet'
interactivate(x, res = DESeq2::results(x), seed = 123, ...)
```

Arguments

`x`	A `DESeqDataSet` class object. It is normally returned by `DESeq`.
`res`	The object returned by `results`.
`seed`	Random seed. It is mainly set for the random colors of annotations.
`...`	Other arguments.

Examples

```
if(interactive()) {
    require(airway)
    data(airway)
    se = airway

    require(DESeq2)
    dds = DESeqDataSet(se, design = ~ dex)
    keep = rowSums(counts(dds)) >= 10
    dds = dds[keep, ]
    dds$dex = relevel(dds$dex, ref = "untrt")
    dds = DESeq(dds)

    interactivate(dds)
}
```

`interactivate.kde` *Interactive Shiny application for 2D density distribution*

Description

Interactive Shiny application for 2D density distribution

Usage

```
## S3 method for class 'kde'
interactivate(x, ...)
```

Arguments

x	a kde object generated by kde.
...	Other arguments.

Examples

```
if(interactive()) {
    require(ks)
   lt = readRDS(system.file("extdata", "2d_density_xy.rds", package = "InteractiveComplexHeatmap"))
    data = cbind(lt$x, lt$y)
    fit = kde(data)
    interactivate(fit)
}
```

---

interactivateDensity2D

Interactive Shiny application for 2D density distribution

Description

Interactive Shiny application for 2D density distribution

Usage

```
interactivateDensity2D(x, y, ...)
```

Arguments

x	A numeric vector.
y	A numeric vector.
...	All pass to kde.

Examples

```
if(interactive()) {
   lt = readRDS(system.file("extdata", "2d_density_xy.rds", package = "InteractiveComplexHeatmap"))
    interactivateDensity2D(lt$x, lt$y)
}
```

InteractiveComplexHeatmapModal *Interactive complex heatmap modal dialog*

Description

Interactive complex heatmap modal dialog

Usage

```
InteractiveComplexHeatmapModal(
    input, output, session, ht_list, heatmap_id = NULL,

    # parameters passed to InteractiveComplexHeatmapOutput()
    title1 = "Original heatmap", title2 = "Selected sub-heatmap",
    width1 = ifelse(layout == "1|(2-3)", 800, 450),
    height1 = ifelse(layout == "1-(2|3)", 700, 350),
    width2 = 370,
    height2 = 350,
    width3 = ifelse(layout == "(1-2)|3", 800, 370),
    layout = ifelse("brush" %in% response, "(1-2)|3", "1-3"), compact = FALSE,
    action = "click", cursor = TRUE, response = c(action, "brush"),
    brush_opt = list(stroke = "#f00", opacity = 0.6),
    output_ui = TRUE, output_ui_float = FALSE,

    # parameters passed to makeInteractiveComplexHeatmap()
    click_action = NULL, brush_action = NULL,

    # other configurations
    js_code = "", close_button = TRUE, cancel_action = c("remove", "hide"))
```

Arguments

input	Passed from the Shiny server function.
output	Passed from the Shiny server function.
session	Passed from the Shiny server function.
ht_list	A Heatmap-class or a HeatmapList-class object.
heatmap_id	ID of the plot. If it is not specified, an internal ID is assigned.
title1	Pass to InteractiveComplexHeatmapOutput.
title2	Pass to InteractiveComplexHeatmapOutput.
width1	Pass to InteractiveComplexHeatmapOutput.
height1	Pass to InteractiveComplexHeatmapOutput.
width2	Pass to InteractiveComplexHeatmapOutput.
height2	Pass to InteractiveComplexHeatmapOutput.

width3	Pass to InteractiveComplexHeatmapOutput.
layout	Pass to InteractiveComplexHeatmapOutput.
compact	Pass to InteractiveComplexHeatmapOutput.
action	Pass to InteractiveComplexHeatmapOutput.
cursor	Pass to InteractiveComplexHeatmapOutput.
response	Pass to InteractiveComplexHeatmapOutput.
brush_opt	Pass to InteractiveComplexHeatmapOutput.
output_ui	Pass to InteractiveComplexHeatmapOutput.
output_ui_float	Pass to InteractiveComplexHeatmapOutput.
click_action	Pass to makeInteractiveComplexHeatmap.
brush_action	Pass to makeInteractiveComplexHeatmap.
js_code	Additional JavaScript code that is put after the interactive heatmap UI. The value can be a text or a function that takes "heatmap ID" as the argument and returns the formatted JavaScript code.
close_button	Whether to add a close button at the end of the widget. If it is FALSE, the widget can be closed by clicking outside of the widget.
cancel_action	Whether to remove the UI from HTML or just hide it when the UI is closed.

Details

It creates an interactive heatmap "modal dialog" according to a certain action.

The function is normally put inside observe or observeEvent.

Value

No value is returned.

Examples

```
if(interactive()) {
    require(ComplexHeatmap)

    ui = fluidPage(
        actionButton("show_heatmap", "Generate_heatmap"),
    )

    server = function(input, output, session) {
        m = matrix(rnorm(100), 10)
        ht = Heatmap(m)

        observeEvent(input$show_heatmap, {
            InteractiveComplexHeatmapModal(input, output, session, ht)
        })
    }
    shiny::shinyApp(ui, server)
}
```

`InteractiveComplexHeatmapOutput` *UI for the interactive complex heatmaps*

Description

UI for the interactive complex heatmaps

Usage

```
InteractiveComplexHeatmapOutput(heatmap_id = NULL,
    title1 = "Original heatmap", title2 = "Selected sub-heatmap",
    title3 = if(output_ui_float) NULL else "Output",
    width1 = ifelse(layout == "1|(2-3)", 800, 450),
    height1 = ifelse(layout == "1-(2|3)", 700, 350),
    width2 = 400,
    height2 = 350,
    width3 = NULL,
    layout = ifelse("brush" %in% response, "(1-2)|3", "1-3"), compact = FALSE,
    action = "click", cursor = TRUE,
    response = c(action, "brush"),
    brush_opt = list(stroke = "#f00", opacity = 0.6),
    output_ui = default_output_ui(heatmap_id),
    output_ui_float = FALSE, containment = FALSE,
    internal = FALSE,
    ...)
```

Arguments

`heatmap_id`	ID of the plot. If it is not specified, an internal ID is assigned.
`title1`	Title of the original heatmap.
`title2`	Title of the sub-heatmap.
`title3`	Title of the output.
`width1`	Width of the original heatmap.
`height1`	Height of the original heatmap.
`width2`	Width of the sub-heatmap.
`height2`	Height of the sub-heatmap.
`width3`	Width of the output div.
`layout`	One of `"(1|2)-3"`, `"1-(2|3)"`, `"1-2-3"`, `"1|2|3"`, `"1|(2-3)"`. If `brush` is not set with the argument `response`, which means there is no sub-heatmap panel, the code `2` can be omitted.
`compact`	If the value is `TRUE`, there will be no sub-heatmap, and output floats at the mouse position when click/hover on the original heatmap.

action	Which action for selecting single cells on the heatmap? Value should be click, hover or dblclick.
cursor	When moving mouse on heatmap, whether to show the cursors on the four sides?
response	Which action needs to be responded on the server side? Value should be in click/hover/dblclick, brush and brush-output. brush responds in two places which are the sub-heatmap and the output components and brush-output only responds in the output component.
brush_opt	A list of parameters passed to brushOpts. Do not set an ID for the brush. An internal brush ID is automatically set.
output_ui	A htmlOutput or other *Output object (defined in shiny or other related packages). If it is set to NULL, there is no output component in the app.
output_ui_float	Whether the UI defined by output_ui floats at the mouse positions.
containment	Whether the resizing is restricted in a certain parent div? Value can be TRUE/FALSE or a JQuery selector.
internal	Internally used.
...	Pass to the UI container which is wrapped by fluidPage.

Details

This function generates HTML fragment for the interactive UI. See the example in makeInteractiveComplexHeatmap page.

layout is defined as follows (1 for the original heatmap, 2 for the selected sub-heatmap and 3 is for the output:

- "(1-2)|3": Heatmap and sub-heatmap are in a same row, and output is in a second row. This is the default layout.
- "1|(2-3)": Heatmap is in a single row, while sub-heatmap and output are in a second row.
- "1-2-3": All three components are in a same row.
- "1|2|3": Each component is in a single row.
- "1-(2|3)": Being different from the other four layouts, this is a two-column layout. Heatmap is in a sigle column. Sub-heatmap and output are vertically aligned and the two are in the second column.

The hover event is implemented with https://github.com/websanova/mousestop .

Value

A UI that can be used in Shiny.

Examples

```
# There is no example
NULL
```

`InteractiveComplexHeatmapWidget` *Interactive complex heatmap widget*

Description

Interactive complex heatmap widget

Usage

```
InteractiveComplexHeatmapWidget(
    input, output, session, ht_list, heatmap_id = NULL, output_id,

    # parameters passed to InteractiveComplexHeatmapOutput()
    title1 = "Original heatmap", title2 = "Selected sub-heatmap",
    width1 = ifelse(layout == "1|(2-3)", 800, 450),
    height1 = ifelse(layout == "1-(2|3)", 700, 350),
    width2 = 370,
    height2 = 350,
    width3 = ifelse(layout == "(1-2)|3", 800, 370),
    layout = ifelse("brush" %in% response, "(1-2)|3", "1-3"), compact = FALSE,
    action = "click", cursor = TRUE, response = c(action, "brush"),
    brush_opt = list(stroke = "#f00", opacity = 0.6),
    output_ui = TRUE, output_ui_float = FALSE,

    # parameters passed to makeInteractiveComplexHeatmap()
    click_action = NULL, brush_action = NULL,

    # other configurations
    js_code = "", close_button = TRUE, cancel_action = c("remove", "hide"))
```

Arguments

`input`	Passed from the Shiny server function.
`output`	Passed from the Shiny server function.
`session`	Passed from the Shiny server function.
`ht_list`	A `Heatmap-class` or a `HeatmapList-class` object.
`heatmap_id`	ID of the plot. If it is not specified, an internal ID is assigned.
`output_id`	Where the heatmap is put.
`title1`	Pass to `InteractiveComplexHeatmapOutput`.
`title2`	Pass to `InteractiveComplexHeatmapOutput`.
`width1`	Pass to `InteractiveComplexHeatmapOutput`.
`height1`	Pass to `InteractiveComplexHeatmapOutput`.
`width2`	Pass to `InteractiveComplexHeatmapOutput`.

height2	Pass to InteractiveComplexHeatmapOutput.
width3	Pass to InteractiveComplexHeatmapOutput.
layout	Pass to InteractiveComplexHeatmapOutput.
compact	Pass to InteractiveComplexHeatmapOutput.
action	Pass to InteractiveComplexHeatmapOutput.
cursor	Pass to InteractiveComplexHeatmapOutput.
response	Pass to InteractiveComplexHeatmapOutput.
brush_opt	Pass to InteractiveComplexHeatmapOutput.
output_ui	Pass to InteractiveComplexHeatmapOutput.
output_ui_float	Pass to InteractiveComplexHeatmapOutput.
click_action	Pass to makeInteractiveComplexHeatmap.
brush_action	Pass to makeInteractiveComplexHeatmap.
js_code	Additional JavaScript code that is put after the interactive heatmap UI. The value can be a text or a function that takes "heatmap ID" as the argument and returns the formatted JavaScript code.
close_button	Whether to add a close button at the end of the widget.
cancel_action	Whether to remove the UI from HTML or just hide it when the UI is closed.

Details

It creates an interactive heatmap widget according to a certain action. The UI is placed to the output ID that user defined.

The function is normally put inside observe or observeEvent.

Value

No value is returned.

Examples

```
if(interactive()) {
    require(ComplexHeatmap)

    ui = fluidPage(
        actionButton("show_heatmap", "Generate_heatmap"),
        htmlOutput("heatmap_output")
    )

    server = function(input, output, session) {
        m = matrix(rnorm(100), 10)
        ht = Heatmap(m)

        observeEvent(input$show_heatmap, {
            InteractiveComplexHeatmapWidget(input, output, session, ht,
                output_id = "heatmap_output")
```

```
        })
    }
    shiny::shinyApp(ui, server)
}
```

`is_in_sub_heatmap` *Test whether it is in sub heatmap*

Description

Test whether it is in sub heatmap

Usage

```
is_in_sub_heatmap()
```

Details

Normally, it is used in `cell_fun`/`layer_fun`.

Examples

```
# There is no example
NULL
```

`makeInteractiveComplexHeatmap` *Process heatmaps on the sever side*

Description

Process heatmaps on the sever side

Usage

```
makeInteractiveComplexHeatmap(input, output, session, ht_list,
    heatmap_id = shiny_env$current_heatmap_id,
    click_action = NULL, hover_action = NULL,
    dblclick_action = NULL, brush_action = NULL, res = 72,
    show_cell_fun = TRUE, show_layer_fun = TRUE)
```

Arguments

input	Passed from the Shiny server function.
output	Passed from the Shiny server function.
session	Passed from the Shiny server function.
ht_list	A Heatmap-class or a HeatmapList-class object.
heatmap_id	The corresponding heatmap ID from the UI. If there is only one interactive heatmap in the app, this argument does not need to be specified and it will use the current one used in InteractiveComplexHeatmapOutput.
click_action	Additional actions on the server side when receiving a click event on the UI. This self-defined function should accept two or four arguments. If it is two arguments, they should be df and output and if it is four arguments, they should be df, input, output and session.
hover_action	Additional actions at the server side when receiving a hover event on the UI.
dblclick_action	Additional actions at the server side when receiving a dblclick event on the UI.
brush_action	Additional actions at the server side when receiving a brush event on the UI.
res	Resolution of the plot, pass to renderPlot.
show_cell_fun	Whether show graphics made by cell_fun on the main heatmap?
show_layer_fun	Whether show graphics made by cell_fun on the main heatmap?

Value

No value is returned.

Examples

```
if(interactive()) {
    ht = Heatmap(m)
    ht = draw(ht)

    ui = fluidPage(
        InteractiveComplexHeatmapOutput()
    )

    server = function(input, output, session) {
        makeInteractiveComplexHeatmap(input, output, session, ht)
    }

    shiny::shinyApp(ui, server)
}
```

originalHeatmapOutput *UI for the original heatmap*

Description

UI for the original heatmap

Usage

```
originalHeatmapOutput(heatmap_id, title = NULL,
    width = 450, height = 350,
    action = "click", cursor = TRUE,
    response = c(action, "brush"),
    brush_opt = list(stroke = "#f00", opacity = 0.6),
    containment = FALSE, internal = FALSE)
```

Arguments

heatmap_id	ID of the plot.
title	Title of the original heatmap.
width	Width of the original heatmap.
height	Height of the original heatmap.
action	Which action for selecting single cells on the heatmap? Value should be `click`, `hover` or `dblclick`.
cursor	When moving mouse on heatmap, whether to show the cursors on the four sides?
response	Which action needs to be responded on the server side? Value should be in `click`/`hover`/`dblclick`, `brush` and `brush-output`. `brush` responds in two places which are the sub-heatmap and the output components and `brush-output` only responds in the output component.
brush_opt	A list of parameters passed to `brushOpts`. Do not set an ID for the brush. An internal brush ID is automatically set.
containment	Whether the resizing is restricted in a certain parent div? Value can be `TRUE`/`FALSE` or a JQuery selector.
internal	Internally used.

See Also

`subHeatmapOutput`, `HeatmapInfoOutput`.

Examples

```
if(interactive()) {
    require(shinydashboard)
    m = matrix(rnorm(100), 10)
    ht = Heatmap(m)

    body = dashboardBody(
        fluidRow(
         box(title = "Original heatmap", width = 4, solidHeader = TRUE, status = "primary",
                originalHeatmapOutput("ht")
            ),
           box(title = "Sub-heatmap", width = 4, solidHeader = TRUE, status = "primary",
                subHeatmapOutput("ht")
            ),
            box(title = "Output", width = 4, solidHeader = TRUE, status = "primary",
                HeatmapInfoOutput("ht")
            )
        )
    )
    ui = dashboardPage(
        dashboardHeader(),
        dashboardSidebar(),
        body
    )
    server = function(input, output, session) {
        makeInteractiveComplexHeatmap(input, output, session, ht, "ht")
    }
    shinyApp(ui, server)
}
```

---

rand_mat *A random matrix*

Description

A random matrix

Usage

```
data(rand_mat)
```

Details

Following code was used to generate `rand_mat`:

```
set.seed(123)
rand_mat = cbind(rbind(matrix(rnorm(20*20, mean = 1, sd = 0.5), nr = 20),
                matrix(rnorm(20*20, mean = 0, sd = 0.5), nr = 20),
                matrix(rnorm(20*20, mean = 0, sd = 0.5), nr = 20)),
```

```
            rbind(matrix(rnorm(20*20, mean = 0, sd = 0.5), nr = 20),
                  matrix(rnorm(20*20, mean = 1, sd = 0.5), nr = 20),
                  matrix(rnorm(20*20, mean = 0, sd = 0.5), nr = 20)),
            rbind(matrix(rnorm(20*20, mean = 0.5, sd = 0.5), nr = 20),
                  matrix(rnorm(20*20, mean = 0.5, sd = 0.5), nr = 20),
                  matrix(rnorm(20*20, mean = 1, sd = 0.5), nr = 20))
          ) + matrix(rnorm(60*60, sd = 0.5), nr = 60)
colnames(rand_mat) = paste0("C", 1:60)
rownames(rand_mat) = paste0("R", 1:60)
```

Author(s)

Zuguang Gu <z.gu@dkfz.de>

Examples

```
data(rand_mat)
rand_mat
```

`record_observation` *Record the observation object*

Description

Record the observation object

Usage

```
record_observation(obs, heatmap_id = shiny_env$current_heatmap_id)
```

Arguments

`obs`	Observation object returned by `observe` or `observeEvent`.
`heatmap_id`	The Heatmap ID.

Examples

```
# There is no example
NULL
```

selectArea *Select an area in the heatmap*

Description

Select an area in the heatmap

Usage

```
selectArea(ht_list = get_last_ht(), pos1 = NULL, pos2 = NULL, mark = TRUE, verbose = TRUE,
    ht_pos = NULL, include_annotation = FALSE, calibrate = TRUE)
```

Arguments

ht_list	A HeatmapList-class object returned by draw,Heatmap-method or draw,HeatmapList-method. If it is omitted, it uses the last generated heatmap.
mark	Whether to mark the selected area as a rectangle.
pos1	If the value is NULL, it can be selected by click on the heatmap (of cource, the heatmap should be on the interactive graphics device). If it is set, it must be a unit object with length two which corresponds to the x and y position of the point.
pos2	Another point as pos1, together with pos1 defines the selected region.
verbose	Whether to print messages.
ht_pos	A value returned by htPositionsOnDevice.
include_annotation	Internally used.
calibrate	Internally used. Mainly works for Rstudio desktop IDE.

Details

The regions can be selected interactively or selected manually by setting pos1 and pos2.

Value

A DataFrame object with row indices and column indices corresponding to the selected region.

Examples

```
if(dev.interactive()) {
    m = matrix(rnorm(100), 10)
    rownames(m) = 1:10
    colnames(m) = 1:10

    ht = Heatmap(m)
    ht = draw(ht)
    selectArea(ht)
```

```
    set.seed(123)
    ht = Heatmap(m, row_km = 2, column_km = 2)
    ht = draw(ht)
    selectArea(ht)
}
```

`selectPosition` *Select a position in the heatmap*

Description

Select a position in the heatmap

Usage

```
selectPosition(ht_list = get_last_ht(), pos = NULL, mark = TRUE, verbose = TRUE,
    ht_pos = NULL, calibrate = TRUE)
```

Arguments

`ht_list`	A `HeatmapList-class` object returned by `draw,Heatmap-method` or `draw,HeatmapList-method`. If it is omitted, it uses the last generated heatmap.
`mark`	Whether to mark the selected position as a point.
`pos`	If the value is `NULL`, it can be selected by click on the heatmap (of cource, the heatmap should be on the interactive graphics device). If it is set, it must be a `unit` object with length two which corresponds to the x and y position of the point.
`verbose`	Whether to print messages.
`ht_pos`	A value returned by `htPositionsOnDevice`.
`calibrate`	Internally used. Mainly works for Rstudio desktop IDE.

Details

The regions can be selected interactively or selected manually by setting `pos`.

Value

A `DataFrame` object with row indices and column indices corresponding to the selected position.

Examples

```
if(dev.interactive()) {
    m = matrix(rnorm(100), 10)
    rownames(m) = 1:10
    colnames(m) = 1:10

    ht = Heatmap(m)
    ht = draw(ht)
    selectPosition(ht)
}
```

---

subHeatmapOutput *UI for the sub-heatmaps*

Description

UI for the sub-heatmaps

Usage

```
subHeatmapOutput(heatmap_id, title = NULL,
    width = 400, height = 350, containment = FALSE, internal = FALSE)
```

Arguments

heatmap_id	ID of the plot.
title	Title of the sub-heatmap.
width	Width of the sub-heatmap.
height	Height of the sub-heatmap.
containment	Whether the resizing is restricted in a certain parent div? Value can be TRUE/FALSE or a JQuery selector.
internal	Internally used.

See Also

originalHeatmapOutput.

Examples

```
# See examples on the help page of originalHeatmapOutput()
```

Index

all_column_indices, 2
all_row_indices, 3

brushOpts, *18*, *23*

DataFrame, *7*, *26, 27*
DESeq, *13*
DESeqDataSet, *13*

fluidPage, *18*

getPositionFromBrush, 3, *4*
getPositionFromClick, *4*, 4
getPositionFromDblclick, *4*, 5
getPositionFromHover, *4*, 5

HeatmapInfoOutput, *6*, 6, *23*
ht_shiny, 11
HTML, *8*
htmlOutput, *6*, *18*
htPositionsOnDevice, 7, *26, 27*
htShiny, 8, *12*
htShinyExample, *10, 11*, 11

interactivate, 12
interactivate.DESeqDataSet, 13
interactivate.kde, 13
interactivateDensity2D, 14
InteractiveComplexHeatmapModal, 15
InteractiveComplexHeatmapOutput, *8, 9*, *15, 16*, 17, *19, 20*, *22*
InteractiveComplexHeatmapWidget, 19
is_in_sub_heatmap, 21

kde, *14*

makeInteractiveComplexHeatmap, *3–5*, *16*, *18*, *20*, 21

observe, *16*, *20*, *25*
observeEvent, *16*, *20*, *25*

originalHeatmapOutput, *6*, 23, *28*

plotOutput, *3–5*

rand_mat, 24
record_observation, 25
renderPlot, *22*
results, *13*

selectArea, 26
selectPosition, 27
shinyApp, *9*
subHeatmapOutput, *6*, *23*, 28

unit, *4–6*, *26, 27*