Package 'MSA2dist'

November 12, 2026

Type Package

Title MSA2dist calculates pairwise distances between all sequences of a DNAStringSet or a AAStringSet using a custom score matrix and conducts codon based analysis

Version 1.16.0

Description MSA2dist calculates pairwise distances between all sequences of a DNAStringSet or a AAStringSet using a custom score matrix and conducts codon based analysis. It uses scoring matrices to be used in these pairwise distance calculations which can be adapted to any scoring for DNA or AA characters. E.g. by using literal distances MSA2dist calculates pairwise IUPAC distances. DNAStringSet alignments can be analysed as codon alignments to look for synonymous and nonsynonymous substitutions (dN/dS) in a parallelised fashion using a variety of substitution models. Non-aligned coding sequences can be directly used to construct pairwise codon alignments (global/local) and calculate dN/dS without any external dependencies.

License GPL-3 + file LICENSE

Encoding UTF-8

LazyData false

biocViews Alignment, Sequencing, Genetics, GO

Depends R (>= 4.4.0)

Imports Rcpp, Biostrings, GenomicRanges, IRanges, ape, doParallel, dplyr, foreach, methods, parallel, pwalign, rlang, seqinr, stats, stringi, stringr, tibble, tidyr, utils

Suggests rmarkdown, knitr, devtools, testthat, ggplot2, BiocStyle

LinkingTo Rcpp, RcppThread

VignetteBuilder knitr

NeedsCompilation yes

SystemRequirements C++11

URL https://gitlab.gwdg.de/mpievolbio-it/MSA2dist, https://mpievolbio-it.pages.gwdg.de/MSA2dist/

BugReports https://gitlab.gwdg.de/mpievolbio-it/MSA2dist/issues

RoxygenNote 7.3.1

git_url https://git.bioconductor.org/packages/MSA2dist

git_branch RELEASE_3_23

git_last_commit 4f21e42

git_last_commit_date 2026-04-28

Repository Bioconductor 3.23

Date/Publication 2026-11-11

Author Kristian K Ullrich [aut, cre] (ORCID:
<https://orcid.org/0000-0003-4308-9626>)

Maintainer Kristian K Ullrich <ullrich@evolbio.mpg.de>

Contents

aa2selfscore . . . 3
aabin2aastring . . . 4
AAMatrix-data . . . 5
aastring2aabin . . . 5
aastring2aln . . . 6
aastring2dist . . . 7
addmask2string . . . 8
addpop2string . . . 9
addpos2string . . . 11
addregion2string . . . 12
aln2aastring . . . 13
aln2dnastring . . . 14
cds2aa . . . 15
cds2codonaln . . . 16
cdsstring2codonaln . . . 17
codon2numberAMBIG . . . 19
codon2numberTCAG . . . 19
codonmat2pnps . . . 20
codonmat2xy . . . 21
compareCodons . . . 23
dnabin2dnastring . . . 24
dnastring2aln . . . 24
dnastring2codonmat . . . 25
dnastring2dist . . . 26
dnastring2dnabin . . . 28
dnastring2kaks . . . 29
GENETIC_CODE_TCAG . . . 31
getmask . . . 32
getpos . . . 33
globalDeletion . . . 34
globalDeletionAA . . . 34

granthamMatrix 35
hiv-data 36
indices2kaks 36
iupac-data 39
iupacMatrix 39
makePostalignedSeqs 40
pal2nal 41
popinteger 42
popnames 43
rcpp_distSTRING 44
rcpp_KaKs 44
rcpp_pairwiseDeletionAA 45
rcpp_pairwiseDeletionDNA 46
region 47
regionused 48
string2region 49
subString 50
uptriidx 51

Index **52**

`aa2selfscore` *aa2selfscore*

Description

This function return the selfscore from an `AAStringSet`.

Usage

```
aa2selfscore(aa, scorematrix = "BLOSUM62")
```

Arguments

`aa`	`AAStringSet` [mandatory]
`scorematrix`	score matrix to use [default: BLOSUM62]

Value

`data.frame`

Author(s)

Kristian K Ullrich

See Also

`XStringSet-class`, `substitution_matrices`

Examples

```
data(woodmouse, package="ape")
#cds2aa(dnabin2dnastring(woodmouse), shorten=TRUE,
#genetic.code=Biostrings::getGeneticCode("2"))
woodmouse |> dnabin2dnastring() |> cds2aa(shorten=TRUE,
genetic.code=Biostrings::getGeneticCode("2")) |> aa2selfscore()
```

---

aabin2aastring *aabin2aastring*

Description

This function converts an ape AAbin into AAStringSet.

Usage

```
aabin2aastring(aabin)
```

Arguments

aabin	ape AAbin [mandatory]

Value

An object of class AAStringSet

Author(s)

Kristian K Ullrich

See Also

as.alignment as.DNAbin.alignment AAStringSet

Examples

```
data(woodmouse, package="ape")
## convert into AAStringSet
#aabin2aastring(ape::trans(woodmouse, 2))
ape::trans(woodmouse, 2) |> aabin2aastring()
```

AAMatrix-data *AAMatrix-data*

Description

`getAAMatrix()` from the `alakazam` package.

Usage

```
data(AAMatrix)
```

Format

an object of class `matrix`

Value

`score matrix`

References

Gupta N, Vander Heiden J, Uduman M, Gadala-Maria D, Yaari G, Kleinstein S (2015) Change-O: a toolkit for analyzing large-scale B cell immunoglobulin repertoire sequencing data. *Bioinformatics.* **31(20)**, 3356-3358.

Examples

```
data("AAMatrix", package="MSA2dist")
```

aastring2aabin *aastring2aabin*

Description

This function converts an `AAStringSet` into an ape `AAbin`.

Usage

```
aastring2aabin(aa)
```

Arguments

aa	`AAStringSet` [mandatory]

Value

An object of class `AAbin`

Author(s)

Kristian K Ullrich

See Also

as.alignment as.DNAbin.alignment

Examples

```
## define two cds sequences
cds1 <- Biostrings::DNAString("ATGCAACATTGC")
cds2 <- Biostrings::DNAString("ATG---CATTGC")
cds1.cds2.aln <- c(Biostrings::DNAStringSet(cds1),
    Biostrings::DNAStringSet(cds2))
## convert into AAbin
#aastring2aabin(cds2aa(cds1.cds2.aln))
cds1.cds2.aln |> cds2aa() |> aastring2aabin()
```

---

aastring2aln *aastring2aln*

Description

This function converts a AAStringSet into an seqinr alignment.

Usage

```
aastring2aln(aa)
```

Arguments

aa	AAStringSet [mandatory]

Value

An object of class alignment which is a list with the following components:
nb the number of aligned sequences
nam a vector of strings containing the names of the aligned sequences
seq a vector of strings containing the aligned sequences
com a vector of strings containing the commentaries for each sequence or NA if there are no comments

Author(s)

Kristian K Ullrich

See Also

as.alignment

Examples

```
## define two cds sequences
cds1 <- Biostrings::DNAString("ATGCAACATTGC")
cds2 <- Biostrings::DNAString("ATG---CATTGC")
cds1.cds2.aln <- c(Biostrings::DNAStringSet(cds1),
    Biostrings::DNAStringSet(cds2))
#aastring2aln(cds2aa(cds1.cds2.aln))
cds1.cds2.aln |> cds2aa() |> aastring2aln()
```

`aastring2dist` *aastring2dist*

Description

This function calculates pairwise distances for all combinations of a `AAStringSet`.

Usage

```
aastring2dist(
  aa,
  threads = 1,
  symmetric = TRUE,
  score = NULL,
  mask = NULL,
  region = NULL
)
```

Arguments

`aa`	`AAStringSet` [mandatory]
`threads`	number of parallel threads [default: 1]
`symmetric`	symmetric score matrix [default: TRUE]
`score`	`score matrix` use a score matrix to calculate distances [mandatory]
`mask`	`IRanges` object indicating masked sites [default: NULL]
`region`	`IRanges` object indicating region to use for dist calculation (by default all sites are used) [default: NULL]

Value

A `data.frame` of pairwise distance values `distSTRING`, sites used `sitesUsed` and region used `regionUsed`

Author(s)

Kristian K Ullrich

See Also

dnastring2dist

Examples

```
## load example sequence data
data("hiv", package="MSA2dist")
#aastring2dist(cds2aa(hiv), score=granthamMatrix())
hiv |> cds2aa() |> aastring2dist(score=granthamMatrix())
## create mask
mask1 <- IRanges::IRanges(start=c(11,41,71), end=c(20,50,80))
## use mask
hiv |> cds2aa() |> aastring2dist(score=granthamMatrix(), mask=mask1)
## use region
region1 <- IRanges::IRanges(start=c(1,75), end=c(45,85))
hiv |> cds2aa() |> aastring2dist(score=granthamMatrix(), region=region1)
## use mask and region
hiv |> cds2aa() |> aastring2dist(score=granthamMatrix(),
    mask=mask1, region=region1)
## use asymmetric score matrix
myscore <- granthamMatrix()
myscore[5, 6] <- 0
h <- hiv |> cds2aa() |> aastring2dist(score=myscore, symmetric=FALSE)
h$distSTRING[1:2, 1:2]
```

---

addmask2string *addmask2string*

Description

This function adds mask information as an IRanges object, START and END information, to a DNAStringSet or an AAStringSet and puts them into the metadata information. This information can be used to restrict the distance calculation to specific regions of the DNAStringSet or the AAStringSet.

Usage

```
addmask2string(seq, mask = NULL, append = TRUE)
```

Arguments

seq	DNAStringSet or AAStringSet [mandatory]
mask	IRanges object [mandatory]
append	indicate if mask should be appended or overwritten [default: TRUE]

Value

An object of class DNAStringSet or AAStringSet

Author(s)

Kristian K Ullrich

See Also

addregion2string, addpop2string, addpos2string

Examples

```
## load example sequence data
data(iupac, package="MSA2dist")
iupac.aa <- iupac |> cds2aa(shorten = TRUE)
## create mask
mask1 <- IRanges::IRanges(start=c(1,41), end=c(20,50))
## add mask
iupac.aa <- iupac.aa |> addmask2string(mask=mask1)
#(iupac.aa |> slot("metadata"))$mask
iupac.aa |> getmask()
## append mask
mask2 <- IRanges::IRanges(start=c(21), end=c(30))
iupac.aa <- iupac.aa |> addmask2string(mask=mask2)
#(iupac.aa |> slot("metadata"))$mask
iupac.aa |> getmask()
## overwrite mask
iupac.aa <- iupac.aa |> addmask2string(mask=mask2, append=FALSE)
#(iupac.aa |> slot("metadata"))$mask
iupac.aa |> getmask()
## reduce by mask
#iupac.aa.region <- iupac.aa |> string2region(mask=
#    (iupac.aa |> slot("metadata"))$mask)
iupac.aa.region <- iupac.aa |> string2region(mask=
    getmask(iupac.aa))
#iupac.aa.region |> slot("metadata")
iupac.aa.region |> getmask()
```

---

addpop2string *addpop2string*

Description

This function adds population information to a DNAStringSet or an AAStringSet and puts them into the metadata information.
__Note__: All unassigned sequences will be put into pop "unassigned"!
Do not use "unassigned" as a population name!
__Note__: Names in a population in the poplist must match sequence names!
__Note__: Duplicated assignments are allowed!

Usage

```
addpop2string(seq, poplist)
```

Arguments

seq	DNAStringSet or AAStringSet [mandatory]
poplist	named list of populations either as index or names per population (do not mix index and names in one population) [mandatory]

Value

An object of class DNAStringSet or AAStringSet

Author(s)

Kristian K Ullrich

See Also

addmask2string, addregion2string, addpos2string

Examples

```
## load example sequence data
data(iupac, package="MSA2dist")
iupac.aa <- iupac |> cds2aa(shorten = TRUE)
## create poplist
poplist <- list(FRA = grep("Mmd.FRA", names(iupac)),
    GER = grep("Mmd.GER", names(iupac)),
    IRA = grep("Mmd.IRA", names(iupac)),
    AFG = grep("Mmm.AFG", names(iupac)))
iupac.aa <- iupac.aa |> addpop2string(poplist)
#(iupac.aa |> slot("metadata"))$pop.integer
iupac.aa |> popinteger()
#(iupac.aa |> slot("metadata"))$pop.names
iupac.aa |> popnames()
## mxixing index and names
poplist <- list(FRA = names(iupac)[grep("Mmd.FRA", names(iupac))],
    GER = grep("Mmd.GER", names(iupac)),
    IRA = names(iupac)[grep("Mmd.IRA", names(iupac))],
    AFG = grep("Mmm.AFG", names(iupac)))
iupac.aa <- iupac.aa |> addpop2string(poplist)
iupac.aa |> popinteger()
iupac.aa |> popnames()
## leaving out some sequences which will be assigned as "unassigned"
poplist <- list(FRA = names(iupac)[grep("Mmd.FRA", names(iupac))],
    GER = grep("Mmd.GER", names(iupac)),
    IRA = names(iupac)[grep("Mmd.IRA", names(iupac))])
iupac.aa <- iupac.aa |> addpop2string(poplist)
iupac.aa |> popinteger()
iupac.aa |> popnames()
```

addpos2string *addpos2string*

Description

This function adds GenomicRanges information, CHROM, START and END to a DNAStringSet or an AAStringSet and puts them into the metadata information. This information can be used to find overlaps with a chromosome wide mask.

Usage

```
addpos2string(seq, chrom = NULL, start = NULL, end = NULL)
```

Arguments

seq	DNAStringSet or AAStringSet [mandatory]
chrom	chromosome name [mandatory]
start	start position [mandatory]
end	end position [mandatory]

Value

An object of class DNAStringSet or AAStringSet

Author(s)

Kristian K Ullrich

See Also

addmask2string, addregion2string, addpop2string

Examples

```
## load example sequence data
data(iupac, package="MSA2dist")
## add position
iupac <- iupac |> addpos2string(chrom="chr1", start=1, end=1000)
#(iupac |> slot("metadata"))$GRanges
iupac |> getpos()
```

addregion2string *addregion2string*

Description

This function adds region information as an IRanges object, START and END information, to a DNAStringSet or an AAStringSet and puts them into the metadata information. This information can be used to restrict the distance calculation to specific regions of the DNAStringSet or the AAStringSet.

Usage

```
addregion2string(seq, region = NULL, append = TRUE)
```

Arguments

seq	DNAStringSet or AAStringSet [mandatory]
region	IRanges object [mandatory]
append	indicate if region should be appended or overwritten [default: TRUE]

Value

An object of class DNAStringSet or AAStringSet

Author(s)

Kristian K Ullrich

See Also

addmask2string, addpop2string, addpos2string

Examples

```
## load example sequence data
data(iupac, package="MSA2dist")
iupac.aa <- iupac |> cds2aa(shorten = TRUE)
## create region
region1 <- IRanges::IRanges(start=c(1,41), end=c(20,50))
## add region
iupac.aa <- iupac.aa |> addregion2string(region=region1)
#(iupac.aa |> slot("metadata"))$region
iupac.aa |> region()
## append region
region2 <- IRanges::IRanges(start=c(21), end=c(30))
iupac.aa <- iupac.aa |> addregion2string(region=region2)
#(iupac.aa |> slot("metadata"))$region
iupac.aa |> region()
```

```
## overwrite region
iupac.aa <- iupac.aa |> addregion2string(region=region2, append=FALSE)
#(iupac.aa |> slot("metadata"))$region
iupac.aa |> region()
## reduce by region
#iupac.aa.region <- iupac.aa |> string2region(region=
#    (iupac.aa |> slot("metadata"))$region)
iupac.aa.region <- iupac.aa |> string2region(region=
    region(iupac.aa))
#iupac.aa.region |> slot("metadata")
iupac.aa.region |> region()
```

---

aln2aastring *aln2aastring*

Description

This function converts a seqinr alignment into an AAStringSet.

Usage

```
aln2aastring(aln)
```

Arguments

aln	seqinr alignment [mandatory]

Value

An object of class AAStringSet

Author(s)

Kristian K Ullrich

See Also

as.alignment AAStringSet

Examples

```
## define two cds sequences
cds1 <- Biostrings::DNAString("ATGCAACATTGC")
cds2 <- Biostrings::DNAString("ATG---CATTGC")
cds1.cds2.aln <- c(Biostrings::DNAStringSet(cds1),
    Biostrings::DNAStringSet(cds2))
#aastring2aln(cds2aa(cds1.cds2.aln))
cds1.cds2.aln |> cds2aa() |> aastring2aln() |> aln2aastring()
```

aln2dnastring *aln2dnastring*

Description

This function converts a seqinr alignment into an DNAStringSet.

Usage

```
aln2dnastring(aln)
```

Arguments

aln	seqinr alignment [mandatory]

Value

An object of class DNAStringSet

Author(s)

Kristian K Ullrich

See Also

as.alignment DNAStringSet

Examples

```
## define two cds sequences
cds1 <- Biostrings::DNAString("ATGCAACATTGC")
cds2 <- Biostrings::DNAString("ATG---CATTGC")
cds1.cds2.aln <- c(Biostrings::DNAStringSet(cds1),
    Biostrings::DNAStringSet(cds2))
## convert into alignment
#dnastring2aln(cds1.cds2.aln)
cds1.cds2.aln |> dnastring2aln()
## convert back into DNAStringSet
#aln2dnastring(dnastring2aln(cds1.cds2.aln))
cds1.cds2.aln |> dnastring2aln() |> aln2dnastring()
```

cds2aa *cds2aa*

Description

This function translates a DNAStringSet into an AAStringSet.

Usage

```
cds2aa(
  cds,
  shorten = FALSE,
  frame = 1,
  framelist = NULL,
  genetic.code = NULL,
  return.cds = FALSE
)
```

Arguments

cds	DNAStringSet [mandatory]
shorten	shorten all sequences to multiple of three [default: FALSE]
frame	indicates the first base of a the first codon [default: 1]
framelist	supply vector of frames for each entry [default: NULL]
genetic.code	The genetic code to use for the translation of codons into Amino Acid letters [default: NULL]
return.cds	return shorten cds instead of aa [default: FALSE]

Value

AAStringSet

Author(s)

Kristian K Ullrich

See Also

XStringSet-class, translate

Examples

```
## define two cds sequences
cds1 <- Biostrings::DNAString("ATGCAACATTGC")
cds2 <- Biostrings::DNAString("ATG---CATTGC")
cds1.cds2.aln <- c(Biostrings::DNAStringSet(cds1),
    Biostrings::DNAStringSet(cds2))
```

```
#cds2aa(cds1.cds2.aln)
cds1.cds2.aln |> cds2aa()
## alternative genetic code
data(woodmouse, package="ape")
#cds2aa(dnabin2dnastring(woodmouse), shorten=TRUE)
woodmouse |> dnabin2dnastring() |> cds2aa(shorten=TRUE)
#cds2aa(dnabin2dnastring(woodmouse), shorten=TRUE,
#genetic.code=Biostrings::getGeneticCode("2"))
woodmouse |> dnabin2dnastring() |> cds2aa(shorten=TRUE,
genetic.code=Biostrings::getGeneticCode("2"))
woodmouse |> dnabin2dnastring() |> cds2aa(shorten=TRUE, return.cds=TRUE) |>
cds2aa(genetic.code=Biostrings::getGeneticCode("2"))
```

---

cds2codonaln *cds2codonaln*

Description

This function takes two single sequence DNAString's or two single sequence DNAStringSet's, converts them into aa, calculates a global alignment and converts this alignment back into a codon alignment.

Usage

```
cds2codonaln(
  cds1,
  cds2,
  type = "global",
  substitutionMatrix = "BLOSUM62",
  gapOpening = 10,
  gapExtension = 0.5,
  remove.gaps = FALSE,
  ...
)
```

Arguments

cds1	single sequence DNAStringSet or DNAString [mandatory]
cds2	single sequence DNAStringSet or DNAString [mandatory]
type	type of alignment (see pairwiseAlignment) [default: global]
substitutionMatrix	substitution matrix representing the fixed substitution scores for an alignment (see pairwiseAlignment) [default: BLOSUM62]
gapOpening	the cost for opening a gap in the alignment (see pairwiseAlignment) [default: 10]
gapExtension	the incremental cost incurred along the length of the gap in the alignment (see pairwiseAlignment) [default: 0.5]

remove.gaps	specify if gaps in the codon alignment should be removed [default: FALSE]
...	other cds2aa parameters

Value

codon alignment as DNAStringSet

Author(s)

Kristian K Ullrich

References

Pagès, H et al. (2014) Biostrings: Efficient manipulation of biological strings. *R package version*, **2(0)**.

See Also

pairwiseAlignment

Examples

```
## define two cds sequences
cds1 <- Biostrings::DNAString("ATGCAACATTGC")
cds2 <- Biostrings::DNAString("ATGCATTGC")
cds2codonaln(cds1, cds2)
```

---

cdsstring2codonaln *cdsstring2codonaln*

Description

This function takes two sequences as DNAStringSet, and their corresponding AAStringSet, calculates a global alignment and converts this alignment back into a codon alignment.

Usage

```
cdsstring2codonaln(
  cds,
  aa,
  type = "global",
  substitutionMatrix = "BLOSUM62",
  gapOpening = 10,
  gapExtension = 0.5,
  remove.gaps = FALSE
)
```

Arguments

cds	two sequences DNAStringSet [mandatory]
aa	two sequences AAStringSet [mandatory]
type	type of alignment (see pairwiseAlignment) [default: global]
substitutionMatrix	substitution matrix representing the fixed substitution scores for an alignment (see pairwiseAlignment) [default: BLOSUM62]
gapOpening	the cost for opening a gap in the alignment (see pairwiseAlignment) [default: 10]
gapExtension	the incremental cost incurred along the length of the gap in the alignment (see pairwiseAlignment) [default: 0.5]
remove.gaps	specify if gaps in the codon alignment should be removed [default: FALSE]

Value

codon alignment as DNAStringSet

Author(s)

Kristian K Ullrich

References

Pagès, H et al. (2014) Biostrings: Efficient manipulation of biological strings. *R package version*, **2(0)**.

See Also

pairwiseAlignment

Examples

```
## define two cds sequences
cds <- Biostrings::DNAStringSet(c("ATGCAACATTGC", "ATGCATTGC"))
names(cds) <- c("cds1", "cds2")
## get protein alignment
aa <- MSA2dist::cds2aa(cds)
cdsstring2codonaln(cds, aa)
```

codon2numberAMBIG *codon2numberAMBIG*

Description

This function converts a codon into a number, but accept N and -.

Usage

```
codon2numberAMBIG(codon)
```

Arguments

codon	[mandatory]

Value

An object of class numeric

Author(s)

Kristian K Ullrich

See Also

GENETIC_CODE

Examples

```
#unlist(lapply(names(Biostrings::GENETIC_CODE), codon2numberAMBIG))
names(Biostrings::GENETIC_CODE) |> codon2numberAMBIG()
```

codon2numberTCAG *codon2numberTCAG*

Description

This function converts a codon into a number.

Usage

```
codon2numberTCAG(codon)
```

Arguments

codon	[mandatory]

Value

An object of class numeric

Author(s)

Kristian K Ullrich

See Also

GENETIC_CODE

Examples

```
#unlist(lapply(names(Biostrings::GENETIC_CODE), codon2numberTCAG))
names(Biostrings::GENETIC_CODE) |> codon2numberTCAG()
```

---

codonmat2pnps *codonmat2pnps*

Description

This function calculates pn/ps according to *Nei and Gojobori (1986)*.

Usage

```
codonmat2pnps(codonmat)
```

Arguments

codonmat	codon matrix of two columns to be compared [mandatory]

Value

An object of class pnps which is a list with the following components:
seq1 sequence1 name
seq2 sequence2 name
Codons sequence2 name
Compared sequence2 name
Ambigiuous sequence2 name
Indels sequence2 name
Ns sequence2 name
Sd sequence2 name
Sn sequence2 name
S sequence2 name
N sequence2 name
ps sequence2 name
pn sequence2 name
pnps sequence2 name

ds sequence2 name
dn sequence2 name
dnds sequence2 name

Author(s)

Kristian K Ullrich

References

Nei and Gojobori. (1986) Simple methods for estimating the numbers of synonymous and nonsynonymous nucleotide substitutions. *Mol. Biol. Evol.*, **3(5)**, 418-426.

Ganeshan et al. (1997) Human immunodeficiency virus type 1 genetic evolution in children with different rates of development of disease. *J. Virology.* **71(1)**, 663-677.

Yang et al. (2000) Codon-substitution models for heterogeneous selection pressure at amino acid sites. *Genetics.* **155(1)**, 431-449.

See Also

kaks

Examples

```
## load example sequence data
data("hiv", package="MSA2dist")
#codonmat2pnps(dnastring2codonmat(hiv)[,c(1, 2)])
(hiv |> dnastring2codonmat())[,c(1, 2)] |> codonmat2pnps()
```

---

codonmat2xy *codonmat2xy*

Description

This function calculates average behavior of each codon for all pairwise comparisons for indels, syn, and nonsyn mutations according to *Nei and Gojobori (1986)*.

Usage

```
codonmat2xy(codonmat, threads = 1)
```

Arguments

codonmat	codon matrix obtained via dnastring2codonmat [mandatory]
threads	number of parallel threads [default: 1]

Value

A `data.frame` object with the following components:
`Codon` Codon index
`n` number of comparison
`SynSum` Sum of syn
`NonSynSum` Sum of nonsyn
`IndelSum` Sum of indels
`SynMean` average syn per codon
`NonSynMean` average nonsyn per codon
`IndelMean` average indels per codon
`CumSumSynMean` cumulative average syn per codon
`CumSumNonSynMean` cumulative average nonsyn per codon
`CumSumIndelMean` cumulative indels per codon

Author(s)

Kristian K Ullrich

References

Nei and Gojobori. (1986) Simple methods for estimating the numbers of synonymous and nonsynonymous nucleotide substitutions. *Mol. Biol. Evol.*, **3(5)**, 418-426.

Ganeshan et al. (1997) Human immunodeficiency virus type 1 genetic evolution in children with different rates of development of disease. *J. Virology.* **71(1)**, 663-677.

Yang et al. (2000) Codon-substitution models for heterogeneous selection pressure at amino acid sites. *Genetics.* **155(1)**, 431-449.

See Also

`dnastring2codonmat` `codonmat2pnps` `dnastring2kaks` `kaks`

Examples

```
## load example sequence data
data("hiv", package="MSA2dist")
#codonmat2xy(dnastring2codonmat(hiv))
hiv |> dnastring2codonmat() |> codonmat2xy()
#codonmat2xy(dnastring2codonmat(hiv), threads=2)
hiv |> dnastring2codonmat() |> codonmat2xy(threads=2)
```

compareCodons *compareCodons*

Description

This function compares two codons and returns the number of syn and non-syn sites according to *Nei and Gojobori (1986).*

Usage

```
compareCodons(codA, codB)
```

Arguments

codA	codon A [mandatory]
codB	codon B [mandatory]

Value

vector of syn and non-syn sites

Author(s)

Kristian K Ullrich

References

Nei and Gojobori. (1986) Simple methods for estimating the numbers of synonymous and nonsynonymous nucleotide substitutions. *Mol. Biol. Evol.*, **3(5)**, 418-426.

Ganeshan et al. (1997) Human immunodeficiency virus type 1 genetic evolution in children with different rates of development of disease. *J. Virology.* **71(1)**, 663-677.

Yang et al. (2000) Codon-substitution models for heterogeneous selection pressure at amino acid sites. *Genetics.* **155(1)**, 431-449.

See Also

kaks

Examples

```
compareCodons("AAA","TTA")
compareCodons("AAA","TAT")
compareCodons("AAA","ATT")
compareCodons("AAA","TTT")
## load example sequence data
data("hiv", package="MSA2dist")
compareCodons(dnastring2codonmat(hiv)[1,1], dnastring2codonmat(hiv)[1,2])
```

dnabin2dnastring *dnabin2dnastring*

Description

This function converts an ape DNAbin into a DNAStringSet.

Usage

```
dnabin2dnastring(dnabin)
```

Arguments

dnabin	ape DNAbin [mandatory]

Value

An object of class DNAStringSet

Author(s)

Kristian K Ullrich

See Also

as.alignment as.DNAbin.alignment DNAStringSet

Examples

```
data(woodmouse, package="ape")
## convert into DNAStringSet
#dnabin2dnastring(woodmouse)
woodmouse |> dnabin2dnastring()
```

dnastring2aln *dnastring2aln*

Description

This function converts a DNAStringSet into an seqinr alignment.

Usage

```
dnastring2aln(dna)
```

Arguments

dna	DNAStringSet [mandatory]

Value

An object of class alignment which is a list with the following components:
nb the number of aligned sequences
nam a vector of strings containing the names of the aligned sequences
seq a vector of strings containing the aligned sequences
com a vector of strings containing the commentaries for each sequence or NA if there are no comments

Author(s)

Kristian K Ullrich

See Also

as.alignment

Examples

```
## define two cds sequences
cds1 <- Biostrings::DNAString("ATGCAACATTGC")
cds2 <- Biostrings::DNAString("ATG---CATTGC")
cds1.cds2.aln <- c(Biostrings::DNAStringSet(cds1),
    Biostrings::DNAStringSet(cds2))
## convert into alignment
#dnastring2aln(cds1.cds2.aln)
cds1.cds2.aln |> dnastring2aln()
```

---

dnastring2codonmat *dnastring2codonmat*

Description

This function converts a DNAStringSet into a codon matrix.

Usage

```
dnastring2codonmat(cds, shorten = FALSE, frame = 1, framelist = NULL)
```

Arguments

cds	DNAStringSet [mandatory]
shorten	shorten all sequences to multiple of three [default: FALSE]
frame	indicates the first base of a the first codon [default: 1]
framelist	supply vector of frames for each entry [default: NULL]

Value

An object of class `alignment` which is a list with the following components:
`nb` the number of aligned sequences
`nam` a vector of strings containing the names of the aligned sequences
`seq` a vector of strings containing the aligned sequences
`com` a vector of strings containing the commentaries for each sequence or `NA` if there are no comments

Author(s)

Kristian K Ullrich

See Also

`as.alignment`

Examples

```
## define two cds sequences
cds1 <- Biostrings::DNAString("ATGCAACATTGC")
cds2 <- Biostrings::DNAString("ATG---CATTGC")
cds1.cds2.aln <- c(Biostrings::DNAStringSet(cds1),
    Biostrings::DNAStringSet(cds2))
## convert into alignment
#dnastring2codonmat(cds1.cds2.aln)
cds1.cds2.aln |> dnastring2codonmat()
## use frame 2 and shorten to circumvent multiple of three error
cds1 <- Biostrings::DNAString("-ATGCAACATTGC-")
cds2 <- Biostrings::DNAString("-ATG---CATTGC-")
cds1.cds2.aln <- c(Biostrings::DNAStringSet(cds1),
    Biostrings::DNAStringSet(cds2))
cds1.cds2.aln |> dnastring2codonmat(frame=2, shorten=TRUE)
```

---

dnastring2dist *dnastring2dist*

Description

This function calculates pairwise distances for all combinations of a `DNAStringSet`.

Usage

```
dnastring2dist(
  dna,
  model = "IUPAC",
  threads = 1,
  symmetric = TRUE,
  score = NULL,
```

```
  mask = NULL,
  region = NULL,
  ...
)
```

Arguments

dna	DNAStringSet [mandatory]
model	specify model either "IUPAC" or any model from ape::dist.dna [default: IUPAC]
threads	number of parallel threads [default: 1]
symmetric	symmetric score matrix [default: TRUE]
score	score matrix use score matrix to calculate distances [default: NULL]
mask	IRanges object indicating masked sites [default: NULL]
region	IRanges object indicating region to use for dist calculation. Default is null, meaning all sites are used [default: NULL]
...	other ape::dist.dna parameters (see dist.dna)

Value

A data.frame of pairwise distance values distSTRING and sites used sitesUsed

Author(s)

Kristian K Ullrich

See Also

dist.dna

Examples

```
## load example sequence data
data("hiv", package="MSA2dist")
#dnastring2dist(hiv, model="IUPAC")
hiv |> dnastring2dist(model="IUPAC")
#dnastring2dist(hiv, model="K80")
hiv |> dnastring2dist(model="K80")
data("woodmouse", package="ape")
#dnastring2dist(dnabin2dnastring(woodmouse), score=iupacMatrix())
woodmouse |> dnabin2dnastring() |> dnastring2dist()
#dnastring2dist(hiv, model = "IUPAC", threads = 2)
hiv |> dnastring2dist(model = "IUPAC", threads = 2)
## create mask
mask1 <- IRanges::IRanges(start=c(1,61,121), end=c(30,90,150))
## use mask
hiv |> dnastring2dist(model="IUPAC", mask=mask1)
## use region
region1 <- IRanges::IRanges(start=c(1,139), end=c(75,225))
```

```
hiv |> dnastring2dist(model="IUPAC", region=region1)
## use mask and region
hiv |> dnastring2dist(model="IUPAC", mask=mask1, region=region1)
## use asymmetric score matrix
myscore <- iupacMatrix()
myscore[1, 4] <- 0.5
(hiv |> dnastring2dist(score=myscore, symmetric=FALSE))$distSTRING[1:2, 1:2]
```

---

dnastring2dnabin *dnastring2dnabin*

Description

This function converts a DNAStringSet into an ape DNAbin.

Usage

```
dnastring2dnabin(dna)
```

Arguments

dna	DNAStringSet [mandatory]

Value

An object of class DNAbin

Author(s)

Kristian K Ullrich

See Also

as.alignment as.DNAbin.alignment

Examples

```
## define two cds sequences
cds1 <- Biostrings::DNAString("ATGCAACATTGC")
cds2 <- Biostrings::DNAString("ATG---CATTGC")
cds1.cds2.aln <- c(Biostrings::DNAStringSet(cds1),
    Biostrings::DNAStringSet(cds2))
## convert into DNAbin
#dnastring2dnabin(cds1.cds2.aln)
cds1.cds2.aln |> dnastring2dnabin()
```

dnastring2kaks *dnastring2kaks*

Description

This function calculates Ka/Ks (pN/pS) for all combinations of a DNAStringSet. If the sequences in the DNAStringSet are not a multiple-sequence alignment, pairwise codon alignments can be calculated on the fly. Models used and implemented according to *Li (1993)* (using seqinr) or *Nei and Gojobori (1986)* (own implementation) or models from KaKs_Calculator2 ported to MSA2dist with Rcpp.

Usage

```
dnastring2kaks(
  cds,
  model = "Li",
  threads = 1,
  isMSA = TRUE,
  sgc = "1",
  verbose = FALSE,
  ...
)
```

Arguments

cds	DNAStringSet coding sequence alignment [mandatory]
model	specify codon model either "Li" or "NG86" or one of KaKs_Calculator2 model "NG", "LWL", "LPB", "MLWL", "MLPB", "GY", "YN", "MYN", "MS", "MA", "GNG", "GLWL", "GLPB", "GMLWL", "GMLPB", "GYN", "GMYN" [default: Li]
threads	number of parallel threads [default: 1]
isMSA	cds DNAStringSet represents MSA [default: TRUE]
sgc	standard genetic code (for KaKs Calculator models) [default: 1]
verbose	verbosity (for KaKs Calculator models) [default: FALSE]
...	other codon alignment parameters

Value

A data.frame of KaKs values

Author(s)

Kristian K Ullrich

References

"MS/MA/GNG/GLWL/GLPB/GMLWL/GMLPB/GYN:" Wang et al. (2010) KaKs_Calculator 2.0: a toolkit incorporating gamma-series methods and sliding window strategies.*Genomics, proteomics & bioinformatics.* **8(1)**, 77-80.

"Li/LWL:" Li et al. (1985) A new method for estimating synonymous and nonsynonymous rates of nucleotide substitution considering the relative likelihood of nucleotide and codon changes. *Mol. Biol. Evol.*, **2(2)**, 150-174.

"Li/LPB:" Li (1993). Unbiased estimation of the rates of synonymous and nonsynonymous substitution. Journal of molecular evolution, 36(1), pp.96-99.

"NG86/NG:" Nei and Gojobori. (1986) Simple methods for estimating the numbers of synonymous and nonsynonymous nucleotide substitutions. *Mol. Biol. Evol.*, **3(5)**, 418-426.

"LPB:" Pamilo and Bianchi. (1993) Evolution of the Zfx and Zfy genes: Rates and interdependence between genes. *Mol. Biol. Evol.*, **10**, 271-281.

"MLWL/MLPB:" Tzeng et al. (2004). Comparison of three methods for estimating rates of synonymous and nonsynonymous nucleotide substitutions. *Mol. Biol. Evol.*, **21(12)**, 2290-2298.

"GY:" Goldman and Yang (1994). A codon-based model of nucleotide substitution for protein-coding DNA sequences. *Mol. Biol. Evol.*, **11(5)** 725-736.

"YN:" Yang et al. (2000) Codon-substitution models for heterogeneous selection pressure at amino acid sites. *Genetics.* **155(1)**, 431-449.

"MYN:" Zhang et al. (2006). Computing Ka and Ks with a consideration of unequal transitional substitutions. *BMC evolutionary biology*, **6(1)**, 1-10.

"data(hiv):" Ganeshan et al. (1997) Human immunodeficiency virus type 1 genetic evolution in children with different rates of development of disease. *J. Virology.* **71(1)**, 663-677.

Wang et al. (2009). gamma-MYN: a new algorithm for estimating Ka and Ks with consideration of variable substitution rates. *Biology Direct*, **4(1)**, 1-18.

See Also

kaks

Examples

```
## load example sequence data
data("hiv", package="MSA2dist")
#dnastring2kaks(hiv, model="Li")
hiv |> dnastring2kaks(model="Li")
#dnastring2kaks(hiv, model="NG86")
hiv |> dnastring2kaks(model="NG86")
#dnastring2kaks(hiv, model="NG86", threads=2)
hiv |> dnastring2kaks(model="NG86", threads=2)

## define three unaligned cds sequences
cds1 <- Biostrings::DNAString("ATGCAACATTGC")
cds2 <- Biostrings::DNAString("ATGCATTGC")
cds3 <- Biostrings::DNAString("ATGCAATGC")
cds_sequences <- Biostrings::DNAStringSet(list(cds1, cds2, cds3))
```

```
names(cds_sequences) <- c("cds1", "cds2", "cds3")
## set isMSA to FALSE to automatically create pairwise codon alignments
#dnastring2kaks(cds_sequences, model="Li", isMSA=FALSE)
cds_sequences |> dnastring2kaks(model="Li", isMSA=FALSE)
```

GENETIC_CODE_TCAG *GENETIC_CODE_TCAG*

Description

GENETIC_CODE from Biostrings extended by codon number and number of syn sites.

Usage

```
codon2number(codon)
```

Arguments

codon	codon [mandatory]

Value

An object of class numeric

Author(s)

Kristian K Ullrich

See Also

GENETIC_CODE

Examples

```
GENETIC_CODE_TCAG
```

getmask *getmask*

Description

This function shows the mask slot from a DNAStringSet or an AAStringSet metadata information.

Usage

```
getmask(seq)
```

Arguments

seq	DNAStringSet or AAStringSet [mandatory]

Value

IRanges information from metadata

Author(s)

Kristian K Ullrich

See Also

addpop2string

Examples

```
## load example sequence data
data(iupac, package="MSA2dist")
iupac.aa <- iupac |> cds2aa(shorten = TRUE)
## create mask
mask1 <- IRanges::IRanges(start=c(1,41), end=c(20,50))
## add mask
iupac.aa <- iupac.aa |> addmask2string(mask=mask1)
#(iupac.aa |> slot("metadata"))$mask
iupac.aa |> getmask()
```

getpos *getpos*

Description

This function shows the position slot from a DNAStringSet or an AAStringSet metadata information.

Usage

```
getpos(seq)
```

Arguments

seq	DNAStringSet or AAStringSet [mandatory]

Value

GenomicRanges information from metadata

Author(s)

Kristian K Ullrich

See Also

addpop2string

Examples

```
## load example sequence data
data(iupac, package="MSA2dist")
## add position
iupac <- iupac |> addpos2string(chrom="chr1", start=1, end=1000)
#(iupac |> slot("metadata"))$GRanges
iupac |> getpos()
```

globalDeletion *globalDeletion*

Description

This function returns a DNAStringSet reduced by all sites containing any gaps ("-", "+", ".") or missing ("N") sites.

Usage

```
globalDeletion(dna)
```

Arguments

dna	DNAStringSet	[mandatory]

Value

DNAStringSet

Author(s)

Kristian K Ullrich

Examples

```
## define two cds sequences
cds1 <- Biostrings::DNAString("ATGCAACATTGC")
cds2 <- Biostrings::DNAString("ATG---CATTGC")
cds1.cds2.aln <- c(Biostrings::DNAStringSet(cds1),
    Biostrings::DNAStringSet(cds2))
globalDeletion(cds1.cds2.aln)
```

globalDeletionAA *globalDeletionAA*

Description

This function returns an AAStringSet reduced by all sites containing any gaps ("-", "+", ".") or missing ("X") sites.

Usage

```
globalDeletionAA(aa)
```

Arguments

aa	AAStringSet [mandatory]

Value

AAStringSet

Author(s)

Kristian K Ullrich

Examples

```
## define two cds sequences
cds1 <- Biostrings::DNAString("ATGCAACATTGC")
cds2 <- Biostrings::DNAString("ATG---CATTGC")
cds1.cds2.aln <- c(Biostrings::DNAStringSet(cds1),
    Biostrings::DNAStringSet(cds2))
#globalDeletionAA(cds2aa(cds1.cds2.aln))
cds1.cds2.aln |> cds2aa() |> globalDeletionAA()
```

---

granthamMatrix *granthamMatrix*

Description

This function creates a granthamMatrix object to be used with the rcpp_distSTRING function. By default,the grantham matrix is defined as from Grantham 1974. (see https://link.springer.com/article/10.1007/s00335-017-9704-9)

Usage

```
granthamMatrix()
```

Value

matrix

Author(s)

Kristian K Ullrich

References

Grantham R. (1974). Amino Acid Difference Formula to Help Explain Protein Evolution. *Science*,**185(4154)**,862-864.

See Also

aastring2dist,dist.dna

Examples

```
granthamMatrix()
```

`hiv-data` *hiv-data*

Description

Example cds sequences from HIV-1 sample 136 patient 1 from Sweden envelope glycoprotein (env) gene, V3 region as `DNAStringSet`.

Usage

```
data(hiv)
```

Format

an object of class `DNAStringSet` see `XStringSet-class`

References

Yang et al. (2000) Codon-substitution models for heterogeneous selection pressure at amino acid sites. *Genetics.* **155(1)**, 431-449.

Examples

```
data("hiv", package="MSA2dist")
```

`indices2kaks` *indices2kaks*

Description

This function calculates Ka/Ks (pN/pS) for all combinations given in an indices `list` of a `DNAStringSet`. If the sequences in the `DNAStringSet` are not a multiple-sequence alignment, pairwise codon alignments can be calculated on the fly. Models used and implemented according to *Li (1993)* (using `seqinr`) or *Nei and Gojobori (1986)* (own implementation) or models from `KaKs_Calculator2` ported to `MSA2dist` with `Rcpp`.

Usage

```
indices2kaks(
  cds,
  indices,
  model = "Li",
  threads = 1,
  isMSA = TRUE,
  sgc = "1",
  verbose = FALSE,
  ...
)
```

Arguments

cds	DNAStringSet coding sequence alignment [mandatory]
indices	list list of indices to calculate Ks/Ks [mandatory]
model	specify codon model either "Li" or "NG86" or one of KaKs_Calculator2 model "NG", "LWL", "LPB", "MLWL", "MLPB", "GY", "YN", "MYN", "MS", "MA", "GNG", "GLWL", "GLPB", "GMLWL", "GMLPB", "GYN", "GMYN" [default: Li]
threads	number of parallel threads [default: 1]
isMSA	cds DNAStringSet represents MSA [default: TRUE]
sgc	standard genetic code (for KaKs Calculator models) [default: 1]
verbose	verbosity (for KaKs Calculator models) [default: FALSE]
...	other codon alignment parameters

Value

A data.frame of KaKs values

Author(s)

Kristian K Ullrich

References

"MS/MA/GNG/GLWL/GLPB/GMLWL/GMLPB/GYN:" Wang et al. (2010) KaKs_Calculator 2.0: a toolkit incorporating gamma-series methods and sliding window strategies.*Genomics, proteomics & bioinformatics.* **8(1)**, 77-80.

"Li/LWL:" Li et al. (1985) A new method for estimating synonymous and nonsynonymous rates of nucleotide substitution considering the relative likelihood of nucleotide and codon changes. *Mol. Biol. Evol.*, **2(2)**, 150-174.

"Li/LPB:" Li (1993). Unbiased estimation of the rates of synonymous and nonsynonymous substitution. Journal of molecular evolution, 36(1), pp.96-99.

"NG86/NG:" Nei and Gojobori. (1986) Simple methods for estimating the numbers of synonymous and nonsynonymous nucleotide substitutions. *Mol. Biol. Evol.*, **3(5)**, 418-426.

"LPB:" Pamilo and Bianchi. (1993) Evolution of the Zfx and Zfy genes: Rates and interdependence between genes. *Mol. Biol. Evol.*, **10**, 271-281.

"MLWL/MLPB:" Tzeng et al. (2004). Comparison of three methods for estimating rates of synonymous and nonsynonymous nucleotide substitutions. *Mol. Biol. Evol.*, **21(12)**, 2290-2298.

"GY:" Goldman and Yang (1994). A codon-based model of nucleotide substitution for protein-coding DNA sequences. *Mol. Biol. Evol.*, **11(5)** 725-736.

"YN:" Yang et al. (2000) Codon-substitution models for heterogeneous selection pressure at amino acid sites. *Genetics.* **155(1)**, 431-449.

"MYN:" Zhang et al. (2006). Computing Ka and Ks with a consideration of unequal transitional substitutions. *BMC evolutionary biology*, **6(1)**, 1-10.

"data(hiv):" Ganeshan et al. (1997) Human immunodeficiency virus type 1 genetic evolution in children with different rates of development of disease. *J. Virology.* **71(1)**, 663-677.

Wang et al. (2009). gamma-MYN: a new algorithm for estimating Ka and Ks with consideration of variable substitution rates. *Biology Direct*, **4(1)**, 1-18.

See Also

kaks

Examples

```
## load example sequence data
data("hiv", package="MSA2dist")
## create indices
idx <- list(c(2, 3), c(5,7,9))
#indices2kaks(hiv, idx, model="Li")
hiv |> indices2kaks(idx, model="Li")
#indices2kaks(hiv, idx, model="NG86")
hiv |> indices2kaks(idx, model="NG86")
#indices2kaks(hiv, idx, model="NG86", threads=2)
hiv |> indices2kaks(idx, model="NG86", threads=2)

## define three unaligned cds sequences
cds1 <- Biostrings::DNAString("ATGCAACATTGC")
cds2 <- Biostrings::DNAString("ATGCATTGC")
cds3 <- Biostrings::DNAString("ATGCAATGC")
cds_sequences <- Biostrings::DNAStringSet(list(cds1, cds2, cds3))
names(cds_sequences) <- c("cds1", "cds2", "cds3")
## create indices
idx <- list(c(1, 2), c(1,3))
## set isMSA to FALSE to automatically create pairwise codon alignments
#indices2kaks(cds_sequences, idx, model="Li", isMSA=FALSE)
cds_sequences |> indices2kaks(idx, model="Li", isMSA=FALSE)
```

iupac-data *iupac-data*

Description

Example IUPAC sequences created with angsd from different house mouse (Mus musculus) subpopulations from Harr et al. (2016) DNAStringSet.

Usage

```
data(iupac)
```

Format

an object of class DNAStringSet see XStringSet-class

References

Harr et al. (2016) Genomic resources for wild populations of the house mouse, Mus musculus and its close relative Mus spretus. *Scientific data.* **3(1)**, 1-14.

Examples

```
data("iupac", package="MSA2dist")
```

iupacMatrix *iupacMatrix*

Description

This function creates a iupacMatrix object to be used with the rcpp_distSTRING function. By default, the iupac matrix is defined as literal distance obtained from Chang et al. 2017. (see https://link.springer.com/article/10.1007/s00335-017-9704-9)

Usage

```
iupacMatrix()
```

Value

score matrix

Author(s)

Kristian K Ullrich

References

Chang,P. L.,Kopania,E.,Keeble,S.,Sarver,B. A.,Larson, E.,Orth,A.,... & Dean,M. D. (2017). Whole exome sequencing of wild-derived inbred strains of mice improves power to link phenotype and genotype. *Mammalian genome*,**28(9-10)**,416-425.

See Also

dnastring2dist,dist.dna

Examples

```
iupacMatrix()
```

`makePostalignedSeqs` *makePostalignedSeqs*

Description

This function is a fork from an internal function from `Biostrings`

Usage

```
makePostalignedSeqs(x)
```

Arguments

x	x

Value

get internal function makePostalignedSeqs

Author(s)

Kristian K Ullrich

See Also

`pairwiseAlignment`, cds2codonaln

Examples

```
## define two cds sequences
cds1 <- Biostrings::DNAString("ATGCAACATTGC")
cds2 <- Biostrings::DNAString("ATGCATTGC")
makePostalignedSeqs(pwalign::pairwiseAlignment(
    cds2aa(Biostrings::DNAStringSet(cds1)),
    cds2aa(Biostrings::DNAStringSet(cds2))))
```

pal2nal *pal2nal*

Description

This function takes an AAStringSet alignment and its corresponding coding sequences DNAStringSet and converts the protein alignment into a codon alignment.

Usage

```
pal2nal(pal, nal, remove.gaps = FALSE)
```

Arguments

pal	AAStringSet [mandatory]
nal	DNAStringSet [mandatory]
remove.gaps	specify if gaps in the codon alignment should be removed [default: FALSE]

Value

codon alignment as DNAStringSet

Author(s)

Kristian K Ullrich

References

Pagès, H et al. (2014) Biostrings: Efficient manipulation of biological strings. *R package version*, **2(0)**.

See Also

pairwiseAlignment

Examples

```
## define two cds sequences
cds <- Biostrings::DNAStringSet(c("ATGCAACATTGC", "ATGCATTGC"))
names(cds) <- c("cds1", "cds2")
## get protein alignment
aa <- MSA2dist::cds2aa(cds)
msa <- makePostalignedSeqs(pwalign::pairwiseAlignment(aa[1], aa[2]))[[1L]]
names(msa) <- names(aa)
## get codon alignment
nal <- MSA2dist::pal2nal(pal=msa, nal=cds)
nal
```

popinteger *popinteger*

Description

This function shows the population integer slot from a DNAStringSet or an AAStringSet metadata information.

Usage

```
popinteger(seq)
```

Arguments

seq	DNAStringSet or AAStringSet [mandatory]

Value

population integer from metadata

Author(s)

Kristian K Ullrich

See Also

addpop2string

Examples

```
## load example sequence data
data(iupac, package="MSA2dist")
iupac.aa <- iupac |> cds2aa(shorten = TRUE)
## create poplist
poplist <- list(FRA = grep("Mmd.FRA", names(iupac)),
    GER = grep("Mmd.GER", names(iupac)),
    IRA = grep("Mmd.IRA", names(iupac)),
    AFG = grep("Mmm.AFG", names(iupac)))
iupac.aa <- iupac.aa |> addpop2string(poplist)
popinteger(iupac.aa)
```

popnames *popnames*

Description

This function shows the population names slot from a DNAStringSet or an AAStringSet metadata information.

Usage

```
popnames(seq)
```

Arguments

seq	DNAStringSet or AAStringSet [mandatory]

Value

population names from metadata

Author(s)

Kristian K Ullrich

See Also

addpop2string

Examples

```
## load example sequence data
data(iupac, package="MSA2dist")
iupac.aa <- iupac |> cds2aa(shorten = TRUE)
## create poplist
poplist <- list(FRA = grep("Mmd.FRA", names(iupac)),
    GER = grep("Mmd.GER", names(iupac)),
    IRA = grep("Mmd.IRA", names(iupac)),
    AFG = grep("Mmm.AFG", names(iupac)))
iupac.aa <- iupac.aa |> addpop2string(poplist)
popnames(iupac.aa)
```

rcpp_distSTRING *rcpp_distSTRING*

Description

calculates pairwise distances using a score matrix

Usage

```
rcpp_distSTRING(dnavector, scoreMatrix, ncores = 1L, symmetric = 1L)
```

Arguments

dnavector	StringVector [mandatory]
scoreMatrix	NumericMatrix [mandatory]
ncores	number of cores [default: 1]
symmetric	symmetric score matrix [default: 1]

Value

list

Author(s)

Kristian K Ullrich

Examples

```
## load example sequence data
data("hiv", package="MSA2dist")
rcpp_distSTRING(dnavector=as.character(hiv), scoreMatrix=iupacMatrix())
```

rcpp_KaKs *rcpp_KaKs*

Description

calculates KaKs as implememted in KaKs Calculator 2.0 `MSA2dist` with `Rcpp`.

Usage

```
rcpp_KaKs(cdsstr, sgc = "1", method = "YN", verbose = FALSE)
```

Arguments

cdsstr	StringVector [mandatory]
sgc	standard genetic code to use [default: 1]
method	KaKs Calculator 2.0 codon model [default: YN]
verbose	specify if verbose output [default: FALSE]

Value

list

Author(s)

Kristian K Ullrich

References

Wang et al. (2010) KaKs_Calculator 2.0: a toolkit incorporating gamma-series methods and sliding window strategies.*Genomics, proteomics & bioinformatics.* **8(1)**, 77-80.

Examples

```
## load example sequence data
data("hiv", package="MSA2dist")
rcpp_KaKs(cdsstr=as.character(hiv[1:3]))
```

---

rcpp_pairwiseDeletionAA

rcpp_pairwiseDeletionAA

Description

returns number of AA sites used

Usage

```
rcpp_pairwiseDeletionAA(aavector, ncores = 1L, symmetric = 1L)
```

Arguments

aavector	StringVector [mandatory]
ncores	number of cores [default: 1]
symmetric	symmetric score matrix [default: 1]

Value

list

Author(s)

Kristian K Ullrich

Examples

```
## load example sequence data
data("hiv", package="MSA2dist")
h <- hiv |> cds2aa() |> as.character()
rcpp_pairwiseDeletionAA(aavector=h, ncores=1)
```

---

rcpp_pairwiseDeletionDNA

rcpp_pairwiseDeletionDNA

Description

returns number of DNA sites used

Usage

```
rcpp_pairwiseDeletionDNA(dnavector, ncores = 1L, symmetric = 1L)
```

Arguments

dnavector	StringVector [mandatory]
ncores	number of cores [default: 1]
symmetric	symmetric score matrix [default: 1]

Value

list

Author(s)

Kristian K Ullrich

Examples

```
## load example sequence data
data("woodmouse", package="ape")
w <- woodmouse |> dnabin2dnastring() |> as.character()
rcpp_pairwiseDeletionDNA(dnavector=w, ncores=1)
```

region *region*

Description

This function shows the region slot from a DNAStringSet or an AAStringSet metadata information.

Usage

```
region(seq)
```

Arguments

seq	DNAStringSet or AAStringSet [mandatory]

Value

region IRanges object from metadata

Author(s)

Kristian K Ullrich

See Also

addpop2string

Examples

```
## load example sequence data
data(iupac, package="MSA2dist")
iupac.aa <- iupac |> cds2aa(shorten = TRUE)
## create region
region1 <- IRanges::IRanges(start=c(1,41), end=c(20,50))
## add region
iupac.aa <- iupac.aa |> addregion2string(region=region1)
iupac.aa |> region()
```

regionused *regionused*

Description

This function shows the region used slot from a DNAStringSet or an AAStringSet metadata information.

Usage

```
regionused(seq)
```

Arguments

seq	DNAStringSet or AAStringSet [mandatory]

Value

population names from metadata

Author(s)

Kristian K Ullrich

See Also

addpop2string

Examples

```
## load example sequence data
data("hiv", package="MSA2dist")
## create mask
mask1 <- IRanges::IRanges(start=c(11,41,71), end=c(20,50,80))
## use mask
hiv.region <- hiv |> cds2aa() |> string2region(mask=mask1)
#(hiv.region |> slot("metadata"))$regionUsed
hiv.region |> regionused()
```

string2region *string2region*

Description

This function subsets a DNAStringSet or an AAStringSet by a mask and region given one or both options as IRanges.

Usage

```
string2region(seq, mask = NULL, region = NULL, add = TRUE)
```

Arguments

seq	DNAStringSet or AAStringSet [mandatory]
mask	IRanges object indicating masked sites [default: NULL]
region	IRanges object indicating region to use for dist calculation (by default all sites are used) [default: NULL]
add	indicate if mask and region should be added to metadata [default: TRUE]

Value

A list object with the following components:
DNAStringSet or AAStringSet
regionUsed

Author(s)

Kristian K Ullrich

See Also

dnastring2dist

Examples

```
## load example sequence data
data("hiv", package="MSA2dist")
## create mask
mask1 <- IRanges::IRanges(start=c(11,41,71), end=c(20,50,80))
## use mask
hiv.region <- hiv |> cds2aa() |> string2region(mask=mask1)
#(hiv.region |> slot("metadata"))$regionUsed
hiv.region |> regionused()
## use region
region1 <- IRanges::IRanges(start=c(1,75), end=c(45,85))
hiv.region <- hiv |> cds2aa() |> string2region(region=region1)
```

```
#(hiv.region |> slot("metadata"))$regionUsed
hiv.region |> regionused()
## use mask and region
hiv.region <- hiv |> cds2aa() |> string2region(mask=mask1, region=region1)
#(hiv.region |> slot("metadata"))$regionUsed
hiv.region |> regionused()
```

---

subString *subString*

Description

This function gets a subsequence from a DNAString, RNAString, AAString, BString, DNAStringSet, RNAStringSet, AAStringSet, BStringSet object from the Biostrings package.

Usage

```
subString(x, s, e)
```

Arguments

x	DNAStringSet, RNAString, AAString, BString, DNAStringSet, RNAStringSet, AAStringSet, BStringSet [mandatory]
s	start vector [mandatory]
e	end vector [mandatory]

Value

subsequence of an Biostrings object

Author(s)

Kristian K Ullrich

See Also

subseq

Examples

```
## define two cds sequences
cds1 <- Biostrings::DNAString("ATGCAACATTGC")
cds2 <- Biostrings::DNAString("ATG---CATTGC")
cds1.cds2.aln <- c(Biostrings::DNAStringSet(cds1),
    Biostrings::DNAStringSet(cds2))
subString(cds1.cds2.aln, c(1,7), c(3,12))
```

uptriidx *uptriidx*

Description

This function returns upper tri index for usage with `pivot_long` reduction.

Usage

```
uptriidx(n, diag = FALSE)
```

Arguments

`n`	dimension of initial matrix [mandatory]
`diag`	indicate if diag should be retained [default: FALSE]

Value

list of positions

Author(s)

Kristian K Ullrich

Examples

```
uptriidx(10)
```

Index

∗ **datasets**
AAMatrix-data, 5
hiv-data, 36
iupac-data, 39

aa2selfscore, 3
aabin2aastring, 4
AAMatrix *(*AAMatrix-data*)*, 5
AAMatrix-data, 5
aastring2aabin, 5
aastring2aln, 6
aastring2dist, 7, *36*
AAStringSet, *4*, *13*
addmask2string, 8, *10–12*
addpop2string, *9*, 9, *11, 12*, *32, 33*, *42, 43*, *47, 48*
addpos2string, *9, 10*, 11, *12*
addregion2string, *9–11*, 12
aln2aastring, 13
aln2dnastring, 14
as.alignment, *4*, *6*, *13, 14*, *24–26*, *28*
as.DNAbin.alignment, *4*, *6*, *24*, *28*

cds2aa, 15
cds2codonaln, 16, *40*
cdsstring2codonaln, 17
codon2number *(*GENETIC_CODE_TCAG*)*, 31
codon2numberAMBIG, 19
codon2numberTCAG, 19
codonmat2pnps, 20, *22*
codonmat2xy, 21
compareCodons, 23

dist.dna, *27*, *36*, *40*
dnabin2dnastring, 24
dnastring2aln, 24
dnastring2codonmat, *21, 22*, 25
dnastring2dist, *8*, 26, *40*, *49*
dnastring2dnabin, 28
dnastring2kaks, *22*, 29
DNAStringSet, *14*, *24*

GENETIC_CODE, *19, 20*, *31*
GENETIC_CODE_TCAG, 31
getmask, 32
getpos, 33
globalDeletion, 34
globalDeletionAA, 34
granthamMatrix, 35

hiv *(*hiv-data*)*, 36
hiv-data, 36

indices2kaks, 36
iupac *(*iupac-data*)*, 39
iupac-data, 39
iupacMatrix, 39

kaks, *21–23*, *30*, *38*

makePostalignedSeqs, 40

pairwiseAlignment, *16–18*, *40, 41*
pal2nal, 41
popinteger, 42
popnames, 43

rcpp_distSTRING, 44
rcpp_KaKs, 44
rcpp_pairwiseDeletionAA, 45
rcpp_pairwiseDeletionDNA, 46
region, 47
regionused, 48

string2region, 49
subseq, *50*
substitution_matrices, *3*
subString, 50

translate, *15*

uptriidx, 51