Package 'MetCirc'

November 12, 2026

Type Package

Title Navigating mass spectral similarity in high-resolution MS/MS metabolomics data metabolomics data

Version 1.42.0

Date 2024-10-16

Author Thomas Naake <thomasnaake@googlemail.com>, Johannes Rainer <johannes.rainer@eurac.edu> and Emmanuel Gaquerel <emmanuel.gaquerel@ibmp-cnrs.unistra.fr>

Maintainer Thomas Naake <thomasnaake@googlemail.com>

VignetteBuilder knitr

Depends R (>= 4.4), amap (>= 0.8), circlize (>= 0.4.16), scales (>= 1.3.0), shiny (>= 1.8.1.1), Spectra (>= 1.15.3)

Imports ggplot2 (>= 3.5.1), MsCoreUtils (>= 1.17.0), S4Vectors (>= 0.43.1)

Suggests BiocGenerics, graphics (>= 4.4), grDevices (>= 4.4), knitr (>= 1.48), testthat (>= 3.2.1.1)

biocViews ShinyApps, Metabolomics, MassSpectrometry, Visualization

Description MetCirc comprises a workflow to interactively explore high-resolution MS/MS metabolomics data. MetCirc uses the Spectra object infrastructure defined in the package Spectra that stores MS/MS spectra. MetCirc offers functionality to calculate similarity between precursors based on the normalised dot product, neutral losses or user-defined functions and visualise similarities in a circular layout. Within the interactive framework the user can annotate MS/MS features based on their similarity to (known) related MS/MS features.

License GPL (>= 3)

RoxygenNote 7.2.2

git_url https://git.bioconductor.org/packages/MetCirc

git_branch RELEASE_3_23

git_last_commit ad495c6

git_last_commit_date 2026-04-28

Repository Bioconductor 3.23

Date/Publication 2026-11-11

Contents

cart2Polar . . . 3
circosLegend . . . 3
compartmentTissue . . . 5
convertExampleDF . . . 5
convertMsp2Spectra . . . 6
createLink0df . . . 7
createLinkDf . . . 8
cutLinkDf . . . 9
getLinkDfIndices . . . 10
highlight . . . 11
minFragCart2Polar . . . 12
msp2spectra . . . 14
neutralloss . . . 14
orderSimilarityMatrix . . . 16
plotCircos . . . 17
plotSpectra . . . 19
printInformationSelect . . . 20
recordPlotFill_degreeFeatures . . . 21
recordPlotHighlight . . . 22
replayPlotAdd . . . 23
replayPlotOrder . . . 24
sd01_outputXCMS . . . 25
sd02_deconvoluted . . . 26
select . . . 26
shinyCircos . . . 27
similarityMat . . . 28
spectraCondition . . . 29
sps_tissue . . . 30
thresholdLinkDf . . . 31
tissue . . . 32
typeMatch_link0 . . . 32

Index **34**

cart2Polar *Calculate polar coordinates from cartesian coordinates*

Description

cart2Polar calculates polar coordinates from cartesian coordinates.

Usage

```
cart2Polar(x, y)
```

Arguments

x	numeric cartesian x coordinate
y	numeric cartesian y coordinate

Details

cart2Polar is employed to translate cartesian coordinates into polar coordinates especially in interactive shiny applications when using hovering and clicking features.

Value

cart2Polar returns a list of colar coordinates r and theta

Author(s)

Thomas Naake, <thomasnaake@googlemail.com>

Examples

```
x <- 1; y <- 1
cart2Polar(x, y)
```

circosLegend *Plot a legend for circos plot*

Description

circosLegend plots a legend for circos plot using group names.

Usage

```
circosLegend(groupname, highlight = TRUE, colour = NULL, cex = 1)
```

Arguments

groupname	character vector containing "group" and "name" to display that is a unique identifier of the features, "group" and "name" have to be separated by "_" where "group" is the first and "name" is the last element
highlight	logical, should colours be adjusted to highlight settings?
colour	NULL or character, colour defines the colours which are used for plotting, if NULL default colours are used
cex	numeric, parameter that controls size of the legend in the plot

Details

Internal use in shinyCircos or outside of shinyCircos to reproduce figures.

Value

The function will open a new plot and display colours together with labels.

Author(s)

Thomas Naake, <thomasnaake@googlemail.com>

Examples

```
data("spectra", package = "MetCirc")

## create similarity matrix
similarityMat <- Spectra::compareSpectra(sps_tissue[1:10],
    FUN = MsCoreUtils::ndotproduct, ppm = 20, m = 0.5, n = 2)
rownames(similarityMat) <- colnames(similarityMat) <- sps_tissue$name[1:10]

linkDf <- createLinkDf(similarityMatrix = similarityMat,
    sps = sps_tissue[1:10],
    condition = c("SPL", "LIM", "ANT", "STY"), lower = 0.01, upper = 1)

## cut link data.frame (here: only display links between groups)
linkDf_cut <- cutLinkDf(linkDf, type = "inter")
groupname <- c(as.character(linkDf_cut[, "spectrum1"]),
            as.character(linkDf_cut[, "spectrum2"]))
groupname <- unique(groupname)

## plot legend
circosLegend(groupname, highlight = TRUE, colour = NULL, cex = 1)
```

compartmentTissue *Example data for 'MetCirc': 'compartmentTissue'*

Description

The 'data.frame' 'compartmentTissue' is used in the subsection 'Preparing the tissue data set for analysis' in the vignette of 'MetCirc'. In 'compartmentTissue', information on the organ-localisation of each MS/MS spectrum is stored.

Format

'data.frame'

Value

'data.frame'

Author(s)

Thomas Naake, <thomasnaake@googlemail.com>

Source

internal

convertExampleDF *Example data for 'MetCirc': convertExampleDF*

Description

'convertExampleDF' is a 'data.frame' which comprises information on a specific metabolite per row stating the average retention time, average m/z, the name of the metabolite, the adduct ion name and the spectrum reference file name. The function 'allocatePrecursor2mz' uses 'data.frame's of the kind of 'sd01_outputXCMS' and 'sd02_deconvoluted' to create a 'data.frame' of the kind of 'convertExampleDF'. Allocation of precursor ions to candidate m/z values is based on minimal distance of m/z and deviance of retention time based on an objective function. See '?allocatePrecursor2mz' for further information.

Format

'data.frame'

Value

'data.frame'

Author(s)

Thomas Naake, <thomasnaake@googlemail.com>

Source

internal

---

convertMsp2Spectra *Convert MSP data frame into object of class* Spectra

---

Description

Convert msp data frame into object of class [Spectra()]

Usage

```
convertMsp2Spectra(msp)
```

Arguments

msp	data.frame that mimicks the .msp file format, see Details for further information.

Details

msp is a data frame of a .msp file, a typical data file for MS/MS libraries. The data frame has two columns and contains in the first column the entries "NAME:", "PRECURSORMZ:" (or "EXACTMASS:"), "RETENTIONTIME:", Num Peaks:" and information on fragments and peak areas/intensities and will extract the respective information in the second column.

Value

convertMsp2Spectra returns an object of class ‘Spectra‘

Author(s)

Thomas Naake, <thomasnaake@googlemail.com>

Examples

```
data("convertMsp2Spectra", package = "MetCirc")
convertMsp2Spectra(msp = msp2spectra)
```

createLink0df *Create a link matrix*

Description

Create a link matrix which links every feature in similarity matrix with another.

Usage

```
createLink0df(similarityMatrix, sps, condition)
```

Arguments

similarityMatrix	matrix, a similarity matrix that contains the NDP similarity measure between all precursors in the data set
sps	Spectra object
condition	character, which conditions should be included?

Details

createLink0df creates a matrix from a similarity matrix which includes all connections between features in the similarity matrix, but exclude links which have a similarity of exactly 0.

Value

createLink0df returns a 'matrix' that gives per each row information on linked features

Author(s)

Thomas Naake, <thomasnaake@googlemail.com>

Examples

```
data("spectra", package = "MetCirc")
data("similarityMat", package = "MetCirc")
link0df <- createLink0df(similarityMatrix = similarityMat,
    sps = sps_tissue, condition = c("SPL", "LIM", "ANT", "STY"))
```

createLinkDf *Create a data frame which contains features to link (indices)*

Description

Create a data frame which contains features to link (indices).

Usage

```
createLinkDf(similarityMatrix, sps, condition, lower, upper)
```

Arguments

similarityMatrix	matrix, a similarity matrix that contains the similarity measure between all precursors in the data set
sps	Spectra object containing spectral data corresponding to features in similarityMatrix
condition	character vector containing the conditions/samples for which a linkDf is created
lower	numeric(1), threshold value for similarity values, linked features below this value will not be included
upper	numeric(1), threshold value for similarity values, linked features above this value will not be included

Details

lower and upper are numerical values and truncate spectra based on their similarity. The function createLinkDf is a wrapper for the functions createLink0df and thresholdLinkDf.

Value

createLinkDf returns a data.frame that gives per each row information on linked features

Author(s)

Thomas Naake, <thomasnaake@googlemail.com>

Examples

```
data("spectra", package = "MetCirc")
data("similarityMat", package = "MetCirc")
link0df <- createLink0df(similarityMatrix = similarityMat,
    sps = sps_tissue, condition = c("SPL", "LIM", "ANT", "STY"))
createLinkDf(similarityMatrix = similarityMat, sps = sps_tissue,
    condition = c("SPL", "LIM", "ANT", "STY"), lower = 0.5, upper = 1)
```

cutLinkDf *Create a cut data frame with information on links*

Description

Create a cut link data frame

Usage

```
cutLinkDf(linkDf, type = c("all", "inter", "intra"))
```

Arguments

linkDf	data.frame, that gives per each row information on linked features
type	character, one of "all", "inter" or "intra"

Details

This function is used to truncate features from linkDf. If type = "all", linkDf will not be changed; if type = "inter" the returned linkDf will only contain entries of links which are between groups and not inside groups; contrary to that, if type = "intra" the returned linkDf will only contain entries of links which are inside groups and not between groups.

Value

cutLinkDf returns a data.frame that gives per each row information on linked features

Author(s)

Thomas Naake, <thomasnaake@googlemail.com>

Examples

```
data("spectra", package = "MetCirc")
data("similarityMat", package = "MetCirc")
linkDf <- createLinkDf(similarityMatrix = similarityMat,
    sps = sps_tissue, condition = c("SPL", "LIM", "ANT", "STY"),
    lower = 0.75, upper = 1)
cutLinkDf(linkDf = linkDf, type = "all")
```

getLinkDfIndices *Get indices in* linkDf *of feature*

Description

Gets indices in linkDf of feature

Usage

```
getLinkDfIndices(groupnameselected, linkDf)
```

Arguments

groupnameselected	character vector with groupname of selected feature, vector containing "group" and "name" to display, that is a unique identifier of the features, "group" and "name" have to be separated by "_" where "group" is the first and "name" is the last element
linkDf	data.frame, in each row there is information about features to be connected

Details

Internal use for function highlight

Value

getLinkDfIndices returns indices concerning linkDf to which groupnameselected connects

Author(s)

Thomas Naake, <thomasnaake@googlemail.com>

Examples

```
## Not run: getLinkDfIndices(groupnameselected, linkMatrix)
```

highlight *Add links and highlight sectors*

Description

A function to add links and highlight sectors to an initialised and plotted `circlize` plot with one track.

Usage

```
highlight(
  groupname,
  ind,
  linkDf,
  colour = NULL,
  transparency = 0.4,
  links = TRUE
)
```

Arguments

`groupname`	`character` vector containing "group" and "name" to display that is a unique identifier of the features, "group" and "name" have to be separated by *"_"* where "group" is the first and "name" is the last element
`ind`	`numeric`, indices which will be highlighted
`linkDf`	`data.frame`, in each row there is information about features to be connected
`colour`	`NULL` or `character`, `colour` defines the colours which are used for plotting, if 'NULL' default colours are used
`transparency`	`numeric`, defines the transparency of the colours
`links`	`logical`, should links of unselected features be plotted

Details

Internal use for `shinyCircos` or outside of `shinyCircos` to reproduce the figure.

Value

The function will update an existing plot by highlighting a specified sector and connected links.

Author(s)

Thomas Naake, <thomasnaake@googlemail.com>

Examples

```
data("spectra", package = "MetCirc")

## create similarity matrix
similarityMat <- Spectra::compareSpectra(sps_tissue[1:10],
    FUN = MsCoreUtils::ndotproduct, ppm = 20, m = 0.5, n = 2)
rownames(similarityMat) <- colnames(similarityMat) <- sps_tissue$name[1:10]

## order similarityMat according to retentionTime and update rownames
simM <- orderSimilarityMatrix(similarityMat, sps = sps_tissue[1:10],
    type = "retentionTime")

## create link matrix
linkDf <- createLinkDf(similarityMatrix = simM, sps = sps_tissue,
    condition = c("SPL", "LIM", "ANT", "STY"), lower = 0.01, upper = 1)

## cut link matrix (here: only display links between groups)
linkDf_cut <- cutLinkDf(linkDf, type = "inter")

## set circlize parameters
circos.clear()
circos.par(gap.degree = 0, cell.padding = c(0.0, 0, 0.0, 0),
    track.margin = c(0.0, 0))
groupname <- c(as.character(linkDf_cut[, "spectrum1"]),
    as.character(linkDf_cut[, "spectrum2"]))
groupname <- unique(groupname)

## here: set indSelected arbitrarily
indSelected <- c(2,3)

## actual plotting
plotCircos(groupname, linkDf_cut, initialize = TRUE,
    featureNames = TRUE, cexFeatureNames = 0.2, groupSector = TRUE,
    groupName = FALSE, links = FALSE, highlight = TRUE)

## highlight
highlight(groupname = groupname, ind = indSelected, linkDf = linkDf_cut,
    colour = NULL, transparency = 0.4, links = TRUE)
```

`minFragCart2Polar` *Calculate the nearest feature in polar coordinates given cartesian coordinates*

Description

Calculates the nearest feature in polar coordinates given cartesian coordinates.

Usage

```
minFragCart2Polar(x, y, degreeOfFeatures)
```

Arguments

x	numeric, cartesian x coordinate
y	numeric, cartesian y coordinate
degreeOfFeatures	list of positions of features

Details

minFragCart2Polar is employed to find the feature with the smallest distance from given cartesian coordinates.

Value

minFragCart2Polar returns the index of the feature that has the smallest distance to the given coordinates. As minFragCart2Polar is used in shinyCircos for the track 1 only polar r coordinates between 0.8 and 1 will be used to find the feature with smallest distance.

Author(s)

Thomas Naake, <thomasnaake@googlemail.com>

Examples

```
library("MsCoreUtils")
data("spectra", package = "MetCirc")

## create similarity matrix
similarityMat <- Spectra::compareSpectra(sps_tissue[1:10],
    FUN = MsCoreUtils::ndotproduct, ppm = 20, m = 0.5, n = 2)
rownames(similarityMat) <- colnames(similarityMat) <- sps_tissue$name[1:10]

linkDf <- createLinkDf(similarityMatrix = similarityMat,
    sps = sps_tissue[1:10],
    condition = c("SPL", "LIM", "ANT", "STY"), lower = 0.5, upper = 1)

## cut link data.frame (here: only display links between groups)
linkDf_cut <- cutLinkDf(linkDf, type = "inter")
groupname <- c(as.character(linkDf_cut[, "spectrum1"]),
                as.character(linkDf_cut[, "spectrum2"]))
groupname <- unique(groupname)

## set circlize parameters
circos.clear()
circos.par(gap.degree = 0, cell.padding = c(0.0, 0, 0.0, 0),
    track.margin = c(0.0, 0))
plotCircos(groupname, NULL, initialize = TRUE, featureNames = FALSE,
    groupName = FALSE, groupSector = FALSE, links = FALSE, highlight = FALSE)
x <- 1
y <- 0
degreeFeatures <- lapply(groupname,
    function(x)
```

```
        mean(circlize:::get.sector.data(x)[c("start.degree", "end.degree")]))
minFragCart2Polar(x, y, degreeOfFeatures = degreeFeatures)
```

`msp2spectra` *Example data for 'MetCirc': 'msp2spectra'*

Description

'convertMsp2Spectra' contains the object 'msp2spectra' that is a data frame in .MSP format, a typical format for MS/MS library building. Each entry consists of the metabolite name (NAME), the precursor mz (PRECURSORMZ), the retention time (RETENTIONTIME), number of peaks (Num Peaks), together with fragments and their intensity values. In the example used in the function 'convertMsp2Spectra' the 'data.frame' 'msp2spectra' is used to construct an object of class 'MSpectra'.

Format

'data.frame'

Value

'data.frame'

Author(s)

Thomas Naake, <thomasnaake@googlemail.com>

Source

http://prime.psc.riken.jp/Metabolomics_Software/MS-DIAL/, truncated .MSP file of GNPS MS/MS Negative (contains 22 entries): http://prime.psc.riken.jp/Metabolomics_Software/MS-DIAL/MSMS-GNPS-Curated-Neg.msp

---

`neutralloss` *Calculate similarity based on neutral losses*

Description

Calculate similarity based on neutral losses (NLS)

Usage

```
neutralloss(x, y, m = 0.5, n = 2, na.rm = TRUE, ...)
```

Arguments

x	Spectra object from Spectra containing intensity and m/z values, first MS/MS spectrum
y	Spectra object from Spectra containing intensity and m/z values, second MS/MS spectrum
m	numeric(1), exponent to calculate peak intensity-based weights
n	numeric(1), exponent to calculate m/z-based weights
na.rm	logical(1), if NA values should be removed
...	further arguments

Details

Similarities of spectra based on neutral losses are calculated according to the following formula:

$$NLS = \frac{\sum(W_{S1,i} \cdot W_{S2,i})^2}{\sum(W_{S1,i}^2) \cdot \sum(W_{S2,i}^2)}$$

,

with $W = [peakintensity]^m \cdot [NL]^n$ and $NL = |m/z - precursorm/z|$. For further information see Li et al. (2015): Navigating natural variation in herbivory-induced secondary metabolism in coyote tobacco populations using MS/MS structural analysis. PNAS, E4147–E4155.

In here, the precursor m/z is taken by the m/z feature with the highest intensity.

neutralloss returns a numeric value ranging between 0 and 1, where 0 indicates no similarity between the two MS/MS features, while 1 indicates that the MS/MS features are identical. Prior to calculating

$$W_{S1}$$

or

$$W_{S2}$$

, all intensity values are divided by the maximum intensity value.

Value

neutralloss returns a numeric similarity coefficient between 0 and 1

Author(s)

Thomas Naake, <thomasnaake@googlemail.com>

Examples

```
data("spectra", package = "MetCirc")
Spectra::compareSpectra(sps_tissue[1:10], FUN = neutralloss, m = 0.5, n = 2)
```

`orderSimilarityMatrix` *Order columns and rows of a similarity matrix according to m/z, retention time and clustering*

Description

Internal function for shiny application. May also be used outside of shiny to reconstruct figures.

Usage

```
orderSimilarityMatrix(
  similarityMatrix,
  sps,
  type = c("retentionTime", "mz", "clustering"),
  group = FALSE
)
```

Arguments

`similarityMatrix`	`matrix`, `similarityMatrix` contains pair-wise similarity coefficients which give information about the similarity between precursors
`sps`	`Spectra` object containing spectra that are compared in `similarityMatrix`
`type`	`character(1)`, one of `"retentionTime"`, `"mz"`, or `"clustering"`
`group`	`logical(1)`, if `TRUE` group separated by `"_"` will be cleaved from `rownames/colnames` of `similarityMatrix` and matched against names of `sps` (`sps$name`), if `FALSE` `rownames/colnames` of `similarityMatrix` are taken as are and matched against names of `sps` (`sps$name`)

Details

`orderSimilarityMatrix` takes a similarity matrix, `Spectra` object (`sps`, containing information on m/z and retention time), and a `character` vector as arguments. It will then reorder rows and columns of the `similarityMatrix` object such, that it orders rows and columns of `similarityMatrix` according to m/z, retention time or clustering in each group.

`orderSimilarityMatrix` is employed in the `shinyCircos` function to create `similarityMatrix` objects which will allow to switch between different types of ordering in between groups (sectors) in the circos plot. It may be used as well externally, to reproduce plots outside of the reactive environment (see vignette for a workflow).

Value

`matrix`, `orderSimilarityMatrix` returns a similarity matrix with ordered `rownames` according to the `character` vector `type`

Author(s)

Thomas Naake, <thomasnaake@googlemail.com>

Examples

```
data("spectra", package = "MetCirc")
similarityMat <- Spectra::compareSpectra(sps_tissue[1:10],
    FUN = MsCoreUtils::ndotproduct, ppm = 10)
rownames(similarityMat) <- colnames(similarityMat) <- sps_tissue$name[1:10]

## order according to retention time
orderSimilarityMatrix(similarityMatrix = similarityMat,
    sps = sps_tissue, type = "retentionTime", group = FALSE)
```

---

plotCircos *Circular plot to visualize similarity*

Description

Circular plot to visualize similarity.

Usage

```
plotCircos(
  groupname,
  linkDf,
  initialize = c(TRUE, FALSE),
  featureNames = c(TRUE, FALSE),
  cexFeatureNames = 0.3,
  groupSector = c(TRUE, FALSE),
  groupName = c(TRUE, FALSE),
  links = c(TRUE, FALSE),
  highlight = c(TRUE, FALSE),
  colour = NULL,
  transparency = 0.2
)
```

Arguments

groupname	character vector containing "group" and "name" to display that is a unique identifier of the features, "group" and "name" have to be separated by "_" where "group" is the first and "name" is the last element
linkDf	data.frame containing linked features in each row, has five columns (group1, spectrum1, group2, spectrum2, similarity)
initialize	logical, should plot be initialized?
featureNames	logical, should feature names be displayed?

cexFeatureNames	numeric size of feature names
groupSector	logical, should groups be displayed with background colours?
groupName	logical, should group names (e.g. compartment names or individual names) be displayed?
links	logical, should links be plotted?
highlight	logical, highlight is set to TRUE by default
colour	NULL or character, colour defines the colours which are used for plotting, if NULL default colours are used
transparency	numeric, defines the transparency of the colours

Details

Internal use for shinyCircos or used outside of shinyCircos to reproduce figure

Value

The function will initialize a circlize plot and/or will plot features of a circlize plot.

Author(s)

Thomas Naake, <thomasnaake@googlemail.com>

Examples

```
library("MsCoreUtils")
data("spectra", package = "MetCirc")

## create similarity matrix
similarityMat <- Spectra::compareSpectra(sps_tissue[1:10],
    FUN = MsCoreUtils::ndotproduct, ppm = 20, m = 0.5, n = 2)
rownames(similarityMat) <- colnames(similarityMat) <- sps_tissue$name[1:10]

## order similarityMat according to retentionTime
simM <- orderSimilarityMatrix(similarityMat, sps = sps_tissue[1:10],
            type = "retentionTime")

## create link data.frame
linkDf <- createLinkDf(similarityMatrix = simM, sps = sps_tissue,
     condition = c("SPL", "LIM", "ANT", "STY"), lower = 0.01, upper = 1)
## cut link data.frame (here: only display links between groups)
linkDf_cut <- cutLinkDf(linkDf, type = "inter")

## set circlize paramters
circos.clear()
circos.par(gap.degree = 0, cell.padding = c(0.0, 0, 0.0, 0),
         track.margin = c(0.0, 0))
groupname <- c(as.character(linkDf_cut[, "spectrum1"]),
                as.character(linkDf_cut[, "spectrum2"]))
groupname <- unique(groupname)
```

```
## actual plotting
plotCircos(groupname, linkDf_cut, initialize = TRUE,
    featureNames = TRUE, cexFeatureNames = 0.3, groupSector = TRUE,
    groupName = FALSE, links = FALSE, highlight = FALSE, colour = NULL,
    transparency = 0.2)
```

---

plotSpectra *Plot pair-wise spectra*

Description

plotSpectra plots a spectra of a subject and query spectra. plotSpectra uses ggplot plotting functionality.

Usage

```
plotSpectra(sps, subject, query)
```

Arguments

sps	Spectra object
subject	character, name of spectra that is aligned against, character with preceding sample name
query	character, name of spectra that is aligned to subject, character with preceding sample name

Details

Internally, all intensities are normalized to 100%.

Value

ggplot2 plot

Author(s)

Thomas Naake, <thomasnaake@googlemail.com>

Examples

```
data("spectra", package = "MetCirc")
plotSpectra(sps = sps_tissue, subject = "SPL_1", query = "SPL_2")
```

printInformationSelect *Display information on connected features of selected features*

Description

Displays information on connected features of selected features.

Usage

```
printInformationSelect(
  select,
  sps = NULL,
  linkDfInd,
  linkDf,
  similarityMatrix,
  roundDigits = 2
)
```

Arguments

select	character, obtained from groupname, character of selected feature
sps	Spectra object containing spectra that are compared in similarityMatrix
linkDfInd	numeric indices of selected features
linkDf	data.frame that contains information of linked features for given thresholds
similarityMatrix	matrix that is used to get information on the degree of similarity, similarityMatrix is an ordered version of a similarity matrix, see ?orderSimilarityMatrix
roundDigits	numeric(1), how many digits should be displayed?

Details

printInformationSelect is for internal use.

Value

character that is in HTML format

Author(s)

Thomas Naake, <thomasnaake@googlemail.com>

Examples

```
data("spectra", package = "MetCirc")
sps_tissue@metadata$names <- rep("Unknown", 259)
sps_tissue@metadata$information <- rep("Unknown", 259)
sps_tissue@metadata$classes <- rep("Unknown", 259)
sps_tissue@metadata$adduct <- rep("Unknown", 259)
similarityMat <- Spectra::compareSpectra(sps_tissue[1:10],
    FUN = MsCoreUtils::ndotproduct, ppm = 20, m = 0.5, n = 2)
rownames(similarityMat) <- colnames(similarityMat) <- sps_tissue$name[1:10]
linkDf <- createLinkDf(similarityMatrix = similarityMat,
    sps = sps_tissue[1:10],
    condition = c("SPL", "LIM", "ANT", "STY"), lower = 0.01, upper = 1)

## cut link data.frame (here: only display links between groups)
linkDf_cut <- cutLinkDf(linkDf, type = "inter")
groupname <- c(as.character(linkDf_cut[, "spectrum1"]),
            as.character(linkDf_cut[, "spectrum2"]))
groupname <- unique(groupname)

## arbitrarily select a feature
ind <- 2
linkDfInds <- getLinkDfIndices(groupname[ind], linkDf_cut)
MetCirc:::printInformationSelect(select = groupname[ind],
    sps = sps_tissue[1:10], linkDfInd = linkDfInds,
    linkDf = linkDf_cut, similarityMatrix = similarityMat)
```

---

recordPlotFill_degreeFeatures

Record a plot of filled features and the degree of features

Description

`recordPlotFill_degreeFeatures` records a plot of filled features and returns the degree of features.

Usage

```
recordPlotFill_degreeFeatures(type_match, ...)
```

Arguments

`type_match`	`character`, ordered vector according to type
`...`	further arguments passed to `plotCircos`

Details

Helper function for `shinyCircos`.

Value

list of length 2, entry plotFill is of recordedplot and entry degreeFeatures is a list of vectors of numeric(1)

Author(s)

Thomas Naake, <thomasnaake@googlemail.com>

Examples

```
type_match <- c("a_1", "a_2", "a_3", "b_1", "b_2", "b_3", "c_1", "c_2")
MetCirc:::recordPlotFill_degreeFeatures(type_match)
```

---

recordPlotHighlight *Return a* recordedplot *of* plotCircos *plot with* highlight = TRUE

Description

recordPlotHighlight returns a recordedplot object of plotCircos with highlight = TRUE

Usage

```
recordPlotHighlight(type_match, ...)
```

Arguments

type_match	character, ordered vector according to type
...	further arguments passed to plotCircos

Details

Helper function for shinyCircos.

Value

recordedplot

Author(s)

Thomas Naake, <thomasnaake@googlemail.com>

Examples

```
type_match <- c("a_1", "a_2", "a_3", "b_1", "b_2", "b_3", "c_1", "c_2")
MetCirc:::recordPlotHighlight(type_match)
```

replayPlotAdd *Plot plotCircos or highlight*

Description

replayPlotAdd plots additional plots on a plot, either plots plotCircos or highlight.

Usage

```
replayPlotAdd(
  orderMatch = "mz",
  onCircle = FALSE,
  linkDf,
  mz_match,
  rt_match,
  clust_match,
  ind,
  indMz,
  indRT,
  indCluster
)
```

Arguments

orderMatch	character(1), either "mz", "retentionTime", or "clustering"
onCircle	logical, are coordinates on circle. If FALSE and no features are selected (length(ind) == 0), then filled plots are replayed, otherwise highlighted plots are replayed.
linkDf	data.frame that contains information of linked features for given thresholds
mz_match	character, ordered vector according to m/z
rt_match	character, ordered vector according to retention time
clust_match	character, ordered vector according to clustering
ind	numeric, indices of clicked features
indMz	numeric, indices of clicked features for "mz" ordering
indRT	numeric, indices of clicked features for "retentionTime" ordering
indCluster	numeric, indices of clicked features for "clustering" ordering

Details

Helper function for shinyCircos.

Value

Depending on onCircle and indMz either returns plotCircos or highlight

Author(s)

Thomas Naake, <thomasnaake@googlemail.com>

Examples

```
data("spectra", package = "MetCirc")
similarityMat <- Spectra::compareSpectra(sps_tissue[1:10],
    FUN = MsCoreUtils::ndotproduct, ppm = 10, m = 0.5, n = 2)
rownames(similarityMat) <- colnames(similarityMat) <- sps_tissue$name[1:10]

## order according to m/z
mz_match <- MetCirc:::typeMatch_link0(similarityMatrix = similarityMat,
    sps = sps_tissue, type = "mz",
    condition = c("SPL", "LIM", "ANT", "STY"))
linkDf <- mz_match[["link0df"]]
mz_match <- mz_match[["type_match"]]

## order according to retention time
rt_match <- MetCirc:::typeMatch_link0(similarityMatrix = similarityMat,
    sps = sps_tissue, type = "retentionTime",
    condition = c("SPL", "LIM", "ANT", "STY"))
rt_match <- rt_match[["type_match"]]

## order according to clustering
clust_match <- MetCirc:::typeMatch_link0(similarityMatrix = similarityMat,
    sps = sps_tissue, type = "clustering",
    condition = c("SPL", "LIM", "ANT", "STY"))
clust_match <- clust_match[["type_match"]]
circos.initialize(mz_match,##, levels  =  mz_match),
    xlim = matrix(rep(c(0,1), length(mz_match)), ncol = 2, byrow = TRUE))
#circos.trackPlotRegion(factor(mz_match, levels = mz_match), ylim = c(0,1))
MetCirc:::replayPlotAdd(orderMatch = "mz", onCircle = FALSE, linkDf = linkDf,
    mz_match = mz_match, rt_match = rt_match, clust_match = clust_match,
    ind = 1, indMz = NULL, indRT = NULL, indCluster = NULL)
```

---

replayPlotOrder *Wrapper for* replayPlot

Description

replayPlotOrder will call replayPlot from grDevices with a recordedplot object based on orderMatch.

Usage

```
replayPlotOrder(orderMatch = "mz", onCircle = FALSE, plot_l, ind)
```

Arguments

orderMatch	character, either "mz", "retentionTime" or "clustering"
onCircle	logical, are coordinates on circle. If FALSE and no features are selected (length(ind) == 0), then filled plots are replayed, otherwise highlighted plots are replayed.
plot_l	list with plots
ind	numeric, indices of clicked features

Details

Helper function for shinyCircos.

Value

replayedplot

Author(s)

Thomas Naake, <thomasnaake@googlemail.com>

Examples

```
type_match <- c("a_1", "a_2", "a_3", "b_1", "b_2", "b_3", "c_1", "c_2")
plotCircos(type_match, NULL, initialize = TRUE, featureNames = TRUE,
    groupSector = TRUE, groupName = FALSE, links = FALSE,
    highlight = TRUE)
p <- recordPlot()
plot.new()
plot_l <- list(highlightMz = p)
MetCirc:::replayPlotOrder(orderMatch = "mz", onCircle = TRUE,
    plot_l = plot_l, ind = NULL)
```

---

sd01_outputXCMS *Example data for 'MetCirc': 'sd01_outputXCMS'*

Description

'sd01_outputXCMS' is the output file from the package 'XCMS' using the data from Li et al. (2015). See Li et al. (2015) for further details.

Format

'data.frame'

Value

'data.frame'

Author(s)

Thomas Naake, <thomasnaake@googlemail.com>

Source

Li et al. (2015)

---

sd02_deconvoluted *Example data for 'MetCirc': sd02_deconvoluted*

Description

'sd02_deconvoluted' contains MS/MS data from Li et al. (2015). It is a 'data.frame' which hosts m/z values, retention time, intensity and the respective precursor m/z values. 'sd02_deconvoluted' originates from Li et al. (2015). See Li et al. (2015) for further information.

Format

'data.frame'

Value

'data.frame'

Author(s)

Thomas Naake, <thomasnaake@googlemail.com>

Source

Li et al. (2015)

---

select *Select variable based on condition*

Description

`select` returns `mz`, `rt` or `clust` depending on `condition`.

Usage

```
select(condition, mz, rt, clust)
```

Arguments

condition	character(1), either "mz", "retentionTime", or "clustering"
mz	object to return if condition == "mz"
rt	object to return if condition == "retentionTime"
clust	object to return if condition == "clustering"

Details

Helper function for shinyCircos, replayPlotOrder and replayPlotAdd.

Value

mz, rt or clust depending on condition

Author(s)

Thomas Naake <thomasnaake@googlemail.com>

Examples

```
mz <- 1
rt <- 2
clust <- 3
MetCirc:::select(condition = "mz", mz = mz, rt = rt, clust = clust)
```

---

shinyCircos *Interactive visualisation of similarity and navigation of MS/MS features*

Description

Visualise the similarity of MS/MS features in a reactive context. See Details the vignette for further descriptions on how to use shinyCircos.

Usage

```
shinyCircos(similarityMatrix, sps, condition, ...)
```

Arguments

similarityMatrix	matrix, similarityMatrix contains pair-wise similarity coefficients which give information about the similarity between MS/MS features
sps	Spectra, sps will be used to display information about the selected feature and will store information of annotation
condition	character vector, specifies which conditions/samples are displayed
...	further arguments passed to shinyCircos, e.g. cexFeatureNames to pass to plotCircos to set font size in plotCircos of feature names

Details

The function is based on the shiny and circlize package. The user can choose interactively thresholds, type of links (between or within groups), display information about MS/MS features, permanently select MS/MS features and export selected precursors. The Spectra object stores annotation information about the MS/MS features. Names of features within the similarityMatrix have to be found as entries in Spectra. sps$name are used as identifiers and colnames/rownames from similarityMatrix are cleaved by the group identifier (separated by "_"). Annotation information is taken from spectra from the columns "names", "information", "classes" and "adduct" in the slot metadata of spectra. After exiting the application, the annotation will be written to the respective columns in the slot metadata. If one or several of these columns is already present in metadata, the column(s) will be used as the source of annotation information.

Value

character, shinyCircos returns a character vector with the permanently selected precursors and an object with the MSpectra object containing the annotation.

Author(s)

Thomas Naake, <thomasnaake@googlemail.com>

Examples

```
data("spectra", package = "MetCirc")
similarityMat <- Spectra::compareSpectra(sps_tissue[1:10],
    FUN = MsCoreUtils::ndotproduct, ppm = 10, m = 0.5, n = 2)
rownames(similarityMat) <- colnames(similarityMat) <- sps_tissue$name[1:10]
## Not run:
shinyCircos(similarityMatrix = similarityMat,
    sps = sps_tissue, condition = c("SPL", "LIM", "ANT", "STY"))

## End(Not run)
```

---

similarityMat *Example data for 'MetCirc': 'similarityMat'*

Description

'similarityMat' is a 'matrix' containing the pair-wise similarity scores derived from the 'idMSMStissueproject' data set. See the vignette for a workflow to reproduce the object 'similarityMat'.

Format

'matrix'

Value

'matrix'

Author(s)

Thomas Naake, <thomasnaake@googlemail.com>

Source

data("spectra", package = "MetCirc") similarityMat <- Spectra::compareSpectra(sps_tissue, fun = ndotproduct, ppm = 10) rownames(similarityMat) <- colnames(similarityMat) <- sps_tissue$name save(similarityMat, file = "similarityMat.RData", compress = "xz")

---

spectraCondition *Get MS/MS spectra that are present in condition*

Description

`spectraCondition` returns the names of `Spectra` that are present in condition, corresponding to the slot `metadata`.

Usage

```
spectraCondition(sps, condition)
```

Arguments

`sps`	`Spectra` object of `Spectra` package
`condition`	`character`, vector with conditions found as columns in the metadata slot

Details

Helper function in `createLink0df` and `shinyCircos`.

Value

`list`, named `list` with `character` vector as entries that contains the names of the MS/MS entries in `spectra` that are present in the `conditon` (tissues, stress conditions, time points, etc.)

Author(s)

Thomas Naake <thomasnaake@googlemail.com>

Examples

```
data("spectra", package = "MetCirc")
MetCirc:::spectraCondition(sps = sps_tissue,
    condition = c("SPL", "LIM", "ANT", "STY"))
```

sps_tissue *Example data for 'MetCirc': 'sps_tissue'*

Description

'sps_tissue' is a 'Spectra' object derived from the 'idMSMStissueproject' data set. See the vignette for a workflow to reproduce the object 'spectra'.

Format

'matrix'

Value

'matrix'

Author(s)

Thomas Naake, <thomasnaake@googlemail.com>

Source

data("idMSMStissueproject", package = "MetCirc") ## get all MS/MS spectra tissue <- tissue[tissue[, "id"] id_uniq <- unique(tissue[, "id"])

obtain precursor m/z from id_uniq prec_mz <- lapply(strsplit(as.character(id_uniq), split = "_"), "[", 1) |> unlist() |> as.numeric()

obtain m/z from fragments per precursor m/z mz_l <- lapply(id_uniq, function(id_i) tissue[tissue[, "id"] == id_i, "mz"])

obtain corresponding intensity values int_l <- lapply(id_uniq, function(id_i) tissue[tissue[, "id"] == id_i, "intensity"])

order mz and intensity values int_l <- lapply(seq_along(int_l), function(i) int_l[[i]][order(mz_l[[i]])]) mz_l <- lapply(seq_along(mz_l), function(i) sort(mz_l[[i]]))

obtain retention time by averaging all retention time values rt <- lapply(id_uniq, function(id_i) tissue[tissue[, "id"] == id_i, "rt"]) |> lapply(mean) |> unlist()

create list of Spectra objects and concatenate sps_l <- lapply(seq_len(length(mz_l)), function(i) spd <- S4Vectors::DataFrame(name = as.character(i), rtime = rt[i], msLevel = 2L, precursorMz = prec_mz[i]) spd$mz <- list(mz_l[[i]]) spd$intensity <- list(int_l[[i]]) Spectra::Spectra(spd)) sps_tissue <- Reduce(c, sps_l)

combine list of spectrum2 objects to MSpectra object, ## use SPL, LIM, ANT, STY for further analysis sps_tissue@metadata <- data.frame(compartmentTissue[, c("SPL", "LIM", "ANT", "STY")])

save(sps_tissue, file = "spectra.RData", compress = "xz")

thresholdLinkDf *Threshold a data frame containing information on links*

Description

Threshold a link data frame based on lower and upper similarity values. The function will return the links that lie within the defined bounds.

Usage

```
thresholdLinkDf(link0df, lower = 0.75, upper = 1)
```

Arguments

link0df	data.frame, a link data frame that gives per each row information on linked features
lower	numeric, threshold value for similarity values, below this value linked features will not be returned
upper	numeric, threshold value for similarity values, above this value linked features will not be returned

Details

lower and upper are numerical values and truncate mass spectra based on their similarity values.

Value

thresholdLinkDf returns a data.frame that gives per each row information on linked features which are linked within certain thresholds.

Author(s)

Thomas Naake, <thomasnaake@googlemail.com>

Examples

```
data("spectra", package = "MetCirc")
data("similarityMat", package = "MetCirc")
link0df <- createLink0df(similarityMatrix = similarityMat,
    sps_tissue, condition = c("SPL", "LIM", "ANT", "STY"))
thresholdLinkDf(link0df = link0df, lower = 0.5, upper = 1)
```

tissue *Example data for 'MetCirc': 'tissue'*

Description

The 'data.frame' 'tissue' is used in the subsection 'Preparing the tissue data set for analysis' in the vignette of 'MetCirc'. MS/MS data are merged across floral organs in this 'data.frame'.

Format

'data.frame'

Value

'data.frame'

Author(s)

Thomas Naake, <thomasnaake@googlemail.com>

Source

internal

typeMatch_link0 *Get typeMatch and link0 data frame*

Description

`typeMatch_link0` returns a list with accessors `"link0df"` and `"type_match"`

Usage

```
typeMatch_link0(similarityMatrix, sps, type, condition)
```

Arguments

`similarityMatrix`	`matrix` with pairwise similarity values
`sps`	`Spectra` object
`type`	`character(1)`, either `"mz"`, `"retentionTime"`, `"clustering"`
`condition`	`character`

Details

Helper function for `shinyCircos`.

Value

`list` of length 2, entry `link0df` is a `data.frame` and entry `type_match` is a `character` vector

Author(s)

Thomas Naake, <thomasnaake@googlemail.com>

Examples

```
data("spectra", package = "MetCirc")
similarityMat <- Spectra::compareSpectra(sps_tissue[1:10],
    FUN = MsCoreUtils::ndotproduct, ppm = 10, m = 0.5, n = 2)
rownames(similarityMat) <- colnames(similarityMat) <- sps_tissue$name[1:10]

## order according to retention time
MetCirc:::typeMatch_link0(similarityMatrix = similarityMat,
    sps = sps_tissue, type = "mz",
    condition = c("SPL", "LIM", "ANT", "STY"))
```

Index

cart2Polar, 3
circosLegend, 3
compartmentTissue, 5
convertExampleDF, 5
convertMsp2Spectra, 6
createLink0df, 7
createLinkDf, 8
cutLinkDf, 9

getLinkDfIndices, 10

highlight, 11

minFragCart2Polar, 12
msp2spectra, 14

neutralloss, 14

orderSimilarityMatrix, 16

plotCircos, 17
plotSpectra, 19
printInformationSelect, 20

recordPlotFill_degreeFeatures, 21
recordPlotHighlight, 22
replayPlotAdd, 23
replayPlotOrder, 24

sd01_outputXCMS, 25
sd02_deconvoluted, 26
select, 26
shinyCircos, 27
similarityMat, 28
spectraCondition, 29
sps_tissue, 30

thresholdLinkDf, 31
tissue, 32
typeMatch_link0, 32