Package 'MiPP'

November 12, 2026

Version 1.84.0

Date 2007-01-31

Title Misclassification Penalized Posterior Classification

Author HyungJun Cho <hj4cho@korea.ac.kr>,
Sukwoo Kim <s4kim@korea.ac.kr>,
Mat Soukup <soukup@fda.gov>, and
Jae K. Lee <jaeklee@virginia.edu>

Maintainer Sukwoo Kim <s4kim@korea.ac.kr>

Depends R (>= 2.4)

Imports Biobase, e1071, MASS, stats

Description This package finds optimal sets of genes that seperate samples into two or more classes.

License GPL (>= 2)

URL http://www.healthsystem.virginia.edu/internet/hes/biostat/bioinformatics/

biocViews Microarray, Classification

git_url https://git.bioconductor.org/packages/MiPP

git_branch RELEASE_3_23

git_last_commit 370860f

git_last_commit_date 2026-04-28

Repository Bioconductor 3.23

Date/Publication 2026-11-11

Contents

colon 2
cv.mipp.rule 2
get.mipp 3
get.mipp.lda 3
get.mipp.logistic 3
get.mipp.qda 3
get.mipp.svm.linear 3

get.mipp.svm.rbf 4
leuk1 4
leuk2 4
leukemia 5
linearkernel.decision.function 5
mipp 6
mipp.preproc 8
mipp.rule 9
mipp.seq 9
pre.select 11
quant.normal 12
quant.normal2 12
rbfkernel.decision.function 12

Index **13**

`colon` *Gene expression data for colon cancer*

Description

This data set consists of gene expression of colon cancer study.

Usage

```
data(colon)
```

Format

A matrix containing 2000 probe sets and 2 classes (T, F)

Source

Alon, U., Barkai, N., Notterman, D.A., Gish, K., Ybarra, S., Mack, D., Levine, A.J. (1999). Broad Patterns of Gene Expression Revealed by Clustering Analysis of Tumor and Normal Colon Tissues probed by Oligonucleotide Arrays, PNAS, 96(12), 6745–6750.

`cv.mipp.rule` *Fitting cross-validaion MiPP*

Description

Fits cross-validation MiPP

`get.mipp` *Choosing a rule*

Description

Choose a rule to compute MiPP

`get.mipp.lda` *Fitting LDA to compute MiPP*

Description

Fits LDA to compute MiPP

`get.mipp.logistic` *Fitting logistic model to compute MiPP*

Description

Fits logistic model to compute MiPP

`get.mipp.qda` *Fitting QDA to compute MiPP*

Description

Fits QDA to compute MiPP

`get.mipp.svm.linear` *Fitting SVM (linear) to compute MiPP*

Description

Fits SVM (linear) to compute MiPP

get.mipp.svm.rbf *Fitting SVM (RBF) to compute MiPP*

Description

Fits SVM (RBF) to compute MiPP

leuk1 *Gene expression data for leukemia*

Description

This data set consists of gene expression of leukemia study.

Usage

```
data(leukemia)
```

Format

A matrix containing 6817 probe sets and 38 samples (2 classes: AML, ALL)

Source

Golub, T.R., Slonim, D.K., Tamayo, P., Huard, C., Gaasenbeek, M., Mesirov, P., Coller, H., Loh, M.L., Downing, J.R., Caliguri, M.A., Bloomfield, C.D., and Lander, E.S. (1999) Molecular classification of cancer: class discovery and class prediction by gene expression monitoring. Science, 286, 531-537.

leuk2 *Gene expression data for leukemia*

Description

This data set consists of gene expression of leukemia study.

Usage

```
data(leukemia)
```

Format

A matrix containing 6817 probe sets and 34 samples (2 classes: AML, ALL)

Source

Golub, T.R., Slonim, D.K., Tamayo, P., Huard, C., Gaasenbeek, M., Mesirov, P., Coller, H., Loh, M.L., Downing, J.R., Caliguri, M.A., Bloomfield, C.D., and Lander, E.S. (1999) Molecular classification of cancer: class discovery and class prediction by gene expression monitoring. Science, 286, 531-537.

---

leukemia *Gene expression data for leukemia*

Description

This data set consists of gene expression of leukemia study.

Usage

```
data(leukemia)
```

Format

A matrix containing 6817 probe sets and 2 classes (AML, ALL)

Source

Golub, T.R., Slonim, D.K., Tamayo, P., Huard, C., Gaasenbeek, M., Mesirov, P., Coller, H., Loh, M.L., Downing, J.R., Caliguri, M.A., Bloomfield, C.D., and Lander, E.S. (1999) Molecular classification of cancer: class discovery and class prediction by gene expression monitoring. Science, 286, 531-537.

---

linearkernel.decision.function *SVM (linear) kernel to compute MiPP*

Description

SVM (linear) kernel to compute MiPP

mipp *MiPP-based Classification*

Description

Finds optimal sets of genes for classification

Usage

```
mipp(x, y, x.test = NULL, y.test = NULL, probe.ID = NULL,
    rule = "lda", method.cut = "t.test", percent.cut = 0.01,
    model.sMiPP.margin = 0.01, min.sMiPP = 0.85, n.drops = 2,
    n.fold = 5, p.test = 1/3, n.split = 20,
    n.split.eval = 100)
```

Arguments

x	data matrix
y	class vector
x.test	test data matrix if available
y.test	test class vector if available
probe.ID	probe set IDs; if NULL, row numbers are assigned.
rule	classification rule: "lda","qda","logistic","svmlin","svmrbf"; the default is "lda".
method.cut	method for pre-selection; t-test is available.
percent.cut	proportion of pre-selected genes; the default is 0.01.
model.sMiPP.margin	smallest set of genes s.t. sMiPP <= (max sMiPP-model.sMiPP.margin); the default is 0.01.
min.sMiPP	Adding genes stops if max sMiPP is at least min.sMiPP; the default is 0.85.
n.drops	Adding genes stops if sMiPP decreases (n.drops) times, in addition to min.sMiPP criterion.; the default is 2.
n.fold	number of folds; default is 5.
p.test	partition percent of train and test samples when test samples are not available; the default is 1/3 for test set.
n.split	number of splits; the default is 20.
n.split.eval	numbr of splits for evalutation; the default is 100.

Value

model	candiadate genes (for each split if no indep set is available
model.eval	Optimal sets of genes for each split when no indep set is available

Author(s)

Soukup M, Cho H, and Lee JK

References

Soukup M, Cho H, and Lee JK (2005). Robust classification modeling on microarray data using misclassification penalized posterior, Bioinformatics, 21 (Suppl): i423-i430.

Soukup M and Lee JK (2004). Developing optimal prediction models for cancer classification using gene expression data, Journal of Bioinformatics and Computational Biology, 1(4) 681-694

Examples

```
##########
#Example 1: When an independent test set is available

data(leukemia)

#Normalize combined data
leukemia <- cbind(leuk1, leuk2)
leukemia <- mipp.preproc(leukemia, data.type="MAS4")

#Train set
x.train <- leukemia[,1:38]
y.train <- factor(c(rep("ALL",27),rep("AML",11)))

#Test set
x.test <- leukemia[,39:72]
y.test <- factor(c(rep("ALL",20),rep("AML",14)))


#Compute MiPP
out <- mipp(x=x.train, y=y.train, x.test=x.test, y.test=y.test, probe.ID = 1:nrow(x.train), n.fold=5, percent.cut=

#Print candidate models
out$model



##########
#Example 2: When an independent test set is not available

data(colon)

#Normalize data
x <- mipp.preproc(colon)
y <- factor(c("T", "N", "T", "N", "T", "N", "T", "N", "T", "N",
       "T", "N", "T", "N", "T", "N", "T", "N", "T", "N",
       "T", "N", "T", "N", "T", "T", "T", "T", "T", "T",
       "T", "T", "T", "T", "T", "T", "T", "T", "N", "T",
       "T", "N", "N", "T", "T", "T", "T", "N", "T", "N",
       "N", "T", "T", "N", "N", "T", "T", "T", "T", "N",
```

```
        "T", "N"))


#Deleting comtaminated chips
x <- x[,-c(51,55,45,49,56)]
y <- y[ -c(51,55,45,49,56)]

#Compute MiPP
out <- mipp(x=x, y=y, probe.ID = 1:nrow(x), n.fold=5, p.test=1/3, n.split=5, n.split.eval=100,
percent.cut= 0.1, rule="lda")

#Print candidate models for each split
out$model

#Print optimal models and independent evaluation for each split
out$model.eval
```

`mipp.preproc` *Preprocessing*

Description

Performs IQR normalization, thesholding, and log2-transformation

Usage

```
mipp.preproc(x, data.type = "MAS5")
```

Arguments

`x`	data
`data.type`	data type is MAS5, MAS4, or dChip

See Also

`mipp`

Examples

```
library(MiPP)

data(colon)
colon.nor <- mipp.preproc(colon)
```

`mipp.rule` *Computing MiPP*

Description

Computes MiPP

`mipp.seq` *MiPP-based Classification*

Description

sequentially finds optimal sets of genes for classification

Usage

```
mipp.seq(x, y, x.test = NULL, y.test = NULL, probe.ID = NULL,
    rule = "lda", method.cut = "t.test", percent.cut = 0.01,
    model.sMiPP.margin = 0.01, min.sMiPP = 0.85, n.drops = 2,
    n.fold = 5, p.test = 1/3, n.split = 20, n.split.eval = 100,
    n.seq=3, cutoff.sMiPP=0.7, remove.gene.each.model="all")
```

Arguments

`x`	data matrix
`y`	class vector
`x.test`	test data matrix if available
`y.test`	test class vector if available
`probe.ID`	probe set IDs; if NULL, row numbers are assigned.
`rule`	classification rule: "lda","qda","logistic","svmlin","svmrbf"; the default is "lda".
`method.cut`	method for pre-selection; t-test is available.
`percent.cut`	proportion of pre-selected genes; the default is 0.01.
`model.sMiPP.margin`	smallest set of genes s.t. sMiPP <= (max sMiPP-model.sMiPP.margin); the default is 0.01.
`min.sMiPP`	Adding genes stops if max sMiPP is at least min.sMiPP; the default is 0.85.
`n.drops`	Adding genes stops if sMiPP decreases (n.drops) times, in addition to min.sMiPP criterion.; the default is 2.
`n.fold`	number of folds; default is 5.
`p.test`	partition percent of train and test samples when test samples are not available; the default is 1/3 for test set.

n.split	number of splits; the default is 20.
n.split.eval	numbr of splits for evalutation; the default is 100.
n.seq	Number of sequential gene model selection; the default is 3.
cutoff.sMiPP	Cutoff point of 5 percent sMiPP to select gene models
remove.gene.each.model	Re-run after removing all genes in the selected models if "all" and the first gene for each of the selected models if "first"

Value

model	candiadate genes (for each split if no indep set is available
model.eval	Optimal sets of genes for each split when no indep set is available
genes.selected	a list of genes selected by sequential selection

Author(s)

Soukup M, Cho H, and Lee JK

References

Soukup M, Cho H, and Lee JK (2005). Robust classification modeling on microarray data using misclassification penalized posterior, Bioinformatics, 21 (Suppl): i423-i430.

Soukup M and Lee JK (2004). Developing optimal prediction models for cancer classification using gene expression data, Journal of Bioinformatics and Computational Biology, 1(4) 681-694

Examples

```
##########
#Example 1: When an independent test set is available

data(leukemia)

#Normalize combined data
leukemia <- cbind(leuk1, leuk2)
leukemia <- mipp.preproc(leukemia, data.type="MAS4")

#Train set
x.train <- leukemia[,1:38]
y.train <- factor(c(rep("ALL",27),rep("AML",11)))

#Test set
x.test <- leukemia[,39:72]
y.test <- factor(c(rep("ALL",20),rep("AML",14)))


#Compute MiPP
out <- mipp.seq(x=x.train, y=y.train, x.test=x.test, y.test=y.test, n.fold=5, percent.cut=0.01, rule="lda", n.seq

#Print candidate models
```

```
out$model

#Print the genes selected
out$genes.selected


##########
#Example 2: When an independent test set is not available

data(colon)

#Normalize data
x <- mipp.preproc(colon)
y <- factor(c("T", "N", "T", "N", "T", "N", "T", "N", "T", "N",
       "T", "N", "T", "N", "T", "N", "T", "N", "T", "N",
       "T", "N", "T", "N", "T", "T", "T", "T", "T", "T",
       "T", "T", "T", "T", "T", "T", "T", "T", "N", "T",
       "T", "N", "N", "T", "T", "T", "T", "N", "T", "N",
       "N", "T", "T", "N", "N", "T", "T", "T", "T", "N",
       "T", "N"))


#Deleting comtaminated chips
x <- x[,-c(51,55,45,49,56)]
y <- y[ -c(51,55,45,49,56)]

#Compute MiPP
out <- mipp.seq(x=x, y=y, n.fold=5, p.test=1/3, n.split=5, n.split.eval=100,
percent.cut= 0.05, rule="lda", n.seq=2)


#Print candidate models for each split
out$model

#Print optimal models and independent evaluation for each split
out$model.eval

#Print the genes selected
out$genes.selected
```

`pre.select` *Pre-selection*

Description

Pre-select genes

`quant.normal` *Quantile normalization*

Description

Performs quantile normalization

`quant.normal2` *Quantile normalization*

Description

Performs quantile normalization

`rbfkernel.decision.function`
SVM (RBF) kernel to compute MiPP

Description

SVM (RBF) kernel to compute MiPP

Index

∗ **datasets**
colon, 2
leuk1, 4
leuk2, 4
leukemia, 5
∗ **models**
cv.mipp.rule, 2
get.mipp, 3
get.mipp.lda, 3
get.mipp.logistic, 3
get.mipp.qda, 3
get.mipp.svm.linear, 3
get.mipp.svm.rbf, 4
linearkernel.decision.function, 5
mipp, 6
mipp.preproc, 8
mipp.rule, 9
mipp.seq, 9
pre.select, 11
quant.normal, 12
quant.normal2, 12
rbfkernel.decision.function, 12

colon, 2
cv.mipp.rule, 2

get.mipp, 3
get.mipp.lda, 3
get.mipp.logistic, 3
get.mipp.qda, 3
get.mipp.svm.linear, 3
get.mipp.svm.rbf, 4

leuk1, 4
leuk2, 4
leukemia, 5
leukimia *(*leukemia*)*, 5
linearkernel.decision.function, 5

mipp, 6, *8*
mipp.preproc, 8
mipp.rule, 9
mipp.seq, 9

pre.select, 11

quant.normal, 12
quant.normal2, 12

rbfkernel.decision.function, 12