Package 'NCIgraph'

November 12, 2026

Title Pathways from the NCI Pathways Database

Version 1.60.0

Date 2012-04-27

Author Laurent Jacob

Maintainer Laurent Jacob <laurent.jacob@gmail.com>

Description Provides various methods to load the pathways from the NCI Pathways Database in R graph objects and to re-format them.

License GPL-3

LazyLoad yes

Imports graph, KEGGgraph, methods, RBGL, RCy3, R.oo

Depends R (>= 4.0.0)

Suggests Rgraphviz

Enhances DEGraph

biocViews Pathways, GraphAndNetwork

git_url https://git.bioconductor.org/packages/NCIgraph

git_branch RELEASE_3_23

git_last_commit 9faaba6

git_last_commit_date 2026-04-28

Repository Bioconductor 3.23

Date/Publication 2026-11-11

Contents

directedBFS 2
edgesToMerge 3
getNCIPathways 3
getSubtype.NCIgraph 5
is.NCIgraph 6
mergeNodes 6
NCI.demo.cyList 7

NCIgraph 8
parseNCInetwork 8
propagateRegulation 9
translateNCI2GeneID 10

Index **11**

`directedBFS` *Uses a breadth first search on a directed graph to identify which genes are regulated by a particular node in the graph*

Description

Uses a breadth first search on a directed graph to identify which genes are regulated by a particular node in the graph.

Usage

```
directedBFS(g, node)
```

Arguments

g	A graph object.
node	A node of g.

Value

A structured list containing the regulated genes and the type of interaction between node and each gene.

Author(s)

Laurent Jacob

See Also

propagateRegulation()

edgesToMerge *Identifies edges that should be merged to parse a NCI network*

Description

Identifies edges that should be merged to parse a NCI network.

Usage

```
edgesToMerge(g)
```

Arguments

g	A graph object.

Value

A list of edges to be merged

Author(s)

Laurent Jacob

See Also

parseNCInetwork()

getNCIPathways *Loads networks from Cytoscape and parses them*

Description

Loads networks from Cytoscape and parses them.

Usage

```
getNCIPathways(cyList=NULL, parseNetworks=TRUE, entrezOnly=TRUE, verbose=FALSE)
```

Arguments

cyList	a list providing the networks loaded from Cytoscape. If NULL, the function will try to build the list from Cytoscape.
verbose	If TRUE, extra information is output.
parseNetworks	A logical. If FALSE, the raw NCI networks are returned as graphNEL objects. If TRUE, some additional parsing is performed by the parseNCInetwork function.
entrezOnly	A logical. If TRUE, only keep nodes with an entrezID property.

Value

A list of two elements: pList, a list of graphNEL objects, and failedW a list containing the names of the networks that R failed to read from cytoscape.

Author(s)

Laurent Jacob

See Also

parseNCInetwork()

Examples

```
##------------------------------
## Load NCIgraph
##------------------------------

library(NCIgraph)

##------------------------------
## Example 1: with Cytoscape
##------------------------------

## Must have Cytoscape running with some networks open and CyREST plugin started.

## In this case, getNCIPathways will both read the raw networks from Cytoscape and parse them.

## Not run:
grList <- getNCIPathways(cyList=NULL, parseNetworks=TRUE, entrezOnly=TRUE, verbose=TRUE)$pList

## End(Not run)

##------------------------------
## Example 2: without Cytoscape
##------------------------------

## Get some raw networks

data("NCIgraphVignette", package="NCIgraph")

## When passed a non null cyList argument (a list of networks),
## getNCIPathways will simply parse the list of networks

grList <- getNCIPathways(cyList=NCI.demo.cyList, parseNetworks=TRUE, entrezOnly=TRUE, verbose=TRUE)$pList
```

getSubtype.NCIgraph *Returns a list of @KEGGEdgeSubType objects describing each edge of the NCI network*

Description

Returns a list of @KEGGEdgeSubType objects describing each edge of the NCI network.

Usage

```
getSubtype.NCIgraph(object)
```

Arguments

object	An NCIgraph object.

Value

A list of KEGGEdgeSubType objects.

Author(s)

Laurent Jacob

Examples

```
##------------------------------
## Load NCIgraph
##------------------------------

library(NCIgraph)

##------------------------------
## Get some raw networks
##------------------------------

data("NCIgraphVignette", package="NCIgraph")

##------------------------------
## Parse them
##------------------------------

grList <- getNCIPathways(cyList=NCI.demo.cyList, parseNetworks=TRUE, entrezOnly=TRUE, verbose=TRUE)$pList

##------------------------------------------------------------------
##
## Get the subtype of the second network. Some activation and some
## inhibition edges.
##
```

```
##------------------------------------------------------------

getSubtype.NCIgraph(grList[[2]])
```

`is.NCIgraph` *Assess whether a graph is a NCI graph*

Description

Assess whether a graph is a NCI graph.

Usage

```
is.NCIgraph(gr)
```

Arguments

gr	A graph object.

Value

A logical, TRUE if the graph is a NCI graph, FALSE otherwise.

Author(s)

Laurent Jacob

See Also

parseNCInetwork()

`mergeNodes` *Merges a given list of nodes in a graph*

Description

Merges a given list of nodes in a graph.

Usage

```
mergeNodes(g, mEdges, separateEntrez=TRUE, entrezOnly=TRUE)
```

Arguments

g	A graph object.
mEdges	A list of nodes to be merged.
separateEntrez	A logical. If TRUE, don't merge two nodes with entrezID.
entrezOnly	A logical. If TRUE, only keep nodes with an entrezID property.

Value

The updated graph object

Author(s)

Laurent Jacob

See Also

parseNCInetwork()

NCI.demo.cyList *10 raw NCI networks from Nature curated pathways and BioCarta imported as graphNEL objects, for demonstration purpose*

Description

These are the ten first elements of the full list of raw networks that can be downloaded using the downloadCyLists.R script.

Usage

```
NCI.demo.cyList
```

Format

A list of 10 graphNEL objects.

Author(s)

Laurent Jacob

Examples

```
data("NCIgraphVignette")
length(NCI.demo.cyList)

library(Rgraphviz)
plot(NCI.demo.cyList[[1]])
```

NCIgraph *Class NCIgraph*

Description

Package: NCIgraph
Class NCIgraph

public static class **NCIgraph**
extends graphNELObject

Class extending graphNEL fro graphs build from NCI gene networks.

Author(s)

Laurent Jacob

parseNCInetwork *Takes a NCI network and transforms it into a simpler graph only representing inhibition/activation relationships between genes*

Description

Takes a NCI network and transforms it into a simpler graph only representing inhibition/activation relationships between genes.

Usage

```
parseNCInetwork(g, propagateReg=TRUE, separateEntrez=TRUE, mergeEntrezCopies=TRUE, entrezOnly=TRUE)
```

Arguments

g	A graph object.
propagateReg	A logical. If TRUE, use propagateRegulation to transform the network before parsing it.
separateEntrez	A logical. If TRUE, don't merge two nodes with entrezID.
mergeEntrezCopies	A logical. If TRUE, merge resulting nodes that have the same entrezID.
entrezOnly	A logical. If TRUE, only keep nodes with an entrezID property.

Value

The new graph object.

Author(s)

Laurent Jacob

Examples

```
## Load NCIgraph

library(NCIgraph)

## Get some raw networks

data("NCIgraphVignette", package="NCIgraph")

## Parse the first of them

parsedNetwork <- parseNCInetwork(NCI.demo.cyList[[1]],propagateReg=TRUE,separateEntrez=TRUE,mergeEntrezCopies=T
```

---

propagateRegulation *Transforms the network in a way that each Biochemical Reaction node pointing to a Complex points to what is regulated by the complex and updates the interaction types accordingly*

Description

Transforms the network in a way that each Biochemical Reaction node pointing to a Complex points to what is regulated by the complex and updates the interaction types accordingly.

Usage

```
propagateRegulation(g)
```

Arguments

g	A graph object.

Value

The updated graph object

Author(s)

Laurent Jacob

See Also

parseNCInetwork()

translateNCI2GeneID *Gives the entrezID corresponding to the nodes of a graph*

Description

Gives the entrezID corresponding to the nodes of a graph.

Usage

```
translateNCI2GeneID(g)
```

Arguments

g	A graph object.

Value

A vector of character giving the entrez ID of the nodes of g.

Author(s)

Laurent Jacob

See Also

parseNCInetwork()

Examples

```
##------------------------------
## Load NCIgraph
##------------------------------

library(NCIgraph)

## Get some raw networks

data("NCIgraphVignette", package="NCIgraph")

## Parse them

grList <- getNCIPathways(cyList=NCI.demo.cyList, parseNetworks=TRUE, entrezOnly=TRUE, verbose=TRUE)$pList

## Get the gene ids for the first of them

gids <- translateNCI2GeneID(grList[[1]])
```

Index

∗ **classes**
    NCIgraph, 8
∗ **datasets**
    NCI.demo.cyList, 7
∗ **documentation**
    NCIgraph, 8

character, *10*

directedBFS, 2

edgesToMerge, 3

FALSE, *3*, *6*

getNCIPathways, 3
getSubtype.NCIgraph, 5
graph, *2, 3*, *6–10*

is.NCIgraph, 6

list, *2–5*, *7*
logical, *3*, *6–8*

mergeNodes, 6

NCI.demo.cyList, 7
NCIgraph, *5*, 8
NCIgraph-class *(*NCIgraph*)*, 8
NULL, *3*

parseNCInetwork, *3, 4*, *6, 7*, 8, *9, 10*
propagateRegulation, *2*, 9

translateNCI2GeneID, 10
TRUE, *3*, *6–8*