Package 'OncoScore'

November 12, 2026

Version 1.40.0

Date 2026-03-09

Title A tool to identify potentially oncogenic genes

Depends R (>= 4.1.0),

Imports biomaRt, grDevices, graphics, utils, methods,

Suggests BiocGenerics, BiocStyle, knitr, testthat,

Description OncoScore is a tool to measure the association of genes to cancer based on citation frequencies in biomedical literature. The score is evaluated from PubMed literature by dynamically updatable web queries.

Encoding UTF-8

License file LICENSE

URL https://github.com/danro9685/OncoScore

BugReports https://github.com/danro9685/OncoScore

biocViews BiomedicalInformatics

RoxygenNote 7.3.3

VignetteBuilder knitr

git_url https://git.bioconductor.org/packages/OncoScore

git_branch RELEASE_3_23

git_last_commit 30cbbd5

git_last_commit_date 2026-04-28

Repository Bioconductor 3.23

Date/Publication 2026-11-11

Author Luca De Sano [cre, aut] (ORCID: <https://orcid.org/0000-0002-9618-3774>), Carlo Gambacorti Passerini [ctb], Rocco Piazza [ctb], Daniele Ramazzotti [aut] (ORCID: <https://orcid.org/0000-0002-6087-2666>), Roberta Spinelli [ctb]

Maintainer Luca De Sano <luca.desano@gmail.com>

Contents

combine.query.results . . . 2
combine.single.matrix . . . 3
compute.frequencies.scores . . . 3
compute.oncoscore . . . 4
compute.oncoscore.from.region . . . 5
compute.oncoscore.timeseries . . . 6
estimate.oncogenes . . . 7
genes . . . 7
get.genes.from.biomart . . . 8
get.list.from.xml . . . 8
get.pubmed.driver.analysis . . . 9
perform.query . . . 9
perform.query.from.region . . . 10
perform.query.timeseries . . . 11
plot.oncoscore . . . 12
plot.oncoscore.timeseries . . . 13
query . . . 14
query.timepoints . . . 14
timepoints . . . 15
try.scan . . . 15

Index **16**

`combine.query.results` *combine.query.results*

Description

Merge a set of genes in a unique one in order to account for possible aliases

Usage

```
combine.query.results(query, genes, new.name)
```

Arguments

`query`	The result of perform.query, perform.query.timeseries of perform.query.from.region
`genes`	A list of genes to be merged
`new.name`	A string containing the new name to be used for the new genes

Value

The frequencies of the genes in the cancer related documents and in all the documents retireved on PubMed

Examples

```
data(query)
combine.query.results(query, c('IDH1', 'IDH2'), 'new_gene')
```

---

combine.single.matrix *combine.single.matrix*

Description

Perform merge procedure on a matrix

Usage

```
combine.single.matrix(query, genes, new.name)
```

Arguments

query	The result of perform.query, perform.query.timeseries of perform.query.from.region
genes	A list of genes to be merged
new.name	A string containing the new name to be used for the new genes

Value

a merged matrix

---

compute.frequencies.scores *compute.frequencies.scores*

Description

compute the logaritmic scores based on the frequencies of the genes

Usage

```
compute.frequencies.scores(data, filter.threshold = 1, analysis.mode = "Log2")
```

Arguments

data	input data as result of the function perform.query
filter.threshold	threshold to filter for a minimum number of citations for the genes
analysis.mode	logaritmic scores to be computed, i.e., log10, log2, natural log or log5

Value

the computed scores

compute.oncoscore *compute.oncoscore*

Description

compute the OncoScore for a list of genes

Usage

```
compute.oncoscore(
  data,
  filter.threshold = 0,
  analysis.mode = "Log2",
  cutoff.threshold = 21.09,
  file = NULL,
  filter.invalid = TRUE
)
```

Arguments

data	input data as result of the function perform.query
filter.threshold	threshold to filter for a minimum number of citations for the genes
analysis.mode	logaritmic scores to be computed, i.e., log10, log2, natural log or log5
cutoff.threshold	threshold to be used to asses the oncogenes
file	should I save the results to text files?
filter.invalid	auto-remove genes with invalid count

Value

the computed OncoScores and the clusters for the genes

Examples

```
data(query)
compute.oncoscore(query)
```

compute.oncoscore.from.region
compute.oncoscore.from.region

Description

Perform OncoScore analysis on a given chromosomic region

Usage

```
compute.oncoscore.from.region(
  chromosome,
  start = NA,
  end = NA,
  gene.num.limit = 100,
  filter.threshold = NA,
  analysis.mode = "Log2",
  cutoff.threshold = 21.09,
  file = NULL
)
```

Arguments

chromosome	chromosome to be retireved
start	initial position to be used
end	final position to be used
gene.num.limit	A limit to the genes to be considered in the analysis; this is done to limit the number of queries to PubMed
filter.threshold	threshold to filter for a minimum number of citations for the genes
analysis.mode	logaritmic scores to be computed, i.e., log10, log2, natural log or log5
cutoff.threshold	threshold to be used to asses the oncogenes
file	should I save the results to text files?

Value

the computed scores

Examples

```
chromosome = 15
start = 200000
end = 300000
```

compute.oncoscore.timeseries
compute.oncoscore.timeseries

Description

perform the OncoScore time series analysis for a list of genes and data times

Usage

```
compute.oncoscore.timeseries(
  data,
  filter.threshold = 0,
  analysis.mode = "Log2",
  cutoff.threshold = 21.09,
  file = NULL
)
```

Arguments

data	input data as result of the function perform.query.timeseries
filter.threshold	threshold to filter for a minimum number of citations for the genes
analysis.mode	logaritmic scores to be computed, i.e., log10, log2, natural log or log5
cutoff.threshold	threshold to be used to asses the oncogenes
file	should I save the results to text files?

Value

the performed OncoScores time series analysis

Examples

```
data(query.timepoints)
compute.oncoscore.timeseries(query.timepoints)
```

`estimate.oncogenes` *estimate.oncogenes*

Description

estimate the oncoscore for the genes

Usage

```
estimate.oncogenes(data, cutoff.threshold = 21.09)
```

Arguments

`data`	input data as result of the function compute.frequencies.scores
`cutoff.threshold`	threshold to be used to asses the oncogenes

Value

the computed scores and oncogenes

`genes` *A list of genes*

Description

This dataset contains a list of genes to be used in the analysis as an example

Usage

```
data(genes)
```

Format

rdata

Value

list of 5 elements

Source

example data

`get.genes.from.biomart` *get.genes.from.biomart*

Description

Get a gene list from biomart

Usage

```
get.genes.from.biomart(chromosome, start = NA, end = NA)
```

Arguments

`chromosome`	chromosome to be retireved
`start`	initial position to be used
`end`	final position to be used

Value

A list of genes

Examples

```
chromosome = 15
start = 200000
end = 300000
```

`get.list.from.xml` *get.list.from.xml*

Description

process the result of the query

Usage

```
get.list.from.xml(webget)
```

Arguments

`webget`	The result from the query to PubMed

Value

Processed result obtained from the query to PubMed

`get.pubmed.driver.analysis` *get.pubmed.driver.analysis*

Description

query PubMed for a list of genes

Usage

```
get.pubmed.driver.analysis(keywords, gene)
```

Arguments

`keywords`	The set of keywords to be used for the query to PubMed
`gene`	The name of a gene to be used for the query to PubMed

Value

The frequency for the current gene retrieved with the query on the provided set of keywords

---

`perform.query` *perform.query*

Description

perform the query to PubMed

Usage

```
perform.query(list.of.genes, gene.num.limit = 100, custom.search = NA)
```

Arguments

`list.of.genes`	The list of genes to be used in the queries to PubMed
`gene.num.limit`	A limit to the genes to be considered in the analysis; this is done to limit the number of queries to PubMed
`custom.search`	A custom set of keyworkds to be used when quering PubMed

Value

The frequencies of the genes in the cancer related documents and in all the documents retireved on PubMed

Examples

```
data(genes)
```

perform.query.from.region *perform.query.from.region*

Description

Perform the query to PubMed on a given chromosomic region

Usage

```
perform.query.from.region(
  chromosome,
  start = NA,
  end = NA,
  gene.num.limit = 100
)
```

Arguments

chromosome	chromosome to be retireved
start	initial position to be used
end	final position to be used
gene.num.limit	A limit to the genes to be considered in the analysis; this is done to limit the number of queries to PubMed

Value

The frequencies of the genes in the cancer related documents and in all the documents retireved on PubMed

Examples

```
chromosome = 15
start = 200000
end = 300000
```

perform.query.timeseries *perform.query.timeseries*

Description

perform the query to PubMed for the time series analysis

Usage

```
perform.query.timeseries(
  list.of.genes,
  list.of.datatimes,
  gene.num.limit = 100,
  timepoints.limit = 10,
  custom.search = NA
)
```

Arguments

list.of.genes	The list of genes to be used in the queries to PubMed
list.of.datatimes	The list of time points to be used in the queries to PubMed
gene.num.limit	A limit to the genes to be considered in the analysis; this is done to limit the number of queries to PubMed
timepoints.limit	A limit to the time points to be considered in the analysis; this is done to limit the number of queries to PubMed
custom.search	A custom set of keyworkds to be used when quering PubMed

Value

The frequencies of the genes in the cancer related documents and in all the documents retireved on PubMed at the specified time points

Examples

```
data(genes)
data(timepoints)
```

plot.oncoscore *plot.oncoscore*

Description

plot the OncoScore for a list of genes

Usage

```
## S3 method for class 'oncoscore'
plot(
  x,
  gene.number = 5,
  main = "OncoScore",
  xlab = "score",
  ylab = "genes",
  file = NA,
  ...
)
```

Arguments

x	input data as result of the function compute.OncoScore
gene.number	number of genes to print
main	the title
xlab	description of x asix (defaul score)
ylab	description of y asix (defaul genes)
file	where to save the plot
...	additional parameter to pass to the barplot function

Value

A plot

Examples

```
data(query)
result = compute.oncoscore(query)
plot.oncoscore(result)
```

`plot.oncoscore.timeseries` *plot.oncoscore.timeseries*

Description

plot the OncoScore for a list of genes

Usage

```
## S3 method for class 'oncoscore.timeseries'
plot(
  x,
  gene.number = 5,
  incremental = FALSE,
  relative = FALSE,
  main = "OncoScore",
  xlab = "timepoints",
  ylab = "score",
  legend.pos = "top",
  file = NA,
  ...
)
```

Arguments

`x`	input data as result of the function compute.OncoScore
`gene.number`	number of genes to print
`incremental`	display the OncoScore increment
`relative`	dispaly the incrementa as relative value
`main`	the title
`xlab`	description of x asix (defaul score)
`ylab`	description of y asix (defaul genes)
`legend.pos`	Position of the legend
`file`	where to save the plot
`...`	additional parameter to pass to the lines function

Value

A plot

Examples

```
data(query.timepoints)
result = compute.oncoscore.timeseries(query.timepoints)
plot.oncoscore.timeseries(result)
```

`query` *The result of perform.web.query on genes*

Description

This dataset contains the result of perform.web.query on genes

Usage

```
data(query)
```

Format

rdata

Value

matrix 5 x 2

Source

example data

`query.timepoints` *The result of perform.time.series.query on genes and timepoints*

Description

This dataset contains the result of perform.time.series.query on genes and timepoints

Usage

```
data(query.timepoints)
```

Format

rdata

Value

list of 5 matrix 5 x 2

Source

example data

`timepoints` *A list of timepoints*

Description

This dataset contains a list of time points to be used in the analysis as an example

Usage

```
data(timepoints)
```

Format

rdata

Value

list of 5 elements

Source

example data

`try.scan` *try.scan*

Description

try to query the given URL

Usage

```
try.scan(getURL)
```

Arguments

`getURL`	The given URL

Value

Result obtained from PubMed

Index

combine.query.results, 2
combine.single.matrix, 3
compute.frequencies.scores, 3
compute.oncoscore, 4
compute.oncoscore.from.region, 5
compute.oncoscore.timeseries, 6

estimate.oncogenes, 7

genes, 7
get.genes.from.biomart, 8
get.list.from.xml, 8
get.pubmed.driver.analysis, 9

perform.query, 9
perform.query.from.region, 10
perform.query.timeseries, 11
plot.oncoscore, 12
plot.oncoscore.timeseries, 13

query, 14
query.timepoints, 14

timepoints, 15
try.scan, 15