Package 'Prostar'

November 12, 2026

Type Package

Title Provides a GUI for DAPAR

Version 1.44.0

Date 2026-04-14

Description This package provides a GUI interface for the DAPAR package. The package Prostar (Proteomics statistical analysis with R) is a Bioconductor distributed R package which provides all the necessary functions to analyze quantitative data from label-free proteomics experiments. Contrarily to most other similar R packages, it is endowed with rich and user-friendly graphical interfaces, so that no programming skill is required.

biocViews Proteomics, MassSpectrometry, Normalization, Preprocessing, Software, GUI

License Artistic-2.0

Depends R (>= 4.5.0)

Suggests BiocStyle, BiocManager, testthat, knitr

Imports DAPAR (>= 1.35.1), DAPARdata (>= 1.30.0), rhandsontable, data.table, shiny, shinyBS, shinyAce, plotly, htmlwidgets, webshot, shinythemes, later, shinycssloaders, future, promises, shinyjqui, tibble, ggplot2, gplots, shinyjs, vioplot, Biobase, DT, R.utils, RColorBrewer, XML, colourpicker, gtools, markdown, rclipboard, sass, shinyTree, shinyWidgets

NeedsCompilation no

RoxygenNote 7.3.3

Encoding UTF-8

URL http://www.prostar-proteomics.org/

BugReports https://github.com/edyp-lab/Prostar/issues

VignetteBuilder knitr

git_url https://git.bioconductor.org/packages/Prostar

git_branch RELEASE_3_23

git_last_commit 05f7f3f

git_last_commit_date 2026-04-28

Repository Bioconductor 3.23

Date/Publication 2026-11-11

Author Thomas Burger [aut],
Florence Combes [aut],
Samuel Wieczorek [cre, aut],
Manon Gaudin [ctb]

Maintainer Samuel Wieczorek <samuel.wieczorek@cea.fr>

Contents

BuildColorStyles 2
getDataForExprs 3
Prostar 3

Index **4**

`BuildColorStyles` *xxxx*

Description

xxxx

Usage

```
BuildColorStyles(obj)
```

Arguments

`obj`	xx

Value

xxx

Examples

```
NULL
```

getDataForExprs *xxxx*

Description

xxxx

Usage

```
getDataForExprs(obj, digits = NULL)
```

Arguments

obj	xx
digits	xxx

Value

xxx

Examples

```
NULL
```

Prostar *Prostar*

Description

Prostar

Usage

```
Prostar()
```

Value

A new window in the default internet browser

Author(s)

Samuel Wieczorek

Examples

```
NULL
```

Index

BuildColorStyles, 2

getDataForExprs, 3

Prostar, 3