Package 'RNAmodR.ML'

November 12, 2026

Type Package

Title Detecting patterns of post-transcriptional modifications using machine learning

Version 1.26.0

Date 2021-11-21

Description RNAmodR.ML extend the functionality of the RNAmodR package and classical detection strategies towards detection through machine learning models. RNAmodR.ML provides classes, functions and an example workflow to establish a detection stratedy, which can be packaged.

biocViews Software, Infrastructure, WorkflowStep, Visualization, Sequencing

License Artistic-2.0

Encoding UTF-8

LazyData false

Depends R (>= 3.6), RNAmodR

Imports methods, BiocGenerics, S4Vectors, IRanges, GenomicRanges, stats, ranger

Suggests BiocStyle, knitr, rmarkdown, testthat, RNAmodR.Data, RNAmodR.AlkAnilineSeq, GenomicFeatures, Rsamtools, rtracklayer, keras

Collate 'RNAmodR.ML.R' 'AllGenerics.R' 'ModifierMLModel-class.R' 'ModifierML-class.R' 'ModifierML-data.R' 'ModifierMLkeras-class.R' 'ModifierMLranger-class.R' 'RNAmodR.ML.example.R' 'utils.R'

RoxygenNote 7.1.1

VignetteBuilder knitr

BugReports https://github.com/FelixErnst/RNAmodR.ML/issues

URL https://github.com/FelixErnst/RNAmodR.ML

git_url https://git.bioconductor.org/packages/RNAmodR.ML

git_branch RELEASE_3_23

git_last_commit f72ed87

git_last_commit_date 2026-04-28

Repository Bioconductor 3.23

Date/Publication 2026-11-11

Author Felix G.M. Ernst [aut, cre] (ORCID:
<https://orcid.org/0000-0001-5064-0928>),
Denis L.J. Lafontaine [ctb]

Maintainer Felix G.M. Ernst <felix.gm.ernst@outlook.com>

Contents

ModifierMLkeras-class 2
ModifierMLranger-class 3
RNAmodR.ML 4
RNAmodR.ML-datasets 4
RNAmodR.ML-example 5
setMLModel<- 6
trainingData 7
useModel 9

Index **11**

`ModifierMLkeras-class` *ModifierMLkeras class*

Description

The `ModifierMLkeras` class extends the virtual class `ModifierMLModel` and unifies the access to `Keras` machine learning models used in the detection of post-transcriptional modifications in RNA sequencing data. The `ModifierMLkeras` class is virtual itself and must be extended from for each individual machine learning model.

The `ModifierMLkeras` class extends the virtual class `ModifierMLModel` and unifies the access to `Keras` machine learning models used in the detection of post-transcriptional modifications in RNA sequencing data. The `ModifierMLkeras` class is virtual itself and must be extended from for each individual machine learning model.

Since a stored model needs to be loaded from file, the additional slot `modelFile` is used and can be accessed through a function of the same name. Upon creation of a `ModifierMLkeras` object, the model is loaded from file, if `modelFile` is not an empty character value and a valid file name.

Usage

```
## S4 method for signature 'ModifierMLkeras,ModifierML'
useModel(x, y)
```

Arguments

x	a ModifierMLkeras object
y	a ModifierML object

Value

a ModifierMLkeras object

Slots

modelFile a character vector of length == 1L, which describes a model to load via load_model_hdf5. The model is then stored in the model slot.

See Also

ModifierMLModel

ModifierMLranger-class *ModifierMLranger class*

Description

The ModifierMLranger class extends the virtual class ModifierMLModel and unifies the access to ranger machine learning models used in the detection of post-transcriptional modifications in RNA sequencing data. The ModifierMLranger class is virtual itself and must be extended from for each individual machine learning model.

Usage

```
## S4 method for signature 'ModifierMLranger,ModifierML'
useModel(x, y)
```

Arguments

x	a ModifierMLranger object
y	a ModifierML object

Value

a ModifierMLranger object

See Also

ModifierMLModel

Examples

```
# example class derived from the virtual ModifierMLranger class
setClass("ModifierMLexample",
         contains = c("ModifierMLranger"))
ModifierMLexample <- function(...){
  new("ModifierMLexample")
}
mlmodel <- ModifierMLexample()
```

RNAmodR.ML *RNAmodR.ML*

Description

To extend the functionality of the RNAmodR package and classical detection strategies towards detection through machine learning models, RNAmodR.ML provides classes and an example workflow.

Author(s)

Felix G M Ernst [aut]

See Also

RNAmodR package.

RNAmodR.ML-datasets *Example data in the RNAmodR.ML package*

Description

This contains an example ModifierSet object

Usage

```
data(dmod)

data(mod7)

data(me)

data(model)
```

Format

a GRanges object containg D positions

a GRanges object containg m7G positions

a ModMLExample object for examples

a ranger object for examples

RNAmodR.ML-example *RNAmodR.ML functions for example*

Description

The exported functions here are used in the vignette as examples. If you want to reuse them, please implement them yourself. This will allow for fine tuning on your side and does not create a depency to example functions, which could change

Usage

```
aggregate_example(x)

find_mod_example(x, minCoverage)
```

Arguments

x	a ModifierML object
minCoverage	the minimum coverage for finding modifications

Value

- aggregate_example a SplitDataFrameList object containing the aggregated data for a Modifier object
- find_mod_example a GRanges object with coordinates of found modifications

Examples

```
# no examples runable. See vignette for explanation on how to use these
# example functions
aggregate_example
find_mod_example
```

setMLModel<- *The ModifierML class*

Description

The ModifierML class is a virtual class, which provides the central functionality for searching with a machine learning models for patterns of post-transcriptional RNA modifications in high throughput sequencing data.

It extends the virtual Modifier class form the RNAmodR package and add the useMLModel function. If not called directly for a ModifierML class, the useMLModel will be called from the aggregate function.

The slot mlModel is added and serves a dual purpose. If mlModel is a character, a class of the type ModifierMLModel is created upon creation of a ModifierML object. However, for developing purposes the slot can also remain empty and a ModifierMLModel object can be set using the setMLModel function and retrieved using the getMLModel. If the mlModel slot is empty, the findMod setting will be set to FALSE and the ModifierML object will be returned just with the aggregate data. Such an object can then be used to train a machine learning model. The data can be accessed using trainingData.

Usage

```
setMLModel(x) <- value

getMLModel(x)

hasMLModel(x)

useMLModel(x)

## S4 replacement method for signature 'ModifierML'
setMLModel(x) <- value

## S4 method for signature 'ModifierML'
getMLModel(x)

## S4 method for signature 'ModifierML'
hasMLModel(x)

## S4 method for signature 'ModifierML'
aggregate(x, force = FALSE)

## S4 method for signature 'ModifierML'
useMLModel(x)

## S4 method for signature 'ModifierML'
modify(x, force = FALSE)
```

Arguments

x	a ModifierML object.
value	a ModifierMLModel object
force	whether to recreate the aggregated data, if it is already stored inside the Modifier object.

Value

a ModifierML object

Slots

mlModel a character describing a class name for creating a ModifierMLModel object or a ModifierMLModel object itself. If mlModel is a character, the class will tried to be create by calling a function of the same name.

See Also

Modifier

Examples

```
# an example implementation of a ModifierML object
setClass("ModMLExample",
         contains = c("RNAModifierML"),
         prototype = list(mod = c("D"),
                          score = "score",
                          dataType = c("PileupSequenceData",
                                       "CoverageSequenceData"),
                          mlModel = character(0)))
# constructor function for ModMLExample
ModMLExample <- function(x, annotation = NA, sequences = NA, seqinfo = NA,
                         ...){
  RNAmodR:::Modifier("ModMLExample", x = x, annotation = annotation,
                     sequences = sequences, seqinfo = seqinfo, ...)
}
```

---

trainingData *Assemble training data from aggregate sequence data*

Description

trainingData subsets the aggregate data of a ModifierML object to positions as defined by coord. Positions with an entry in the mod column are labeled TRUE.

Usage

```
trainingData(x, coord, ...)

## S4 method for signature 'ModifierML,GRanges'
trainingData(x, coord, ...)

## S4 method for signature 'ModifierML,GRangesList'
trainingData(x, coord, ...)
```

Arguments

x	a ModifierML object
coord	a GRanges or a GRangesList object
...	See subsetByCoord for more details. type is hard coded to FALSE to disregard subsetting by type. In addition, merge is set to FALSE by default, but it can be set to TRUE.

Value

a CompressedSplitDataFrameList with aggregate data and an addition label column.

See Also

For more details have a look at subsetByCoord.

Examples

```
data("dmod",package = "RNAmodR.ML")
setClass("ModMLExample",
         contains = c("RNAModifierML"),
         prototype = list(mod = c("D"),
                          score = "score",
                          dataType = c("PileupSequenceData",
                                       "CoverageSequenceData"),
                          mlModel = character(0)))
data("me",package = "RNAmodR.ML")
nextUPos <- function(gr){
  nextU <- lapply(seq.int(1L,2L),
                  function(i){
                   subseq <- subseq(RNAmodR::sequences(me)[dmod$Parent], start(dmod)+3L)
                    pos <- start(dmod) + 2L +
                      vapply(strsplit(as.character(subseq),""),
                             function(y){which(y == "U")[i]},integer(1))
                    ans <- dmod
                    ranges(ans) <- IRanges(start = pos, width = 1L)
                    ans
                  })
  nextU <- do.call(c,nextU)
  nextU$mod <- NULL
  unique(nextU)
```

```
}
nondmod <- nextUPos(dmod)
nondmod <- nondmod[!(nondmod %in% dmod)]
coord <- unique(c(dmod,nondmod))
coord <- coord[order(as.integer(coord$Parent))]
trainingData(me,coord)
```

---

useModel *ModifierMLModel virtual class*

Description

The ModifierMLModel is a virtual class and is used for representing different types of machine learning models used in the detection of post transcriptional modifiations in RNA sequencing data.

The next class inheriting from here should only implement a certain type of model and also be virtual. The grand child of the ModifierMLModel class should than implement a specific model for detecting certain types of modifications.

Usage

```
useModel(x, y)

## S4 method for signature 'ModifierMLModel,ANY'
useModel(x, y)
```

Arguments

x	a ModifierMLModel object
y	See ModifierMLranger for an example

Value

a ModifierMLModel object

Slots

model a machine learning object of any type

See Also

ModifierMLranger ModifierMLkeras

ModifierMLranger for an example implementation

Examples

```
# an example implementation of a ModifierMLModel object using the
# ModifierMLModel derived class ModifierMLranger
setClass("ModifierMLexample",
         contains = c("ModifierMLranger"))
ModifierMLexample <- function(...){
  new("ModifierMLexample")
}
```

Index

∗ **datasets**
RNAmodR.ML-datasets, 4

aggregate,ModifierML-method
(setMLModel<-), 6
aggregate_example (RNAmodR.ML-example), 5

calculate_correct_base_score
(RNAmodR.ML-example), 5

dmod (RNAmodR.ML-datasets), 4
DNAModifierML-class (setMLModel<-), 6

find_mod_example (RNAmodR.ML-example), 5

getMLModel (setMLModel<-), 6
getMLModel,ModifierML-method
(setMLModel<-), 6

hasMLModel (setMLModel<-), 6
hasMLModel,ModifierML-method
(setMLModel<-), 6

load_model_hdf5, *3*

me (RNAmodR.ML-datasets), 4
mod7 (RNAmodR.ML-datasets), 4
model (RNAmodR.ML-datasets), 4
Modifier, *7*
ModifierML (setMLModel<-), 6
ModifierML-class (setMLModel<-), 6
ModifierMLkeras, *9*
ModifierMLkeras
(ModifierMLkeras-class), 2
ModifierMLkeras-class, 2
ModifierMLModel, *3*
ModifierMLModel (useModel), 9
ModifierMLModel-class (useModel), 9
ModifierMLranger, *9*
ModifierMLranger
(ModifierMLranger-class), 3
ModifierMLranger-class, 3
modify,ModifierML-method
(setMLModel<-), 6

ranger, *3*
RNAModifierML-class (setMLModel<-), 6
RNAmodR, *4*
RNAmodR.ML, 4
RNAmodR.ML-datasets, 4
RNAmodR.ML-example, 5
RNAmodR.ML.example
(RNAmodR.ML-example), 5

setMLModel<-, 6
setMLModel<-,ModifierML-method
(setMLModel<-), 6
subsetByCoord, *8*

trainingData, *6*, 7
trainingData,ModifierML,GRanges-method
(trainingData), 7
trainingData,ModifierML,GRangesList-method
(trainingData), 7

useMLModel (setMLModel<-), 6
useMLModel,ModifierML-method
(setMLModel<-), 6
useModel, 9
useModel,ModifierMLkeras,ModifierML-method
(ModifierMLkeras-class), 2
useModel,ModifierMLModel,ANY-method
(useModel), 9
useModel,ModifierMLranger,ModifierML-method
(ModifierMLranger-class), 3