Package 'Rhtslib'

November 12, 2026

Title HTSlib high-throughput sequencing library as an R package

Description This package provides version 1.18 of the 'HTSlib' C library for high-throughput sequence analysis. The package is primarily useful to developers of other R packages who wish to make use of HTSlib. Motivation and instructions for use of this package are in the vignette, vignette(package=``Rhtslib'', ``Rhtslib'').

biocViews DataImport, Sequencing

URL https://bioconductor.org/packages/Rhtslib, http://www.htslib.org/

BugReports https://github.com/Bioconductor/Rhtslib/issues

Version 3.8.0

License LGPL (>= 2)

Copyright Unless otherwise noted in the file, all files outside src/htslib-1.18 or inst/include copyright Bioconductor; for files inside src/htslib-1.18 or inst/include, see file src/htslib-1.18/LICENSE.

Encoding UTF-8

Imports tools

Suggests knitr, rmarkdown, BiocStyle

SystemRequirements libbz2 & liblzma & libcurl (with header files), GNU make

StagedInstall no

VignetteBuilder knitr

git_url https://git.bioconductor.org/packages/Rhtslib

git_branch RELEASE_3_23

git_last_commit 7adc5c8

git_last_commit_date 2026-04-28

Repository Bioconductor 3.23

Date/Publication 2026-11-11

Author Nathaniel Hayden [led, aut],
Martin Morgan [aut],
Hervé Pagès [aut, cre],
Tomas Kalibera [ctb],
Jeroen Ooms [ctb]

Maintainer Hervé Pagès <hpages.on.github@gmail.com>

Contents

Rhtslib-package 2
pkgconfig 3

Index **4**

`Rhtslib-package` *An R packaged HTSlib 1.18*

Description

This package is interesting to package developers only, and provides a compiled HTSlib for developers to use in their own packages. See the vignette for instructions on use.

Details

Instructions for use are in the vignette, available with `browseVignettes(package="Rhtslib")`

Author(s)

Nathaniel Hayden nhayden@fredhutch.org

References

The HTSlib included in the package is based on release 1.18 of HTSlib found at https://github.com/samtools/htslib/releases/

See Also

pkgconfig

Examples

```
packageDescription('Rhtslib')
Rhtslib:::htsVersion()
```

pkgconfig *Compiler configuration arguments for use of Rhtslib*

Description

This function prints values for PKG_LIBS and PKG_CPPFLAGS variables for use in Makevars files. See vignette("Rhtslib") for details. The environment variable RHTSLIB_RPATH can be used to over-ride the inferred location of the installed package.

Usage

```
pkgconfig(opt = c("PKG_LIBS", "PKG_CPPFLAGS"))
```

Arguments

opt	A scalar character from the list of available options; default is PKG_LIBS.

Value

The function prints the PKG_LIBS or PKG_CPPFLAGS value and returns an invisible NULL.

Author(s)

Nathaniel Hayden mailto:nhayden@fredhutch.org

Examples

```
pkgconfig("PKG_LIBS")

pkgconfig("PKG_CPPFLAGS")
```

Index

∗ **manip**
    pkgconfig, 3
∗ **package**
    Rhtslib-package, 2

htsVersion *(*Rhtslib-package*)*, 2

pkgconfig, *2*, 3

Rhtslib *(*Rhtslib-package*)*, 2
Rhtslib-package, 2