Package 'alabaster.vcf'

November 11, 2026

Title Save and Load Variant Data to/from File

Version 1.12.0

Date 2024-01-02

Description Save variant calling SummarizedExperiment to file and load them back as VCF objects.
This is a more portable alternative to serialization of such objects into RDS files.
Each artifact is associated with metadata for further interpretation;
downstream applications can enrich this metadata with context-specific properties.

License MIT + file LICENSE

Depends alabaster.base, VariantAnnotation

Imports methods, S4Vectors, alabaster.se, alabaster.string, Rsamtools

Suggests knitr, rmarkdown, BiocStyle, testthat

RoxygenNote 7.2.3

VignetteBuilder knitr

biocViews DataImport, DataRepresentation

git_url https://git.bioconductor.org/packages/alabaster.vcf

git_branch RELEASE_3_23

git_last_commit c7924d6

git_last_commit_date 2026-04-28

Repository Bioconductor 3.23

Date/Publication 2026-11-11

Author Aaron Lun [aut, cre]

Maintainer Aaron Lun <infinite.monkeys.with.keyboards@gmail.com>

Contents

readVCF 2
saveObject,VCF-method 3

Index **4**

readVCF *Read a VCF object from disk*

Description

Read a VCF object from its on-disk representation.

Usage

```
readVCF(path, metadata, ...)
```

Arguments

path	String containing a path to a directory, usually generated by the saveObject method for VCF object.s
metadata	Named list of metadata for this object, see readObjectFile for details.
...	Further arguments passed to internal altReadObject calls.

Value

A VCF object.

Author(s)

Aaron Lun

See Also

saveObject,VCF-method, to save VCF objects to disk.

Examples

```
fl <- system.file("extdata", "structural.vcf", package="VariantAnnotation")
vcf <- readVcf(fl)

tmp <- tempfile()
saveObject(vcf, tmp)
readObject(tmp)
```

saveObject,VCF-method *Save a VCF object to disk*

Description

Save a VCF object to its on-disk representation, namely a VCF file with the same contents.

Usage

```
## S4 method for signature 'VCF'
saveObject(x, path, ...)
```

Arguments

x	Any instance of a VCF class or one of its subclasses.
path	String containing the path to a directory in which to save x.
...	Further arguments to pass to specific methods.

Value

x is saved to file inside path, and NULL is returned.

Author(s)

Aaron Lun

See Also

readVCF, to read a VCF object back to the R session.

Examples

```
fl <- system.file("extdata", "structural.vcf", package="VariantAnnotation")
vcf <- readVcf(fl)

tmp <- tempfile()
saveObject(vcf, tmp)
```

Index

altReadObject, *2*

loadVCF *(*readVCF*)*, 2
loadVCFHeader *(*readVCF*)*, 2

readObjectFile, *2*
readVCF, 2, *3*

saveObject, *2*
saveObject,VCF-method, 3
stageObject,VCF-method
        *(*saveObject,VCF-method*)*, 3
stageObject,VCFHeader-method
        *(*saveObject,VCF-method*)*, 3

VCF, *2*, *3*