Package 'antiProfiles'

November 11, 2026

Maintainer Hector Corrada Bravo <hcorrada@gmail.com>

Author Hector Corrada Bravo, Rafael A. Irizarry and Jeffrey T. Leek

Version 1.52.0

License Artistic-2.0

Title Implementation of gene expression anti-profiles

Description Implements gene expression anti-profiles as described in Corrada Bravo et al., BMC Bioinformatics 2012, 13:272 doi:10.1186/1471-2105-13-272.

Depends R (>= 3.0), matrixStats (>= 0.50.0), methods (>= 2.14), locfit (>= 1.5)

URL https://github.com/HCBravoLab/antiProfiles

biocViews GeneExpression,Classification

Suggests antiProfilesData, RColorBrewer

Collate 'AllClasses.r' 'AllGenerics.r' 'show-methods.r' 'antiProfiles-package.r' 'ap-methods.r' 'apCounts-methods.r' 'apReorder-methods.r' 'apStats.r' 'accessors.r' 'ev.R'

RoxygenNote 5.0.1

git_url https://git.bioconductor.org/packages/antiProfiles

git_branch RELEASE_3_23

git_last_commit 1d94c41

git_last_commit_date 2026-04-28

Repository Bioconductor 3.23

Date/Publication 2026-11-11

Contents

antiProfiles-package 2
AntiProfile-class 2
AntiProfileStats-class 3
apCount 4
apReorder 5

apStats 6
buildAntiProfile 7
ev 7
TissueSpecAntiProfile-class 8

Index **10**

`antiProfiles-package` *Gene Expression Anti-profiles*

Description

This package implements the anti-profile method of Corrada Bravo et al., BMC Bioinformatics 2012, 13:272 doi:10.1186/1471-2105-13-272.

Author(s)

Hector Corrada Bravo <hcorrada@gmail.com>

`AntiProfile-class` *A gene expression anti-profile*

Description

This class encapsulates anti-profiles. Objects of this class should be built from `AntiProfileStats` objects using the `buildAntiProfile` method. Anti-profile scores can be computed for new samples using the `apCount` method.

Usage

```
## Accessors

getProbesetIds(object)
getNormalRegions(object)
```

Arguments

`object`	Object of class (or inheriting from) `AntiProfile`

Accessors

In the following code `object` is a `AntiProfile` object.

`getProbesetIds`: vector of Affymetrix ids for probesets included in the anti-profile (character)

`getNormalRegions`: median and upper boundary of normal expression regions (numeric matrix of dimension s-by-2, where s is the size of the anti-profile)

Author(s)

Hector Corrada Bravo <hcorrada@gmail.com>

See Also

AntiProfileStats for the class of objects from which anti-profiles are built. *buildAntiProfile* for the method used to construct objects of this class. apCount for the function used to calculate anti-profile scores from objects of this class.

Examples

```
if (require(antiProfilesData)) {
    data(apColonData)
    colonStats=apStats(exprs(apColonData), pData(apColonData)$Status)
    colonAP = buildAntiProfile(colonStats, tissueSpec=FALSE, sigsize=10)
    show(colonAP)

    head(getProbesetIds(colonAP))
    head(getNormalRegions(colonAP))
  }
```

AntiProfileStats-class

Statistics used to build anti-profiles

Description

This class stores statistics required to build anti-profiles. Objects of this class should be built using the apStats function. To build anti-profiles from objects of this class, use the buildAntiProfile function.

Usage

```
## Accessors
getProbeStats(object)
```

Arguments

object	Object of class AntiProfileStats

Accessors

In the following code object is a AntiProfileStats object.

getProbeStats: Gets probeset statistics. A data.frame with columns

- affyid: Affymetrix probeset id (character)
- SD0: Normal expression standard deviation aggregated over tissue types (numeric)
- SD1: Cancer expression standard deviation aggregated over tumor types (numeric)

`stat`: The log2-variance ratio statistic (numeric)

`meds0`: Median normal expression aggregated over tissue types (numeric)

`mads0`: Median absolute deviation of normal expression aggregate over tissue types (numeric)

Author(s)

Hector Corrada Bravo <hcorrada@gmail.com>

See Also

`apStats` to construct objects of this class, `buildAntiProfile` to build anti-profiles from objects of this class.

Examples

```
if (require(antiProfilesData)) {
   data(apColonData)
   colonStats = apStats(exprs(apColonData), pData(apColonData)$Status)
   show(getProbeStats(colonStats))
 }
```

---

apCount *Obtain the anti-profile score for a set of samples*

Description

This function applies the given anti-profile to a new set of samples. Rownames in the expression matrix are used to match probenames in the AntiProfile object.

Arguments

`fit`	an object of class AntiProfile as produced by the buildAntiProfile method
`expr`	a matrix of gene expression, rownames are used as identifiers

Value

a numeric vector of anti-profile scores

Author(s)

Hector Corrada Bravo <hcorrada@gmail.com>

Examples

```
if (require(antiProfilesData)) {
    data(apColonData)

    # compute statistics
    colonStats = apStats(exprs(apColonData), pData(apColonData)$Status)

   # create an anti-profile, ignoring tissue-specificity of probesets, with 10 probesets
    ap = buildAntiProfile(colonStats, tissueSpec=FALSE, sigsize=10)

    # get counts for the original dataset
    counts =apCount(ap, exprs(apColonData))
 }
```

---

apReorder *Reorder an AntiProfileStats object*

Description

Reorders given AntiProfileStats object using provided ordering o

Arguments

stats	An object of class AntiProfileStats
o	A numeric vector giving new probe ordering

Value

A reordered AntiProfileStats object

Author(s)

Hector Corrada Bravo <hcorrada@gmail.com>

Examples

```
if (require(antiProfilesData)) {
  data(apColonData)
  colonStats = apStats(exprs(apColonData), pData(apColonData)$Status)
  o = sample(seq(len=nrow(slot(colonStats,"probes"))))
  newStats = apReorder(colonStats, o)
}
```

apStats *Compute statistics used to construct antiProfile*

Description

This function calculates normal ranges of expressions and variance ratios for all probesets. To create an anti-profile, call buildAntiProfile on the output of this function

Usage

```
apStats(e, cl, tiss = NULL, minL = 10, cutoff = 5,
  OnCutoff = 2.54)
```

Arguments

e	matrix of gene expression, with one column per sample
cl	vector of normal/cancer indicators as 0/1
tiss	vector of tissue types for each sample
minL	minimum number of samples of a given tissue/class to compute stats
cutoff	median absolute deviation multiplier used to determine proportion of samples within normal range of expression
OnCutoff	gene expression barcode z-score to determine if a gene is expressed

Value

An object of class SuccsStats

Author(s)

Hector Corrada Bravo <hcorrada@gmail.com>

See Also

AntiProfileStats for the type of object returned. buildAntiProfile to construct anti-profiles with objects returned by this function.

Examples

```
if (require(antiProfilesData)) {
   data(apColonData)
   colonStats = apStats(exprs(apColonData), pData(apColonData)$Status)
 }
```

buildAntiProfile *Create an anti-profile from a AntiProfileStats object*

Description

This function creates anti-profile using statistics stored in a AntiProfileStats object

Arguments

stats	an object of class AntiProfileStats as produced by the apStats function
tissueSpec	use tissue-specific regions of normal expression
tissueFilter	use only tissue-specific genes in the anti-profile
sigsize	desired size of signature, if NULL, computed from statCutoff
cutoff	median absolute deviation multiplier used to define normal regions of expression
statCutoff	cutoff used to include probesets in anti-profile

Value

an object of class AntiProfilesSig or AntiProfilesTissueSig depending on the tissueSpec argument

Author(s)

Hector Corrada Bravo <hcorrada@gmail.com>

Examples

```
if (require(antiProfilesData)) {
  # create an anti-profile, ignoring tissue-specificity of probesets, with 10 probesets
  data(apColonData)
  colonStats = apStats(exprs(apColonData), pData(apColonData)$Status)
  ap = buildAntiProfile(colonStats, tissueSpec=FALSE, sigsize=10)
}
```

ev *Compute expression variability measure*

Description

This function computes expression variability in a way that removes dependence on mean expression. It uses a local polynomial likelihood method to estimate variance as gamma distributed around given mean expression for each probeset. This function makes this calculation using all samples in argument. To calculate expression variability for samples in different groups, call this function for each subset of columns separately.

Usage

```
ev(x, cutoff = NULL, plot = FALSE, ...)
```

Arguments

x	matrix of gene expression, with one column per sample
cutoff	minimum expression value to be included in computation (for frma normalized data, we find 2.54 to be a good value for determining if a probeset is expressed in a given sample (default NULL)
plot	make a plot of local likelihood model using smoothScatter (default=FALSE)
...	arguments passed to smoothScatter

Value

numeric vector of length equal to number of rows of x

Author(s)

Hector Corrada Bravo <hcorrada@gmail.com>

References

E. Alemu, H. Corrada Bravo, S. Hannenhalli (2014). Determinants of Expression Variability. Nucleic Acids Research, 42 (6), 3503-14.

See Also

frma for normalization

Examples

```
if (require(antiProfilesData)) {
  data(apColonData)
  e <- exprs(apColonData)[,pData(apColonData)$Status==1]
  ev <- ev(e, cutoff=2.54)
}
```

TissueSpecAntiProfile-class

A gene expression anti-profile using tissue-specific regions

Description

This class encapsulates anti-profiles with tissue-specific normal expression regions. Objects of this class should be built from AntiProfileStats objects using the buildAntiProfile method. Anti-profile scores can be computed for new samples using the apCount method.

Usage

```
  ## Accessors

  ## S4 method for signature 'TissueSpecAntiProfile'
getProbesetIds(object)
  ## S4 method for signature 'TissueSpecAntiProfile'
getNormalRegions(object)
  getNormalTissueRegions(object)
```

Arguments

object	Object of class TissueSpecAntiProfile

Accessors

In the following code object is a TissueSpecAntiProfile object.

getProbesetIds: vector of Affymetrix ids for probesets included in the anti-profile (character)

getNormalRegions: median and upper boundary of normal expression regions (numeric matrix of dimension s-by-2, where s is the size of the anti-profile)

getNormalTissueRegions: median and upper boundary of normal expression regions (numeric array of dimension s-by-2-by-t, where s is the size of the anti-profile, and t the number of normal tissues used in the anti-profile)

Author(s)

Hector Corrada Bravo <hcorrada@gmail.com>

See Also

AntiProfileStats for the class of objects from which anti-profiles are built. *buildAntiProfile* for the method used to construct objects of this class. apCount for the function used to calculate anti-profile scores from objects of this class. #'

Examples

```
if (require(antiProfilesData)) {
    data(apColonData)
    # fake tissues
    tissue=rep(c("colon","lung"), len=length(sampleNames(apColonData)))
   tissStats=apStats(exprs(apColonData), pData(apColonData)$Status, tiss=tissue, minL=3)
    tissAP=buildAntiProfile(tissStats, sigsize=10)
    show(tissAP)

    head(getProbesetIds(tissAP))
    head(getNormalRegions(tissAP))
    head(getNormalTissueRegions(tissAP))
  }
```

Index

AntiProfile, *2*
AntiProfile-class, 2
antiProfiles-package, 2
AntiProfileStats, *2, 3*, *6*, *8, 9*
AntiProfileStats-class, 3
apCount, *2, 3*, 4, *8, 9*
apCount,AntiProfile,matrix-method *(apCount)*, 4
apCount,TissueSpecAntiProfile,matrix-method *(apCount)*, 4
apReorder, 5
apReorder,AntiProfileStats,numeric-method *(apReorder)*, 5
apStats, *3, 4*, 6

buildAntiProfile, *2–4*, *6*, 7, *8, 9*
buildAntiProfile,AntiProfileStats-method *(buildAntiProfile)*, 7

ev, 7

getNormalRegions *(AntiProfile-class)*, 2
getNormalRegions,AntiProfile-method *(AntiProfile-class)*, 2
getNormalRegions,TissueSpecAntiProfile-method *(TissueSpecAntiProfile-class)*, 8
getNormalTissueRegions *(TissueSpecAntiProfile-class)*, 8
getNormalTissueRegions,TissueSpecAntiProfile-method *(TissueSpecAntiProfile-class)*, 8
getProbesetIds *(AntiProfile-class)*, 2
getProbesetIds,AntiProfile-method *(AntiProfile-class)*, 2
getProbesetIds,TissueSpecAntiProfile-method *(TissueSpecAntiProfile-class)*, 8
getProbeStats *(AntiProfileStats-class)*, 3
getProbeStats,AntiProfileStats-method *(AntiProfileStats-class)*, 3

TissueSpecAntiProfile, *9*
TissueSpecAntiProfile-class, 8