Package 'escheR'

November 12, 2026

Title Unified multi-dimensional visualizations with Gestalt principles

Version 1.12.0

Description The creation of effective visualizations is a fundamental component of data analysis. In biomedical research, new challenges are emerging to visualize multi-dimensional data in a 2D space, but current data visualization tools have limited capabilities. To address this problem, we leverage Gestalt principles to improve the design and interpretability of multi-dimensional data in 2D data visualizations, layering aesthetics to display multiple variables. The proposed visualization can be applied to spatially-resolved transcriptomics data, but also broadly to data visualized in 2D space, such as embedding visualizations. We provide this open source R package escheR, which is built off of the state-of-the-art ggplot2 visualization framework and can be seamlessly integrated into genomics toolboxes and workflows.

License MIT + file LICENSE

Encoding UTF-8

Roxygen list(markdown = TRUE)

RoxygenNote 7.2.3

biocViews Spatial, SingleCell, Transcriptomics, Visualization, Software

Depends ggplot2, R (>= 4.3)

Imports SpatialExperiment (>= 1.6.1), SingleCellExperiment, rlang, SummarizedExperiment

BugReports https://github.com/boyiguo1/escheR/issues

URL https://github.com/boyiguo1/escheR

Suggests STexampleData, BumpyMatrix, knitr, rmarkdown, BiocStyle, ggpubr, scran, scater, scuttle, Seurat, hexbin

VignetteBuilder knitr

git_url https://git.bioconductor.org/packages/escheR

git_branch RELEASE_3_23

git_last_commit a5e8f24

git_last_commit_date 2026-04-28

Repository Bioconductor 3.23

Date/Publication 2026-11-11

Author Boyi Guo [aut, cre] (ORCID: <https://orcid.org/0000-0003-2950-2349>),
Stephanie C. Hicks [aut] (ORCID:
<https://orcid.org/0000-0002-7858-0231>),
Erik D. Nelson [ctb] (ORCID: <https://orcid.org/0000-0001-8477-0982>)

Maintainer Boyi Guo <boyi.guo.work@gmail.com>

Contents

.contain_reserved_col_name 2
add_fill 3
add_ground 4
add_symbol 5
make_escheR 5

Index **8**

`.contain_reserved_col_name` *Check if rowData(spe) contains reserved name*

Description

Internal Funciton

Usage

```
.contain_reserved_col_name(col_name)
```

Arguments

`col_name`	the colnames

Value

TRUE when col_name contains reserved names, FALSE

add_fill *Adding fill to highlight the figure in the spatial map*

Description

Adding fill to highlight the figure in the spatial map

Usage

```
add_fill(p, var, point_size = 2, ...)

add_fill_bin(p, var, bins = 30, point_size = 2.8, fun = sum, ...)
```

Arguments

p	a spatial map created by make_escheR(), with or without other layers of aesthetics.
var	A character(1) with the name of the colData(spe) column that has the values to be used as the background.
point_size	A numeric(1) specifying the size of the spot in the ggplot. Defaults to 2.
...	Reserved for future arguments.
bins	numeric vector giving number of bins in both vertical and horizontal directions. Set to 30 by default.
fun	function for summary. See more detail in stat_summary_hex

Value

an ggplot object.

Examples

```
library(STexampleData)

spe <- Visium_humanDLPFC()

make_escheR(spe) |>
    add_fill(var = "ground_truth")
```

add_ground *Adding border to highlight the ground in the spatial map*

Description

Adding border to highlight the ground in the spatial map

Usage

```
add_ground(p, var, stroke = 0.5, point_size = 2, ...)

add_ground_bin(p, var, bins = 30, stroke = 1, point_size = 3, ...)
```

Arguments

p	a spatial map created by make_escheR(), with or without other layers of aesthetics.
var	A character(1) with the name of the colData(spe) column that has the values to be used as the background.
stroke	A numeric(1) specifying the thickness of the border.
point_size	A numeric(1) specifying the size of the spot in the ggplot. Defaults to 2.
...	Reserved for future arguments.
bins	numeric vector giving number of bins in both vertical and horizontal directions. Set to 30 by default.

Value

an ggplot object.

Examples

```
library(STexampleData)

spe <- Visium_humanDLPFC()

make_escheR(spe) |>
    add_ground(var = "ground_truth")
```

add_symbol *Adding symbols to each spot in the spatial map*

Description

Adding symbols to each spot in the spatial map

Usage

```
add_symbol(p, var, size = 1, ...)
```

Arguments

p	a spatial map created by make_escheR(), with or without other layers of aesthetics.
var	A character(1) with the name of the colData(spe) column that has the values to be used as the background.
size	A numeric(1) specifying the size of the symbols in the ggplot. Defaults to 1.
...	Reserved for future arguments.

Value

an ggplot object.

Examples

```
library(STexampleData)

spe <- Visium_humanDLPFC()

# Convert a continuous variable to categorical
spe$in_tissue <- factor(spe$in_tissue)

make_escheR(spe) |>
    add_ground(var = "ground_truth") |>
    add_symbol(var = "in_tissue", size = 0.5)
```

make_escheR *Create a new spatial map for spatial transcriptomics data*

Description

make_escheR() is a generic function to initialize a ggplot object that contains a spatial map. Because the ggplot object saves the input spatial transcriptomics data, the transcriptomics data will be used in the following layering process to add more aesthestic components in the plot following the grammar of graphics and ggplot2 syntax.

Usage

```
make_escheR(object, spot_size = 2, ...)

## S3 method for class 'SingleCellExperiment'
make_escheR(object, spot_size = 2, dimred = "PCA", ...)

## S3 method for class 'SpatialExperiment'
make_escheR(object, spot_size = 2, dimred = NULL, y_reverse = TRUE, ...)

## S3 method for class 'data.frame'
make_escheR(object, spot_size = 2, .x, .y, ...)
```

Arguments

object	a data object that contains the spatial transcriptomics data. Currently only working for spatial transcriptomics data as SpatialExperiment objects.
spot_size	A numeric(1) specifying the size of the spot in the ggplot. Defaults to 2.
...	Reserved for future arguments.
dimred	String or integer scalar specifying the existing dimensionality reduction results to use.
y_reverse	(logical) Whether to reverse y coordinates, which is often required for 10x Genomics Visium data. Default = TRUE.
.x	the X-coordinate
.y	the Y-coordinate

Value

an ggplot object that contains the spatial transcriptomics data.

References

Guo B, Huuki-Myers LA, Grant-Peters M, Collado-Torres L, Hicks SC (2023). escheR: Unified multi-dimensional visualizations with Gestalt principles. *Bioinformatics Advances*, Volume 3, Issue 1, vbad179, doi:10.1093/bioadv/vbad179

Examples

```
library(STexampleData)
# SpatialExperiment Object
spe <- Visium_humanDLPFC()
make_escheR(spe)

# SingleCellExperiment Object
sce <- SingleCellExperiment(counts(spe))
reducedDims(sce) <- list(
   # Example embedding
    EG = matrix(seq.int(1, ncol(spe)*2), ncol = 2)
    )
```

```
make_escheR(sce, dimred = "EG")

# data.frame Object
x <- spatialCoords(spe)[,1]
y <- spatialCoords(spe)[,2]
df <- colData(spe) |> data.frame()
make_escheR(object = df, .x = x , .y = y)
```

Index

.contain_reserved_col_name, 2

add_fill, 3
add_fill_bin *(*add_fill*)*, 3
add_ground, 4
add_ground_bin *(*add_ground*)*, 4
add_symbol, 5

make_escheR, 5

stat_summary_hex, *3*