Package 'esetVis'

November 12, 2026

Type Package

Title Visualizations of expressionSet Bioconductor object

Version 1.38.0

Date 2023-12-15

Author Laure Cougnaud <laure.cougnaud@openanalytics.eu>

Maintainer Laure Cougnaud <laure.cougnaud@openanalytics.eu>

Description Utility functions for visualization of expressionSet (or SummarizedExperiment) Bioconductor object, including spectral map, tsne and linear discriminant analysis. Static plot via the ggplot2 package or interactive via the ggvis or rbokeh packages are available.

Imports mpm, hexbin, Rtsne, MLP, grid, Biobase, MASS, stats, utils, grDevices, methods

Suggests ggplot2, ggvis, plotly, ggrepel, knitr, rmarkdown, ALL, hgu95av2.db, AnnotationDbi, pander, SummarizedExperiment, GO.db

biocViews Visualization, DataRepresentation, DimensionReduction, PrincipalComponent, Pathways

VignetteBuilder knitr

License GPL-3

NeedsCompilation no

RoxygenNote 7.2.3

git_url https://git.bioconductor.org/packages/esetVis

git_branch RELEASE_3_23

git_last_commit 2af516f

git_last_commit_date 2026-04-28

Repository Bioconductor 3.23

Date/Publication 2026-11-11

Contents

characterORexpressionOrCall-class . . . 2
esetLda . . . 3
esetPlot-class . . . 8
esetPlotInteractive-class . . . 10
esetPlotWrapper . . . 11
esetSpectralMap . . . 16
esetTsne . . . 22
formatManualScale . . . 26
formatOutput . . . 27
getAxesLimits . . . 27
getCoordGeneSets . . . 28
getDataPlotSamplesWithAnnotation . . . 29
getGeneSetsForPlot . . . 29
getMethodsInputObjectEsetVis . . . 31
getTopElements . . . 32
ggPlotEset . . . 33
ggplotEsetPlot-class . . . 33
ggvisEsetPlot-class . . . 34
ggvisPlotEset . . . 34
plotEset . . . 35
plotlyEsetPlot-class . . . 35
plotlyPlotEset . . . 36
plotTopElements . . . 36
setFixElement . . . 37
setManualScale . . . 38
simpleCap . . . 39
varToFm . . . 39

Index **40**

`characterORexpressionOrCall-class`

S4 Class Union with character/expression/call

Description

This is used for the definition of the title/axes labels for the ggplot2 version

esetLda *plot a biplot of a linear discriminant analysis of an eSet object*

Description

esetLda reduces the dimension of the data contained in the eSet via a linear discriminant analysis on the specified grouping variable with the lda function and plot the subsequent biplot, possibly with sample annotation and gene annotation contained in the eSet.

Usage

```
esetLda(
  eset,
  ldaVar,
  psids = 1:nrow(eset),
  dim = c(1, 2),
  colorVar = character(),
  color = if (length(colorVar) == 0) "black" else character(),
  shapeVar = character(),
  shape = if (length(shapeVar) == 0) 15 else numeric(),
  sizeVar = character(),
  size = if (length(sizeVar) == 0) {
     ifelse(typePlot[1] == "interactive" &&
    packageInteractivity[1] == "plotly", 20, 2.5)
 } else {
     numeric()
 },
  sizeRange = numeric(),
  alphaVar = character(),
  alpha = if (length(alphaVar) == 0) 1 else numeric(),
  alphaRange = numeric(),
  title = "",
  symmetryAxes = c("combine", "separate", "none"),
  packageTextLabel = c("ggrepel", "ggplot2"),
  cloudGenes = TRUE,
  cloudGenesColor = "black",
  cloudGenesNBins = sqrt(length(psids)),
  cloudGenesIncludeLegend = FALSE,
  cloudGenesTitleLegend = "nGenes",
  topGenes = 10,
 topGenesCex = ifelse(typePlot[1] == "interactive" && packageInteractivity[1] ==
    "plotly", 10, 2.5),
  topGenesVar = character(),
  topGenesJust = c(0.5, 0.5),
  topGenesColor = "black",
  topSamples = 10,
 topSamplesCex = ifelse(typePlot[1] == "interactive" && packageInteractivity[1] ==
```

```
    "plotly", 10, 2.5),
  topSamplesVar = character(),
  topSamplesJust = c(0.5, 0.5),
  topSamplesColor = "black",
  geneSets = list(),
  geneSetsVar = character(),
  geneSetsMaxNChar = numeric(),
  topGeneSets = 10,
 topGeneSetsCex = ifelse(typePlot[1] == "interactive" && packageInteractivity[1] ==
    "plotly", 10, 2.5),
  topGeneSetsJust = c(0.5, 0.5),
  topGeneSetsColor = "black",
  includeLegend = TRUE,
  includeLineOrigin = TRUE,
  typePlot = c("static", "interactive"),
  packageInteractivity = c("plotly", "ggvis"),
  figInteractiveSize = c(600, 400),
  ggvisAdjustLegend = TRUE,
  interactiveTooltip = TRUE,
  interactiveTooltipExtraVars = character(),
  returnAnalysis = FALSE,
  returnEsetPlot = FALSE
)
```

Arguments

`eset`	expressionSet (or SummarizedExperiment) object with data
`ldaVar`	name of variable (in varLabels of the `eset`) used for grouping for lda
`psids`	featureNames of genes to include in the plot, all by default
`dim`	dimensions of the analysis to represent, first two dimensions by default
`colorVar`	name of variable (in varLabels of the `eset`) used for coloring, empty by default
`color`	character or factor with specified color(s) for the points, replicated if needed. This is used only if `colorVar` is empty. By default: 'black' if `colorVar` is not specified and default `ggplot` palette otherwise
`shapeVar`	name of variable (in varLabels of the `eset`) used for the shape, empty by default
`shape`	character or factor with specified shape(s) (pch) for the points, replicated if needed. This is used only if `shapeVar` is empty. By default: '15' (filled square) if `shapeVar` is not specified and default `ggplot` shape(s) otherwise
`sizeVar`	name of variable (in varLabels of the `eset`) used for the size, empty by default
`size`	character or factor with specified size(s) (cex) for the points, replicated if needed. This is used only if `sizeVar` is empty. By default: '2.5' if `sizeVar` is not specified (20 for a plotly plot) and default `ggplot` size(s) otherwise
`sizeRange`	size (cex) range used in the plot, possible only if the `sizeVar` is 'numeric' or 'integer'

`alphaVar` name of variable (in varLabels of the `eset`) used for the transparency, empty by default. This parameter is currently only available for static plot and ggvis (only numeric in this case).

`alpha` character or factor with specified transparency(s) for the points, replicated if needed. This is used only if `shapeVar` is empty. By default: '1' if `alphaVar` is not specified and default `ggplot` alpha otherwise This parameter is currently only available for static and ggvis.

`alphaRange` transparency (alpha) range used in the plot, possible only if the `alphaVar` is 'numeric' or 'integer' This parameter is currently only available for static and ggvis plot.

`title` plot title, '' by default

`symmetryAxes` set symmetry for axes, either:

- 'combine' (by default): both axes are symmetric and with the same limits
- 'separate': each axis is symmetric and has its own limits
- 'none': axes by default (plot limits)

`packageTextLabel` package used to label the outlying genes/samples/gene sets, either `ggrepel` (by default, only used if package `ggrepel` is available), or `ggplot2`

`cloudGenes` logical, if TRUE (by default), include the cloud of genes in the plot

`cloudGenesColor` if `cloudGenes` is TRUE, color for the cloud of genes, black by default

`cloudGenesNBins` number of bins to used for the clouds of genes, by default the square root of the number of genes

`cloudGenesIncludeLegend` logical, if TRUE (FALSE by default) include the legend for the cloud of genes (in the top position if multiple legends)

`cloudGenesTitleLegend` string with title for the legend for the cloud of genes 'nGenes' by default

`topGenes` numeric indicating which percentile (if <1) or number (if >=1) of genes most distant to the origin of the plot to annotate, by default: 10 genes are selected If no genes should be annotated, set this parameter to 0 Currently only available for static plot.

`topGenesCex` cex for gene annotation (used when `topGenes` > 0)

`topGenesVar` variable of the featureData used to label the genes, by default: empty, the featureNames are used for labelling (used when `topGenes` > 0)

`topGenesJust` text justification for the genes (used when `topGenes` > 0 and if `packageTextLabel` is `ggplot2`), by default: c(0.5, 0.5) so centered

`topGenesColor` text color for the genes (used when `topGenes` > 0), black by default

`topSamples` numeric indicating which percentile (if <1) or number (if >=1) of samples most distant to the origin of the plot to annotate, by default: 10 samples are selected If no samples should be annotated, set this parameter to 0. Currently available for static plot.

topSamplesCex cex for sample annotation (used when topSamples > 0)

topSamplesVar variable of the phenoData used to label the samples, by default: empty, the sampleNames are used for labelling (used when topSamples > 0)

topSamplesJust text justification for the samples (used when topSamples > 0 and if packageTextLabel is ggplot2), by default: c(0.5, 0.5) so centered

topSamplesColor
text color for the samples (used when topSamples > 0), black by default

geneSets list of gene sets/pathways, each containing identifiers of genes contained in the set. E.g. pathways from Gene Ontology databases output from the getGeneSetsForPlot function or any custom list of pathways. The genes identifiers should correspond to the variable geneSetsVar contained in the phenoData, if not specified the featureNames are used. If several gene sets have the same name, they will be combine to extract the top gene sets.

geneSetsVar variable of the featureData used to match the genes contained in geneSets, most probably ENTREZID, if not specified the featureNames of the eSet are used Only used when topGeneSets > 0 and the parameter geneSets is specified.

geneSetsMaxNChar
maximum number of characters for pathway names, by default keep entire names Only used when topGeneSets > 0 and the parameter geneSets is specified. If returnAnalysis is set to TRUE and geneSetsMaxNChar specified, the top pathways will be returned in the output object, named with the identifiers used in the plot (so with maximum geneSetsMaxNChar number of characters)

topGeneSets numeric indicating which percentile (if <=1) or number (if >1) of gene sets most distant to the origin of the plot to annotate, by default: 10 gene sets are selected If no gene sets should be annotated, set this parameter to 0. Currently available for static plot. Only used when topGeneSets > 0 and the parameter geneSets is specified.

topGeneSetsCex cex for gene sets annotation Only used when topGeneSets > 0 and the parameter geneSets is specified.

topGeneSetsJust
text justification for the gene sets by default: c(0.5, 0.5) so centered Only used when topGeneSets > 0, the parameter geneSets is specified and if packageTextLabel is ggplot2.

topGeneSetsColor
color for the gene sets (used when topGeneSets > 0 and geneSets is specified), black by default Only used when topGeneSets > 0 and the parameter geneSets is specified.

includeLegend logical if TRUE (by default) include a legend, otherwise not

includeLineOrigin
if TRUE (by default) include vertical line at x = 0 and horizontal line at y = 0

typePlot type of the plot returned, either 'static' (static) or interactive' (potentially interactive)

packageInteractivity
if typePlot is 'interactive', package used for interactive plot, either 'plotly' (by default) (by default) or 'ggvis'.

figInteractiveSize
: vector containing the size of the interactive plot, as [width, height] by default: c(600, 400). This is passed to the `width` and `height` parameters of:
  - for plotly plots: the `ggplotly` function
  - for ggvis plots: the `ggvis::set_options` function

ggvisAdjustLegend
: logical, if TRUE (by default) adjust the legends in `ggvis` to avoid overlapping legends when multiple legends

interactiveTooltip
: logical, if TRUE, add hoover functionality showing sample annotation (variables used in the plot) in the plot

interactiveTooltipExtraVars
: name of extra variable(s) (in varLabels of the `eset`) to add in plotlyEsetPlot to label the samples, empty by default

returnAnalysis
: logical, if TRUE (FALSE by default), return also the output of the analysis, and the outlying samples in the topElements element if any, otherwise only the plot object

returnEsetPlot
: logical, if TRUE return also the esetPlot object

Value

if `returnAnalysis` is TRUE, return a list:

- analysis: output of the spectral map analysis, whose parameters can be given as input to the `esetPlotWrapper` function
  - dataPlotSamples: coordinates of the samples
  - dataPlotGenes: coordinates of the genes
  - esetUsed: expressionSet used in the plot
- topElements: list with top outlying elements if any, possibly genes, samples and gene sets
- plot: the plot output

otherwise return only the plot

Author(s)

Laure Cougnaud

References

Fisher, R. A. (1936). The Use of Multiple Measurements in Taxonomic Problems. Annals of Eugenics, 7 (2), 179–188

See Also

the function used internally: `lda`

Examples

```
# load data
library(ALL)
data(ALL)

# specify several variables in ldaVar (this might take a few minutes to run...)

# sample subsetting: currently cannot deal with missing values
samplesToRemove <- which(apply(pData(ALL)[, c("sex", "BT")], 1, anyNA))

# extract random features, because analysis is quite time consuming
retainedFeatures <- sample(featureNames(ALL), size = floor(nrow(ALL)/5))

# create the plot
esetLda(eset = ALL[retainedFeatures, -samplesToRemove],
  ldaVar = "BT", colorVar = "BT", shapeVar = "sex", sizeVar = "age",
  title = "Linear discriminant analysis on the ALL dataset")
```

`esetPlot-class` *An S4 class to represent* `esetPlot` *object expressionSet with visualization data from dimension-reduction methods*

Description

Constructor of the esetPlot class

Usage

```
## S4 method for signature 'esetPlot'
initialize(.Object, ...)
```

Arguments

`.Object`	esetPlot object
`...`	additional class arguments

Value

S4 object of class `esetPlot`

Slots

`dataPlotSamples` data.frame with columns 'X', 'Y' with coordinates for the samples and with rownames which should correspond and be in the same order as the sampleNames of `esetUsed`

`dataPlotGenes` data.frame with two columns 'X' and 'Y' with coordinates for the genes

`eset` expressionSet (or SummarizedExperiment) object with data

`colorVar` name of variable (in varLabels of the `eset`) used for coloring, empty by default

color character or factor with specified color(s) for the points, replicated if needed. This is used only if colorVar is empty. By default: 'black' if colorVar is not specified and default ggplot palette otherwise

shapeVar name of variable (in varLabels of the eset) used for the shape, empty by default

shape character or factor with specified shape(s) (pch) for the points, replicated if needed. This is used only if shapeVar is empty. By default: '15' (filled square) if shapeVar is not specified and default ggplot shape(s) otherwise

sizeVar name of variable (in varLabels of the eset) used for the size, empty by default

size size character or factor with specified size(s) (cex) for the points, replicated if needed. This is used only if sizeVar is empty. By default: '2.5' if sizeVar is not specified and default ggplot size(s) otherwise

sizeRange, size (cex) range used in the plot, possible only if the sizeVar is 'numeric' or 'integer'

alphaVar name of variable (in varLabels of the eset) used for the transparency, empty by default.

alpha alpha character or factor with specified transparency(s) for the points, replicated if needed. This is used only if shapeVar is empty. By default: '1' if alphaVar is not specified and default ggplot alpha otherwise.

alphaRange transparency (alpha) range used in the plot, possible only if the alphaVar is 'numeric' or 'integer'

symmetryAxes set symmetry for axes, either:

- 'combine' (by default): both axes are symmetric and with the same limits
- 'separate': each axis is symmetric and has its own limits
- 'none': axes by default (plot limits)

cloudGenes logical, if TRUE (by default), include the cloud of genes in the spectral map

cloudGenesColor if cloudGenes is TRUE, color for the cloud of genes, black by default

cloudGenesNBins number of bins to used for the clouds of genes, by default the square root of the number of genes

cloudGenesIncludeLegend logical, if TRUE (FALSE by default) include the legend for the cloud of genes (in the top position if multiple legends)

cloudGenesTitleLegend string with title for the legend for the cloud of genes 'nGenes' by default

packageTextLabel package used to label the outlying genes/samples/gene sets, either ggrepel (by default, only used if package ggrepel is available), or ggplot2

topGenes numeric indicating which percentile (if <1) or number (if >=1) of genes most distant to the origin of the plot to annotate, by default: 10 genes are selected If no genes should be annotated, set this parameter to 0 Currently only available for static plot.

topGenesCex cex for gene annotation (used when topGenes > 0)

topGenesVar variable of the featureData used to label the genes, by default: empty, the featureNames are used for labelling (used when topGenes > 0)

topGenesJust text justification for the genes (used when topGenes > 0 and if packageTextLabel is ggplot2), by default: c(0.5, 0.5) so centered

topGenesColor text color for the genes (used when topGenes > 0), black by default

`topSamples` numeric indicating which percentile (if <1) or number (if >=1) of samples most distant to the origin of the plot to annotate, by default: 10 samples are selected If no samples should be annotated, set this parameter to 0. Currently available for static plot.

`topSamplesCex` cex for sample annotation (used when `topSamples` > 0)

`topSamplesVar` variable of the phenoData used to label the samples, by default: empty, the sampleNames are used for labelling (used when `topSamples` > 0)

`topSamplesJust` text justification for the samples (used when `topSamples` > 0 and if `packageTextLabel` is `ggplot2`), by default: c(0.5, 0.5) so centered

`topSamplesColor` text color for the samples (used when `topSamples` > 0), black by default

`geneSets` list of gene sets/pathways, each containing identifiers of genes contained in the set. E.g. pathways from Gene Ontology databases output from the `getGeneSetsForPlot` function or any custom list of pathways. The genes identifiers should correspond to the variable `geneSetsVar` contained in the phenoData, if not specified the featureNames are used. If several gene sets have the same name, they will be combine to extract the top gene sets.

`geneSetsVar` variable of the featureData used to match the genes contained in geneSets, most probably ENTREZID, if not specified the featureNames of the eSet are used Only used when `topGeneSets` > 0 and the parameter geneSets is specified.

`geneSetsMaxNChar` maximum number of characters for pathway names, by default keep entire names Only used when `topGeneSets` > 0 and the parameter `geneSets` is specified.

`topGeneSets` numeric indicating which percentile (if <=1) or number (if >1) of gene sets most distant to the origin of the plot to annotate, by default: 10 gene sets are selected If no gene sets should be annotated, set this parameter to 0. Currently available for static plot. Only used when `topGeneSets` > 0 and the parameter geneSets is specified.

`topGeneSetsCex` cex for gene sets annotation Only used when `topGeneSets` > 0 and the parameter geneSets is specified.

`topGeneSetsJust` text justification for the gene sets by default: c(0.5, 0.5) so centered Only used when `topGeneSets` > 0, the parameter `geneSets` is specified and if `packageTextLabel` is `ggplot2`.

`topGeneSetsColor` color for the gene sets (used when `topGeneSets` > 0 and `geneSets` is specified), black by default Only used when `topGeneSets` > 0 and the parameter geneSets is specified.

`includeLegend` logical if TRUE (by default) include a legend, otherwise not

`includeLineOrigin` if TRUE (by default) include vertical line at x = 0 and horizontal line at y = 0

`esetPlotInteractive-class`

a S4 class to represent interactive plots

Description

a S4 class to represent interactive plots

Value

S4 object of class `esetPlotInteractive`

Slots

`includeTooltip` logical, if TRUE, add hoover functionality showing sample annotation (variables used in the plot) in the plot

`tooltipVars` name of extra phenotypic variable(s) to add in plotlyEsetPlot to label the samples

`sizePlot` vector containing the size of the interactive plot, as [width, height], by default: c(600, 400).

`title` string plot title, '' by default

`xlab` string label for the x axis

`ylab` string label for the y axis

Author(s)

Laure Cougnaud

---

esetPlotWrapper *wrapper for biplot of features/samples contained in a eSet object*

Description

Wrapper function used for all plots of the visualizations contained in the package.

Usage

```
esetPlotWrapper(
  dataPlotSamples,
  dataPlotGenes = data.frame(),
  esetUsed,
  xlab = "",
  ylab = "",
  colorVar = character(0),
  color = if (length(colorVar) == 0) "black" else character(0),
  shapeVar = character(0),
  shape = if (length(shapeVar) == 0) 15 else numeric(0),
  sizeVar = character(0),
  size = if (length(sizeVar) == 0) {
     ifelse(typePlot[1] == "interactive" &&
    packageInteractivity[1] == "plotly", 20, 2.5)
 } else {
     numeric()
 },
  sizeRange = numeric(0),
```

```
  alphaVar = character(0),
  alpha = if (length(alphaVar) == 0) 1 else numeric(0),
  alphaRange = numeric(0),
  title = "",
  symmetryAxes = c("combine", "separate", "none"),
  cloudGenes = TRUE,
  cloudGenesColor = "black",
 cloudGenesNBins = if (nrow(dataPlotGenes) > 0) sqrt(nrow(dataPlotGenes)) else numeric(),
  cloudGenesIncludeLegend = FALSE,
  cloudGenesTitleLegend = "nGenes",
  packageTextLabel = c("ggrepel", "ggplot2"),
  topGenes = 10,
 topGenesCex = ifelse(typePlot[1] == "interactive" && packageInteractivity[1] ==
    "plotly", 10, 2.5),
  topGenesVar = character(0),
  topGenesJust = c(0.5, 0.5),
  topGenesColor = "black",
  topSamples = 10,
  topSamplesCex = 2.5,
  topSamplesVar = character(0),
  topSamplesJust = c(0.5, 0.5),
  topSamplesColor = "black",
  geneSets = list(),
  geneSetsVar = character(0),
  geneSetsMaxNChar = numeric(0),
  topGeneSets = 10,
  topGeneSetsCex = 2.5,
  topGeneSetsJust = c(0.5, 0.5),
  topGeneSetsColor = "black",
  includeLegend = TRUE,
  includeLineOrigin = TRUE,
  typePlot = c("static", "interactive"),
  figInteractiveSize = c(600, 400),
  ggvisAdjustLegend = TRUE,
  interactiveTooltip = TRUE,
  interactiveTooltipExtraVars = character(0),
  packageInteractivity = c("plotly", "ggvis"),
  returnTopElements = FALSE,
  returnEsetPlot = FALSE
)
```

Arguments

dataPlotSamples	data.frame with columns 'X', 'Y' with coordinates for the samples and with rownames which should correspond and be in the same order as the sampleNames of esetUsed
dataPlotGenes	data.frame with two columns 'X' and 'Y' with coordinates for the genes

esetUsed	expressionSet (or SummarizedExperiment) object with data
xlab	label for the x axis
ylab	label for the y axis
colorVar	name of variable (in varLabels of the eset) used for coloring, empty by default
color	character or factor with specified color(s) for the points, replicated if needed. This is used only if colorVar is empty. By default: 'black' if colorVar is not specified and default ggplot palette otherwise
shapeVar	name of variable (in varLabels of the eset) used for the shape, empty by default
shape	character or factor with specified shape(s) (pch) for the points, replicated if needed. This is used only if shapeVar is empty. By default: '15' (filled square) if shapeVar is not specified and default ggplot shape(s) otherwise
sizeVar	name of variable (in varLabels of the eset) used for the size, empty by default
size	character or factor with specified size(s) (cex) for the points, replicated if needed. This is used only if sizeVar is empty. By default: '2.5' if sizeVar is not specified (20 for a plotly plot) and default ggplot size(s) otherwise
sizeRange	size (cex) range used in the plot, possible only if the sizeVar is 'numeric' or 'integer'
alphaVar	name of variable (in varLabels of the eset) used for the transparency, empty by default. This parameter is currently only available for static plot and ggvis (only numeric in this case).
alpha	character or factor with specified transparency(s) for the points, replicated if needed. This is used only if shapeVar is empty. By default: '1' if alphaVar is not specified and default ggplot alpha otherwise This parameter is currently only available for static and ggvis.
alphaRange	transparency (alpha) range used in the plot, possible only if the alphaVar is 'numeric' or 'integer' This parameter is currently only available for static and ggvis plot.
title	plot title, '' by default
symmetryAxes	set symmetry for axes, either: • 'combine' (by default): both axes are symmetric and with the same limits • 'separate': each axis is symmetric and has its own limits • 'none': axes by default (plot limits)
cloudGenes	logical, if TRUE (by default), include the cloud of genes in the plot
cloudGenesColor	if cloudGenes is TRUE, color for the cloud of genes, black by default
cloudGenesNBins	number of bins to used for the clouds of genes, by default the square root of the number of genes
cloudGenesIncludeLegend	logical, if TRUE (FALSE by default) include the legend for the cloud of genes (in the top position if multiple legends)
cloudGenesTitleLegend	string with title for the legend for the cloud of genes 'nGenes' by default

packageTextLabel
: package used to label the outlying genes/samples/gene sets, either ggrepel (by default, only used if package ggrepel is available), or ggplot2

topGenes
: numeric indicating which percentile (if <1) or number (if >=1) of genes most distant to the origin of the plot to annotate, by default: 10 genes are selected If no genes should be annotated, set this parameter to 0 Currently only available for static plot.

topGenesCex
: cex for gene annotation (used when topGenes > 0)

topGenesVar
: variable of the featureData used to label the genes, by default: empty, the featureNames are used for labelling (used when topGenes > 0)

topGenesJust
: text justification for the genes (used when topGenes > 0 and if packageTextLabel is ggplot2), by default: c(0.5, 0.5) so centered

topGenesColor
: text color for the genes (used when topGenes > 0), black by default

topSamples
: numeric indicating which percentile (if <1) or number (if >=1) of samples most distant to the origin of the plot to annotate, by default: 10 samples are selected If no samples should be annotated, set this parameter to 0. Currently available for static plot.

topSamplesCex
: cex for sample annotation (used when topSamples > 0)

topSamplesVar
: variable of the phenoData used to label the samples, by default: empty, the sampleNames are used for labelling (used when topSamples > 0)

topSamplesJust
: text justification for the samples (used when topSamples > 0 and if packageTextLabel is ggplot2), by default: c(0.5, 0.5) so centered

topSamplesColor
: text color for the samples (used when topSamples > 0), black by default

geneSets
: list of gene sets/pathways, each containing identifiers of genes contained in the set. E.g. pathways from Gene Ontology databases output from the getGeneSetsForPlot function or any custom list of pathways. The genes identifiers should correspond to the variable geneSetsVar contained in the phenoData, if not specified the featureNames are used. If several gene sets have the same name, they will be combine to extract the top gene sets.

geneSetsVar
: variable of the featureData used to match the genes contained in geneSets, most probably ENTREZID, if not specified the featureNames of the eSet are used Only used when topGeneSets > 0 and the parameter geneSets is specified.

geneSetsMaxNChar
: maximum number of characters for pathway names, by default keep entire names Only used when topGeneSets > 0 and the parameter geneSets is specified. If returnAnalysis is set to TRUE and geneSetsMaxNChar specified, the top pathways will be returned in the output object, named with the identifiers used in the plot (so with maximum geneSetsMaxNChar number of characters)

topGeneSets
: numeric indicating which percentile (if <=1) or number (if >1) of gene sets most distant to the origin of the plot to annotate, by default: 10 gene sets are selected If no gene sets should be annotated, set this parameter to 0. Currently available for static plot. Only used when topGeneSets > 0 and the parameter geneSets is specified.

`topGeneSetsCex` cex for gene sets annotation Only used when `topGeneSets` > 0 and the parameter geneSets is specified.

`topGeneSetsJust`
text justification for the gene sets by default: c(0.5, 0.5) so centered Only used when `topGeneSets` > 0, the parameter `geneSets` is specified and if `packageTextLabel` is `ggplot2`.

`topGeneSetsColor`
color for the gene sets (used when `topGeneSets` > 0 and `geneSets` is specified), black by default Only used when `topGeneSets` > 0 and the parameter geneSets is specified.

`includeLegend` logical if TRUE (by default) include a legend, otherwise not

`includeLineOrigin`
if TRUE (by default) include vertical line at x = 0 and horizontal line at y = 0

`typePlot` type of the plot returned, either 'static' (static) or interactive' (potentially interactive)

`figInteractiveSize`
vector containing the size of the interactive plot, as [width, height] by default: c(600, 400). This is passed to the `width` and `height` parameters of:

- for plotly plots: the `ggplotly` function
- for ggvis plots: the `ggvis::set_options` function

`ggvisAdjustLegend`
logical, if TRUE (by default) adjust the legends in `ggvis` to avoid overlapping legends when multiple legends

`interactiveTooltip`
logical, if TRUE, add hoover functionality showing sample annotation (variables used in the plot) in the plot

`interactiveTooltipExtraVars`
name of extra variable(s) (in varLabels of the `eset`) to add in plotlyEsetPlot to label the samples, empty by default

`packageInteractivity`
if `typePlot` is 'interactive', package used for interactive plot, either 'plotly' (by default) (by default) or 'ggvis'.

`returnTopElements`
logical, if TRUE return also the top elements

`returnEsetPlot` logical, if TRUE return also the esetPlot object

Value

if `typePlot` is:

- `static`:
  - if `returnTopElements` is TRUE, and top elements can be displayed, a list with:
    - 'topElements': the top elements labelled in the plot
    - 'plot': the `ggplot` object
  - otherwise, the `ggplot` object only
- `interactive`: a `ggvis` or `plotly` object, depending on the `packageInteractivity` parameter

Author(s)

Laure Cougnaud

Examples

```
library(ALL)
data(ALL)

## run one spectral map analysis

# create custom color palette
colorPalette <- c("dodgerblue", colorRampPalette(c("white","dodgerblue2", "darkblue"))(5)[-1],
 "red", colorRampPalette(c("white", "red3", "darkred"))(5)[-1])

# run the analysis
# with 'returnAnalysis' set to TRUE to have all objects required for the esetPlotWrapper
outputEsetSPM <- esetSpectralMap(eset = ALL,
 title = "Acute lymphoblastic leukemia dataset \n Spectral map complete",
 colorVar = "BT", color = colorPalette,
 shapeVar = "sex", shape = 15:16,
 sizeVar = "age", sizeRange = c(2, 6),
 symmetryAxes = "separate",
 topGenes = 10, topGenesJust = c(1, 0), topGenesCex = 2, topGenesColor = "darkgrey",
 topSamples = 15, topSamplesVar = "cod", topSamplesColor = "black",
 topSamplesJust = c(1, 0), topSamplesCex = 3, returnAnalysis = TRUE)

# plot the biplot
print(outputEsetSPM$plot)


## re-call the plot function, to change some visualizations parameters
esetPlotWrapper(
 dataPlotSamples = outputEsetSPM$analysis$dataPlotSamples,
 dataPlotGenes = outputEsetSPM$analysis$dataPlotGenes,
 esetUsed = outputEsetSPM$analysis$esetUsed,
 title = paste("Acute lymphoblastic leukemia dataset \n Spectral map"),
 colorVar = "BT", color = colorPalette,
 shapeVar = "relapse",
 sizeVar = "age", sizeRange = c(2, 6),
 topSamplesVar = "cod", topGenesVar = "SYMBOL"
)
```

`esetSpectralMap` *plot a spectral map biplot of an eSet.*

Description

`esetSpectralMap` reduces the dimension of the data contained in the eSet with the `mpm` function and plot the subsequent biplot of the specified dimensions, possibly with gene and sample annotation contained in the eSet. A spectral map with the default parameters is equivalent to a principal

component analysis on the log-transformed, double centered and global normalized data (from documentation of the mpm function).

Usage

```
esetSpectralMap(
  eset,
  psids = 1:nrow(eset),
  dim = c(1, 2),
  colorVar = character(),
  color = if (length(colorVar) == 0) "black" else character(),
  shapeVar = character(),
  shape = if (length(shapeVar) == 0) 15 else numeric(),
  sizeVar = character(),
  size = if (length(sizeVar) == 0) {
     ifelse(typePlot[1] == "interactive" &&
    packageInteractivity[1] == "plotly", 20, 2.5)
 } else {
     numeric()
 },
  sizeRange = numeric(),
  alphaVar = character(),
  alpha = if (length(alphaVar) == 0) 1 else numeric(),
  alphaRange = numeric(),
  title = "",
 mpm.args = list(closure = "none", center = "double", normal = "global", row.weight =
    "mean", col.weight = "constant", logtrans = FALSE),
 plot.mpm.args = list(scale = "uvc"),
 symmetryAxes = c("combine", "separate", "none"),
 packageTextLabel = c("ggrepel", "ggplot2"),
 cloudGenes = TRUE,
 cloudGenesColor = "black",
 cloudGenesNBins = sqrt(length(psids)),
 cloudGenesIncludeLegend = FALSE,
 cloudGenesTitleLegend = "nGenes",
 topGenes = 10,
 topGenesCex = ifelse(typePlot[1] == "interactive" && packageInteractivity[1] ==
    "plotly", 10, 2.5),
 topGenesVar = character(),
 topGenesJust = c(0.5, 0.5),
 topGenesColor = "black",
 topSamples = 10,
 topSamplesCex = ifelse(typePlot[1] == "interactive" && packageInteractivity[1] ==
    "plotly", 10, 2.5),
 topSamplesVar = character(),
 topSamplesJust = c(0.5, 0.5),
 topSamplesColor = "black",
 geneSets = list(),
 geneSetsVar = character(),
```

```
  geneSetsMaxNChar = numeric(),
  topGeneSets = 10,
 topGeneSetsCex = ifelse(typePlot[1] == "interactive" && packageInteractivity[1] ==
    "plotly", 10, 2.5),
  topGeneSetsJust = c(0.5, 0.5),
  topGeneSetsColor = "black",
  includeLegend = TRUE,
  includeLineOrigin = TRUE,
  typePlot = c("static", "interactive"),
  packageInteractivity = c("plotly", "ggvis"),
  figInteractiveSize = c(600, 400),
  ggvisAdjustLegend = TRUE,
  interactiveTooltip = TRUE,
  interactiveTooltipExtraVars = character(),
  returnAnalysis = FALSE,
  returnEsetPlot = FALSE
)
```

Arguments

eset	expressionSet (or SummarizedExperiment) object with data
psids	featureNames of genes to include in the plot, all by default
dim	dimensions of the analysis to represent, first two dimensions by default
colorVar	name of variable (in varLabels of the eset) used for coloring, empty by default
color	character or factor with specified color(s) for the points, replicated if needed. This is used only if colorVar is empty. By default: 'black' if colorVar is not specified and default ggplot palette otherwise
shapeVar	name of variable (in varLabels of the eset) used for the shape, empty by default
shape	character or factor with specified shape(s) (pch) for the points, replicated if needed. This is used only if shapeVar is empty. By default: '15' (filled square) if shapeVar is not specified and default ggplot shape(s) otherwise
sizeVar	name of variable (in varLabels of the eset) used for the size, empty by default
size	character or factor with specified size(s) (cex) for the points, replicated if needed. This is used only if sizeVar is empty. By default: '2.5' if sizeVar is not specified (20 for a plotly plot) and default ggplot size(s) otherwise
sizeRange	size (cex) range used in the plot, possible only if the sizeVar is 'numeric' or 'integer'
alphaVar	name of variable (in varLabels of the eset) used for the transparency, empty by default. This parameter is currently only available for static plot and ggvis (only numeric in this case).
alpha	character or factor with specified transparency(s) for the points, replicated if needed. This is used only if shapeVar is empty. By default: '1' if alphaVar is not specified and default ggplot alpha otherwise This parameter is currently only available for static and ggvis.

`alphaRange` transparency (alpha) range used in the plot, possible only if the `alphaVar` is 'numeric' or 'integer' This parameter is currently only available for static and ggvis plot.

`title` plot title, '' by default

`mpm.args` list with input parameters for the `mpm` function. The default value is: `list(closure = 'none', center = 'double', normal = 'global', 'row.weight' = 'mean',col.weight = 'constant', logtrans = FALSE)`. This assumes that the data are already in a log scale.

`plot.mpm.args` list with input parameters for the `plot.mpm` function. The default value is: list(scale = "uvc").

`symmetryAxes` set symmetry for axes, either:

- 'combine' (by default): both axes are symmetric and with the same limits
- 'separate': each axis is symmetric and has its own limits
- 'none': axes by default (plot limits)

`packageTextLabel` package used to label the outlying genes/samples/gene sets, either `ggrepel` (by default, only used if package `ggrepel` is available), or `ggplot2`

`cloudGenes` logical, if TRUE (by default), include the cloud of genes in the plot

`cloudGenesColor` if `cloudGenes` is TRUE, color for the cloud of genes, black by default

`cloudGenesNBins` number of bins to used for the clouds of genes, by default the square root of the number of genes

`cloudGenesIncludeLegend` logical, if TRUE (FALSE by default) include the legend for the cloud of genes (in the top position if multiple legends)

`cloudGenesTitleLegend` string with title for the legend for the cloud of genes 'nGenes' by default

`topGenes` numeric indicating which percentile (if <1) or number (if >=1) of genes most distant to the origin of the plot to annotate, by default: 10 genes are selected If no genes should be annotated, set this parameter to 0 Currently only available for static plot.

`topGenesCex` cex for gene annotation (used when `topGenes` > 0)

`topGenesVar` variable of the featureData used to label the genes, by default: empty, the featureNames are used for labelling (used when `topGenes` > 0)

`topGenesJust` text justification for the genes (used when `topGenes` > 0 and if `packageTextLabel` is `ggplot2`), by default: c(0.5, 0.5) so centered

`topGenesColor` text color for the genes (used when `topGenes` > 0), black by default

`topSamples` numeric indicating which percentile (if <1) or number (if >=1) of samples most distant to the origin of the plot to annotate, by default: 10 samples are selected If no samples should be annotated, set this parameter to 0. Currently available for static plot.

`topSamplesCex` cex for sample annotation (used when `topSamples` > 0)

topSamplesVar variable of the phenoData used to label the samples, by default: empty, the sampleNames are used for labelling (used when topSamples > 0)

topSamplesJust text justification for the samples (used when topSamples > 0 and if packageTextLabel is ggplot2), by default: c(0.5, 0.5) so centered

topSamplesColor
text color for the samples (used when topSamples > 0), black by default

geneSets list of gene sets/pathways, each containing identifiers of genes contained in the set. E.g. pathways from Gene Ontology databases output from the getGeneSetsForPlot function or any custom list of pathways. The genes identifiers should correspond to the variable geneSetsVar contained in the phenoData, if not specified the featureNames are used. If several gene sets have the same name, they will be combine to extract the top gene sets.

geneSetsVar variable of the featureData used to match the genes contained in geneSets, most probably ENTREZID, if not specified the featureNames of the eSet are used Only used when topGeneSets > 0 and the parameter geneSets is specified.

geneSetsMaxNChar
maximum number of characters for pathway names, by default keep entire names Only used when topGeneSets > 0 and the parameter geneSets is specified. If returnAnalysis is set to TRUE and geneSetsMaxNChar specified, the top pathways will be returned in the output object, named with the identifiers used in the plot (so with maximum geneSetsMaxNChar number of characters)

topGeneSets numeric indicating which percentile (if <=1) or number (if >1) of gene sets most distant to the origin of the plot to annotate, by default: 10 gene sets are selected If no gene sets should be annotated, set this parameter to 0. Currently available for static plot. Only used when topGeneSets > 0 and the parameter geneSets is specified.

topGeneSetsCex cex for gene sets annotation Only used when topGeneSets > 0 and the parameter geneSets is specified.

topGeneSetsJust
text justification for the gene sets by default: c(0.5, 0.5) so centered Only used when topGeneSets > 0, the parameter geneSets is specified and if packageTextLabel is ggplot2.

topGeneSetsColor
color for the gene sets (used when topGeneSets > 0 and geneSets is specified), black by default Only used when topGeneSets > 0 and the parameter geneSets is specified.

includeLegend logical if TRUE (by default) include a legend, otherwise not

includeLineOrigin
if TRUE (by default) include vertical line at x = 0 and horizontal line at y = 0

typePlot type of the plot returned, either 'static' (static) or interactive' (potentially interactive)

packageInteractivity
if typePlot is 'interactive', package used for interactive plot, either 'plotly' (by default) (by default) or 'ggvis'.

figInteractiveSize
: vector containing the size of the interactive plot, as [width, height] by default: c(600, 400). This is passed to the `width` and `height` parameters of:
  - for plotly plots: the `ggplotly` function
  - for ggvis plots: the `ggvis::set_options` function

ggvisAdjustLegend
: logical, if TRUE (by default) adjust the legends in `ggvis` to avoid overlapping legends when multiple legends

interactiveTooltip
: logical, if TRUE, add hoover functionality showing sample annotation (variables used in the plot) in the plot

interactiveTooltipExtraVars
: name of extra variable(s) (in varLabels of the `eset`) to add in plotlyEsetPlot to label the samples, empty by default

returnAnalysis
: logical, if TRUE (FALSE by default), return also the output of the analysis, and the outlying samples in the topElements element if any, otherwise only the plot object

returnEsetPlot
: logical, if TRUE return also the esetPlot object

Value

if `returnAnalysis` is TRUE, return a list:

- analysis: output of the spectral map analysis, can be given as input to the `esetPlotWrapper` function
  - dataPlotSamples: coordinates of the samples
  - dataPlotGenes: coordinates of the genes
  - esetUsed: expressionSet used in the plot
  - axisLabels: axes labels indicating percentage of variance explained by the selected axes
  - axesContributionsPercentages: percentages of variance explained by each axis (not only the ones specified in `dim`)
- topElements: list with top outlying elements if any, possibly genes, samples and gene sets
- plot: the plot output

otherwise return only the plot

Author(s)

Laure Cougnaud

References

Lewi, P.J. (1976). Spectral mapping, a technique for classifying biological activity profiles of chemical compounds. Arzneimittel Forschung (Drug Research), 26, 1295–1300

See Also

the function used internally: `mpm` and `spectralMap` for spectral map in base R graphics

Examples

```
library(ALL)
data(ALL)

## complete example (most of the parameters are optional)
# create custom color palette
colorPalette <- c("dodgerblue", colorRampPalette(c("white","dodgerblue2", "darkblue"))(5)[-1],
 "red", colorRampPalette(c("white", "red3", "darkred"))(5)[-1])
# plot the spectral map
print(esetSpectralMap(eset = ALL,
 title = "Acute lymphoblastic leukemia dataset \n Spectral map complete",
colorVar = "BT", color = colorPalette,
shapeVar = "sex", shape = 15:16,
sizeVar = "age", sizeRange = c(2, 6),
symmetryAxes = "separate",
topGenes = 10, topGenesJust = c(1, 0), topGenesCex = 2, topGenesColor = "darkgrey",
topSamples = 15, topSamplesVar = "cod", topSamplesColor = "black",
topSamplesJust = c(1, 0), topSamplesCex = 3)
)

# see vignette for other examples, especially one with gene sets specification
```

`esetTsne` *plot a t-SNE of an eSet object*

Description

`esetTsne` reduces the dimension of the data contained in the eSet via t-Distributed Stochastic Neighbor Embedding with the `Rtsne` function and plot the subsequent biplot, possibly with sample annotation contained in the eSet.

Usage

```
esetTsne(
  eset,
  psids = 1:nrow(eset),
  trace = TRUE,
  colorVar = character(),
  color = if (length(colorVar) == 0) "black" else character(),
  shapeVar = character(),
  shape = if (length(shapeVar) == 0) 15 else numeric(),
  sizeVar = character(),
  size = if (length(sizeVar) == 0) {
     ifelse(typePlot[1] == "interactive" &&
    packageInteractivity[1] == "plotly", 20, 2.5)
 } else {
     numeric()
```

```
 },
  sizeRange = numeric(),
  alphaVar = character(),
  alpha = if (length(alphaVar) == 0) 1 else numeric(),
  alphaRange = numeric(),
  title = "",
 Rtsne.args = list(perplexity = floor((ncol(eset) - 1)/3), theta = 0.5, dims = 2,
    initial_dims = 50),
  fctTransformDataForInputTsne = NULL,
  symmetryAxes = c("combine", "separate", "none"),
  packageTextLabel = c("ggrepel", "ggplot2"),
  topSamples = 10,
 topSamplesCex = ifelse(typePlot[1] == "interactive" && packageInteractivity[1] ==
    "plotly", 10, 2.5),
  topSamplesVar = character(),
  topSamplesJust = c(0.5, 0.5),
  topSamplesColor = "black",
  includeLegend = TRUE,
  includeLineOrigin = TRUE,
  typePlot = c("static", "interactive"),
  packageInteractivity = c("plotly", "ggvis"),
  figInteractiveSize = c(600, 400),
  ggvisAdjustLegend = TRUE,
  interactiveTooltip = TRUE,
  interactiveTooltipExtraVars = character(),
  returnAnalysis = FALSE,
  returnEsetPlot = FALSE
)
```

Arguments

eset	expressionSet (or SummarizedExperiment) object with data
psids	featureNames of genes to include in the plot, all by default
trace	logical, if TRUE (by default), print some messages during tsne is running
colorVar	name of variable (in varLabels of the eset) used for coloring, empty by default
color	character or factor with specified color(s) for the points, replicated if needed. This is used only if colorVar is empty. By default: 'black' if colorVar is not specified and default ggplot palette otherwise
shapeVar	name of variable (in varLabels of the eset) used for the shape, empty by default
shape	character or factor with specified shape(s) (pch) for the points, replicated if needed. This is used only if shapeVar is empty. By default: '15' (filled square) if shapeVar is not specified and default ggplot shape(s) otherwise
sizeVar	name of variable (in varLabels of the eset) used for the size, empty by default
size	character or factor with specified size(s) (cex) for the points, replicated if needed. This is used only if sizeVar is empty. By default: '2.5' if sizeVar is not specified (20 for a plotly plot) and default ggplot size(s) otherwise

`sizeRange` size (cex) range used in the plot, possible only if the `sizeVar` is 'numeric' or 'integer'

`alphaVar` name of variable (in varLabels of the `eset`) used for the transparency, empty by default. This parameter is currently only available for static plot and ggvis (only numeric in this case).

`alpha` character or factor with specified transparency(s) for the points, replicated if needed. This is used only if `shapeVar` is empty. By default: '1' if `alphaVar` is not specified and default `ggplot` alpha otherwise This parameter is currently only available for static and ggvis.

`alphaRange` transparency (alpha) range used in the plot, possible only if the `alphaVar` is 'numeric' or 'integer' This parameter is currently only available for static and ggvis plot.

`title` plot title, '' by default

`Rtsne.args` arguments for the Rtsne function, by default: perplexite parameter = optimal number of neighbours, theta = speed/accuracy trade-off (increase for less accuracy), set to 0.0 for exact TSNE

`fctTransformDataForInputTsne`
function which transform the data in the eSet object before calling the `Rtsne` function. This should be a function which takes a matrix as input and return a matrix, e.g. the dist function.

`symmetryAxes` set symmetry for axes, either:

- 'combine' (by default): both axes are symmetric and with the same limits
- 'separate': each axis is symmetric and has its own limits
- 'none': axes by default (plot limits)

`packageTextLabel`
package used to label the outlying genes/samples/gene sets, either `ggrepel` (by default, only used if package `ggrepel` is available), or `ggplot2`

`topSamples` numeric indicating which percentile (if <1) or number (if >=1) of samples most distant to the origin of the plot to annotate, by default: 10 samples are selected If no samples should be annotated, set this parameter to 0. Currently available for static plot.

`topSamplesCex` cex for sample annotation (used when `topSamples` > 0)

`topSamplesVar` variable of the phenoData used to label the samples, by default: empty, the sampleNames are used for labelling (used when `topSamples` > 0)

`topSamplesJust` text justification for the samples (used when `topSamples` > 0 and if `packageTextLabel` is `ggplot2`), by default: c(0.5, 0.5) so centered

`topSamplesColor`
text color for the samples (used when `topSamples` > 0), black by default

`includeLegend` logical if TRUE (by default) include a legend, otherwise not

`includeLineOrigin`
if TRUE (by default) include vertical line at x = 0 and horizontal line at y = 0

`typePlot` type of the plot returned, either 'static' (static) or interactive' (potentially interactive)

packageInteractivity
: if typePlot is 'interactive', package used for interactive plot, either 'plotly' (by default) (by default) or 'ggvis'.

figInteractiveSize
: vector containing the size of the interactive plot, as [width, height] by default: c(600, 400). This is passed to the width and height parameters of:
  - for plotly plots: the ggplotly function
  - for ggvis plots: the ggvis::set_options function

ggvisAdjustLegend
: logical, if TRUE (by default) adjust the legends in ggvis to avoid overlapping legends when multiple legends

interactiveTooltip
: logical, if TRUE, add hoover functionality showing sample annotation (variables used in the plot) in the plot

interactiveTooltipExtraVars
: name of extra variable(s) (in varLabels of the eset) to add in plotlyEsetPlot to label the samples, empty by default

returnAnalysis
: logical, if TRUE (FALSE by default), return also the output of the analysis, and the outlying samples in the topElements element if any, otherwise only the plot object

returnEsetPlot
: logical, if TRUE return also the esetPlot object

Value

if returnAnalysis is TRUE, return a list:

- analysis: output of the spectral map analysis, whose elements can be given to the esetPlotWrapper function
  - dataPlotSamples: coordinates of the samples
  - esetUsed: expressionSet used in the plot
- topElements: list with top outlying elements if any, possibly genes, samples and gene sets
- plot: the plot output

otherwise return only the plot

Author(s)

Laure Cougnaud

References

L.J.P. van der Maaten and G.E. Hinton (2008). Visualizing High-Dimensional Data Using t-SNE. Journal of Machine Learning Research, 2579–2605

See Also

the function used internally: Rtsne or http://homepage.tudelft.nl/19j49/t-SNE.html for further explanations about this technique.

Examples

```
library(ALL)
data(ALL)

## complete example (most of the parameters are optional)

# create custom color palette
colorPalette <- c("dodgerblue", colorRampPalette(c("white","dodgerblue2", "darkblue"))(5)[-1],
 "red", colorRampPalette(c("white", "red3", "darkred"))(5)[-1])

# create tsne
print(esetTsne(eset = ALL,
 title = "Acute lymphoblastic leukemia dataset \n Tsne complete",
 colorVar = "BT", color = colorPalette,
 shapeVar = "sex", shape = 15:16,
 sizeVar = "age", sizeRange = c(2, 6),
 symmetryAxes = "separate",
 topSamples = 15, topSamplesVar = "cod", topSamplesColor = "black",
 topSamplesJust = c(1, 0), topSamplesCex = 3)
)
```

---

formatManualScale *extend manual scale values if required*

Description

extend manual scale values if required

Usage

```
formatManualScale(x, valVar, nameVar)
```

Arguments

x	data.frame with nameVar
valVar	fixed value of variable of aesthetic
nameVar	name of variable for aesthetic

Value

vector of manual scales

Author(s)

Laure Cougnaud

formatOutput *format output of plotEset function*

Description

format output of plotEset function

Usage

```
formatOutput(res, object, type, returnEsetPlot)
```

Arguments

res	result of specific plotEset function
object	esetPlot object or extended class
type	string type of plot
returnEsetPlot	logical, should the object be returned in the output function?

Value

result

Author(s)

Laure Cougnaud

getAxesLimits *generic for get axes limits*

Description

generic for get axes limits

Usage

```
getAxesLimits(object)

## S4 method for signature 'esetPlot'
getAxesLimits(object)
```

Arguments

object	plotEset object

Value

matrix with limits for axes: columns x and y

Author(s)

Laure Cougnaud

`getCoordGeneSets` *extract coordinates gene sets*

Description

extract coordinates gene sets

Usage

```
getCoordGeneSets(dataPlotGenes, geneSets, esetUsed, geneSetsVar = list())
```

Arguments

`dataPlotGenes`	data.frame with two columns 'X' and 'Y' with coordinates for the genes
`geneSets`	geneSets list of gene sets, e.g. gene pathways, output from the 'getGeneSets' function in MLP the genes IDs must correspond to the sampleNames in the eset
`esetUsed`	expressionSet (or SummarizedExperiment) object with data
`geneSetsVar`	variable of the featureData used to match the genes contained in geneSets, most probably ENTREZID, if NULL the featureNames of the eSet are used
`...`	Any parameters passed to the `getTopElements`

Value

data.frame with two columns 'X' and 'Y' with coordinates for the gene sets

Author(s)

Laure Cougnaud

getDataPlotSamplesWithAnnotation *get sample data for plot*

Description

get sample data for plot

Usage

```
getDataPlotSamplesWithAnnotation(object)

## S4 method for signature 'esetPlot'
getDataPlotSamplesWithAnnotation(object)

## S4 method for signature 'ggvisEsetPlot'
getDataPlotSamplesWithAnnotation(object)

## S4 method for signature 'plotlyEsetPlot'
getDataPlotSamplesWithAnnotation(object)
```

Arguments

object	plotEset object

Value

data.frame with 'dataPlotSamples' binded with variables displayed in the plot

Author(s)

Laure Cougnaud

getGeneSetsForPlot *get gene sets for plot of eSet object.*

Description

get and format gene sets to be used as geneSets for the functions: esetSpectralMap, esetLda, or esetPlotWrapper Use the getGeneSets function to get the gene sets, combine all databases, and format the gene sets name if required.

Usage

```
getGeneSetsForPlot(
  entrezIdentifiers,
  species = "Human",
  geneSetSource = c("GOBP", "GOMF", "GOCC", "KEGG"),
  useDescription = TRUE,
  trace = TRUE
)
```

Arguments

entrezIdentifiers	string with Entrez Gene identifiers of the genes of interest
species	species to use, given to the getGeneSets function
geneSetSource	gene set source, either 'GOBP', 'GOMF', 'GOCC' or 'KEGG'. Multiple choices are available
useDescription	logical, if TRUE (by default) use the description to label the gene sets, otherwise use the original gene set identifiers Function 'substr' is used.
trace	logical, if TRUE (by default) a few extra information are printed during the process

Value

list with gene sets, each element is a gene set and contains the ENTREZ IDs of the genes contained in this set. If useDescription is:

- FALSE: pathways are labelled with identifiers (Gene Ontology IDs for GOBP, GOMF and GOCC, KEGG IDs for KEGG)
- TRUE: pathways are labelled with gene sets descriptions

Author(s)

Laure Cougnaud

See Also

the function used internally: getGeneSets

Examples

```
# example dataset
library(ALL)
data(ALL)

# get gene annotation from probe IDs
library("hgu95av2.db")
probeIDs <- featureNames(ALL)
geneInfo <- select(hgu95av2.db, probeIDs,"ENTREZID", "PROBEID")
```

```
# get pathway annotation for the genes contained in the ALL dataset (can take a few minutes)
geneSets <- getGeneSetsForPlot(entrezIdentifiers = geneInfo$ENTREZID, species = "Human",
 geneSetSource = 'GOBP',
 useDescription = FALSE, trace = TRUE)
head(geneSets) # returns a pathway list of genes

# gene sets labelled with gene sets description
geneSets <- getGeneSetsForPlot(entrezIdentifiers = geneInfo$ENTREZID, species = "Human",
 geneSetSource = 'GOBP', useDescription = TRUE, trace = TRUE)
head(geneSets) # returns a pathway list of genes

# see also vignette for an example of the use of this function as input for the esetSpectralMap, esetLda or esetPlotW
```

`getMethodsInputObjectEsetVis` *wrapper to extract useful functions, depending if the object is an ExpressionSet or a SummarizedExperiment.*

Description

This returns an error is `x` is not of the correct class. The package `SummarizedExperiment` should be available if `x` is of class `SummarizedExperiment`.

Usage

```
getMethodsInputObjectEsetVis(x)
```

Arguments

x	object

Value

if the object is an ExpressionSet or a SummarizedExperiment, returns a list with the functions specific of the class of `x`, and equivalent of the ExpressionSet functions: 'sampleNames', 'featureNames', 'fData', 'pData', 'exprs'

- sampleNames: sample names
- featureNames: feature names
- fData: feature annotation
- pData: sample annotation
- exprs: data matrix
- varLabels: sample annotation variables
- fvarLabels: feature annotation variables

Author(s)

Laure Cougnaud

getTopElements *create* geom_text *object with top genes/sample/pathways*

Description

create geom_text object with top genes/sample/pathways

Usage

```
getTopElements(
  top,
  type = c("gene", "sample", "geneSets"),
  var = character(),
  dataPlotGenes = data.frame(),
  dataPlotSamples = data.frame(),
  esetUsed,
  geneSets = list(),
  geneSetsVar = character(),
  geneSetsMaxNChar = numeric()
)
```

Arguments

top	numeric, number of top elements
type	type of elements to plot, either 'gene', 'sample', or 'geneSets'
var	variable used to annotate the elements, only used for 'gene' and 'sample'
dataPlotGenes	data.frame with two columns 'X' and 'Y' with coordinates for the genes
dataPlotSamples	data.frame with two columns 'X' and 'Y' with coordinates for the samples
esetUsed	expressionSet (or SummarizedExperiment) object with data
geneSets	list of gene sets, e.g. gene pathways, output from the 'getGeneSets' function in MLP the genes IDs must correspond to the sampleNames in the eset. If several gene sets have the same name, they will be combine to extract the top gene sets.
geneSetsVar	variable of the featureData used to match the genes contained in geneSets, most probably ENTREZID, if not specified the featureNames of the eSet are used
geneSetsMaxNChar	maximum number of characters for pathway names, by default keep entire names
returnTopElements	logical if TRUE (FALSE by default) return the outlying elements

Value

Data.frame with coordinates and labels of the top elements

Author(s)

Laure Cougnaud

`ggPlotEset` *visualize and esetPlot with the 'ggplot2' package*

Description

visualize and esetPlot with the 'ggplot2' package

Usage

```
ggPlotEset(object)
```

Arguments

`object`	object of class esetPlot

Value

`ggplot` object

Author(s)

Laure Cougnaud

`ggplotEsetPlot-class` *a S4 class to represent* `ggplot` *plots*

Description

a S4 class to represent `ggplot` plots

Value

S4 object of class `ggplotEsetPlot`

Slots

`returnTopElements`	logical, if TRUE (FALSE by default) return the outlying elements labelled in the plot (if any)
`title`	string or expression with plot title, '' by default
`xlab`	string or expression with label for the x axis
`ylab`	string or expression with label for the y axis

Author(s)

Laure Cougnaud

ggvisEsetPlot-class *a S4 class for* ggvis *plot*

Description

a S4 class for ggvis plot

Value

S4 object of class ggvisEsetPlot

Slots

adjustLegend logical, if TRUE (by default) adjust the legends in ggvis to avoid overlapping legends when multiple legends

alphaRange transparency (alpha) range used in the plot, c(0.1, 1) by default.

Author(s)

Laure Cougnaud

ggvisPlotEset *visualize and esetPlot with the the 'ggvis' package*

Description

visualize and esetPlot with the the 'ggvis' package

Usage

```
ggvisPlotEset(object)
```

Arguments

object	object of class esetPlot

Value

ggvis plot object

Author(s)

Laure Cougnaud

plotEset *plot an plotEset object*

Description

plot an plotEset object

Usage

```
plotEset(object, returnEsetPlot = FALSE)

## S4 method for signature 'ggplotEsetPlot'
plotEset(object, returnEsetPlot = FALSE)

## S4 method for signature 'ggvisEsetPlot'
plotEset(object, returnEsetPlot = FALSE)

## S4 method for signature 'plotlyEsetPlot'
plotEset(object, returnEsetPlot = FALSE)
```

Arguments

`object`	object of class esetPlot
`returnEsetPlot`	logical, if TRUE return also the esetPlot object, such as can be re-use for future call to plotEset

Value

the plot object if `returnEsetPlot` is FALSE, otherwise a list with 'plot': the plot object and 'esetPlot': the esetPlot object

Author(s)

Laure Cougnaud

plotlyEsetPlot-class *a S4 class to represent* `plotly` *plots*

Description

a S4 class to represent `plotly` plots

Value

S4 object of class `plotlyEsetPlot`

Slots

`returnTopElements` logical, if TRUE (FALSE by default) return the outlying elements labelled in the plot (if any)

`size` specified size(s) (cex) for the points, replicated if needed, used only if `sizeVar` is empty, a factor or character by default: '20' if `sizeVar` is not specified

Author(s)

Laure Cougnaud

---

plotlyPlotEset *visualize and esetPlot with the the 'plotly' package*

Description

visualize and esetPlot with the the 'plotly' package

Usage

```
plotlyPlotEset(object)
```

Arguments

`object`	object of class esetPlot

Value

`plotly` plot

Author(s)

Laure Cougnaud

---

plotTopElements *plot top elements for a static plot*

Description

This create `geom_text` object with top genes/sample/pathways

Usage

```
plotTopElements(
  packageTextLabel = c("ggrepel", "ggplot2"),
  cex = 1,
  just = c(0.5, 0.5),
  color = "black",
  returnTopElements = FALSE,
  ...
)
```

Arguments

packageTextLabel	package used to label the outlying genes/samples/gene sets, either 'ggrepel' (by default, only used if package ggrepel is available), or 'ggplot2'
cex	cex of text in the plot
just	justification of elements in the plot, only use if packageTextLabel is 'ggplot2'
color	color for the elements in the plot
returnTopElements	logical if TRUE (FALSE by default) return the outlying elements

Value

- if the elements are present in the data: if returnTopElements is:
  - TRUE: return a list with two arguments:
    - topElements: string with top elements labelled in the plot
    - geomText: output of geom_text
  - FALSE: only return the output of geom_text
- if not, return NULL

Author(s)

Laure Cougnaud

---

setFixElement *check if the aesthetic is fixed (e.g. color, shape, size 'palette')*

Description

check if the aesthetic is fixed (e.g. color, shape, size 'palette')

Usage

```
setFixElement(typeVar, valVar)
```

Arguments

typeVar	name of variable for aesthetic
valVar	fixed value of variable of aesthetic

Value

logical, if TRUE the element is fixed

Author(s)

Laure Cougnaud

---

setManualScale *check if manual aesthetic should be set*

Description

This is the case only if typeVar and valVar are specified, and if the variable is not numeric or integer (doesn't work with ggplot2)

Usage

```
setManualScale(x, typeVar, valVar)
```

Arguments

x	data.frame with typeVar
typeVar	name of variable for aesthetic
valVar	fixed value of variable of aesthetic

Value

logical, if TRUE the manual scale should be set

Author(s)

Laure Cougnaud

simpleCap — *capitalize the first letter of a word*

Description

capitalize the first letter of a word

Usage

```
simpleCap(x)
```

Arguments

x	string

Value

string with first letter capitalized

varToFm — *Get formula for a specific variable, to be used in aesthetic specification in* plot_ly.

Description

Get formula for a specific variable, to be used in aesthetic specification in plot_ly.

Usage

```
varToFm(var)
```

Arguments

var	Character vector with variable to combine. Otherwise with the '+' operator.

Value

as.formula

Author(s)

Laure Cougnaud

Index

∗ **internal**
    characterORexpressionOrCall-class, 2
    esetPlot-class, 8
    esetPlotInteractive-class, 10
    formatManualScale, 26
    formatOutput, 27
    getAxesLimits, 27
    getCoordGeneSets, 28
    getDataPlotSamplesWithAnnotation, 29
    getMethodsInputObjectEsetVis, 31
    getTopElements, 32
    ggPlotEset, 33
    ggvisEsetPlot-class, 34
    ggvisPlotEset, 34
    plotEset, 35
    plotlyEsetPlot-class, 35
    plotlyPlotEset, 36
    plotTopElements, 36
    setFixElement, 37
    setManualScale, 38
    simpleCap, 39
    varToFm, 39

as.formula, *39*

characterORexpressionOrCall-class, 2

eSet, *3*, *11*, *16*, *22*, *29*
esetLda, 3, *29*
esetPlot, *7, 8*, *15*, *21*, *25*, *33–36*
esetPlot *(*esetPlot-class*)*, 8
esetPlot-class, 8
esetPlotInteractive *(*esetPlotInteractive-class*)*, 10
esetPlotInteractive-class, 10
esetPlotWrapper, *7*, 11, *25*, *29*
esetSpectralMap, 16, *29*
esetTsne, 22

formatManualScale, 26
formatOutput, 27

getAxesLimits, 27
getAxesLimits,esetPlot-method *(*getAxesLimits*)*, 27
getCoordGeneSets, 28
getDataPlotSamplesWithAnnotation, 29
getDataPlotSamplesWithAnnotation,esetPlot-method *(*getDataPlotSamplesWithAnnotation*)*, 29
getDataPlotSamplesWithAnnotation,ggvisEsetPlot-method *(*getDataPlotSamplesWithAnnotation*)*, 29
getDataPlotSamplesWithAnnotation,plotlyEsetPlot-method *(*getDataPlotSamplesWithAnnotation*)*, 29
getGeneSets, *29, 30*
getGeneSetsForPlot, *6*, *10*, *14*, *20*, 29
getMethodsInputObjectEsetVis, 31
getTopElements, *28*, 32
ggPlotEset, 33
ggplotEsetPlot *(*ggplotEsetPlot-class*)*, 33
ggplotEsetPlot-class, 33
ggplotly, *7*, *15*, *21*, *25*
ggvisEsetPlot *(*ggvisEsetPlot-class*)*, 34
ggvisEsetPlot-class, 34
ggvisPlotEset, 34

initialize,esetPlot-method *(*esetPlot-class*)*, 8

lda, *7*

mpm, *16, 17*, *19*, *21*

plot.mpm, *19*
plot_ly, *39*
plotEset, *27*, *29*, *35*, 35

plotEset,ggplotEsetPlot-method
(plotEset), 35
plotEset,ggvisEsetPlot-method
(plotEset), 35
plotEset,plotlyEsetPlot-method
(plotEset), 35
plotlyEsetPlot (plotlyEsetPlot-class),
35
plotlyEsetPlot-class, 35
plotlyPlotEset, 36
plotTopElements, 36

Rtsne, *22*, *24, 25*

setFixElement, 37
setManualScale, 38
simpleCap, 39
spectralMap, *21*

varToFm, 39