Package 'miaDash'

November 12, 2026

Version 1.4.0

Title Dashboard for the interactive analysis and exploration of microbiome data

Description miaDash provides a Graphical User Interface for the exploration of microbiome data. This way, no knowledge of programming is required to perform analyses. Datasets can be imported, manipulated, analysed and visualised with a user-friendly interface.

biocViews Microbiome, Software, Visualization, GUI, ShinyApps, DataImport

License Artistic-2.0

Encoding UTF-8

Depends R (>= 4.4.0), iSEE (>= 2.19.4), shiny

Imports ape, bluster, htmltools, iSEEtree (>= 1.1.4), mia, rintrojs, scater, scuttle, shinydashboard, shinyjs, shinyWidgets, S4Vectors, SingleCellExperiment, SummarizedExperiment, TreeSummarizedExperiment, utils, vegan

Suggests BiocStyle, knitr, philr, remotes, rmarkdown, testthat (>= 3.0.0)

URL https://github.com/microbiome/miaDash

BugReports https://github.com/microbiome/miaDash/issues

Roxygen list(markdown = TRUE)

RoxygenNote 7.3.3

VignetteBuilder knitr

Config/testthat/edition 3

git_url https://git.bioconductor.org/packages/miaDash

git_branch RELEASE_3_23

git_last_commit 1a2f1ad

git_last_commit_date 2026-04-28

Repository Bioconductor 3.23

Date/Publication 2026-11-11

Author Giulio Benedetti [aut, cre] (ORCID:
<https://orcid.org/0000-0002-8732-7692>),
Akewak Jeba [ctb] (ORCID: <https://orcid.org/0009-0007-1347-7552>),
Leo Lahti [aut] (ORCID: <https://orcid.org/0000-0001-5537-637X>)

Maintainer Giulio Benedetti <giulio.benedetti@utu.fi>

Contents

constants 2
create_observers 3
landing_page 4
miaDash 4
render_output 5
utils 5

Index **7**

`constants` *Constants*

Description

Constant values used throughout the miaDash app.

Usage

```
.miaDashDefaultPanels

.miaDashOtherPanels

.transformMethods

.qualityMetrics

.alphaMetrics

.betaMetrics

.betaMethods

.clustMethods

.DmmCriteria
```

Format

An object of class `character` of length 7.

An object of class `character` of length 9.

An object of class `character` of length 19.

An object of class `list` of length 4.

An object of class `character` of length 23.

An object of class `character` of length 4.

An object of class `character` of length 4.

An object of class `character` of length 4.

An object of class `character` of length 3.

Panel layout

`.miaDashDefaultPanels` List of panel names in the default layout of miaDash.

`.miaDashOtherPanels` List of panel names not in the default layout of miaDash.

`.transformMethods` List of transformations applicable to assays.

`.alphaMetrics` List of alpha diversity metrics.

`.betaMetrics` List of beta diversity metrics.

`.betaMethods` List of beta diversity methods.

`.qualityMetrics` List of metrics for quality control.

Author(s)

Giulio Benedetti

`create_observers` *Observers*

Description

`.create_observers` and `.create_launch_observers` define the server to import and build TreeSE objects and track the state of the Build and Launch buttons.

Usage

```
.create_import_observers(input, rObjects)

.create_manipulate_observers(input, rObjects)

.create_estimate_observers(input, rObjects)

.update_observers(input, session, rObjects)

.create_launch_observers(FUN, input, session, rObjects)
```

Arguments

input	The Shiny input object from the server function.
rObjects	A reactive list of values generated in the landing page.

Value

Observers are created in the server function in which this is called. A NULL value is invisibly returned.

---

landing_page *Landing page*

Description

.landing_page creates the landing page of miaDash, where TreeSE objects can be built and iSEE can be launched.

Usage

```
.landing_page(FUN, input, output, session)
```

Value

The UI is defined by the function. A NULL value is invisibly returned.

---

miaDash *miaDash*

Description

miaDash is a web app that provides an interface to build and explore TreeSummarizedExperiment (TreeSE) objects by means of iSEE.

Usage

```
miaDash()
```

Value

An iSEE app with a custom landing page to build TreeSE objects and explore mia datasets.

See Also

iSEE mia miaViz

Examples

```
app <- miaDash()

if (interactive()) {
  shiny::runApp(app)
}
```

`render_output` *Outputs*

Description

`.render_overview` and `.render_download` create the output of the UI, which consists of the overview of the TreeSE object and the download object, respectively.

Usage

```
.render_overview(output, rObjects)

.render_download(output, rObjects)
```

Arguments

`output`	The Shiny output object from the server function.

Value

Adds a rendered item to `output`. A `NULL` value is invisibly returned.

`utils` *miaDash utilities*

Description

Helper functions to support the app functionality.

Usage

```
.import_datasets(selection)

.update_tse(tse, fun, fun.args = list())

.print_message(..., title = "Invalid input:")

.set_optarg(item, loader = NULL, alternative = NULL, ...)
```

```
.check_formula(form, tse)

.importBIOM(file, col.data = NULL, tree.file = NULL, ...)

.rownames2taxa(x)
```

Arguments

selection	Numeric vector. A list of indices for the mia datasets to return.
tse	a TreeSummarizedExperiment object.
fun	Function scalar. Function to apply to tse.
fun.args	Named list. A list of arguments to pass to fun.
...	Either a series of strings to form the message returned by .print_message or named arguments for loader.
title	Character scalar. The title of the error message to print. (Default: "Invalid input:")
item	Character scalar. The file path from which the object should be loaded.
loader	Function scalar. The function to load item. (Default: NULL)
alternative	an alternative output to return when at least one item and loader are not defined. (Default: NULL)
form	Character scalar The formula to be checked.

Value

- .import_datasets: returns the list of available mia datasets.
- .update_tse: returns a TreeSE object after applying fun with arguments fun.args. Eventual messages and errors are also printed.
- .print_message: returns a modalDialog with the error message specified with ... and titled title.
- .set_optarg: returns an optional element for a TreeSE constructor. The output is either an object located at the file path item and loaded with loader or alternative.
- .check_formula: returns TRUE or FALSE depending whether or not all variables included in form are present in se colData.

Index

∗ **datasets**
    constants, 2
∗ **internal**
    constants, 2
    create_observers, 3
    landing_page, 4
    render_output, 5
    utils, 5
.DmmCriteria *(*constants*)*, 2
.alphaMetrics *(*constants*)*, 2
.betaMethods *(*constants*)*, 2
.betaMetrics *(*constants*)*, 2
.check_formula *(*utils*)*, 5
.clustMethods *(*constants*)*, 2
.create_estimate_observers
        *(*create_observers*)*, 3
.create_import_observers
        *(*create_observers*)*, 3
.create_launch_observers
        *(*create_observers*)*, 3
.create_manipulate_observers
        *(*create_observers*)*, 3
.importBIOM *(*utils*)*, 5
.import_datasets *(*utils*)*, 5
.landing_page *(*landing_page*)*, 4
.miaDashDefaultPanels *(*constants*)*, 2
.miaDashOtherPanels *(*constants*)*, 2
.print_message *(*utils*)*, 5
.qualityMetrics *(*constants*)*, 2
.render_download *(*render_output*)*, 5
.render_overview *(*render_output*)*, 5
.rownames2taxa *(*utils*)*, 5
.set_optarg *(*utils*)*, 5
.transformMethods *(*constants*)*, 2
.update_observers *(*create_observers*)*, 3
.update_tse *(*utils*)*, 5

constants, 2
create_observers, 3

iSEE, *4*

landing_page, 4

mia, *4*
mia datasets, *4*
miaDash, 4
miaViz, *4*

render_output, 5

TreeSummarizedExperiment, *4*, *6*

utils, 5