# Package 'mnem'

November 12, 2026

**Type** Package

**Title** Mixture Nested Effects Models

**Version** 1.28.0

**Description** Mixture Nested Effects Models (mnem) is an extension of Nested Effects Models and allows for the analysis of single cell perturbation data provided by methods like Perturb-Seq (Dixit et al., 2016) or Crop-Seq (Datlinger et al., 2017). In those experiments each of many cells is perturbed by a knock-down of a specific gene, i.e. several cells are perturbed by a knock-down of gene A, several by a knock-down of gene B, ... and so forth. The observed read-out has to be multi-trait and in the case of the Perturb-/Crop-Seq gene are expression profiles for each cell. mnem uses a mixture model to simultaneously cluster the cell population into k clusters and and infer k networks causally linking the perturbed genes for each cluster. The mixture components are inferred via an expectation maximization algorithm.

**Depends** R (>= 4.1)

**License** GPL-3

**Encoding** UTF-8

**LazyData** true

**biocViews** Pathways, SystemsBiology, NetworkInference, Network, RNASeq, PooledScreens, SingleCell, CRISPR, ATACSeq, DNASeq, GeneExpression

**RoxygenNote** 7.3.2

**Imports** cluster, graph, Rgraphviz, flexclust, lattice, naturalsort, snowfall, stats4, tsne, methods, graphics, stats, utils, Linnorm, data.table, Rcpp, RcppEigen, matrixStats, grDevices, e1071, ggplot2, wesanderson

**LinkingTo** Rcpp, RcppEigen

**VignetteBuilder** knitr

**Suggests** knitr, devtools, rmarkdown, BiocGenerics, RUnit, epiNEM, BiocStyle

**NeedsCompilation** yes

**BugReports** https://github.com/cbg-ethz/mnem/issues

**URL** https://github.com/cbg-ethz/mnem/

**git_url** https://git.bioconductor.org/packages/mnem

**git_branch** RELEASE_3_23

**git_last_commit** bfb80be

**git_last_commit_date** 2026-04-28

**Repository** Bioconductor 3.23

**Date/Publication** 2026-11-11

**Author** Martin Pirkl [aut, cre]

**Maintainer** Martin Pirkl <martinpirkl@yahoo.de>

# Contents

app . . . 3
bootstrap . . . 3
clustNEM . . . 4
createApp . . . 5
fitacc . . . 7
fuzzyindex . . . 8
getAffinity . . . 9
getIC . . . 10
hamSim . . . 11
mnem . . . 12
mnemh . . . 15
mnemk . . . 16
moreboxplot . . . 17
nem . . . 19
plot.bootmnem . . . 21
plot.mnem . . . 21
plot.mnem_mcmc . . . 23
plot.mnem_sim . . . 24
plotConvergence . . . 25
plotConvergence.mnem . . . 25
plotDnf . . . 26
scoreAdj . . . 29
simData . . . 31
transitive.closure . . . 33
transitive.reduction . . . 33

**Index** **35**

## app *Processed scRNAseq from pooled CRISPR screens*

### Description

Example data: mnem results for the Dixit et al., 2016 and Datlinger et al., pooled CRISPR screens. For details see the vignette or function createApp().

### Usage

```
app
```

### References

Datlinger, P., Rendeiro, A., Schmidl, C., Krausgruber, T., Traxler, P., Klughammer, J., Schuster, L. C., Kuchler, A., Alpar, D., and Bock, C. (2017). Pooled crispr screening with single-cell transcriptome readout. Nature Methods, 14, 297-301.

Dixit, A., Parnas, O., Li, B., Chen, J., Fulco, C. P., Jerby-Arnon, L., Marjanovic, N. D., Dionne, D., Burks, T., Raychowdhury, R., Adamson, B., Norman, T. M., Lander, E. S., Weissman, J. S., Friedman, N., and Regev, A. (2016). Perturb-seq: Dissecting molecular circuits with scalable single-cell rna profiling of pooled genetic screens. Cell, 167(7), 1853-1866.e17.

### Examples

```
data(app)
```

## bootstrap *Bootstrap.*

### Description

Run bootstrap simulations on the components (phi) of an object of class mnem.

### Usage

```
bootstrap(x, size = 1000, p = 1, logtype = 2, complete = FALSE, ...)
```

### Arguments

| | |
|---|---|
| x | mnem object |
| size | size of the booststrap simulations |
| p | percentage of samples (e.g. for 100 E-genes p=0.5 means sampling 50) |
| logtype | logarithm type of the data (e.g. 2 for log2 data or exp(1) for natural) |
| complete | if TRUE, complete data log likelihood is considered (for very large data sets, e.g. 1000 cells and 1000 E-genes) |
| ... | additional parameters for the nem function |

## Value

returns bootstrap support for each edge in each component (phi); list of adjacency matrices

## Author(s)

Martin Pirkl

## Examples

```
sim <- simData(Sgenes = 3, Egenes = 2, Nems = 2, mw = c(0.4,0.6))
data <- (sim$data - 0.5)/0.5
data <- data + rnorm(length(data), 0, 1)
result <- mnem(data, k = 2, starts = 1)
boot <- bootstrap(result, size = 2)
```

---

# clustNEM *Cluster NEM.*

---

## Description

This function clusters the data and performs standard nem on each cluster.

## Usage

```
clustNEM(
  data,
  k = 2:10,
  cluster = NULL,
  starts = 1,
  logtype = 2,
  nem = TRUE,
  getprobspars = list(),
  getaffinitypars = list(),
  Rho = NULL,
  ...
)
```

## Arguments

| | |
|---|---|
| data | data of log ratios with cells in columns and features in rows |
| k | number of clusters to check |
| cluster | given clustering has to correspond to the columns of data |
| starts | number of random starts for the kmeans algorithm |
| logtype | logarithm type of the data |
| nem | if FALSE only clusters the data |
| getprobspars | list of parameters for the getProbs function |

getaffinitypars
: list of parameters for the getAffinity function

Rho
: perturbation matrix with dimensions nxl with n S-genes and l samples; either as probabilities with the sum of probabilities for a sample less or equal to 1 or discrete with 1s and 0s

...
: additional arguments for standard nem function

## Value

family of nems; the first k list entries hold full information of the standard nem search

comp
: list of all adjacency matrices phi

mw
: vector of mixture weights

probs
: fake cell probabilities (see mw: mixture weights)

## Author(s)

Martin Pirkl

## Examples

```
sim <- simData(Sgenes = 3, Egenes = 2, Nems = 2, mw = c(0.4,0.6))
data <- (sim$data - 0.5)/0.5
data <- data + rnorm(length(data), 0, 1)
resulst <- clustNEM(data, k = 2:3)
```

---

# createApp *Creating app data.*

---

## Description

This function is for the reproduction of the application results in the vignette and publication. See the publication Pirkl & Beerenwinkel (2018) on how to download the data files: GSE92872_CROP-seq_Jurkat_TCR.digital_expression.csv k562_both_filt.txt GSM2396861_k562_ccycle_cbc_gbc_dict.csv GSM2396858_k562_tfs_7_cbc_gbc_dict.csv

## Usage

```
createApp(
  sets = seq_len(3),
  m = NULL,
  n = NULL,
  o = NULL,
  maxk = 5,
  parallel = NULL,
  path = "",
  types = c("data", "lods", "mnem"),
```

```
  allcrop = FALSE,
  multi = FALSE,
  file = NULL,
  ...
)
```

## Arguments

| | |
|---|---|
| sets | numeric vector with the data sets: 1 (CROPseq), 2, 3 (both PERTURBseq); default is all three |
| m | number of Sgenes (for testing) |
| n | number of most variable E-genes (for testing) |
| o | number of samples per S-gene (for testing) |
| maxk | maximum number of component in mnem inference (default: 5) |
| parallel | number of threads for parallelisation |
| path | path to the data files path/file.csv: "path/" |
| types | types of data/analysis; "data" creates the gene expression matrix, "lods" includes the log odds, "mnem" additionally performes the mixture nem analysis; default c("data", "lods", "mnem") |
| allcrop | if TRUE, does not restrict and uses the full CROPseq dataset |
| multi | if TRUE, includes cells with more than one perturbed gene |
| file | path and filename of the rda file with the raw data from the command "data <- createApp(..., types = "data")" |
| ... | additional parameters for the mixture nem function |

## Value

app data object

## Author(s)

Martin Pirkl

## Examples

```
## recreate the app data object (takes very long, i.e. days)
## Not run:
createApp()

## End(Not run)
data(app)
```

`fitacc` *Simulation accuracy.*

## Description

Computes the accuracy of the fit between simulated and inferred mixture.

## Usage

```
fitacc(x, y, strict = FALSE, unique = TRUE, type = "ham")
```

## Arguments

| | |
|---|---|
| `x` | mnem object |
| `y` | simulation object or another mnem object |
| `strict` | if TRUE, accounts for over/underfitting, i.e. the number of components |
| `unique` | if TRUE, phis of x and y are made unique each (FALSE if strict is TRUE) |
| `type` | type of accuracy. "ham" for hamming, "sens" for sensitivity and "spec for Specificity" |

## Value

plot of EM convergence

## Author(s)

Martin Pirkl

## Examples

```
sim <- simData(Sgenes = 3, Egenes = 2, Nems = 2, mw = c(0.4,0.6))
data <- (sim$data - 0.5)/0.5
data <- data + rnorm(length(data), 0, 1)
result <- mnem(data, k = 2, starts = 1)
fitacc(result, sim)
fitacc(result, sim, type = "sens")
fitacc(result, sim, type = "spec")
fitacc(result, sim, strict = TRUE, type = "sens")
fitacc(result, sim, strict = TRUE, type = "spec")
```

`fuzzyindex` *Calculate fuzzy ground truth.*

## Description

Calculates responsibilities and mixture weights based on the ground truth and noisy data.

## Usage

```
fuzzyindex(x, data, logtype = 2, complete = FALSE, marginal = FALSE, ...)
```

## Arguments

| | |
|---|---|
| `x` | mnem_sim object |
| `data` | noisy data matrix |
| `logtype` | logarithm type of the data |
| `complete` | if TRUE, complete data log likelihood is considered (for very large data sets, e.g. 1000 cells and 1000 E-genes) |
| `marginal` | logical to compute the marginal likelihood (TRUE) |
| `...` | additional parameters for the function getAffinity |

## Value

list with cell log odds mixture weights and log likelihood

## Author(s)

Martin Pirkl

## Examples

```
sim <- simData(Sgenes = 3, Egenes = 2, Nems = 2, mw = c(0.4,0.6))
data <- sim$data
data[which(sim$data == 1)] <- rnorm(sum(sim$data == 1), 1, 1)
data[which(sim$data == 0)] <- rnorm(sum(sim$data == 0), -1, 1)
fuzzy <- fuzzyindex(sim, data)
```

getAffinity *Calculate responsibilities.*

## Description

This function calculates the responsibilities of each component for all cells from the expected log distribution of the hidden data.

## Usage

```
getAffinity(
  x,
  affinity = 0,
  norm = TRUE,
  logtype = 2,
  mw = NULL,
  data = matrix(0, 2, ncol(x)),
  complete = FALSE
)
```

## Arguments

| | |
|---|---|
| x | log odds for l cells and k components as a kxl matrix |
| affinity | 0 for standard soft clustering, 1 for hard clustering during inference (not recommended) |
| norm | if TRUE normalises to probabilities (recommended) |
| logtype | logarithm type of the data (e.g. 2 for log2 data or exp(1) for natural) |
| mw | mixture weights of the components |
| data | data in log odds |
| complete | if TRUE, complete data log likelihood is considered (for very large data sets, e.g. 1000 cells and 1000 E-genes) |

## Value

responsibilities as a kxl matrix (k components, l cells)

## Author(s)

Martin Pirkl

## Examples

```
sim <- simData(Sgenes = 3, Egenes = 2, Nems = 2, mw = c(0.4,0.6))
data <- (sim$data - 0.5)/0.5
data <- data + rnorm(length(data), 0, 1)
result <- mnem(data, k = 2, starts = 1)
resp <- getAffinity(result$probs, mw = result$mw, data = data)
```

getIC *Calculate negative penalized log likelihood.*

## Description

This function calculates a negative penalized log likelihood given a object of class mnem. This penalized likelihood is based on the normal likelihood and penalizes complexity of the mixture components (i.e. the networks).

## Usage

```
getIC(
  x,
  man = FALSE,
  degree = 4,
  logtype = 2,
  pen = 2,
  useF = FALSE,
  Fnorm = FALSE
)
```

## Arguments

| | |
|---|---|
| x | mnem object |
| man | logical. manual data penalty, e.g. man=TRUE and pen=2 for an approximation of the Akaike Information Criterion |
| degree | different degree of penalty for complexity: positive entries of transitively reduced phis or phi^r (degree=0), phi^r and mixture components minus one k-1 (1), phi^r, k-1 and positive entries of thetas (2), positive entries of transitively closed phis or phi^t, k-1 (3), phi^t, theta, k-1 (4, default), all entries of phis, thetas and k-1 (5) |
| logtype | logarithm type of the data (e.g. 2 for log2 data or exp(1) for natural) |
| pen | penalty weight for the data (e.g. pen=2 for approximate Akaike Information Criterion) |
| useF | use F (see publication) as complexity instead of phi and theta |
| Fnorm | normalize complexity of F, i.e. if two components have the same entry in F, it is only counted once |

## Value

penalized log likelihood

## Author(s)

Martin Pirkl

## Examples

```
sim <- simData(Sgenes = 3, Egenes = 2, Nems = 2, mw = c(0.4,0.6))
data <- (sim$data - 0.5)/0.5
data <- data + rnorm(length(data), 0, 1)
pen <- numeric(3)
result <- list()
for (k in seq_len(2)) {
    result[[k]] <- mnem(data, k = k, starts = 1)
    pen[k] <- getIC(result[[k]])
}
print(pen)
```

---

`hamSim` *Accuracy for two phis.*

---

## Description

This function uses the hamming distance to calculate an accuracy for two networks (phi).

## Usage

```
hamSim(a, b, diag = 1, symmetric = TRUE)
```

## Arguments

| | |
|---|---|
| `a` | adjacency matrix (phi) |
| `b` | adjacency matrix (phi) |
| `diag` | if 1 includes diagonal in distance, if 0 not |
| `symmetric` | comparing a to b is asymmetrical, if TRUE includes comparison b to a |

## Value

normalized hamming accuracy for a and b

## Author(s)

Martin Pirkl

## Examples

```
sim <- simData(Sgenes = 3, Egenes = 2, Nems = 2, mw = c(0.4,0.6))
similarity <- hamSim(sim$Nem[[1]], sim$Nem[[2]])
```

mnem *Mixture NEMs - main function.*

## Description

This function simultaneously learns a mixture of causal networks and clusters of a cell population from single cell perturbation data (e.g. log odds of fold change) with a multi-trait readout. E.g. Pooled CRISPR scRNA-Seq data (Perturb-Seq. Dixit et al., 2016, Crop-Seq. Datlinger et al., 2017).

## Usage

```
mnem(
  D,
  inference = "em",
  search = "greedy",
  phi = NULL,
  theta = NULL,
  mw = NULL,
  method = "llr",
  marginal = FALSE,
  parallel = NULL,
  reduce = FALSE,
  runs = 1,
  starts = 3,
  type = "networks",
  complete = FALSE,
  p = NULL,
  k = NULL,
  kmax = 10,
  verbose = FALSE,
  max_iter = 100,
  parallel2 = NULL,
  converged = -Inf,
  redSpace = NULL,
  affinity = 0,
  evolution = FALSE,
  lambda = 1,
  subtopoX = NULL,
  ratio = TRUE,
  logtype = 2,
  domean = TRUE,
  modulesize = 5,
  compress = FALSE,
  increase = TRUE,
  fpfn = c(0.1, 0.1),
  Rho = NULL,
```

```
  ksel = c("kmeans", "silhouette", "cor"),
  nullcomp = FALSE,
  tree = FALSE,
  burnin = 10,
  hastings = TRUE,
  nodeswitch = TRUE,
  postgaps = 10,
  penalized = FALSE,
  accept_range = 1,
  ...
)
```

## Arguments

| | |
|---|---|
| D | data with cells indexing the columns and features (E-genes) indexing the rows |
| inference | inference method "em" for expectation maximization or "mcmc" for markov chain monte carlo sampling |
| search | search method for single network inference "greedy", "exhaustive" or "modules" (also possible: "small", which is greedy with only one edge change per M-step to make for a smooth convergence) |
| phi | a list of n lists of k networks for n starts of the EM and k components |
| theta | a list of n lists of k attachment vector for the E-genes for n starts of the EM and k components |
| mw | mixture weights; if NULL estimated or uniform |
| method | "llr" for log ratios or foldchanges as input (see ratio) |
| marginal | logical to compute the marginal likelihood (TRUE) |
| parallel | number of threads for parallelization of the number of em runs |
| reduce | logical - reduce search space for exhaustive search to unique networks |
| runs | number of runs for greedy search |
| starts | number of starts for the em or mcmc |
| type | initialize with responsibilities either by "random", "cluster" (each S-gene is clustered and the different S-gene clustered differently combined for several starts), "cluster2" (clustNEM is used to infer reasonable phis, which are then used as a start for one EM run), "cluster3" (global clustering as a start), or "networks" (initialize with random phis), inference='mcmc' only supports 'networks' and 'empty' for unconncected networks phi |
| complete | if TRUE, optimizes the expected complete log likelihood of the model, otherwise the log likelihood of the observed data |
| p | initial probabilities as a k (components) times l (cells) matrix |
| k | number of components |
| kmax | maximum number of components when k=NULL is inferred |
| verbose | verbose output |
| max_iter | maximum iterations (moves for inference='mcmc'. adjust parameter burnin) |

| | |
|---|---|
| parallel2 | if parallel=NULL, number of threads for single component optimization |
| converged | absolute distance for convergence between new and old log likelihood; if set to -Inf, the EM stops if neither the phis nor thetas were changed in the most recent iteration |
| redSpace | space for "exhaustive" search |
| affinity | 0 is default for soft clustering, 1 is for hard clustering |
| evolution | logical. If TRUE components are penelized for being different from each other. |
| lambda | smoothness value for the prior put on the components, if evolution set to TRUE |
| subtopoX | hard prior on theta as a vector with entry i equal to j, if E-gene i is attached to S-gene j |
| ratio | logical, if true data is log ratios, if false foldchanges |
| logtype | logarithm type of the data (e.g. 2 for log2 data or exp(1) for natural) |
| domean | average the data, when calculating a single NEM (speed improvment) |
| modulesize | max number of S-genes per module in module search |
| compress | compress networks after search (warning: penelized likelihood not interpretable) |
| increase | if set to FALSE, the algorithm will not stop if the likelihood decreases |
| fpfn | numeric vector of length two with false positive and false negative rates for discrete data |
| Rho | perturbation matrix with dimensions nxl with n S-genes and l samples; either as probabilities with the sum of probabilities for a sample less or equal to 1 or discrete with 1s and 0s |
| ksel | character vector of methods for the inference of k; can combine as the first two vlues "hc" (hierarchical clustering) or "kmeans" with "silhouette", "BIC" or "AIC"; the third value is either "cor" for correlation distance or any method accepted by the function 'dist' |
| nullcomp | if TRUE, adds a null component (k+1) |
| tree | if TRUE, restrict inference on trees (MCMC not included) |
| burnin | number of iterations to be discarded prior to analyzing the posterior distribution of the mcmc |
| hastings | if set to TRUE, the Hastings ratio is calculated |
| nodeswitch | if set to TRUE, node switching is allowed as a move, additional to the edge moves |
| postgaps | can be set to numeric. Determines after how many iterations the next Phi mixture is added to the Phi edge Frequency tracker in the mcmc |
| penalized | if set to TRUE, the penalized likelihood will be used for the mcmc. Per default this is FALSE, since no component learning is involved and sparcity is hence not enforced |
| accept_range | the random probability the acceptance probability is compared to (default: 1) |
| ... | arguments to function nem |

## Value

object of class mnem

| | |
|---|---|
| comp | list of the component with each component being a list of the causal network phi and the E-gene attachment theta |
| data | input data matrix |
| limits | list of results for all indpendent searches |
| ll | log likelihood of the best model |
| lls | log likelihood ascent of the best model search |
| mw | vector with mixture weights |
| probs | kxl matrix containing the cell log likelihoods of the model |

## Author(s)

Martin Pirkl

## Examples

```
sim <- simData(Sgenes = 3, Egenes = 2, Nems = 2, mw = c(0.4,0.6))
data <- (sim$data - 0.5)/0.5
data <- data + rnorm(length(data), 0, 1)
result <- mnem(data, k = 2, starts = 1)
```

---

# mnemh *Hierarchical mixture.*

---

## Description

This function does a hierarchical mixture. That means it uses the approximate BIC to check, if there are more than one component. It recursively splits the data if there is evidence for k > 1 components.

## Usage

```
mnemh(data, k = 2, logtype = 2, getprobspars = list(), ...)
```

## Arguments

| | |
|---|---|
| data | data matrix either binary or log odds |
| k | number of maximal components for each hierarchy leaf |
| logtype | log type of the data |
| getprobspars | list of parameters for the getProbs function |
| ... | additional parameters for the mnem function |

## Value

object of class mnem

### Author(s)

Martin Pirkl

### Examples

```
sim <- simData(Sgenes = 3, Egenes = 2, Nems = 2, mw = c(0.4,0.6))
data <- (sim$data - 0.5)/0.5
data <- data + rnorm(length(data), 0, 1)
result <- mnemh(data, starts = 1, k = 1)
```

---

## mnemk *Learn the number of components K and optimize the mixture.*

---

### Description

High level function for learning the number of components k, if unknown.

### Usage

```
mnemk(
  D,
  ks = seq_len(5),
  man = FALSE,
  degree = 4,
  logtype = 2,
  pen = 2,
  useF = FALSE,
  Fnorm = FALSE,
  ...
)
```

### Arguments

| | |
|---|---|
| D | data with cells indexing the columns and features (E-genes) indexing the rows |
| ks | vector of number of components k to test |
| man | logical. manual data penalty, e.g. man=TRUE and pen=2 for an approximation of the Akaike Information Criterion |
| degree | different degree of penalty for complexity: positive entries of transitively reduced phis or phi^r (degree=0), phi^r and mixture components minus one k-1 (1), phi^r, k-1 and positive entries of thetas (2), positive entries of transitively closed phis or phi^t, k-1 (3), phi^t, theta, k-1 (4, default), all entries of phis, thetas and k-1 (5) |
| logtype | logarithm type of the data (e.g. 2 for log2 data or exp(1) for natural) |
| pen | penalty weight for the data (e.g. pen=2 for approximate Akaike Information Criterion) |

| | |
|---|---|
| useF | use F (see publication) as complexity instead of phi and theta |
| Fnorm | normalize complexity of F, i.e. if two components have the same entry in F, it is only counted once |
| ... | additional parameters for the mnem main function |

## Value

list containing the result of the best k as an mnem object and the raw and penalized log likelihoods

## Author(s)

Martin Pirkl

## Examples

```
sim <- simData(Sgenes = 3, Egenes = 2, Nems = 2, mw = c(0.4,0.6))
data <- (sim$data - 0.5)/0.5
data <- data + rnorm(length(data), 0, 1)
result <- mnemk(data, ks = seq_len(2), starts = 1)
```

---

# moreboxplot *Boxplot with scatter and density options*

---

## Description

Plots a boxplots plus x-axis randomised scatter and mirrored densities to visualise a distribution.

## Usage

```
moreboxplot(
  x,
  box = TRUE,
  dens = TRUE,
  scatter = "no",
  polygon = TRUE,
  sd = 0.1,
  dcol = NULL,
  scol = NULL,
  dlty = 1,
  dlwd = 1,
  spch = 1,
  gcol = rgb(0, 0, 0, 0.5),
  glty = 2,
  glen = 2001,
  gmin = -100,
  gmax = 100,
  sig = NULL,
```

```
  sigfun = wilcox.test,
  sigpars = list(col = 1, lwd = 1, cex = 1, add = "auto"),
  ...
)
```

## Arguments

| | |
|---|---|
| x | list, matrix or data.frame |
| box | if TRUE, draws boxes |
| dens | if TRUE, draws densities |
| scatter | if set to "random", draws x-axis randomised scatter points |
| polygon | if TRUE, filles the densities |
| sd | standard deviation of the scatter |
| dcol | color of the densities |
| scol | color of the scatter points |
| dlty | line type of the densities |
| dlwd | line width of the densities |
| spch | type of scatter points |
| gcol | color of the grid |
| glty | line type of the grid |
| glen | length of the grid |
| gmin | minimal point of the grid |
| gmax | maximal point of the grid |
| sig | matrix of n rows and 2 columns, each row is for a pair of box/violin plots to compare; uses standard wilcox.test |
| sigfun | function of the form f(x,y) with x and y as numerical vectors and returns a list with one entry "p.value", which is a scalar between 0 and 1 |
| sigpars | list of paramters for drawing significance levels; standard drawing parameters except for "add", which is a number or "auto" stating how far above or below (negative number) of the largest entry the line is drawn |
| ... | optional parameters for boxplot or plot |

## Value

transitively closed matrix or graphNEL

## Author(s)

Martin Pirkl

## Examples

```
D <- matrix(rnorm(100*3), 100, 3)
moreboxplot(D)
```

nem *Implementation of the original NEM*

## Description

Infers a signalling pathway from perturbation experiments.

## Usage

```
nem(
  D,
  search = "greedy",
  start = NULL,
  method = "llr",
  marginal = FALSE,
  parallel = NULL,
  reduce = FALSE,
  weights = NULL,
  runs = 1,
  verbose = FALSE,
  redSpace = NULL,
  trans.close = TRUE,
  subtopo = NULL,
  prior = NULL,
  ratio = TRUE,
  domean = TRUE,
  modulesize = 5,
  fpfn = c(0.1, 0.1),
  Rho = NULL,
  logtype = 2,
  modified = FALSE,
  tree = FALSE,
  learnRates = FALSE,
  stepSize = 0.01,
  ...
)
```

## Arguments

| | |
|---|---|
| D | data matrix with observed genes as rows and knock-down experiments as columns |
| search | either "greedy", "modules" or "exhaustive" (not recommended for more than five S-genes) |
| start | either NULL ("null") or a specific network to start the greedy |
| method | "llr" for log odds or p-values densities or "disc" for binary data |
| marginal | logical to compute the marginal likelihood (TRUE) |

| | |
|---|---|
| parallel | NULL for no parallel optimization or an integer for the number of threads |
| reduce | reduce search space (TRUE) for exhaustive search |
| weights | a numeric vector of weights for the columns of D |
| runs | the number of runs for the greedy search |
| verbose | for verbose output (TRUE) |
| redSpace | reduced search space for exhaustive search; see result of exhaustive search with reduce = TRUE |
| trans.close | if TRUE uses the transitive closure of adj |
| subtopo | optional matrix with the subtopology theta as adjacency matrix |
| prior | a prior network matrix for adj |
| ratio | if FALSE uses alternative distance for the model score |
| domean | if TRUE summarizes duplicate columns |
| modulesize | the max number of S-genes included in one module for search = "modules" |
| fpfn | numeric vector of length two with false positive and false negative rates |
| Rho | optional perturbation matrix |
| logtype | log base of the log odds |
| modified | if TRUE, assumes a preprocessed data matrix |
| tree | if TRUE forces tree; does not allow converging edges |
| learnRates | if TRUE learns rates for false positives/negatives |
| stepSize | numerical step size for learning rates |
| ... | optional parameters for future search methods |

## Value

transitively closed matrix or graphNEL

## Author(s)

Martin Pirkl

## Examples

```
D <- matrix(rnorm(100*3), 100, 3)
colnames(D) <- 1:3
rownames(D) <- 1:100
adj <- diag(3)
colnames(adj) <- rownames(adj) <- 1:3
scoreAdj(D, adj)
```

## plot.bootmnem *Plot bootstrap mnem result.*

### Description

Plot bootstrap mnem result.

### Usage

```
## S3 method for class 'bootmnem'
plot(x, reduce = TRUE, ...)
```

### Arguments

| | |
|---|---|
| x | bootmnem object |
| reduce | if TRUE transitively reduces the graphs |
| ... | additional parameters for the plotting function plotDNF |

### Value

visualization of bootstrap mnem result with Rgraphviz

### Author(s)

Martin Pirkl

### Examples

```
sim <- simData(Sgenes = 3, Egenes = 2, Nems = 2, mw = c(0.4,0.6))
data <- (sim$data - 0.5)/0.5
data <- data + rnorm(length(data), 0, 1)
result <- mnem(data, k = 2, starts = 1)
boot <- bootstrap(result, size = 2)
plot(boot)
```

## plot.mnem *Plot mnem result.*

### Description

Plot mnem result.

## Usage

```
## S3 method for class 'mnem'
plot(
  x,
  oma = c(3, 1, 1, 3),
  main = "M&NEM",
  anno = TRUE,
  cexAnno = 1,
  scale = NULL,
  global = TRUE,
  egenes = TRUE,
  sep = FALSE,
  tsne = FALSE,
  affinity = 0,
  logtype = 2,
  cells = TRUE,
  pch = ".",
  legend = FALSE,
  showdata = FALSE,
  bestCell = TRUE,
  showprobs = FALSE,
  shownull = TRUE,
  ratio = TRUE,
  method = "llr",
  marginal = FALSE,
  showweights = TRUE,
  ...
)
```

## Arguments

| | |
|---|---|
| x | mnem object |
| oma | outer margin |
| main | main text |
| anno | annotate cells by their perturbed gene |
| cexAnno | text size of the cell annotations |
| scale | scale cells to show relative and not absolute distances |
| global | if TRUE clusters all cells, if FALSE clusters cells within a component |
| egenes | show egene attachments, i.e. number of E-genes assigned to each S-gene |
| sep | seperate clusters and not put them on top of each other for better visualization |
| tsne | if TRUE use tsne instead of pca |
| affinity | use hard clustering if TRUE |
| logtype | logarithm type of the data (e.g. 2 for log2 data or exp(1) for natural) |
| cells | show cell attachments, .i.e how many cells are assigned to each S-gene |

| | |
|---|---|
| pch | cell symbol |
| legend | show legend |
| showdata | show data if TRUE |
| bestCell | show probability of best fitting cell for each S-gene |
| showprobs | if TRUE, shows responsibilities for all cells and components |
| shownull | if TRUE, shows the null node |
| ratio | use log ratios (TRUE) or foldchanges (FALSE) |
| method | "llr" for ratios |
| marginal | logical to compute the marginal likelihood (TRUE) |
| showweights | if TRUE, shows mixture weights for all components |
| ... | additional parameters |

## Value

visualization of mnem result with Rgraphviz

## Author(s)

Martin Pirkl

## Examples

```
sim <- simData(Sgenes = 3, Egenes = 2, Nems = 2, mw = c(0.4,0.6))
data <- (sim$data - 0.5)/0.5
data <- data + rnorm(length(data), 0, 1)
result <- mnem(data, k = 2, starts = 1)
plot(result)
```

---

# plot.mnem_mcmc *Plot mnem_mcmc result.*

---

## Description

Plot mnem_mcmc result.

## Usage

```
## S3 method for class 'mnem_mcmc'
plot(x, starts = NULL, burnin = 0, ...)
```

## Arguments

| | |
|---|---|
| x | mnem_mcmc object |
| starts | restarts of mcmc as used in mnem function |
| burnin | number of iteration to start from |
| ... | parameters for function ggplot2 |

## Value

visualization of mcmc result with Rgraphviz

## Author(s)

Viktoria Brunner

## Examples

```
sim <- simData(Sgenes = 3, Egenes = 2, Nems = 2, mw = c(0.4,0.6))
data <- (sim$data - 0.5)/0.5
data <- data + rnorm(length(data), 0, 1)
result <- mnem(data, k = 2, starts = 1)
plot(result)
```

---

# plot.mnem_sim *Plot simulated mixture.*

---

## Description

Plot simulated mixture.

## Usage

```
## S3 method for class 'mnem_sim'
plot(x, data = NULL, logtype = 2, fuzzypars = list(), ...)
```

## Arguments

| | |
|---|---|
| x | mnem_sim object |
| data | noisy data matrix (optional) |
| logtype | logarithm type of the data |
| fuzzypars | list of parameters for the function fuzzyindex |
| ... | additional parameters for the plotting function plotDNF |

## Value

visualization of simulated mixture with Rgraphviz

## Author(s)

Martin Pirkl

## Examples

```
sim <- simData(Sgenes = 3, Egenes = 2, Nems = 2, mw = c(0.4,0.6))
plot(sim)
```

## plotConvergence *Plot convergence of EM*

### Description

Generic function plotting convergence diagnostics for different methods.

### Usage

```
plotConvergence(x, ...)
```

### Arguments

| | |
|---|---|
| x | object with convergence statistics |
| ... | additional parameters for the specific object type |

### Value

plot of EM convergence

### Author(s)

Martin Pirkl

### Examples

```
sim <- simData(Sgenes = 3, Egenes = 2, Nems = 2, mw = c(0.4,0.6))
data <- (sim$data - 0.5)/0.5
data <- data + rnorm(length(data), 0, 1)
result <- mnem(data, k = 2, starts = 1)
par(mfrow=c(2,2))
plotConvergence(result)
```

## plotConvergence.mnem *Plot convergence of EM*

### Description

This function plots the convergence of the different EM iterations (four figures, e.g. par(mfrow=(2,2))).

### Usage

```
## S3 method for class 'mnem'
plotConvergence(x, col = NULL, type = "b", convergence = 0.1, ...)
```

### Arguments

| | |
|---|---|
| x | mnem object |
| col | vector of colors for the iterations |
| type | see ?plot.default |
| convergence | difference of when two log likelihoods are considered equal; see also convergence for the function mnem() |
| ... | additional parameters for the plots/lines functions |

### Value

plot of EM convergence

### Author(s)

Martin Pirkl

### Examples

```
sim <- simData(Sgenes = 3, Egenes = 2, Nems = 2, mw = c(0.4,0.6))
data <- (sim$data - 0.5)/0.5
data <- data + rnorm(length(data), 0, 1)
result <- mnem(data, k = 2, starts = 1)
par(mfrow=c(2,2))
plotConvergence(result)
```

---

## plotDnf *Plot disjunctive normal form.*

---

### Description

This function visualizes a graph encoded as a disjunctive nromal form. See the graphviz documentation for possible input arguments, like edgehead/tail: https://graphviz.org/docs/attr-types/arrowType/

### Usage

```
plotDnf(
  dnf = NULL,
  freq = NULL,
  stimuli = c(),
  signals = c(),
  inhibitors = c(),
  connected = TRUE,
  CNOlist = NULL,
  cex = NULL,
  fontsize = NULL,
  labelsize = NULL,
```

```
  type = 2,
  lwd = 1,
  edgelwd = 1,
  legend = 0,
  x = 0,
  y = 0,
  xjust = 0,
  yjust = 0,
  width = 1,
  height = 1,
  layout = "dot",
  main = "",
  sub = "",
  cex.main = 1.5,
  cex.sub = 1,
  col.sub = "grey",
  fontcolor = NULL,
  nodestates = NULL,
  simulate = NULL,
  edgecol = NULL,
  labels = NULL,
  labelcol = "blue",
  nodelabel = NULL,
  nodecol = NULL,
  bordercol = NULL,
  nodeshape = NULL,
  verbose = FALSE,
  edgestyle = NULL,
  nodeheight = NULL,
  nodewidth = NULL,
  edgewidth = NULL,
  lty = NULL,
  hierarchy = NULL,
  showall = FALSE,
  edgehead = NULL,
  edgelabel = NULL,
  edgetail = NULL,
  bool = TRUE,
  draw = TRUE,
  ...
)
```

## Arguments

| | |
|---|---|
| dnf | Hyper-graph in disjunctive normal form, e.g. c("A=B", "A=C+D", "E=!B") with the child on the left and the parents on the right of the equation with "A=C+D" for A = C AND D. Alternatively, dnf can be an adjacency matrix, which is converted on the fly to a disjunctive normal form. |

| | |
|---|---|
| freq | Frequency of hyper-edges which are placed on the edges. |
| stimuli | Highlights vertices which can be stimulated. |
| signals | Highlights vertices which regulate E-genes. |
| inhibitors | Highlights vertices which can be inhibited. |
| connected | If TRUE, only includes vertices which are connected to other vertices. |
| CNOlist | CNOlist object. Optional instead of stimuli, inhibitors or signals. See package CellNOptR. |
| cex | Global font size. |
| fontsize | Vertice label size. |
| labelsize | Edge label size. |
| type | Different plot types. 2 for Rgraphviz and 1 for graph. |
| lwd | Line width of nodeborder. |
| edgelwd | Global edgeline width. |
| legend | 0 shows no legend. 1 shows legend as a graph. 2 shows legend in a standard box. |
| x | x coordinate of box legend. |
| y | y coordinate of box legend. |
| xjust | Justification of legend box left, right or center (-1,1,0). |
| yjust | Justification of legend box top, bottom or middle (-1,1,0). |
| width | Vertice width. |
| height | Vertice height. |
| layout | Graph layout. See graphvizCapabilities()$layoutTypes. |
| main | Main title. |
| sub | Subtitle. |
| cex.main | Main title font size. |
| cex.sub | Subtitle font size. |
| col.sub | Font color of subtitle. |
| fontcolor | Global font color. |
| nodestates | Binary state of each vertice. |
| simulate | Simulate stimulation and inhibition of a list of vertices. E.g. simulate = list(stimuli = c("A", "B"), inhibitors = c("C", "D")). |
| edgecol | Vector with colors for every edge of the graph (not hyper-graph). E.g. an AND gate consists of three distinct edges. |
| labels | Vector with labels for the edges. |
| labelcol | Vector with label colors for the edges. |
| nodelabel | List of vertices with labels as input. E.g. labels = list(A="test", B="label for B"). |
| nodecol | List of vertices with colors as input. |

| | |
|---|---|
| bordercol | List of vertices with colors as input. |
| nodeshape | List of vertices with shapes (diamond, box, square,...). |
| verbose | Verbose output. |
| edgestyle | set the edge style like dashed, can be numerical |
| nodeheight | List of vertices with height as input. |
| nodewidth | List of vertices with width as input. |
| edgewidth | Vector with edge widths for individual edges. |
| lty | Vector with edge styles (line, dotted,...). |
| hierarchy | List with the hierarchy of the vertices. E.g. list(top = c("A", "B"), bottom = c("C", "D")). |
| showall | See "connected" above. |
| edgehead | Vector with edge heads. |
| edgelabel | Vector with edge labels. |
| edgetail | Vector with edge tails. |
| bool | If TRUE, only shows normal graph and no AND gates. |
| draw | Do not plot the graph and only output the graphNEL object. |
| ... | additional arguments |

## Value

Rgraphviz object

## Author(s)

Martin Pirkl

## Examples

```
g <- c("!A+B+C=G", "C=G", "!D=G")
plotDnf(g)
```

---

# scoreAdj *Network score*

---

## Description

Computes the fit (score of a network) of the data given a network matrix

## Usage

```
scoreAdj(
  D,
  adj,
  method = "llr",
  marginal = FALSE,
  logtype = 2,
  weights = NULL,
  trans.close = TRUE,
  subtopo = NULL,
  prior = NULL,
  ratio = TRUE,
  fpfn = c(0.1, 0.1),
  Rho = NULL,
  dotopo = FALSE,
  P = NULL,
  oldadj = NULL,
  modified = TRUE
)
```

## Arguments

| | |
|---|---|
| D | data matrix; use modified = FALSE |
| adj | adjacency matrix of the network phi |
| method | either llr if D consists of log odds or disc, if D is binary |
| marginal | logical to compute the marginal likelihood (TRUE) |
| logtype | log base of the log odds |
| weights | a numeric vector of weights for the columns of D |
| trans.close | if TRUE uses the transitive closure of adj |
| subtopo | optional matrix with the subtopology theta as adjacency matrix |
| prior | a prior network matrix for adj |
| ratio | if FALSE uses alternative distance for the model score |
| fpfn | numeric vector of length two with false positive and false negative rates |
| Rho | optional perturbation matrix |
| dotopo | if TRUE computes and returns the subtopology theta (optional) |
| P | previous score matrix (only used internally) |
| oldadj | previous adjacency matrix (only used internally) |
| modified | if TRUE, assumes a prepocessed data matrix |

## Value

transitively closed matrix or graphNEL

### Author(s)

Martin Pirkl

### Examples

```
D <- matrix(rnorm(100*3), 100, 3)
colnames(D) <- 1:3
rownames(D) <- 1:100
adj <- diag(3)
colnames(adj) <- rownames(adj) <- 1:3
scoreAdj(D, adj)
```

---

## simData *Simulate data.*

---

### Description

This function simulates single cell data from a random mixture of networks.

### Usage

```
simData(
  Sgenes = 5,
  Egenes = 1,
  Nems = 2,
  reps = NULL,
  mw = NULL,
  evolution = FALSE,
  nCells = 1000,
  uninform = 0,
  unitheta = FALSE,
  edgeprob = c(0, 1),
  multi = FALSE,
  subsample = 1,
  scalefree = FALSE,
  badCells = 0,
  exactProb = TRUE,
  tree = FALSE,
  ...
)
```

### Arguments

| | |
|---|---|
| Sgenes | number of Sgenes |
| Egenes | number of Egenes |
| Nems | number of components |
| reps | number of replicates, if set (not realistic for cells) |

| | |
|---|---|
| mw | mixture weights (has to be vector of length Nems) |
| evolution | evolving and not purely random network, if set to TRUE |
| nCells | number of cells |
| uninform | number of uninformative Egenes |
| unitheta | uniform theta, if TRUE |
| edgeprob | edge probability, value between 0 and 1 for sparse or dense networks or a range c(l,u) with lower and upper bound |
| multi | a vector with the percentages of cell with multiple perturbations, e.g. c(0.2,0.1,0) for 20 no quadruple knock-downs |
| subsample | range to subsample data. 1 means the full simulated data is used |
| scalefree | if TRUE, graph is scale free |
| badCells | number of cells, which are just noise and not connected to the ground truth network |
| exactProb | logical; if TRUE generates random network with exact fraction of edges provided by edgeprob |
| tree | if TRUE, restricts dag to a tree |
| ... | additional parameters for the scale free network sampler (see 'nem' package) |

## Value

simulation object with meta information and data

| | |
|---|---|
| Nem | list of adjacency matrixes generatign the data |
| theta | E-gene attachaments |
| data | data matrix |
| index | index for which Nem generated which cell (data column) |
| mw | vector of input mixture weights |

## Author(s)

Martin Pirkl

## Examples

```
sim <- simData(Sgenes = 3, Egenes = 2, Nems = 2, mw = c(0.4,0.6))
```

## transitive.closure *Transitive closure of a directed acyclic graph (dag)*

### Description

Computes the transitive closure of a dag or only of a deletion/addition of an edge

### Usage

```
transitive.closure(g, u = NULL, v = NULL)
```

### Arguments

| | |
|---|---|
| g | graph as matrix or graphNEL object |
| u | index of the parent of an edge (optional) |
| v | index of the child of an edge (optional) |

### Value

transitively closed matrix or graphNEL

### Author(s)

Martin Pirkl

### Examples

```
g <- matrix(c(0,0,0,1,0,0,0,1,0), 3)
transitive.closure(g)
```

## transitive.reduction *Transitive reduction*

### Description

Computes the transitive reduction of an adjacency matrix or graphNEL object. Originally imported from the package 'nem'.

### Usage

```
transitive.reduction(g)
```

### Arguments

| | |
|---|---|
| g | adjacency matrix or graphNEL object |

## Value

transitively reduced adjacency matrix

## Author(s)

Holger Froehlich

## References

R. Sedgewick, Algorithms, Pearson, 2002.

## Examples

```
g <- matrix(c(0,0,0,1,0,0,0,1,0), 3)
rownames(g) <- colnames(g) <- seq_len(3)
g.tr <- transitive.reduction(g)
```

# Index

app, 3

bootstrap, 3

clustNEM, 4
createApp, 5

fitacc, 7
fuzzyindex, 8

getAffinity, 9
getIC, 10

hamSim, 11

mnem, 12
mnemh, 15
mnemk, 16
moreboxplot, 17

nem, 19

plot.bootmnem, 21
plot.mnem, 21
plot.mnem_mcmc, 23
plot.mnem_sim, 24
plotConvergence, 25
plotConvergence.mnem, 25
plotDnf, 26

scoreAdj, 29
simData, 31

transitive.closure, 33
transitive.reduction, 33