Package 'phantasus'

November 12, 2026

Title Visual and interactive gene expression analysis

Version 1.32.0

Description Phantasus is a web-application for visual and interactive gene expression analysis. Phantasus is based on Morpheus – a web-based software for heatmap visualisation and analysis, which was integrated with an R environment via OpenCPU API. Aside from basic visualization and filtering methods, R-based methods such as k-means clustering, principal component analysis or differential expression analysis with limma package are supported.

URL https://alserglab.wustl.edu/phantasus

BugReports https://github.com/ctlab/phantasus/issues

Depends R (>= 4.3)

biocViews GeneExpression, GUI, Visualization, DataRepresentation, Transcriptomics, RNASeq, Microarray, Normalization, Clustering, DifferentialExpression, PrincipalComponent, ImmunoOncology

Imports ggplot2, protolite, Biobase, GEOquery, htmltools, httpuv, jsonlite, limma, edgeR, opencpu, assertthat, methods, httr, rhdf5, utils, parallel, stringr, fgsea (>= 1.9.4), svglite, gtable, stats, Matrix, pheatmap, scales, ccaPP, grid, grDevices, AnnotationDbi, DESeq2, data.table, curl, apeglm, config (>= 0.3.2), rhdf5client (>= 1.25.1), yaml, fs, phantasusLite, XML

License MIT + file LICENSE

Encoding UTF-8

LazyData true

RoxygenNote 7.3.3

Suggests testthat, BiocStyle, knitr, rmarkdown, org.Hs.eg.db, org.Mm.eg.db

VignetteBuilder knitr

NeedsCompilation no

Config/build/copy-method link

git_url https://git.bioconductor.org/packages/phantasus

git_branch RELEASE_3_23

git_last_commit 988aa34

git_last_commit_date 2026-04-28

Repository Bioconductor 3.23

Date/Publication 2026-11-11

Author Maxim Kleverov [aut],
Daria Zenkova [aut],
Vladislav Kamenev [aut],
Margarita Sablina [ctb],
Maxim Artyomov [aut],
Alexey Sergushichev [aut, cre]

Maintainer Alexey Sergushichev <alsergbox@gmail.com>

Contents

adjustDataset . . . 3
annotationDBMeta . . . 4
calcPCA . . . 5
calculatedAnnotation . . . 5
checkGPLsFallback . . . 6
checkGSEType . . . 7
collapseDataset . . . 7
colMeansByGroups . . . 8
convertByAnnotationDB . . . 8
createDockerConf . . . 9
createES . . . 10
es . . . 11
fgseaExample . . . 11
generatePreloadedSession . . . 11
getArchs4Files . . . 12
getCountsMetaPart . . . 13
getES . . . 14
getGDS . . . 15
getGSE . . . 15
getPhantasusConf . . . 16
gseaPlot . . . 17
isHSDS . . . 18
limmaAnalysis . . . 18
loadCounts . . . 19
loadFromARCHS4 . . . 20
loadGEO . . . 20
loadPreloaded . . . 21
parseCharacteristics . . . 21
performKmeans . . . 22
queryAnnotationDBMeta . . . 23

read.gct 23
reparseCachedESs 24
reproduceInR 24
servePhantasus 25
setupPhantasus 26
shinyGAMAnalysis 26
subsetES 27
updateARCHS4 27
updateARCHS4meta 28
updateCountsMeta 29
updateDEE2meta 29
validateCountsCollection 30
write.gct 31

Index **32**

`adjustDataset` *Adjust dataset*

Description

Adjust dataset

Usage

```
adjustDataset(
  es,
  scaleColumnSum = NULL,
  log2 = FALSE,
  onePlusLog2 = FALSE,
  inverseLog2 = FALSE,
  quantileNormalize = FALSE,
  zScore = FALSE,
  robustZScore = FALSE,
  sweep = NULL
)
```

Arguments

`es`	Expression set to perform adjustment on
`scaleColumnSum`	perform sum scaling of columns (default FALSE)
`log2`	perform logarithm2 adjustment (default FALSE)
`onePlusLog2`	perform log2(1+x) adjustment (default FALSE)
`inverseLog2`	perform 2^x adjustment (default FALSE)
`quantileNormalize`	perform quantile normalization (default FALSE)

zScore	perform zScore adjustment: subtract mean, divide by std (default FALSE)
robustZScore	perform robustZScore adjustment: subtract median, divide by MAD (default FALSE)
sweep	perform sweep adjustment on rows/columns (default FALSE)

Value

Nothing. Adjusted dataset will be assigned as ES in global environment

Examples

```
## Not run:
es <- gseGSE('GSE53986')[[1]]
adjustDataset(es, log2 = T, quantileNormalize = T)

## End(Not run)
```

---

annotationDBMeta *Create meta file for AnnotationDB*

Description

annotationDBMeta function creates txt files containing meta information of provided sqlite files for AnnotationDB.

Usage

```
annotationDBMeta(annotDir)
```

Arguments

annotDir	path to folder with annotationDB sqlite files

Value

nothing

Examples

```
## Not run:
annotationDBMeta('/var/phantasus/cache')

## End(Not run)
```

calcPCA *Principal Component Analysis.*

Description

calcPCA calculates PCA-matrix for the given ExpressionSet and returns this matrix encoded to JSON.

Usage

```
calcPCA(es, replacena = "mean")
```

Arguments

es	an ExpressionSet object, should be normalized
replacena	method for replacing NA values (mean by default)

Value

json with full description of the plot for plotly.js

Examples

```
## Not run:
data(es)
calcPCA(es)

## End(Not run)
```

calculatedAnnotation *Create calculated annotation*

Description

calculatedAnnotation adds a column calculated by operation

Usage

```
calculatedAnnotation(
  es,
  operation,
  rows = c(),
  columns = c(),
  isColumns = FALSE,
  name = NULL
)
```

Arguments

es	ExpressionSet object.
operation	Name of the operation to perform calculation
rows	List of specified rows' indices (optional), indices start from 0
columns	List of specified columns' indices (optional), indices start from 0#'
isColumns	Apply fn to columns
name	Name of the new annotation

Value

Nothing. Annotated dataset will be assigned to es in environment

---

checkGPLsFallback *Check possible annotations for GEO Dataset.*

Description

checkGPLs returns GPL-names for the specified GEO identifier.

Usage

```
checkGPLsFallback(name)
```

Arguments

name	String, containing GEO identifier of the dataset.

Value

Vector of filenames serialized in JSON format. If there is only one GPL for that dataset, the function will return name.

Examples

```
## Not run:
checkGPLs('GSE27112')
checkGPLs('GSE14308')

## End(Not run)
```

checkGSEType *Checks GSE to be supported*

Description

Checks GSE to be supported

Usage

```
checkGSEType(name, destDir, combine = any)
```

Arguments

name	GSE id, with optional GPL specification
destDir	path to cache directory
combine	function on how to combine results, when multiple platforms are present

Value

logical vector if the dataset is supported or not

collapseDataset *Collapse dataset*

Description

`collapseDataset` performs a collapse action on expression set

Usage

```
collapseDataset(
  es,
  isRows = TRUE,
  selectOne = FALSE,
  fn,
  fields,
  removeEmpty = TRUE
)
```

Arguments

es	Expression set
isRows	Work with rows. False if columns (default True - row mode)
selectOne	select best match or merge duplicates
fn	select/merge function
fields	fields to unique on
removeEmpty	remove unannotated genes

Value

Nothing. Collapsed dataset will be assigned to es in environment

Examples

```
## Not run:
es <- getGSE('GSE53986')[[1]]
collapseDataset(es, isRows = TRUE, selectOne = TRUE,
fn = mean, fields = c('Gene ID', 'Gene symbol'))

## End(Not run)
```

---

colMeansByGroups *Calculate column averages in row groups*

Description

Calculate column averages in row groups

Usage

```
colMeansByGroups(m, groups)
```

Arguments

m	matrix n x m
groups	vector of size n of numbers from 1 to k

Value

matrix k*m of column averages by groups

---

convertByAnnotationDB *Map indexes using Annotation DB*

Description

convertByAnnotationDB function returns keyType ids from dbName mapped to columnName in es.

Usage

```
convertByAnnotationDB(
  es,
  dbName,
  columnName,
  columnType,
  keyType,
  otherOptions
)
```

Arguments

es	source ExpressionSet
dbName	name of AnnotationDB file
columnName	name of column in featureData of source ExpressionSet
columnType	Type of indexes in columnName
keyType	Type of mapped indexes
otherOptions	additional parameters for conversion. Currently only named boolean deleteDotVersion is not ignored.

Value

JSON object with a vector of converted IDs

`createDockerConf` *Creates default Docker conf file Copies the package user.conf template to* `user_conf_file` *when the file is absent. When it already exists, any keys present in the template but missing from the existing file are added (e.g.* `internal_ports` *on an upgrade from a pre-multiport installation).*

Description

Creates default Docker conf file Copies the package user.conf template to `user_conf_file` when the file is absent. When it already exists, any keys present in the template but missing from the existing file are added (e.g. `internal_ports` on an upgrade from a pre-multiport installation).

Usage

```
createDockerConf(user_conf_file = confFile("user.conf"))
```

Arguments

user_conf_file	Location of the user conf file to write.

createES *Create ExpressionSet.*

Description

createES function produces an ExpressionSet object from given data, and exports it to global scope.

Usage

```
createES(data, pData, varLabels, fData, fvarLabels, eData)
```

Arguments

data	Gene expression matrix.
pData	Matrix with phenotypical data.
varLabels	Names of phenoData columns.
fData	Matrix with feature data.
fvarLabels	Names of featureData columns.
eData	List with experimentData

Value

produced ExpressionSet object

Examples

```
## Not run:
data <- matrix(1:15, 5, 3)
pData <- c("A", "B", "C")
varLabels <- "cat"
fData <- c("p", "r", "s", "t", "u")
fvarLabels <- "id"
eData <- list(name="", lab="", contact="", title="", url="", other=list(), pubMedIds="")
createES(data, pData, varLabels, fData, fvarLabels, eData)

## End(Not run)
```

es *Example dataset*

Description

Small slice from GSE27112-GPL6103 for runnable examples.

Usage

```
es
```

Format

An object of class `ExpressionSet` with 20 rows and 5 columns.

Examples

```
## Not run:
data(es)
performKmeans(es, k = 2)

## End(Not run)
```

fgseaExample *Example pathway data.frame for fgsea tool*

Description

Example pathway data.frame for fgsea tool

generatePreloadedSession *Generate files for preloaded session from a session link.*

Description

Generate files for preloaded session from a session link.

Usage

```
generatePreloadedSession(sessionURL, preloadedName, preloadedDir)
```

Arguments

sessionURL	String with session link produced by phantasus.
preloadedName	String with name that should be assigned to the session.
preloadedDir	Path to the directory with preloaded datasets and sessions.

Value

Function produces two files (preloadedName.rda with ExpressionSet and preloadedName.json with session features) in preloadedDir folder.

Examples

```
## Not run:
sessionURL <- "https://ctlab.itmo.ru/phantasus/?session=x063c1b365b9211" # link from 'Get dataset link...' tool ir
newName <- "my_session" # user defined name
preloadedDir <- "./preloaded" # directory where files will be stored. In order too get access through phantasus web-
dir.create(preloadedDir, showWarnings = FALSE)
generatePreloadedSession(sessionURL= sessionURL,
                         preloadedName = newName,
                         preloadedDir = preloadedDir)

servePhantasus(preloadedDir=preloadedDir, openInBrowser=FALSE)
# open browser manually at http://0.0.0.0:8000/phantasus/index.html?preloaded=my_session

## End(Not run)
```

---

getArchs4Files *Returns list of ARCHS4 hdf5 files with expression data*

Description

Returns list of ARCHS4 hdf5 files with expression data

Usage

```
getArchs4Files(cacheDir)
```

Arguments

cacheDir	base directory for cache

Value

list of .h5 files

getCountsMetaPart *Create meta-data for single counts collection*

Description

Creates a part of counts collections meta-data

Usage

```
getCountsMetaPart(counts_dir, collection_name, verbose)
```

Arguments

counts_dir	path to directory with count collections
collection_name	name of collection and collection's directory
verbose	logical value which determines a content of the output.

Details

Function assumes that collection_name contains meta.txt which is valid (in sence of validateCountsCollection). For each row in meta.txt function reads specified sample_id dataset and writes every sample id to the resulting data.table with source file name and collection name.

Value

data.table with meta-data or nothing if destdir does not exist or does not contain files.

See Also

validateCountsCollection,getCountsMetaPart

Examples

```
## Not run:
    collDir <- "/path/to/my/collection"
    valid_collection = validateCountsCollection(collectionDir = collDir, verbose = TRUE)
    if (valid_collection){
        metaPart = getCountsMetaPart(destdir = collDir, verbose = TRUE)
     }

## End(Not run)
```

getES *Load ExpressionSet by GEO identifier*

Description

getES return the ExpressionSet object(s) corresponding to GEO identifier.

Usage

```
getES(
  name,
  type = NA,
  destdir = getPhantasusConf("cache_folders")$geo_path,
  mirrorPath = getPhantasusConf("geo_mirrors")
)
```

Arguments

name	String, containing GEO identifier of the dataset. It should start with 'GSE' or 'GDS' and can include exact GPL to annotate dataset, separated with dash ('-') from the identifier.
type	Type of the dataset: 'GSE' or 'GDS'. If not specified, the function will take first three letters of name variable as type.
destdir	Directory for caching loaded Series and GPL files from GEO database.
mirrorPath	URL string which specifies the source of matrices.

Value

List of ExpressionSet objects, that were available by given in name variable GEO identifier.

Examples

```
## Not run:
    getES('GSE14308', type = 'GSE', destdir = 'cache')
    getES('GSE27112')
    getES('GDS4922')

## End(Not run)
```

getGDS *Load ExpressionSet from GEO Datasets*

Description

getGDS return the ExpressionSet object corresponding to GEO Dataset identifier.

Usage

```
getGDS(
  name,
  destdir = getPhantasusConf("cache_folders")$geo_path,
  mirrorPath = getPhantasusConf("geo_mirrors")
)
```

Arguments

name	String, containing GEO identifier of the dataset. It should start with 'GSE' or 'GDS' and can include exact GPL to annotate dataset, separated with dash ('-') from the identifier.
destdir	Directory for caching loaded Series and GPL files from GEO database.
mirrorPath	URL string which specifies the source of matrices.

Value

ExpressionSet object wrapped in list, that was available by given in name variable GEO identifier.

Examples

```
## Not run:
   getGDS('GDS4922', destdir = tempdir(), mirrorPath = "https://ftp.ncbi.nlm.nih.gov")

## End(Not run)
```

getGSE *Load ExpressionSet from GEO Series*

Description

getGSE return the ExpressionSet object(s) corresponding to GEO Series Identifier.

Usage

```
getGSE(
  name,
  destdir = getPhantasusConf("cache_folders")$geo_path,
  mirrorPath = getPhantasusConf("geo_mirrors")
)
```

Arguments

name	String, containing GEO identifier of the dataset. It should start with 'GSE' or 'GDS' and can include exact GPL to annotate dataset, separated with dash ('-') from the identifier.
destdir	Directory for caching loaded Series and GPL files from GEO database.
mirrorPath	URL string which specifies the source of matrices.

Value

List of ExpressionSet objects, that were available by given in name variable GEO identifier.

Examples

```
## Not run:
    getGSE('GSE14308', destdir = 'cache')
    getGSE('GSE27112')
    getGSE('GSE53986')

## End(Not run)
```

---

getPhantasusConf *Read Phantasus Config*

Description

Read Phantasus Config

Usage

```
getPhantasusConf(
  value = NULL,
  configName = Sys.getenv("R_CONFIG_ACTIVE"),
  file = file.path(tools::R_user_dir(package = "phantasus", which = "config"),
    "user.conf")
)
```

Arguments

value	Value to retrieve from the config file.
configName	R_CONFIG_ACTIVE value. If unset, "default".
file	Location of the config file

---

gseaPlot *Returns path to an svg file with enrichment plot*

Description

Returns path to an svg file with enrichment plot

Usage

```
gseaPlot(
  es,
  rankBy,
  selectedGenes,
  width,
  height,
  vertical = FALSE,
  addHeatmap = FALSE,
  showAnnotation = NULL,
  annotationColors = NULL,
  pallete = c("blue", "white", "red")
)
```

Arguments

es	ExpressionSet object.
rankBy	name of the numeric column used for gene ranking
selectedGenes	indexes of selected genes (starting from one, in the order of fData)
width	width of the image (in inches)
height	height of the image (in inches)
vertical	whether to use vertical orientation (default: FALSE)
addHeatmap	whether to add an expression heatmap, sorted by rankBy (default: FALSE)
showAnnotation	a name of column annotation to add to the heatmap, default: NULL (no annotation)
annotationColors	a list of colors to use in annotation
pallete	a vector of colors to draw heatmap

Value

path to an svg file

`isHSDS` *check if url responding as HSDS server TRUE - hsds FALSE - web link but not working NULL - not web link*

Description

check if url responding as HSDS server TRUE - hsds FALSE - web link but not working NULL - not web link

Usage

```
isHSDS(url)
```

Arguments

`url`	URL to check

`limmaAnalysis` *Differential Expression analysis.*

Description

`limmaAnalysis` performs differential expression analysis from limma package and returns a ProtoBuf-serialized resulting de-matrix.

Usage

```
limmaAnalysis(
  es,
  fieldValues,
  version = "One-factor design",
  contrast = list("Comparison", "Target", "Reference"),
  designData = NULL
)
```

Arguments

`es`	ExpressionSet object. It should be normalized for more accurate analysis.
`fieldValues`	Vector of comparison values, mapping categories' names to columns/samples
`version`	name of the limma analysis implementation. Should be "One-factor design" or "Advanced design"
`contrast`	a character vector with exactly three elements: the name of a factor in the design formula, the name of the numerator level for the fold change, and the name of the denominator level for the fold change
`designData`	data.frame with design matrix

Value

Name of the file containing serialized de-matrix.

Examples

```
## Not run:
data(es)
limmaAnalysis(es, fieldValues = c("A", "A", "A", "B", "B"))

## End(Not run)
```

`loadCounts` *Loads expression data from .h5 count files. Only samples with counted expression are kept. If es already containts expression data it is returned as is.*

Description

Loads expression data from .h5 count files. Only samples with counted expression are kept. If es already containts expression data it is returned as is.

Usage

```
loadCounts(es, counts_dir)
```

Arguments

`es`	ExpressionSet from GEO to check for expression in ARCHS4/dee2 or other h5 files
`counts_dir`	directory with .h5 files collections. There must be meta.rda file in counts_dir and each collection's sub directory must have meta.txt file with description. Also `counts_dir` must contain `counts_priority.txt` file.

Value

either original es or an ExpressionSet with loaded count data from ARCHS4

`loadFromARCHS4` *Loads expression data from ARCHS4 count files. Only sapmles with counted expression are kept. If es already containts expression data it is returned as is.*

Description

Loads expression data from ARCHS4 count files. Only sapmles with counted expression are kept. If es already containts expression data it is returned as is.

Usage

```
loadFromARCHS4(es, archs4_files)
```

Arguments

`es`	ExpressionSet from GEO to check for expression in ARCHS4
`archs4_files`	list of available .h5 files from ARCHS4 project

Value

either original es or an ExpressionSet with loaded count data from ARCHS4

`loadGEO` *Load GEO Dataset.*

Description

`loadGEO` returns the file with serialized ExpressionSet using ProtoBuf, parsed from data downloaded from GEO by identifier.

Usage

```
loadGEO(name, type = NA)
```

Arguments

`name`	String, containing GEO identifier of the dataset. It should start with 'GSE' or 'GDS' and can include exact GPL to annotate dataset, separated with dash ('-') from the identifier.
`type`	Type of the dataset: 'GSE' or 'GDS'. If not specified, the function will take first three letters of `name` variable as type.

Value

File with ProtoBuf-serialized ExpressionSet-s that were downloaded by this identifier. For GSE-datasets there can be multiple annotations, so in file will be a list mapping name with GPL to ExpressionSet.

Examples

```
## Not run:
    loadGEO("GSE27112")
    loadGEO("GDS4922")

## End(Not run)
```

---

loadPreloaded *Load GEO Dataset.*

Description

`loadPreloaded` returns the file with serialized ExpressionSets using ProtoBuf, that were preloaded on server.

Usage

```
loadPreloaded(name)
```

Arguments

`name`	String, containing filename. Assuming that in the directory with preloaded files `preloadedDir` exists file `filename.rda` with list of ExpressionSets `ess`.

Value

File with ProtoBuf-serialized ExpressionSet-s that were loaded from specified file.

---

parseCharacteristics *Parse characteristics columns somewhat intelligently*

Description

Parse characteristics columns somewhat intelligently

Usage

```
parseCharacteristics(pdata)
```

Arguments

pdata	AnnotatedDataFrame with characteristics columns

Value

named data.frame with parsed annotations, rows are in the same order as the input

---

performKmeans *K-means clusterisation.*

Description

performKmeans returns a vector of corresponding clusters for each gene from a given ExpressionSet.

Usage

```
performKmeans(es, k, replacena = "mean")
```

Arguments

es	ExpressionSet object.
k	Expected number of clusters.
replacena	Method for replacing NA values in series matrix (mean by default)

Value

Vector of corresponding clusters, serialized to JSON.

Examples

```
## Not run:
data(es)
performKmeans(es, k = 2)

## End(Not run)
```

queryAnnotationDBMeta *Get meta list for annotationDB files*

Description

queryAnnotationDBMeta Function reads txt meta files for provided sqlite annotation databases.

Usage

```
queryAnnotationDBMeta()
```

Value

meta info in JSON

Examples

```
## Not run:
queryAnnotationDBMeta()

## End(Not run)
```

read.gct *Reads ExpressionSet from a GCT file. Function is deprecated, please use phantasusLite:::readGct() instead*

Description

Reads ExpressionSet from a GCT file. Function is deprecated, please use phantasusLite:::readGct() instead

Usage

```
read.gct(...)
```

Arguments

...	parameters for phantasusLite:::readGct() call

Value

ExpressionSet object

reparseCachedESs *Reparse cached expression sets from GEO.*

Description

The function should be used on phantasus version updates that change behavior of loading datasets from GEO. It finds all the datasets that were cached and runs ‘getES‘ for them again. The function uses cached Series and other files from GEO.

Usage

```
reparseCachedESs(destdir, mirrorPath = getPhantasusConf("geo_mirrors"))
```

Arguments

destdir	Directory used for caching loaded Series files from GEO database.
mirrorPath	URL string which specifies the source of matrices.

Value

vector of previously cached GSE IDs

Examples

```
reparseCachedESs(destdir=tempdir(), "https://ftp.ncbi.nlm.nih.gov")
```

reproduceInR *Reproduce session in R code*

Description

Reproduce session in R code

Usage

```
reproduceInR(sessionName, leaf = T, step = 0, savedEnv = new.env())
```

Arguments

sessionName	String, OCPU session name
leaf	Boolean, is it leaf (default = F)
step	Integer, step of recursion (default = 0)
savedEnv	Environment, where to store complex arguments (default = new.env())

Value

JSON with R code

Examples

```
## Not run:
  setwd(tempdir())
  reproduceInR('x039f1672026678');

## End(Not run)
```

`servePhantasus` *Serve phantasus.*

Description

`servePhantasus` starts http server handling phantasus static files and opencpu server.

Usage

```
servePhantasus(
  host = getPhantasusConf("host"),
  port = getPhantasusConf("port"),
  staticRoot = getPhantasusConf("static_root"),
  preloadedDir = getPhantasusConf("preloaded_dir"),
  openInBrowser = TRUE,
  quiet = TRUE,
  background = FALSE
)
```

Arguments

`host`	Host to listen.
`port`	Single integer port to listen on.
`staticRoot`	Path to static files with phantasus.js (on local file system).
`preloadedDir`	Full path to directory with preloaded files.
`openInBrowser`	Boolean value which states if application will be automatically loaded in default browser.
`quiet`	Boolean value which states whether the connection log should be hidden (default: TRUE)
`background`	Boolean value which states whether the server should be started in background (default: FALSE). Returns an httpuv server handle when `TRUE`.

Value

In `background=TRUE` mode, the httpuv server handle. Otherwise does not return (blocks until interrupted).

Examples

```
## Not run:
# Returns handle immediately
s <- servePhantasus(background=TRUE)
s$stop()

## End(Not run)

httpuv::stopAllServers() # can be used if handle is lost
```

`setupPhantasus` *Setup phantasus. Read user config file (or create default one) and fill* `cache_root` *using sources in* `file`.

Description

Setup phantasus. Read user config file (or create default one) and fill `cache_root` using sources in `file`.

Usage

```
setupPhantasus(setup_name = "default", file = confFile("setup.yml"))
```

Arguments

`setup_name`	name of config from `file`. If unset or not existed, "default".
`file`	Location of the setup.yml file with setup parameters. If not existed use file from package

---

`shinyGAMAnalysis` *Constructs data frame with gene annotations and submits it into Shiny GAM web-server*

Description

Constructs data frame with gene annotations and submits it into Shiny GAM web-server

Usage

```
shinyGAMAnalysis(es)
```

Arguments

`es`	Expression set object

Value

URL for Shiny GAM

subsetES *Subsets es, if rows or columns are not specified, all are retained*

Description

Subsets es, if rows or columns are not specified, all are retained

Usage

```
subsetES(es, columns = c(), rows = c())
```

Arguments

es	ExpressionSet object.#'
columns	List of specified columns' indices (optional), indices start from 0#'
rows	List of specified rows' indices (optional), indices start from 0

Value

new expression set 'es'

updateARCHS4 *Update archs4 files.*

Description

Download archs4 or archs4zoo counts in `cacheDir`. If directory does not exists function makes nothing and produce corresponding warnings.

Usage

```
updateARCHS4(
 cacheDir = file.path(getPhantasusConf("cache_folders")$rnaseq_counts, "archs4"),
  organism = c("all"),
  force = FALSE
)
```

Arguments

cacheDir	file path to **archs4** cache directory
organism	vector which determines organisms to download: human, mouse, zoo or all as default. Also can be a genus. Possible genus: 1. drosophila 2. gallus

3. bos
4. caenorhabditis
5. danio
6. rattus
7. saccharomyces
8. arabidopsis

`force` logical value which let function replace current files

`updateARCHS4meta` *Update ARCHS4 meta files*

Description

Creates `meta.txt` file, which describes typical archs4 and archs4Zoo files.

Usage

```
updateARCHS4meta(
  archDir = file.path(getPhantasusConf("cache_folders")$rnaseq_counts, "archs4")
)
```

Arguments

`archDir` path to directory with arch4 .h5 files.

Details

This function produces very specific "hardcoded" `meta.txt` file for arch4 and archs4ZOO counts collections. See `validateCountsCollection` for more common information and `meta.txt` file structure

See Also

`validateCountsCollection`

updateCountsMeta *Update meta-data for counts collections*

Description

Creates `meta.rda` file which contain information about all samples in all collections. Also function checks `priority.txt` file. This file is used to manage collections with the same samples.

Usage

```
updateCountsMeta(
  counts_dir = getPhantasusConf("cache_folders")$rnaseq_counts,
  force = FALSE,
  verbose = FALSE
)
```

Arguments

`counts_dir`	path to counts cache directory
`force`	logical value wich lets function replace existing `meta.rda` file
`verbose`	logical value which determines a content of the output.

Details

First of all function checks validity of `priority.txt` file. **Every** Collection should have **unique** priority. If `priority.txt` is not valid function creates new one, setting priorities for each subdirectory(=collection) equal to order in `list.dir` output.

Function updates `meta.rda` if this file is older than at least one `.h5` file in counts files. `meta.rda` is `data.table` which is a result of union `data.tables` produced by `getCountsMetaPart` for each collection

See Also

`validateCountsCollection`,`updateCountsMeta`

updateDEE2meta *Update DEE2 meta files*

Description

Creates `meta.txt` file, which describes typical dee2 files.

Usage

```
updateDEE2meta(
  destDir = file.path(getPhantasusConf("cache_folders")$rnaseq_counts, "dee2")
)
```

Arguments

destDir	path to directory with DEE2 .h5 files.

Details

This function produces very specific "hardcoded" `meta.txt` file for dee2 counts colletction. See `validateCountsCollection` for more common information and `meta.txt` file structure

See Also

`validateCountsCollection`

---

validateCountsCollection

Check a counts collection

Description

Function checks existing and structure of `meta.txt` file in specified counts folder.Also it checks accessibility of specified datasets in corresponding `.h5` files.

Usage

```
validateCountsCollection(collectionDir, verbose = FALSE)
```

Arguments

collectionDir	path to directory with collection
verbose	logical value which determines a content of the output.

Details

`collectionDir` should contain a bunch of `.h5` files and a single `meta.txt`. `meta.txt` is `.tsv`-like file where for each `.h5` exists a row wit columns:

file_name name of `.h5` file in `collectionDir`.

sample_id name of dataset in `file_name` which contains sample IDs (sample_geo_accession for example).

sample_dim which dimension of the expression matrix in `file_name` corresponds to samples. Should be one of `c("rows", "columns")`

gene_id name of dataset in `file_name` which contains ids for genes and the "meaning" for that ids(column name in result ES). For correct work this dataset should contain unique values. Example: ENSEMBLID:/meta/genes/ensembl_gene_id

genes_annot Names of datasets and their meanings to extract gene-related metadata from `file_name`. Can be empty or `gene_id`-like values separated with semicolon(;).

`write.gct` *Saves ExpressionSet to a GCT file (version 1.3). Function is deprecated, please use phantasusLite:::writeGct() instead*

Description

Saves ExpressionSet to a GCT file (version 1.3). Function is deprecated, please use phantasusLite:::writeGct() instead

Usage

```
write.gct(...)
```

Arguments

...	parameters for phantasusLite:::writeGct() call

Value

Result of the closing file (as in ‘close()‘ function‘)

Index

∗ **datasets**
  es, 11
∗ **internal**
  adjustDataset, 3
  annotationDBMeta, 4
  calcPCA, 5
  calculatedAnnotation, 5
  checkGPLsFallback, 6
  checkGSEType, 7
  collapseDataset, 7
  colMeansByGroups, 8
  convertByAnnotationDB, 8
  createDockerConf, 9
  createES, 10
  getArchs4Files, 12
  getCountsMetaPart, 13
  gseaPlot, 17
  isHSDS, 18
  limmaAnalysis, 18
  loadCounts, 19
  loadFromARCHS4, 20
  loadGEO, 20
  loadPreloaded, 21
  parseCharacteristics, 21
  performKmeans, 22
  queryAnnotationDBMeta, 23
  reproduceInR, 24
  shinyGAMAnalysis, 26
  subsetES, 27
  updateARCHS4, 27
  updateARCHS4meta, 28
  updateCountsMeta, 29
  updateDEE2meta, 29
  validateCountsCollection, 30

adjustDataset, 3
annotationDBMeta, 4

calcPCA, 5
calculatedAnnotation, 5
checkGPLsFallback, 6
checkGSEType, 7
collapseDataset, 7
colMeansByGroups, 8
convertByAnnotationDB, 8
createDockerConf, 9
createES, 10

es, 11

fgseaExample, 11

generatePreloadedSession, 11
getArchs4Files, 12
getCountsMetaPart, *13*, 13, *29*
getES, 14
getGDS, 15
getGSE, 15
getPhantasusConf, 16
gseaPlot, 17

isHSDS, 18

limmaAnalysis, 18
loadCounts, 19
loadFromARCHS4, 20
loadGEO, 20
loadPreloaded, 21

parseCharacteristics, 21
performKmeans, 22

queryAnnotationDBMeta, 23

read.gct, 23
reparseCachedESs, 24
reproduceInR, 24

servePhantasus, 25
setupPhantasus, 26
shinyGAMAnalysis, 26

subsetES, 27

updateARCHS4, 27
updateARCHS4meta, 28
updateCountsMeta, *29*, 29
updateDEE2meta, 29

validateCountsCollection, *13*, *28–30*, 30

write.gct, 31