Package 'rfPred'

November 12, 2026

Type Package

Title Assign rfPred functional prediction scores to a missense variants list

Version 1.50.0

Date 2025-07-23

Author Fabienne Jabot-Hanin, Hugo Varet and Jean-Philippe Jais

Depends R (>= 3.5.0), methods

Imports utils, Seqinfo, data.table, IRanges, GenomicRanges, parallel, Rsamtools

Suggests BiocStyle

Maintainer Hugo Varet <varethugo@gmail.com>

Description Based on external numerous data files where rfPred scores are pre-calculated on all genomic positions of the human exome, the package gives rfPred scores to missense variants identified by the chromosome, the position (hg19 version), the referent and alternative nucleotids and the uniprot identifier of the protein. Note that for using the package, the user has to download the TabixFile and index (approximately 3.3 Go).

License GPL (>=2)

Encoding UTF-8

biocViews Software, Annotation, Classification

RoxygenNote 7.3.2

git_url https://git.bioconductor.org/packages/rfPred

git_branch RELEASE_3_23

git_last_commit 8ef11e9

git_last_commit_date 2026-04-28

Repository Bioconductor 3.23

Date/Publication 2026-11-11

Contents

rfPred-package 2
example_GRanges 2
rfPred_scores 3
rfPred_scores_motor 6
variant_list_Y 7

Index **8**

`rfPred-package` *Assign functional prediction rfPred scores to human missense variants (random forest method based on SIFT, Polyphen2, PhyloP, LRT and Mutation Taster)*

Description

The package provides a function which returns the rfPred score for a list of non-synonymous missense variants. All the rfPred scores are pre-calculated and stored in a `TabixFile` available on a server and which can be downloaded for using the package while not connected on the Internet. The package does not work without an access to the `TabixFile`. However, a toy example on the chromosome Y is available within the package to test the `rfPred_scores` function. curves with numbers of subjects at risk, compare data sets, display spaghetti-plot, build multi-contingency tables...

Author(s)

Fabienne Jabot-Hanin, Hugo Varet and Jean-Philippe Jais

References

dbNSFP database: Liu X, Jian X and Boerwinkle E. 2011. dbNSFP: a lightweight database of human non-synonymous SNPs and their functional predictions. Human Mutation. 32:894-899.

rfPred method: Jabot-Hanin F, Varet H, Tores F and Jais J-P. 2013. rfPred: a new meta-score for functional prediction of missense variants in human exome (submitted).

`example_GRanges` *Toy example of GRanges object*

Description

Toy example of GRanges object

Format

A GRanges object with 11 rows and several columns:

seqnames Chromosome number (only Y in this example)

ranges IRanges object for which start=end: position on the chromosome

reference Referent nucleotid (A, C, G or T)

alteration Alteration nucleotid (A, C, G or T)

---

rfPred_scores *Assign functional prediction rfPred scores to human missense variants*

Description

rfPred is a statistical method which combines 5 algorithms predictions in a random forest model: SIFT, Polyphen2, LRT, PhyloP and MutationTaster. These scores are available in the dbNFSP database for all the possible missense variants in hg19 version, and the package rfPred gives a composite score more reliable than each of the isolated algorithms.

Usage

```
rfPred_scores(
  variant_list,
  data = system.file("extdata/chrY_rfPred.txtz", package = "rfPred"),
  index = system.file("extdata/chrY_rfPred.txtz.tbi", package = "rfPred"),
  all.col = FALSE,
  file.export = NULL,
  n.cores = 1
)

rfPred_scores(variant_list,
                data=system.file("extdata/chrY_rfPred.txtz", package="rfPred"),
              index=system.file("extdata/chrY_rfPred.txtz.tbi", package="rfPred"),
                    all.col=FALSE, file.export=NULL, n.cores=1)

## S4 method for signature 'character'
rfPred_scores(
  variant_list,
  data = system.file("extdata/chrY_rfPred.txtz", package = "rfPred"),
  index = system.file("extdata/chrY_rfPred.txtz.tbi", package = "rfPred"),
  all.col = FALSE,
  file.export = NULL,
  n.cores = 1
)

## S4 method for signature 'GRanges'
rfPred_scores(
```

```
  variant_list,
  data = system.file("extdata/chrY_rfPred.txtz", package = "rfPred"),
  index = system.file("extdata/chrY_rfPred.txtz.tbi", package = "rfPred"),
  all.col = FALSE,
  file.export = NULL,
  n.cores = 1
)
```

Arguments

variant_list	A variants list in a data.frame containing 4 or 5 columns: chromosome number, hg19 genomic position on the chromosome, reference nucleotid, variant nucleotid and uniprot protein identifier (optional); or a character string of the path to a VCF (Variant Call Format) file; or a GRanges object with metadata containing textually reference, alteration and proteine (optional) columns names for reference and alteration
data	Path to the compressed TabixFile, either on the server (default) or on the user's computer
index	Path to the index of the TabixFile, either on the server (default) or on the user's computer
all.col	TRUE to return all available information, FALSE to return a more compact result (the most informative columns, see Value)
file.export	Optional, name of the CSV file in which export the results (default is NULL)
n.cores	number of cores to use when scaning the TabixFile, can be efficient for large request (default is 1)

Value

The variants list with the assigned rfPred scores, as well as the scores used to build rfPred meta-score: SIFT, phyloP, MutationTaster, LRT (transformed) and Polyphen2 (corresponding to Polyphen2_HVAR_score). The data frame returned contains these columns:

chromosome	chromosome number
position_hg19	physical position on the chromosome as to hg19 (1-based coordinate)
reference	reference nucleotide allele (as on the + strand)
alteration	alternative nucleotide allele (as on the + strand)
proteine	Uniprot accession number
aaref	reference amino acid
aaalt	alternative amino acid
aapos	amino acid position as to the protein
rfPred_score	rfPred score betwen 0 and 1 (higher it is, higher is the probability of pathogenicity)
SIFT_score	SIFT score between 0 and 1 (higher it is, higher is the probability of pathogenicity contrary to the original SIFT score) = 1-original SIFT score

`Polyphen2_score`
: Polyphen2 (HVAR one) score between 0 and 1, used to calculate rfPred (higher it is, higher is the probability of pathogenicity)

`MutationTaster_score`
: MutationTaster score between 0 and 1 (higher it is, higher is the probability of pathogenicity)

`PhyloP_score`
: PhyloP score between 0 and 1 (higher it is, higher is the probability of pathogenicity): PhyloP_score=1-0.5x10^phyloP if phyloP>0 or PhyloP_score=0.5x10^-phyloP if phyloP<0

`LRT_score`
: LRT score between 0 and 1 (higher it is, higher is the probability of pathogenicity): LRT_score=1-LRToriginalx0.5 if LRT_Omega<1 or LRT_score=LRToriginalx0.5 if LRT_Omega>=1

The following columns are also returned if `all.col` is `TRUE`:

`Uniprot_id`
: Uniprot ID number

`genename`
: gene name

`position_hg18`
: physical position on the chromosome as to hg18 (1-based coordinate)

`Polyphen2_HDIV_score`
: Polyphen2 score based on HumDiv, i.e. hdiv_prob. The score ranges from 0 to 1: the corresponding prediction is "probably damaging" if it is in [0.957,1]; "possibly damaging" if it is in [0.453,0.956]; "benign" if it is in [0,0.452]. Score cut-off for binary classification is 0.5, i.e. the prediction is "neutral" if the score is lower than 0.5 and "deleterious" if the score is higher than 0.5. Multiple entries separated by ";"

`Polyphen2_HDIV_pred`
: Polyphen2 prediction based on HumDiv: `D` (probably damaging), `P` (possibly damaging) and `B` (benign). Multiple entries separated by ";"

`Polyphen2_HVAR_score`
: Polyphen2 score based on HumVar, i.e. hvar_prob. The score ranges from 0 to 1, and the corresponding prediction is "probably damaging" if it is in [0.909,1]; "possibly damaging" if it is in [0.447,0.908]; "benign" if it is in [0,0.446]. Score cut-off for binary classification is 0.5, i.e. the prediction is "neutral" if the score is lower than 0.5 and "deleterious" if the score is higher than 0.5. Multiple entries separated by ";"

`Polyphen2_HVAR_pred`
: Polyphen2 prediction based on HumVar: `D` (probably damaging), `P` (possibly damaging) and `B` (benign). Multiple entries separated by ";"

`MutationTaster_pred`
: MutationTaster prediction: `A` (disease_causing_automatic), `D` (disease_causing), `N` (polymorphism) or `P` (polymorphism_automatic)

`phyloP`
: original phyloP score

`LRT_Omega`
: estimated nonsynonymous-to-synonymous-rate ratio

`LRT_pred`
: LRT prediction, `D`(eleterious), `N`(eutral) or `U`(nknown)

Author(s)

Fabienne Jabot-Hanin, Hugo Varet and Jean-Philippe Jais

References

Jabot-Hanin F, Varet H, Tores F and Jais J-P. 2013. rfPred: a new meta-score for functional prediction of missense variants in human exome (submitted).

Examples

```
# from a data.frame without uniprot protein identifier
data(variant_list_Y)
res=rfPred_scores(variant_list = variant_list_Y[,1:4],
            data = system.file("extdata", "chrY_rfPred.txtz", package="rfPred",mustWork=TRUE),
            index = system.file("extdata", "chrY_rfPred.txtz.tbi", package="rfPred",mustWork=TRUE))
# from a data.frame with uniprot protein identifier
res2=rfPred_scores(variant_list = variant_list_Y,
             data = system.file("extdata", "chrY_rfPred.txtz", package="rfPred",mustWork=TRUE),
             index = system.file("extdata", "chrY_rfPred.txtz.tbi", package="rfPred",mustWork=TRUE))
# from a VCF file
res3=rfPred_scores(variant_list = system.file("extdata", "example.vcf", package="rfPred",mustWork=TRUE),
             data = system.file("extdata", "chrY_rfPred.txtz", package="rfPred",mustWork=TRUE),
             index = system.file("extdata", "chrY_rfPred.txtz.tbi", package="rfPred",mustWork=TRUE))
# from a GRanges object
data(example_GRanges)
res4=rfPred_scores(variant_list = example_GRanges,
             data = system.file("extdata", "chrY_rfPred.txtz", package="rfPred",mustWork=TRUE),
             index = system.file("extdata", "chrY_rfPred.txtz.tbi", package="rfPred",mustWork=TRUE))
```

---

rfPred_scores_motor *Motor of* rfPred_scores

Description

Motor of rfPred_scores

Usage

```
rfPred_scores_motor(variant_list, data, index, all.col, file.export, n.cores)
```

Arguments

variant_list	Variants list in a data.frame containing 4 or 5 columns: chromosome number, hg19 genomic position on the chromosome, reference nucleotid, variant nucleotid and uniprot protein identifier (optional)
data	Path to the compressed TabixFile, either on the server (default) or on the user's computer
index	Path to the index of the TabixFile, either on the server (default) or on the user's computer
all.col	TRUE to return all available information, FALSE to return a more compact result (the most informative columns, see Value)

file.export	Optional, name of the CSV file in which export the results (default is NULL)
n.cores	number of cores to use when scaning the TabixFile, can be efficient for large request (default is 1)

Value

see the rfPred_scores function

Note

This function is called by the rfPred_scores S4 method

---

variant_list_Y *Toy example of data.frame*

Description

Toy example of data.frame

Format

A data frame with 5 observations on the following 5 variables:

chr Chromosome number (only Y in this example)

pos Position on the chromosome (numeric)

ref Referent nucleotid (A, C, G or T)

alt Alteration nucleotid (A, C, G or T)

uniprot Uniprot protein identifier (factor)

Index

∗ **data**
example_GRanges, 2
variant_list_Y, 7

example_GRanges, 2

rfPred *(*rfPred-package*)*, 2
rfPred-package, 2
rfPred_scores, 3, *7*
rfPred_scores,character-method *(*rfPred_scores*)*, 3
rfPred_scores,data.frame-method *(*rfPred_scores*)*, 3
rfPred_scores,GRanges-method *(*rfPred_scores*)*, 3
rfPred_scores_motor, 6

variant_list_Y, 7