Package 'rsbml'

November 12, 2026

Version 2.70.0

Title R support for SBML, using libsbml

Author Michael Lawrence <michafla@gene.com>

Depends R (>= 2.6.0), BiocGenerics (>= 0.3.2), methods, utils

Imports BiocGenerics, graph, utils

SystemRequirements libsbml (==5.10.2)

Maintainer Michael Lawrence <michafla@gene.com>

Description Links R to libsbml for SBML parsing, validating output, provides an S4 SBML DOM, converts SBML to R graph objects. Optionally links to the SBML ODE Solver Library (SOSLib) for simulating models.

License Artistic-2.0

URL http://www.sbml.org

biocViews GraphAndNetwork, Pathways, Network

git_url https://git.bioconductor.org/packages/rsbml

git_branch RELEASE_3_23

git_last_commit 5cdd954

git_last_commit_date 2026-04-28

Repository Bioconductor 3.23

Date/Publication 2026-11-11

Contents

AlgebraicRule-class 3
AssignmentRule-class 4
BoundingBox-class 5
Compartment-class 6
CompartmentGlyph-class 7
CompartmentType-class 8
CompartmentVolumeRule-class 9

Constraint-class . . . 10
CubicBezier-class . . . 11
Curve-class . . . 13
CVTerm-class . . . 14
Delay-class . . . 15
describe . . . 16
Dimensions-class . . . 17
Event-class . . . 18
EventAssignment-class . . . 19
Experiment-class . . . 20
FunctionDefinition-class . . . 21
GraphicalObject-class . . . 22
InitialAssignment-class . . . 23
KineticLaw-class . . . 24
Layout-class . . . 25
LineSegment-class . . . 27
math . . . 28
Model-class . . . 29
ModelCreator-class . . . 31
ModelHistory-class . . . 32
ModifierSpeciesReference-class . . . 33
Parameter-class . . . 34
ParameterRule-class . . . 35
Point-class . . . 37
RateRule-class . . . 38
Reaction-class . . . 39
ReactionGlyph-class . . . 40
Rule-class . . . 42
SBase-class . . . 43
SBML import . . . 44
SBML-class . . . 45
SBMLDocument-class . . . 46
SBMLProblem-class . . . 48
SBMLProblems-class . . . 49
SimpleSpeciesReference-class . . . 49
SOSDesign-class . . . 50
SOSExperiment-class . . . 52
SOSProtocol-class . . . 53
SOSResult-class . . . 55
SOSSubject-class . . . 56
Species-class . . . 57
SpeciesConcentrationRule-class . . . 59
SpeciesGlyph-class . . . 60
SpeciesReference-class . . . 61
SpeciesReferenceGlyph-class . . . 62
SpeciesType-class . . . 63
StoichiometryMath-class . . . 64
TextGlyph-class . . . 65

Trigger-class 66
Unit-class 68
UnitDefinition-class 69

Index **71**

`AlgebraicRule-class` *SBML type "AlgebraicRule"*

Description

Expresses equations that are not assignments nor rates of change.

Instantiation

Objects can be created by calls of the form `new("AlgebraicRule", ...)`.

Slots

`math`**:** Object of class `"expression"` specifying the equation.

`metaId`**:** Object of class `"character"` that is an XML ID "described" by an RDF resource. This links an SBML element to an RDF resource. RDF may appear anywhere in an SBML element, but is usually placed inside the `annotation` element.

`notes`**:** Object of class `"character"` containing user-readable XHTML notes about an element.

`annotation`**:** Object of class `"character"` containing additional machine-readable information about an element, usually as RDF, such as BioPAX. This is where application-specific data belongs.

`cvTerms`**:** Object of class `"list"` containing instances of `CVTerm` associated with this element.

`sboTerm`**:** Object of class `"integer"` identifying a term in the Systems Biology Ontology (SBO).

Extends

Class `"Rule"`, directly. Class `"SBase"`, by class "Rule", distance 2.

Methods

No methods defined with class "AlgebraicRule" in the signature.

Author(s)

Michael Lawrence

References

`http://sbml.org/documents/`

`AssignmentRule-class` *SBML type "AssignmentRule"*

Description

An equation that assigns a value to the quantity of a `Species`, the size of a `Compartment` or the value of a `Parameter`.

Instantiation

Objects can be created by calls of the form `new("AssignmentRule", ...)`.

Slots

`variable`**:** Object of class `"character"` naming the variable (the id of a `Species`, `Compartment` or `Parameter`) to set.

`type`**:** Object of class `"character"`, deprecated.

`math`**:** Object of class `"expression"` specifying the equation.

`metaId`**:** Object of class `"character"` that is an XML ID "described" by an RDF resource. This links an SBML element to an RDF resource. RDF may appear anywhere in an SBML element, but is usually placed inside the `annotation` element.

`notes`**:** Object of class `"character"` containing user-readable XHTML notes about an element.

`annotation`**:** Object of class `"character"` containing additional machine-readable information about an element, usually as RDF, such as BioPAX. This is where application-specific data belongs.

`cvTerms`**:** Object of class `"list"` containing instances of `CVTerm` associated with this element.

`sboTerm`**:** Object of class `"integer"` identifying a term in the Systems Biology Ontology (SBO).

Extends

Class `"Rule"`, directly. Class `"SBase"`, by class "Rule", distance 2.

Methods

variable `signature(object = "AssignmentRule")`: gets the `variable` slot

variable<- `signature(object = "AssignmentRule")`: sets the `variable` slot

type `signature(object = "AssignmentRule")`: gets the `type` slot

type<- `signature(object = "AssignmentRule")`: sets the `type` slot

Author(s)

Michael Lawrence

References

http://sbml.org/documents/

BoundingBox-class *SBML type "BoundingBox"*

Description

Species the size and position of an SBML layout object.

Instantiation

Objects can be created by calls of the form `new("BoundingBox", ...)`.

Slots

`id`: Object of class `"character"` uniquely identifying this component.

`position`: Object of class `"Point"` specifying the positon.

`dimensions`: Object of class `"Dimensions"` specifying the size.

`metaId`: Object of class `"character"` that is an XML ID "described" by an RDF resource. This links an SBML element to an RDF resource. RDF may appear anywhere in an SBML element, but is usually placed inside the `annotation` element.

`notes`: Object of class `"character"` containing user-readable XHTML notes about an element.

`annotation`: Object of class `"character"` containing additional machine-readable information about an element, usually as RDF, such as BioPAX. This is where application-specific data belongs.

`cvTerms`: Object of class `"list"` containing instances of `CVTerm` associated with this element.

`sboTerm`: Object of class `"integer"` identifying a term in the Systems Biology Ontology (SBO).

Extends

Class `"SBase"`, directly.

Methods

id `signature(object = "BoundingBox")`: gets the `id` slot

id<- `signature(object = "BoundingBox")`: sets the `id` slot

dimensions `signature(object = "BoundingBox")`: gets the `dimensions` slot

dimensions<- `signature(object = "BoundingBox")`: sets the `dimensions` slot

position `signature(object = "BoundingBox")`: gets the `position` slot

position<- `signature(object = "BoundingBox")`: sets the `position` slot

Author(s)

Michael Lawrence

References

http://projects.villa-bosch.de/bcb/sbml

`Compartment-class` *SBML type "Compartment"*

Description

A bounded space that contains `Species`.

Instantiation

Objects can be created by calls of the form `new("Compartment", ...)`.

Slots

`id`: Object of class `"character"` uniquely identifying this component.

`name`: Object of class `"character"` naming this component.

`spatialDimensions`: Object of class `"integer"` indicating the number of dimensions (0, 1, 2, or 3)

`size`: Object of class `"numeric"` indicating the size in the given units.

`units`: Object of class `"character"` indicating the units (built-in or the id of a `UnitDefinition`).

`outside`: Object of class `"character"` identifying the compartment containing this compartment.

`constant`: Object of class `"logical"` indicating whether the size changes during simulation.

`metaId`: Object of class `"character"` that is an XML ID "described" by an RDF resource. This links an SBML element to an RDF resource. RDF may appear anywhere in an SBML element, but is usually placed inside the `annotation` element.

`notes`: Object of class `"character"` containing user-readable XHTML notes about an element.

`annotation`: Object of class `"character"` containing additional machine-readable information about an element, usually as RDF, such as BioPAX. This is where application-specific data belongs.

`cvTerms`: Object of class `"list"` containing instances of `CVTerm` associated with this element.

`sboTerm`: Object of class `"integer"` identifying a term in the Systems Biology Ontology (SBO).

Extends

Class `"SBase"`, directly.

Methods

id `signature(object = "Compartment")`: gets the `id` slot

id<- `signature(object = "Compartment")`: sets the `id` slot

name `signature(object = "Compartment")`: gets the `name` slot

name<- `signature(object = "Compartment")`: sets the `name` slot

constant `signature(object = "Compartment")`: gets the `constant` slot

constant<- `signature(object = "Compartment")`: sets the `constant` slot

outside `signature(object = "Compartment")`: gets the `outside` slot

outside<- `signature(object = "Compartment")`: sets the `outside` slot

size `signature(object = "Compartment")`: gets the `size` slot

size<- `signature(object = "Compartment")`: sets the `size` slot

units `signature(object = "Compartment")`: gets the `constant` slot

units<- `signature(object = "Compartment")`: sets the `constant` slot

spatialDimensions `signature(object = "Compartment")`: gets the `spatialDimensions` slot

spatialDimensions<- `signature(object = "Compartment")`: sets the `spatialDimensions` slot

Author(s)

Michael Lawrence

References

http://sbml.org/documents/

CompartmentGlyph-class

SBML type "CompartmentGlyph"

Description

A glyph representing a `Compartment`.

Instantiation

Objects can be created by calls of the form `new("CompartmentGlyph", ...)`.

Slots

`compartment`: Object of class `"character"` identifying the compartment this glyph represents.

`id`: Object of class `"character"` uniquely identifying this component.

`boundingBox`: Object of class `"BoundingBox"` describing the position and size of the graphical object.

`metaId`: Object of class `"character"` that is an XML ID "described" by an RDF resource. This links an SBML element to an RDF resource. RDF may appear anywhere in an SBML element, but is usually placed inside the `annotation` element.

`notes`: Object of class `"character"` containing user-readable XHTML notes about an element.

`annotation`: Object of class `"character"` containing additional machine-readable information about an element, usually as RDF, such as BioPAX. This is where application-specific data belongs.

`cvTerms`: Object of class `"list"` containing instances of `CVTerm` associated with this element.

`sboTerm`: Object of class `"integer"` identifying a term in the Systems Biology Ontology (SBO).

Extends

Class "GraphicalObject", directly. Class "SBase", by class "GraphicalObject", distance 2.

Methods

compartment `signature(object = "CompartmentGlyph")`: gets the `compartment` slot

compartment<- `signature(object = "CompartmentGlyph")`: sets the `compartment` slot

Author(s)

Michael Lawrence

References

http://projects.villa-bosch.de/bcb/sbml

CompartmentType-class *SBML Type "CompartmentType"*

Description

Declares a type of Compartment. Compartments with the same type are logically similar.

Objects from the Class

Objects can be created by calls of the form `new("CompartmentType", ...)`.

Slots

id: Object of class "character" uniquely identifying this component.

name: Object of class "character" naming this component.

metaId: Object of class "character" that is an XML ID "described" by an RDF resource. This links an SBML element to an RDF resource. RDF may appear anywhere in an SBML element, but is usually placed inside the annotation element.

notes: Object of class "character" containing user-readable XHTML notes about an element.

annotation: Object of class "character" containing additional machine-readable information about an element, usually as RDF, such as BioPAX. This is where application-specific data belongs.

cvTerms: Object of class "list" containing instances of CVTerm associated with this element.

sboTerm: Object of class "integer" identifying a term in the Systems Biology Ontology (SBO).

Extends

Class "SBase", directly.

Methods

id `signature(object = "CompartmentType")`: gets the `id` slot

id<- `signature(object = "CompartmentType")`: sets the `id` slot

name `signature(object = "CompartmentType")`: gets the `name` slot

name<- `signature(object = "CompartmentType")`: sets the `name` slot

Note

Requires libsbml >= 3.0

Author(s)

Michael Lawrence

References

http://sbml.org/documents/

See Also

`Compartment`

CompartmentVolumeRule-class

SBML type "CompartmentVolumeRule"

Description

Obsolete way to assign a volume to a `Compartment`.

Instantiation

Objects can be created by calls of the form `new("CompartmentVolumeRule", ...)`.

Slots

`compartment`**:** Object of class `"character"` identifying the compartment

`variable`**:** Object of class `"character"`, ignored.

`type`**:** Object of class `"character"`, deprecated.

`math`**:** Object of class `"expression"` specifying the equation.

`metaId`**:** Object of class `"character"` that is an XML ID "described" by an RDF resource. This links an SBML element to an RDF resource. RDF may appear anywhere in an SBML element, but is usually placed inside the `annotation` element.

`notes`**:** Object of class `"character"` containing user-readable XHTML notes about an element.

annotation: Object of class "character" containing additional machine-readable information about an element, usually as RDF, such as BioPAX. This is where application-specific data belongs.

cvTerms: Object of class "list" containing instances of CVTerm associated with this element.

sboTerm: Object of class "integer" identifying a term in the Systems Biology Ontology (SBO).

Extends

Class "AssignmentRule", directly. Class "Rule", by class "AssignmentRule", distance 2. Class "SBase", by class "AssignmentRule", distance 3.

Methods

compartment signature(object = "CompartmentVolumeRule"): gets the compartment slot

compartment<- signature(object = "CompartmentVolumeRule"): sets the compartment slot

Author(s)

Michael Lawrence

References

http://sbml.org/documents/

Constraint-class *SBML Type "Constraint"*

Description

A constraint that must be continuously satisfied throughout the simulation of a model. Once a constraint is no longer met, the simulation must halt.

Objects from the Class

Objects can be created by calls of the form new("Constraint", ...).

Slots

math: Object of class "expression" that evaluates to FALSE if the constraint is not satisfied, otherwise evaluates to TRUE.

message: Object of class "character", formatted in XHTML, that is displayed to the user by an application when the constraint is not satisfied.

metaId: Object of class "character" that is an XML ID "described" by an RDF resource. This links an SBML element to an RDF resource. RDF may appear anywhere in an SBML element, but is usually placed inside the annotation element.

notes: Object of class "character" containing user-readable XHTML notes about an element.

`annotation`: Object of class `"character"` containing additional machine-readable information about an element, usually as RDF, such as BioPAX. This is where application-specific data belongs.

`cvTerms`: Object of class `"list"` containing instances of `CVTerm` associated with this element.

`sboTerm`: Object of class `"integer"` identifying a term in the Systems Biology Ontology (SBO).

Extends

Class `"SBase"`, directly.

Methods

math `signature(domain = "Constraint")`: gets the `math` slot.

math<- `signature(object = "Constraint")`: sets the `math` slot.

msg `signature(domain = "Constraint")`: gets the `msg` slot.

msg<- `signature(object = "Constraint")`: sets the `msg` slot.

Note

Requires libsbml >= 3.0

Author(s)

Michael Lawrence

References

http://sbml.org/documents/

CubicBezier-class *SBML type "CubicBezier"*

Description

A cubic bezier curve in an SBML layout.

Instantiation

Objects can be created by calls of the form `new("CubicBezier", ...)`.

Slots

`basePoint1`: Object of class `"Point"` indicating the position of the base point closest to the starting point.

`basePoint2`: Object of class `"Point"` indicating the position of the base point farthest from the starting point.

`start`: Object of class `"Point"` ~~

`end`: Object of class `"Point"` ~~

`metaId`: Object of class `"character"` that is an XML ID "described" by an RDF resource. This links an SBML element to an RDF resource. RDF may appear anywhere in an SBML element, but is usually placed inside the `annotation` element.

`notes`: Object of class `"character"` containing user-readable XHTML notes about an element.

`annotation`: Object of class `"character"` containing additional machine-readable information about an element, usually as RDF, such as BioPAX. This is where application-specific data belongs.

`cvTerms`: Object of class `"list"` containing instances of `CVTerm` associated with this element.

`sboTerm`: Object of class `"integer"` identifying a term in the Systems Biology Ontology (SBO).

Extends

Class `"LineSegment"`, directly. Class `"SBase"`, by class "LineSegment", distance 2.

Methods

basePoint1 `signature(object = "CubicBezier")`: gets the `basePoint1` slot

basePoint1<- `signature(object = "CubicBezier")`: sets the `basePoint1` slot

basePoint2 `signature(object = "CubicBezier")`: gets the `basePoint2` slot

basePoint2<- `signature(object = "CubicBezier")`: sets the `basePoint2` slot

Author(s)

Michael Lawrence

References

http://projects.villa-bosch.de/bcb/sbml

Curve-class *SBML type "Curve"*

Description

A curve (list of line segments) in an SBML layout.

Instantiation

Objects can be created by calls of the form `new("Curve", ...)`.

Slots

`curveSegments`**:** Object of class `"list"` containing the `LineSegment`s that compose the curve.

`metaId`**:** Object of class `"character"` that is an XML ID "described" by an RDF resource. This links an SBML element to an RDF resource. RDF may appear anywhere in an SBML element, but is usually placed inside the `annotation` element.

`notes`**:** Object of class `"character"` containing user-readable XHTML notes about an element.

`annotation`**:** Object of class `"character"` containing additional machine-readable information about an element, usually as RDF, such as BioPAX. This is where application-specific data belongs.

`cvTerms`**:** Object of class `"list"` containing instances of `CVTerm` associated with this element.

`sboTerm`**:** Object of class `"integer"` identifying a term in the Systems Biology Ontology (SBO).

Extends

Class `"SBase"`, directly.

Methods

curveSegments `signature(object = "Curve")`: gets the `curveSegments` slot

curveSegments<- `signature(object = "Curve")`: sets the `curveSegments` slot

Author(s)

Michael Lawrence

References

http://projects.villa-bosch.de/bcb/sbml

`CVTerm-class` *SBML Type "CVTerm"*

Description

A MIRIAM annotation, consisting of a qualifier ("model", "biological" or something else) and a resource (URI).

Objects from the Class

Objects can be created by calls of the form `new("CVTerm", ...)`.

Slots

`qualifierType`**:** Object of class `"character"` specifying the type of qualifier for this term. Types "model" and "biological" have special meaning, but any string may be specified.

`modelQualifierType`**:** Object of class `"character"` specifying the type of model qualifier, if `qualifierType` is set to "model". Types "is" and "isDescribedBy" are formally defined in MIRIAM, but any string may be specified.

`biologicalQualifierType`**:** Object of class `"character"` specifying the type of biological qualifier, if `qualifierType` is set to "biological". Types "is", "hasPart", "isPartOf", "isVersionOf", "hasVersion", "isHomologTo", and "isDescribedBy" are formally defined in MIRIAM, though any string may be specified.

`resources`**:** Object of class `"character"` specifying a URI that identifies some resource related an SBML element by the qualifier.

Methods

biologicalQualifierType `signature(object = "CVTerm")`: gets the `biologicalQualifierType` slot.

biologicalQualifierType<- `signature(object = "CVTerm")`: sets the `biologicalQualifierType` slot.

modelQualifierType `signature(object = "CVTerm")`: gets the `modelQualifierType` slot.

modelQualifierType<- `signature(object = "CVTerm")`: sets the `modelQualifierType` slot.

qualifierType `signature(object = "CVTerm")`: gets the `qualifierType` slot.

qualifierType<- `signature(object = "CVTerm")`: sets the `qualifierType` slot.

resources `signature(object = "CVTerm")`: gets the `resources` slot.

resources<- `signature(object = "CVTerm")`: sets the `resources` slot.

Author(s)

Michael Lawrence

References

http://sbml.org/documents/

Delay-class *SBML Type "Delay"*

Description

The length of time between the Triggering of an Event and the execution of its EventAssignments.

Objects from the Class

Objects can be created by calls of the form `new("Delay", ...)`.

Slots

math: Object of class `"expression"` that evaluates to a quantity of time.

metaId: Object of class `"character"` that is an XML ID "described" by an RDF resource. This links an SBML element to an RDF resource. RDF may appear anywhere in an SBML element, but is usually placed inside the `annotation` element.

notes: Object of class `"character"` containing user-readable XHTML notes about an element.

annotation: Object of class `"character"` containing additional machine-readable information about an element, usually as RDF, such as BioPAX. This is where application-specific data belongs.

cvTerms: Object of class `"list"` containing instances of CVTerm associated with this element.

sboTerm: Object of class `"integer"` identifying a term in the Systems Biology Ontology (SBO).

Extends

Class "SBase", directly.

Methods

math `signature(domain = "Delay")`: gets the `math` slot.

math<- `signature(object = "Delay")`: sets the `math` slot.

Note

Requires libsbml >= 3.0

Author(s)

Michael Lawrence

References

http://sbml.org/documents/

See Also

Event

`describe` *Describing objects*

Description

Each class in the SBML DOM extends the `Describable` class and thus has a `describe` method, which describes an object with a short string. This is used by the `show` method to output terse textual representations of the DOM.

Usage

```
describe(object, ...)
```

Arguments

`object`	The object to be described.
`...`	Additional arguments for methods.

Value

A short textual (string) representation of `object`.

Describable objects

An object that extends `Describable` has a method for the `describe` generic, and by default `Describable` objects are `shown` by printing the output of `describe`. Note that `Describable` is a virtual tag class, no objects may be created from it.

Describable methods

show `signature(object = "Describable")`: outputs the return value of `describe`.

Author(s)

Michael Lawrence

`Dimensions-class` *SBML type "Dimensions"*

Description

Holds the size of an SBML layout object.

Instantiation

Objects can be created by calls of the form `new("Dimensions", ...)`.

Slots

`width`: Object of class `"numeric"` indicating the width, in pixels

`height`: Object of class `"numeric"` indicating the height, in pixels

`depth`: Object of class `"numeric"` indicating the depth, in pixels

`metaId`: Object of class `"character"` that is an XML ID "described" by an RDF resource. This links an SBML element to an RDF resource. RDF may appear anywhere in an SBML element, but is usually placed inside the `annotation` element.

`notes`: Object of class `"character"` containing user-readable XHTML notes about an element.

`annotation`: Object of class `"character"` containing additional machine-readable information about an element, usually as RDF, such as BioPAX. This is where application-specific data belongs.

`cvTerms`: Object of class `"list"` containing instances of `CVTerm` associated with this element.

`sboTerm`: Object of class `"integer"` identifying a term in the Systems Biology Ontology (SBO).

Extends

Class `"SBase"`, directly.

Methods

depth `signature(object = "Dimensions")`: gets the `depth` slot

depth<- `signature(object = "Dimensions")`: sets the `depth` slot

height `signature(object = "Dimensions")`: gets the `height` slot

height<- `signature(object = "Dimensions")`: sets the `height` slot

width `signature(object = "Dimensions")`: gets the `width` slot

width<- `signature(object = "Dimensions")`: sets the `width` slot

Author(s)

Michael Lawrence

References

http://projects.villa-bosch.de/bcb/sbml

`Event-class` *SBML type "Event"*

Description

Description of a instantaneous, discontinuous change in the model state.

Instantiation

Objects can be created by calls of the form `new("Event", ...)`.

Slots

`id`: Object of class `"character"` uniquely identifying this component.

`name`: Object of class `"character"` naming this component.

`trigger`: Object of class `"expression"` that evaluates to `TRUE` when the event is to be fired.

`eventDelay`: Object of class `"expression"` that evaluates to the time until execution of this event after it has been fired.

`timeUnits`: Object of class `"character"` identifying the units of the delay.

`eventAssignments`: Object of class `"list"` containing `EventAssignment`s that are performed at execution.

`useValuesFromTriggerTime`: Object of class `"logical"`. If `FALSE`, the event is evaluated after the delay, rather than when the event is executed.

`metaId`: Object of class `"character"` that is an XML ID "described" by an RDF resource. This links an SBML element to an RDF resource. RDF may appear anywhere in an SBML element, but is usually placed inside the `annotation` element.

`notes`: Object of class `"character"` containing user-readable XHTML notes about an element.

`annotation`: Object of class `"character"` containing additional machine-readable information about an element, usually as RDF, such as BioPAX. This is where application-specific data belongs.

`cvTerms`: Object of class `"list"` containing instances of `CVTerm` associated with this element.

`sboTerm`: Object of class `"integer"` identifying a term in the Systems Biology Ontology (SBO).

Extends

Class `"SBase"`, directly.

Methods

id `signature(object = "Event")`: gets the `id` slot

id<- `signature(object = "Event")`: sets the `id` slot

name `signature(object = "Event")`: gets the `name` slot

name<- `signature(object = "Event")`: sets the `name` slot

timeUnits `signature(object = "Event")`: gets the `timeUnits` slot

timeUnits<- `signature(object = "Event")`: sets the `timeUnits` slot

eventDelay `signature(x = "Event")`: ...

eventDelay<- `signature(object = "Event")`: sets the `delay` slot

eventAssignments `signature(object = "Event")`: gets the `eventAssignments` slot

eventAssignments<- `signature(object = "Event")`: sets the `eventAssignments` slot

trigger `signature(object = "Event")`: gets the `trigger` slot

trigger<- `signature(object = "Event")`: sets the `trigger` slot

Author(s)

Michael Lawrence

References

http://sbml.org/documents/

`EventAssignment-class` *SBML type "EventAssignment"*

Description

As part of an event, assigns a value to the quantity of a `Species`, the size of a `Compartment` or the value of a `Parameter`.

Instantiation

Objects can be created by calls of the form `new("EventAssignment", ...)`.

Slots

`variable`: Object of class `"character"` ~~

`math`: Object of class `"expression"` that evaluates to the value to assign.

`metaId`: Object of class `"character"` that is an XML ID "described" by an RDF resource. This links an SBML element to an RDF resource. RDF may appear anywhere in an SBML element, but is usually placed inside the `annotation` element.

`notes`: Object of class `"character"` containing user-readable XHTML notes about an element.

`annotation`: Object of class `"character"` containing additional machine-readable information about an element, usually as RDF, such as BioPAX. This is where application-specific data belongs.

`cvTerms`: Object of class `"list"` containing instances of `CVTerm` associated with this element.

`sboTerm`: Object of class `"integer"` identifying a term in the Systems Biology Ontology (SBO).

Extends

Class "SBase", directly.

Methods

math signature(object = "EventAssignment"): gets the math slot

math<- signature(object = "EventAssignment"): sets the math slot

variable signature(object = "EventAssignment"): gets the variable slot

variable<- signature(object = "EventAssignment"): sets the variable slot

Author(s)

Michael Lawrence

References

http://sbml.org/documents/

Experiment-class *Experiment*

Description

This class is an abstraction for an experiment, e.g. in a simulation. An experiment consists of a ExperimentProtocol, ExperimentDesign, ExperimentSubject and ExperimentResult.

Objects from the Class

A virtual Class: No objects may be created from it.

Slots

protocol: Object of empty virtual class ExperimentProtocol, how the experiment was or is to be performed.

design: Object of empty virtual class ExperimentDesign, the design of the experiment.

subject: Object of empty virtual class ExperimentSubject, the object being observed by the experiment.

result: Object of empty virtual class ExperimentResult, the result of the experiment.

Methods

design `signature(object = "Experiment")`: Gets the `design` slot.

design<- `signature(object = "Experiment")`: Sets the `design` slot.

protocol `signature(object = "Experiment")`: Gets the `protocol` slot.

protocol<- `signature(object = "Experiment")`: Sets the `protocol` slot.

result `signature(object = "Experiment")`: Gets the `result` slot.

result<- `signature(object = "Experiment")`: Sets the `result` slot.

subject `signature(object = "Experiment")`: Gets the `subject` slot.

subject<- `signature(object = "Experiment")`: Sets the `subject` slot.

Author(s)

Michael Lawrence

See Also

`SOSExperiment`, an implementation that simulates SBML modules using the SBML ODE Solver library.

`FunctionDefinition-class`

SBML type "FunctionDefinition"

Description

Identifies a mathematical expression so that it may be referenced in other expressions.

Instantiation

Objects can be created by calls of the form `new("FunctionDefinition", ...)`.

Slots

`id`: Object of class `"character"` uniquely identifying this component.

`name`: Object of class `"character"` naming this component.

`math`: Object of class `"expression"` that defines the function.

`metaId`: Object of class `"character"` that is an XML ID "described" by an RDF resource. This links an SBML element to an RDF resource. RDF may appear anywhere in an SBML element, but is usually placed inside the `annotation` element.

`notes`: Object of class `"character"` containing user-readable XHTML notes about an element.

`annotation`: Object of class `"character"` containing additional machine-readable information about an element, usually as RDF, such as BioPAX. This is where application-specific data belongs.

`cvTerms`: Object of class `"list"` containing instances of `CVTerm` associated with this element.

`sboTerm`: Object of class `"integer"` identifying a term in the Systems Biology Ontology (SBO).

Extends

Class "SBase", directly.

Methods

id signature(object = "FunctionDefinition"): gets the id slot

id<- signature(object = "FunctionDefinition"): sets the id slot

name signature(object = "FunctionDefinition"): gets the name slot

name<- signature(object = "FunctionDefinition"): sets the name slot

math signature(object = "FunctionDefinition"): gets the math slot

math<- signature(object = "FunctionDefinition"): sets the math slot

Author(s)

Michael Lawrence

References

http://sbml.org/documents/

GraphicalObject-class *SBML type "GraphicalObject"*

Description

The base class for graphical objects (e.g. glyphs) in SBML layouts.

Instantiation

Objects can be created by calls of the form new("GraphicalObject", ...).

Slots

id: Object of class "character" uniquely identifying this component.

boundingBox: Object of class "BoundingBox" describing the position and size of the graphical object.

metaId: Object of class "character" that is an XML ID "described" by an RDF resource. This links an SBML element to an RDF resource. RDF may appear anywhere in an SBML element, but is usually placed inside the annotation element.

notes: Object of class "character" containing user-readable XHTML notes about an element.

annotation: Object of class "character" containing additional machine-readable information about an element, usually as RDF, such as BioPAX. This is where application-specific data belongs.

cvTerms: Object of class "list" containing instances of CVTerm associated with this element.

sboTerm: Object of class "integer" identifying a term in the Systems Biology Ontology (SBO).

Extends

Class "SBase", directly.

Methods

id signature(object = "GraphicalObject"): gets the id slot

id<- signature(object = "GraphicalObject"): sets the id slot

boundingBox signature(object = "GraphicalObject"): gets the boundingBox slot

boundingBox<- signature(object = "GraphicalObject"): sets the boundingBox slot

Author(s)

Michael Lawrence

References

http://projects.villa-bosch.de/bcb/sbml

InitialAssignment-class

SBML Type "InitialAssignment"

Description

Calculates the value of a symbol when the model is initialized.

Objects from the Class

Objects can be created by calls of the form new("InitialAssignment", ...).

Slots

symbol: Object of class "character" to which the value is assigned.

math: Object of class "expression" that evaluates to the assigned value.

metaId: Object of class "character" that is an XML ID "described" by an RDF resource. This links an SBML element to an RDF resource. RDF may appear anywhere in an SBML element, but is usually placed inside the annotation element.

notes: Object of class "character" containing user-readable XHTML notes about an element.

annotation: Object of class "character" containing additional machine-readable information about an element, usually as RDF, such as BioPAX. This is where application-specific data belongs.

cvTerms: Object of class "list" containing instances of CVTerm associated with this element.

sboTerm: Object of class "integer" identifying a term in the Systems Biology Ontology (SBO).

Extends

Class "SBase", directly.

Methods

math signature(object = "InitialAssignment"): gets the math slot.

math<- signature(object = "InitialAssignment"): sets the math slot.

symbol signature(object = "InitialAssignment"): gets the symbol slot.

symbol<- signature(object = "InitialAssignment"): sets the symbol slot.

Note

Requires libsbml >= 3.0

Author(s)

Michael Lawrence

References

http://sbml.org/documents/

See Also

AssignmentRule, which can set a value at any time but cannot set constants.

KineticLaw-class *SBML type "KineticLaw"*

Description

Describes the rate of a Reaction.

Instantiation

Objects can be created by calls of the form new("KineticLaw", ...).

Slots

math: Object of class "expression" defining the rate of the reaction.

parameters: Object of class "list" containing Parameters that may be used in math. The names of the list correspond to the IDs of the elements.

timeUnits: Object of class "character" indicating the units for time.

substanceUnits: Object of class "character" indicating the units for substance.

`metaId`: Object of class `"character"` that is an XML ID "described" by an RDF resource. This links an SBML element to an RDF resource. RDF may appear anywhere in an SBML element, but is usually placed inside the `annotation` element.

`notes`: Object of class `"character"` containing user-readable XHTML notes about an element.

`annotation`: Object of class `"character"` containing additional machine-readable information about an element, usually as RDF, such as BioPAX. This is where application-specific data belongs.

`cvTerms`: Object of class `"list"` containing instances of `CVTerm` associated with this element.

`sboTerm`: Object of class `"integer"` identifying a term in the Systems Biology Ontology (SBO).

Extends

Class `"SBase"`, directly.

Methods

math `signature(object = "KineticLaw")`: gets the `math` slot

math<- `signature(object = "KineticLaw")`: sets the `math` slot

substanceUnits `signature(object = "KineticLaw")`: gets the `substanceUnits` slot

substanceUnits<- `signature(object = "KineticLaw")`: sets the `substanceUnits` slot

timeUnits `signature(object = "KineticLaw")`: gets the `timeUnits` slot

timeUnits<- `signature(object = "KineticLaw")`: sets the `timeUnits` slot

parameters `signature(object = "KineticLaw")`: gets the `parameters` slot

parameters<- `signature(object = "KineticLaw")`: sets the `parameters` slot

Author(s)

Michael Lawrence

References

http://sbml.org/documents/

Layout-class *SBML type "Layout"*

Description

Contains the glyphs and other graphical objects that compose an SBML layout. Layouts are not part of the core SBML specification. See the reference for the SBML layout extension specification.

Instantiation

Objects can be created by calls of the form `new("Layout", ...)`.

Slots

id: Object of class "character" uniquely identifying this component.

dimensions: Object of class "Dimensions" specifing the size of the layout.

compartmentGlyphs: Object of class "list" containing the CompartmentGlyphs. The names of the list correspond to the IDs of the elements.

speciesGlyphs: Object of class "list" containing the SpeciesGlyphs. The names of the list correspond to the IDs of the elements.

reactionGlyphs: Object of class "list" containing the ReactionGlyphs. The names of the list correspond to the IDs of the elements.

textGlyphs: Object of class "list" containing the TextGlyphs. The names of the list correspond to the IDs of the elements.

additionalGraphicalObjects: Object of class "list" containing the additional GraphicalObjects that are not bound to any model component. The names of the list correspond to the IDs of the elements.

metaId: Object of class "character" that is an XML ID "described" by an RDF resource. This links an SBML element to an RDF resource. RDF may appear anywhere in an SBML element, but is usually placed inside the annotation element.

notes: Object of class "character" containing user-readable XHTML notes about an element.

annotation: Object of class "character" containing additional machine-readable information about an element, usually as RDF, such as BioPAX. This is where application-specific data belongs.

cvTerms: Object of class "list" containing instances of CVTerm associated with this element.

sboTerm: Object of class "integer" identifying a term in the Systems Biology Ontology (SBO).

Extends

Class "SBase", directly.

Methods

id signature(object = "Layout"): gets the id slot

id<- signature(object = "Layout"): sets the id slot

additionalGraphicalObjects signature(object = "Layout"): gets the additionalGraphicalObjects slot

additionalGraphicalObjects<- signature(object = "Layout"): sets the additionalGraphicalObjects slot

compartmentGlyphs signature(object = "Layout"): gets the compartmentGlyphs slot

compartmentGlyphs<- signature(object = "Layout"): sets the compartmentGlyphs slot

dimensions signature(object = "Layout"): gets the dimensions slot

dimensions<- signature(object = "Layout"): sets the dimensions slot

reactionGlyphs signature(object = "Layout"): gets the reactionGlyphs slot

reactionGlyphs<- signature(object = "Layout"): sets the reactionGlyphs slot

speciesGlyphs `signature(object = "Layout")`: gets the `speciesGlyphs` slot

speciesGlyphs<- `signature(object = "Layout")`: sets the `speciesGlyphs` slot

textGlyphs `signature(object = "Layout")`: gets the `textGlyphs` slot

textGlyphs<- `signature(object = "Layout")`: sets the `textGlyphs` slot

Author(s)

Michael Lawrence

References

http://projects.villa-bosch.de/bcb/sbml

`LineSegment-class` *SBML type "LineSegment"*

Description

Describes a simple A-B line.

Instantiation

Objects can be created by calls of the form `new("LineSegment", ...)`.

Slots

`start`: Object of class `"Point"` indicating the start position.

`end`: Object of class `"Point"` indicating the end position.

`metaId`: Object of class `"character"` that is an XML ID "described" by an RDF resource. This links an SBML element to an RDF resource. RDF may appear anywhere in an SBML element, but is usually placed inside the `annotation` element.

`notes`: Object of class `"character"` containing user-readable XHTML notes about an element.

`annotation`: Object of class `"character"` containing additional machine-readable information about an element, usually as RDF, such as BioPAX. This is where application-specific data belongs.

`cvTerms`: Object of class `"list"` containing instances of `CVTerm` associated with this element.

`sboTerm`: Object of class `"integer"` identifying a term in the Systems Biology Ontology (SBO).

Extends

Class `"SBase"`, directly.

Methods

end `signature(x = "LineSegment")`: ...

end<- `signature(object = "LineSegment")`: sets the end slot

start `signature(x = "LineSegment")`: ...

start<- `signature(object = "LineSegment")`: sets the `start` slot

Author(s)

Michael Lawrence

References

http://projects.villa-bosch.de/bcb/sbml

`math` *MathML Utilities*

Description

Each of these functions implements a trigonometry function found in the MathML specification but not found in base R. These are all simple wrappers around existing R trig functions.

Usage

```
acot(x)
acoth(x)
acsc(x)
acsch(x)
asec(x)
asech(x)
cot(x)
coth(x)
csc(x)
csch(x)
sec(x)
sech(x)
```

Arguments

`x`	The `numeric` value(s) for the trigonometry operation

Value

A `numeric` vector, the same length as `x`.

Author(s)

Michael Lawrence

Model-class *SBML type "Model"*

Description

The central SBML element. Contains the Species, Reactions, Compartments and other components of the model. See the SBML specification, at the reference, for further details.

Instantiation

Objects can be created by calls of the form `new("Model", ...)`.

Slots

`id`: Object of class `"character"` uniquely identifying this component.

`name`: Object of class `"character"` naming this component.

`functionDefinitions`: Object of class `"list"` containing FunctionDefinitions. The names of the list correspond to the IDs of the elements.

`unitDefinitions`: Object of class `"list"` containing UnitDefinitions. The names of the list correspond to the IDs of the elements.

`compartments`: Object of class `"list"` containing Compartments. The names of the list correspond to the IDs of the elements.

`species`: Object of class `"list"` containing Speciess. The names of the list correspond to the IDs of the elements.

`parameters`: Object of class `"list"` containing Parameters. The names of the list correspond to the IDs of the elements.

`rules`: Object of class `"list"` containing Rules.

`reactions`: Object of class `"list"` containing Reactions. The names of the list correspond to the IDs of the elements.

`events`: Object of class `"list"` containing Events. The names of the list correspond to the IDs of the elements.

`layouts`: Object of class `"list"` containing Layouts. The names of the list correspond to the IDs of the elements.

`speciesTypes`: Object of class `"list"` containing SpeciesTypes. The names of the list correspond to the IDs of the elements.

`compartmentTypes`: Object of class `"list"` containing CompartmentTypes. The names of the list correspond to the IDs of the elements.

`constraints`: Object of class `"list"` containing Constraints. The names of the list correspond to the IDs of the elements.

`initialAssignments`: Object of class `"list"` containing InitialAssignments.

`modelHistory`: Object of class ModelHistory recording the history of the model.

`metaId`: Object of class `"character"` that is an XML ID "described" by an RDF resource. This links an SBML element to an RDF resource. RDF may appear anywhere in an SBML element, but is usually placed inside the `annotation` element.

`notes`: Object of class `"character"` containing user-readable XHTML notes about an element.

`annotation`: Object of class `"character"` containing additional machine-readable information about an element, usually as RDF, such as BioPAX. This is where application-specific data belongs.

`cvTerms`: Object of class `"list"` containing instances of `CVTerm` associated with this element.

`sboTerm`: Object of class `"integer"` identifying a term in the Systems Biology Ontology (SBO).

Extends

Class `"SBase"`, directly.

Methods

id `signature(object = "Model")`: gets the `id` slot

id<- `signature(object = "Model")`: sets the `id` slot

name `signature(object = "Model")`: gets the `name` slot

name<- `signature(object = "Model")`: sets the `name` slot

compartments `signature(object = "Model")`: gets the `compartments` slot

compartments<- `signature(object = "Model")`: sets the `compartments` slot

events `signature(object = "Model")`: gets the `events` slot

events<- `signature(object = "Model")`: sets the `events` slot

functionDefinitions `signature(object = "Model")`: gets the `functionDefinitions` slot

functionDefinitions<- `signature(object = "Model")`: sets the `functionDefinitions` slot

layouts `signature(object = "Model")`: gets the `layouts` slot

layouts<- `signature(object = "Model")`: sets the `layouts` slot

parameters `signature(object = "Model")`: gets the `parameters` slot

parameters<- `signature(object = "Model")`: sets the `parameters` slot

species `signature(object = "Model")`: gets the `species` slot

species<- `signature(object = "Model")`: sets the `species` slot

reactions `signature(object = "Model")`: gets the `reactions` slot

reactions<- `signature(object = "Model")`: sets the `reactions` slot

rules `signature(object = "Model")`: gets the `rules` slot

rules<- `signature(object = "Model")`: sets the `rules` slot

unitDefinitions `signature(object = "Model")`: gets the `unitDefinitions` slot

unitDefinitions<- `signature(object = "Model")`: sets the `unitDefinitions` slot

compartmentTypes `signature(object = "Model")`: gets the `compartmentTypes` slot

compartmentTypes<- `signature(object = "Model")`: sets the `compartmentTypes` slot

constraints `signature(object = "Model")`: gets the `constraints` slot

constraints<- `signature(object = "Model")`: sets the `constraints` slot

initialAssignments `signature(object = "Model")`: gets the `initialAssignments` slot

initialAssignments<- `signature(object = "Model")`: sets the `initialAssignments` slot

speciesTypes `signature(object = "Model")`: gets the `speciesTypes` slot

speciesTypes<- `signature(object = "Model")`: sets the `speciesTypesslot`

modelHistory `signature(object = "Model")`: gets the `modelHistory` slot

modelHistory<- `signature(object = "Model")`: sets the `modelHistory` slot

stoichiometryMatrix `signature(object = "Model")`: calculates the stoichiometry matrix of the model

Author(s)

Michael Lawrence

References

http://sbml.org/documents/

`ModelCreator-class` *SBML Type "ModelCreator"*

Description

Information, such as name, email and organization, about a creator of an SBML model.

Objects from the Class

Objects can be created by calls of the form `new("ModelCreator", ...)`.

Slots

`familyName`**:** Object of class `"character"` specifying the family name of the creator.

`givenName`**:** Object of class `"character"` specifying the given name of the creator.

`email`**:** Object of class `"character"` specifying the email address of the creator.

`organization`**:** Object of class `"character"` specifying the name of the organization to which the creator belongs.

Methods

email `signature(object = "ModelCreator")`: gets the `email` slot.

email<- `signature(object = "ModelCreator")`: sets the `email<-` slot.

familyName `signature(object = "ModelCreator")`: gets the `familyName` slot.

familyName<- `signature(object = "ModelCreator")`: sets the `familyName<-` slot.

givenName `signature(object = "ModelCreator")`: gets the `givenName` slot.

givenName<- `signature(object = "ModelCreator")`: sets the `givenName<-` slot.

organization `signature(object = "ModelCreator")`: gets the `organization` slot.

organization<- `signature(object = "ModelCreator")`: sets the `organization<-` slot.

Author(s)

Michael Lawrence

References

http://sbml.org/documents/

`ModelHistory-class` *SBML Type "ModelHistory"*

Description

Stores the history of an SBML model, including the created/modified dates and the creators.

Objects from the Class

Objects can be created by calls of the form `new("ModelHistory", ...)`.

Slots

`createdDate`**:** Object of class `"character"` representing the date/time of creation, in W3CDTF format: `YYYY-MM-DDThh:mm:ssTZD`, e.g. "1997-07-16T19:20:30+01:00".

`modifiedDate`**:** Object of class `"character"` representing the date/time of last modification, in W3CDTF format: `YYYY-MM-DDThh:mm:ssTZD`, e.g. "1997-07-16T19:20:30+01:00".

`creators`**:** Object of class `"list"` of instances of `ModelCreator`, one for each creator of the model.

Methods

createdDate `signature(object = "ModelHistory")`: get the `createdDate` slot.

createdDate<- `signature(object = "ModelHistory", value = "character")`: Set the `createdDate` slot to a correctly formatted string.

createdDate<- `signature(object = "ModelHistory", value = "POSIXt")`: Set the `createdDate` slot with a `POSIXt` instance, obtained e.g. from `Sys.time`.

creators `signature(object = "ModelHistory")`: gets the `creators` slot.

creators<- `signature(object = "ModelHistory")`: sets the `creators` slot.

modifiedDate `signature(object = "ModelHistory")`: get the `modifiedDate` slot.

modifiedDate<- `signature(object = "ModelHistory", value = "character")`: Set the `modifiedDate` slot to a correctly formatted string.

modifiedDate<- `signature(object = "ModelHistory", value = "POSIXt")`: Set the `modifiedDate` slot with a `POSIXt` instance, obtained e.g. from `Sys.time`.

Author(s)

Michael Lawrence

References

http://sbml.org/documents/

ModifierSpeciesReference-class

SBML type "ModifierSpeciesReference"

Description

Identifies a `Species` that modifies the parent `Reaction`.

Instantiation

Objects can be created by calls of the form `new("ModifierSpeciesReference", ...)`.

Slots

`id`: Object of class `"character"` uniquely identifying this component.

`species`: Object of class `"character"` identifying the `Species` being referenced.

`metaId`: Object of class `"character"` that is an XML ID "described" by an RDF resource. This links an SBML element to an RDF resource. RDF may appear anywhere in an SBML element, but is usually placed inside the `annotation` element.

`notes`: Object of class `"character"` containing user-readable XHTML notes about an element.

`annotation`: Object of class `"character"` containing additional machine-readable information about an element, usually as RDF, such as BioPAX. This is where application-specific data belongs.

`cvTerms`: Object of class `"list"` containing instances of `CVTerm` associated with this element.

`sboTerm`: Object of class `"integer"` identifying a term in the Systems Biology Ontology (SBO).

Extends

Class `"SimpleSpeciesReference"`, directly. Class `"SBase"`, by class "SimpleSpeciesReference", distance 2.

Methods

No methods defined with class "ModifierSpeciesReference" in the signature.

Author(s)

Michael Lawrence

References

`http://sbml.org/documents/`

Parameter-class *SBML type "Parameter"*

Description

Declares a variable to be used in a mathematical expression.

Instantiation

Objects can be created by calls of the form `new("Parameter", ...)`.

Slots

`id`: Object of class `"character"` uniquely identifying this component.

`name`: Object of class `"character"` naming this component.

`value`: Object of class `"numeric"` specifying the initial value.

`units`: Object of class `"character"` identifying the units.

`constant`: Object of class `"logical"` indicating whether the value of this parameter is constant.

`metaId`: Object of class `"character"` that is an XML ID "described" by an RDF resource. This links an SBML element to an RDF resource. RDF may appear anywhere in an SBML element, but is usually placed inside the `annotation` element.

`notes`: Object of class `"character"` containing user-readable XHTML notes about an element.

`annotation`: Object of class `"character"` containing additional machine-readable information about an element, usually as RDF, such as BioPAX. This is where application-specific data belongs.

`cvTerms`: Object of class `"list"` containing instances of `CVTerm` associated with this element.

`sboTerm`: Object of class `"integer"` identifying a term in the Systems Biology Ontology (SBO).

Extends

Class `"SBase"`, directly.

Methods

id `signature(object = "Parameter")`: gets the `id` slot

id<- `signature(object = "Parameter")`: sets the `id` slot

name `signature(object = "Parameter")`: gets the `name` slot

name<- `signature(object = "Parameter")`: sets the `name` slot

units `signature(object = "Parameter")`: gets the `units` slot

units<- `signature(object = "Parameter")`: sets the `units` slot

constant `signature(object = "Parameter")`: gets the `constant` slot

constant<- `signature(object = "Parameter")`: sets the `constant` slot

value `signature(object = "Parameter")`: gets the `value` slot

value<- `signature(object = "Parameter")`: sets the `value` slot

Author(s)

Michael Lawrence

References

http://sbml.org/documents/

ParameterRule-class *SBML type "ParameterRule"*

Description

Obsolete rule that controls the value of a `Parameter`.

Instantiation

Objects can be created by calls of the form `new("ParameterRule", ...)`.

Slots

`name`: Object of class `"character"` naming this component.

`units`: Object of class `"character"` identifying the units of the assigned value.

`variable`: Object of class `"character"`, ignored.

`type`: Object of class `"character"`, deprecated.

`math`: Object of class `"expression"` specifying the equation.

`metaId`: Object of class `"character"` that is an XML ID "described" by an RDF resource. This links an SBML element to an RDF resource. RDF may appear anywhere in an SBML element, but is usually placed inside the `annotation` element.

`notes`: Object of class `"character"` containing user-readable XHTML notes about an element.

`annotation`: Object of class `"character"` containing additional machine-readable information about an element, usually as RDF, such as BioPAX. This is where application-specific data belongs.

`cvTerms`: Object of class `"list"` containing instances of `CVTerm` associated with this element.

`sboTerm`: Object of class `"integer"` identifying a term in the Systems Biology Ontology (SBO).

Extends

Class `"AssignmentRule"`, directly. Class `"Rule"`, by class "AssignmentRule", distance 2. Class `"SBase"`, by class "AssignmentRule", distance 3.

Methods

name `signature(object = "Parameter")`: gets the `name` slot

name<- `signature(object = "Parameter")`: sets the `name` slot

units `signature(object = "Parameter")`: gets the `units` slot

units<- `signature(object = "Parameter")`: sets the `units` slot

variable `signature(object = "Parameter")`: gets the `variable` slot

variable<- `signature(object = "Parameter")`: sets the `variable` slot

type `signature(object = "Parameter")`: gets the `type` slot

type<- `signature(object = "Parameter")`: sets the `type` slot

math `signature(object = "Parameter")`: gets the `math` slot

math<- `signature(object = "Parameter")`: sets the `math` slot

Author(s)

Michael Lawrence

References

http://sbml.org/documents/

`Point-class` *SBML type "Point"*

Description

Specifies a position in 3D space.

Instantiation

Objects can be created by calls of the form `new("Point", ...)`.

Slots

`x`: Object of class `"numeric"` indicating the X coordinate

`y`: Object of class `"numeric"` indicating the Y coordinate

`z`: Object of class `"numeric"` indicating the Z coordinate

`metaId`: Object of class `"character"` that is an XML ID "described" by an RDF resource. This links an SBML element to an RDF resource. RDF may appear anywhere in an SBML element, but is usually placed inside the `annotation` element.

`notes`: Object of class `"character"` containing user-readable XHTML notes about an element.

`annotation`: Object of class `"character"` containing additional machine-readable information about an element, usually as RDF, such as BioPAX. This is where application-specific data belongs.

`cvTerms`: Object of class `"list"` containing instances of `CVTerm` associated with this element.

`sboTerm`: Object of class `"integer"` identifying a term in the Systems Biology Ontology (SBO).

Extends

Class `"SBase"`, directly.

Methods

x `signature(object = "Point")`: gets the x slot

x<- `signature(object = "Point")`: sets the x slot

y `signature(object = "Point")`: gets the y slot

y<- `signature(object = "Point")`: sets the y slot

z `signature(object = "Point")`: gets the z slot

z<- `signature(object = "Point")`: sets the z slot

Author(s)

Michael Lawrence

References

http://projects.villa-bosch.de/bcb/sbml

RateRule-class *SBML type "RateRule"*

Description

An equation that describes the rate of change in the quantity of a Species, the size of a Compartment or the value of a Parameter.

Instantiation

Objects can be created by calls of the form `new("RateRule", ...)`.

Slots

`variable`: Object of class `"character"` naming the variable (the id of a Species, Compartment or Parameter) being described.

`math`: Object of class `"expression"` specifying the equation.

`metaId`: Object of class `"character"` that is an XML ID "described" by an RDF resource. This links an SBML element to an RDF resource. RDF may appear anywhere in an SBML element, but is usually placed inside the `annotation` element.

`notes`: Object of class `"character"` containing user-readable XHTML notes about an element.

`annotation`: Object of class `"character"` containing additional machine-readable information about an element, usually as RDF, such as BioPAX. This is where application-specific data belongs.

`cvTerms`: Object of class `"list"` containing instances of CVTerm associated with this element.

`sboTerm`: Object of class `"integer"` identifying a term in the Systems Biology Ontology (SBO).

Extends

Class "Rule", directly. Class "SBase", by class "Rule", distance 2.

Methods

variable `signature(object = "RateRule")`: gets the `variable` slot

variable<- `signature(object = "RateRule")`: sets the `variable` slot

Author(s)

Michael Lawrence

References

http://sbml.org/documents/

Reaction-class *SBML type "Reaction"*

Description

Any transformation, transportation or binding process that changes the quantity of one or more Species.

Instantiation

Objects can be created by calls of the form `new("Reaction", ...)`.

Slots

id: Object of class "character" uniquely identifying this component.

name: Object of class "character" naming this component.

reactants: Object of class "list" containing SpeciesReferences specifying the Species that are reactants for this reaction. The names of the list correspond to the IDs of the species.

products: Object of class "list" containing SpeciesReferences specifying the Species that are products for this reaction. The names of the list correspond to the IDs of the species.

modifiers: Object of class "list" containing ModifierSpeciesReferences specifying the Species that are modifiers for this reaction. The names of the list correspond to the IDs of the species.

kineticLaw: Object of class "KineticLaw" that dynamically defines the rate of the reaction.

reversible: Object of class "logical" indicating whether the direction of this reaction is reversible.

fast: Object of class "logical" indicating whether this reaction should be considered instantaneous relative to non-fast reactions.

metaId: Object of class "character" that is an XML ID "described" by an RDF resource. This links an SBML element to an RDF resource. RDF may appear anywhere in an SBML element, but is usually placed inside the annotation element.

notes: Object of class "character" containing user-readable XHTML notes about an element.

annotation: Object of class "character" containing additional machine-readable information about an element, usually as RDF, such as BioPAX. This is where application-specific data belongs.

cvTerms: Object of class "list" containing instances of CVTerm associated with this element.

sboTerm: Object of class "integer" identifying a term in the Systems Biology Ontology (SBO).

Extends

Class "SBase", directly.

Methods

id `signature(object = "Reaction")`: gets the `id` slot

id<- `signature(object = "Reaction")`: sets the `id` slot

name `signature(object = "Reaction")`: gets the `name` slot

name<- `signature(object = "Reaction")`: sets the `name` slot

fast `signature(object = "Reaction")`: gets the `fast` slot

fast<- `signature(object = "Reaction")`: sets the `fast` slot

kineticLaw `signature(object = "Reaction")`: gets the `kineticLaw` slot

kineticLaw<- `signature(object = "Reaction")`: sets the `kineticLaw` slot

modifiers `signature(object = "Reaction")`: gets the `modifiers` slot

modifiers<- `signature(object = "Reaction")`: sets the `modifiers` slot

products `signature(object = "Reaction")`: gets the `products` slot

products<- `signature(object = "Reaction")`: sets the `products` slot

reactants `signature(object = "Reaction")`: gets the `reactants` slot

reactants<- `signature(object = "Reaction")`: sets the `reactants` slot

reversible `signature(object = "Reaction")`: gets the `reversible` slot

reversible<- `signature(object = "Reaction")`: sets the `reversible` slot

Author(s)

Michael Lawrence

References

http://sbml.org/documents/

ReactionGlyph-class *SBML type "ReactionGlyph"*

Description

A glyph representing a `Reaction` in the SBML layout.

Instantiation

Objects can be created by calls of the form `new("ReactionGlyph", ...)`.

Slots

`reaction`: Object of class `"character"` identifying the reaction represented by this glyph.

`glyphCurve`: Object of class `"Curve"` describing this glyph as a curve (optional).

`speciesReferenceGlyphs`: Object of class `"list"` containing `SpeciesReferenceGlyph`s that represent the `SpeciesReference`s of the underlying `Reaction`. The names of the list correspond to the IDs of the elements.

`id`: Object of class `"character"` uniquely identifying this component.

`boundingBox`: Object of class `"BoundingBox"` describing the position and size of the graphical object.

`metaId`: Object of class `"character"` that is an XML ID "described" by an RDF resource. This links an SBML element to an RDF resource. RDF may appear anywhere in an SBML element, but is usually placed inside the `annotation` element.

`notes`: Object of class `"character"` containing user-readable XHTML notes about an element.

`annotation`: Object of class `"character"` containing additional machine-readable information about an element, usually as RDF, such as BioPAX. This is where application-specific data belongs.

`cvTerms`: Object of class `"list"` containing instances of `CVTerm` associated with this element.

`sboTerm`: Object of class `"integer"` identifying a term in the Systems Biology Ontology (SBO).

Extends

Class `"GraphicalObject"`, directly. Class `"SBase"`, by class "GraphicalObject", distance 2.

Methods

glyphCurve `signature(expr = "ReactionGlyph")`: gets the `glyphCurve` slot

glyphCurve<- `signature(object = "ReactionGlyph")`: sets the `glyphCurve` slot

reaction `signature(object = "ReactionGlyph")`: gets the `reaction` slot

reaction<- `signature(object = "ReactionGlyph")`: sets the `reaction` slot

speciesReferenceGlyphs `signature(object = "ReactionGlyph")`: gets the `speciesReferenceGlyphs` slot

speciesReferenceGlyphs<- `signature(object = "ReactionGlyph")`: sets the `speciesReferenceGlyphs` slot

Author(s)

Michael Lawrence

References

http://projects.villa-bosch.de/bcb/sbml

Rule-class *SBML type "Rule"*

Description

A mathematical equation.

Instantiation

A virtual Class: No objects may be created from it.

Slots

`math`: Object of class `"expression"` specifying the equation.

`metaId`: Object of class `"character"` that is an XML ID "described" by an RDF resource. This links an SBML element to an RDF resource. RDF may appear anywhere in an SBML element, but is usually placed inside the `annotation` element.

`notes`: Object of class `"character"` containing user-readable XHTML notes about an element.

`annotation`: Object of class `"character"` containing additional machine-readable information about an element, usually as RDF, such as BioPAX. This is where application-specific data belongs.

`cvTerms`: Object of class `"list"` containing instances of `CVTerm` associated with this element.

`sboTerm`: Object of class `"integer"` identifying a term in the Systems Biology Ontology (SBO).

Extends

Class `"SBase"`, directly.

Methods

math `signature(object = "Rule")`: gets the `math` slot

math<- `signature(object = "Rule")`: sets the `math` slot

Author(s)

Michael Lawrence

References

http://sbml.org/documents/

SBase-class *SBML type "SBase"*

Description

The abstract type from which all other SBML types are derived.

Instantiation

A virtual Class: No objects may be created from it.

Slots

`metaId`: Object of class `"character"` that is an XML ID "described" by an RDF resource. This links an SBML element to an RDF resource. RDF may appear anywhere in an SBML element, but is usually placed inside the `annotation` element.

`notes`: Object of class `"character"` containing user-readable XHTML notes about an element.

`annotation`: Object of class `"character"` containing additional machine-readable information about an element, usually as RDF, such as BioPAX. This is where application-specific data belongs.

`cvTerms`: Object of class `"list"` containing instances of `CVTerm` associated with this element.

`sboTerm`: Object of class `"integer"` identifying a term in the Systems Biology Ontology (SBO).

Methods

annotation `signature(object = "SBase")`: gets the `annotation` slot

annotation<- `signature(object = "SBase")`: sets the `annotation` slot

metaId `signature(object = "SBase")`: gets the `metaId` slot

metaId<- `signature(object = "SBase")`: sets the `metaId` slot

notes `signature(object = "SBase")`: gets the `notes` slot

notes<- `signature(object = "SBase")`: sets the `notes`slot

cvTerms `signature(object = "SBase")`: gets the `cvTerms` slot.

cvTerms<- `signature(object = "SBase")`: sets the `cvTerms` slot.

sboTerm `signature(object = "SBase")`: gets the `sboTerm` slot.

sboTerm<- `signature(object = "SBase")`: sets the `sboTerm` slot.

Author(s)

Michael Lawrence

References

http://sbml.org/documents/

SBML import *Read in an SBML file (start here)*

Description

Read an SBML file into R.

Usage

```
rsbml_read(filename, text, dom = TRUE, strict = FALSE, schema = FALSE,
                  consistency = TRUE)
```

Arguments

filename	the name of the SBML file to parse
text	a string of SBML text to parse (instead of file)
dom	whether to convert directly to the S4 DOM (TRUE, the default) or leave as the internal SBMLDocument.
strict	whether to report warnings in addition to errors or not (FALSE, the default).
schema	whether to perform XML schema validation
consistency	whether to perform consistency checks; recommended but might cause performance deficiencies.

Value

a SBML object, or a SBMLDocument if dom is FALSE.

Author(s)

Michael Lawrence

Examples

```
# Read an SBML file
file <- system.file("sbml", "GlycolysisLayout.xml", package = "rsbml")
doc <- rsbml_read(file)

# Read an SBML string
string <- paste(readLines(file),collapse="\n")
doc <- rsbml_read(text = string)
```

SBML-class *SBML type "SBML"*

Description

The root element of an SBML document. An actual SBML Model may be retrieved from an instance of this class.

Instantiation

Objects can be created by calls of the form new("SBML", ...).

Slots

level: Object of class "integer" indicating the level of the SBML standard (currently at 2).

ver: Object of class "integer" indicating the version of the level (currently at 2 for level 2).

model: Object of class "Model" the SBML model itself.

metaId: Object of class "character" that is an XML ID "described" by an RDF resource. This links an SBML element to an RDF resource. RDF may appear anywhere in an SBML element, but is usually placed inside the annotation element.

notes: Object of class "character" containing user-readable XHTML notes about an element.

annotation: Object of class "character" containing additional machine-readable information about an element, usually as RDF, such as BioPAX. This is where application-specific data belongs.

cvTerms: Object of class "list" containing instances of CVTerm associated with this element.

sboTerm: Object of class "integer" identifying a term in the Systems Biology Ontology (SBO).

Extends

Class "SBase", directly.

Methods

coerce signature(from = "SBMLDocument", to = "SBML"): constructs the S4 object model from a low-level libsbml document.

coerce signature(from = "SBML", to = "SBMLDocument"): converts the S4 object model to a low-level libsbml document.

coerce signature(from = "SBML", to = "graph"): converts the S4 object model to a graph.

level signature(object = "SBML"): gets the level slot

level<- signature(object = "SBML"): sets the level slot

model signature(object = "SBML"): gets the model slot

model<- signature(object = "SBML"): sets the model slot

rsbml_doc `signature(model = "SBML")`: converts the S4 object model to a low-level libsbml document.

rsbml_write `signature(object = "SBML")`: writes this document to a file as SBML.

rsbml_xml `signature(object = "SBML")`: converts this document to a string as SBML.

rsbml_graph `signature(object = "SBML")`: converts this document to a graph object.

rsbml_check `signature(object = "SBML")`: perform consistency checks, see `rsbml_check`.

simulate `signature(object = "SBML")`: converts this document to an internal `SBMLDocument` and calls `simulate` on it.

ver `signature(object = "SBML")`: gets the `ver` slot

ver<- `signature(object = "SBML")`: sets the `ver` slot

Author(s)

Michael Lawrence

References

http://sbml.org/documents/

Examples

```
# Get a DOM
dom <- rsbml_read(system.file("sbml", "GlycolysisLayout.xml", package = "rsbml"))

# Get the species ID's
sapply(species(model(dom)), id)

# Convert DOM back to a low-level document for checking
doc <- rsbml_doc(dom)
rsbml_check(doc)

# Write a DOM to a file
## Not run: rsbml_write(dom, "my.xml")
```

SBMLDocument-class *"SBMLDocument" from libsbml*

Description

Low-level libsbml document structure.

Instantiation

A virtual Class: No objects may be created from it.

Extends

Class "oldClass", directly.

Methods

rsbml_check `signature(object = "SBMLDocument")`: `rsbml_check(object, strict = FALSE, consistency = TRUE)`: Check for problems with the document and signal R conditions if any errors are detected. If `strict` is `TRUE`, libsbml warnings will be emitted as R warnings (these are often too pedantic). If `consistency` is also `TRUE`, reports problems regarding internal model inconsistencies. This can be time consuming.

rsbml_dom `signature(doc = "SBMLDocument")`: Constructs an S4 object model from a libsbml document.

rsbml_graph `signature(doc = "SBMLDocument")`: Converts a libsbml document to a graph.

rsbml_problems `signature(object = "SBMLDocument")`: reports problems encountered during parsing and/or validation.

rsbml_write `signature(object = "SBMLDocument")`: writes this document to a file as SBML.

rsbml_xml `signature(object = "SBMLDocument")`: converts this document to a string as SBML.

simulate `signature(object = "SBMLDocument")`: `simulate(object, nsim = 10, seed, ...)`: a shortcut for simulating the model in this document using the SBML ODE Solver library. Arguments in `...` should match slots of SOSProtocol. See simulate for more details.

Author(s)

Michael Lawrence

References

http://sbml.org/documents/

Examples

```
  # Read a document into an R DOM
  dom <- rsbml_read(system.file("sbml", "GlycolysisLayout.xml", package
= "rsbml"))

  # Convert to a graph
  graph <- rsbml_graph(dom)

  # Write it out to a file
  ## Not run: rsbml_write(dom, "my.xml")

  # Or convert it to a string of XML
  rsbml_xml(dom)

  # Read into external libsbml data structure
  doc <- rsbml_read(system.file("sbml", "GlycolysisLayout.xml", package
= "rsbml"), dom = FALSE)
```

```
# Convert it explicitly to an S4 DOM
dom <- rsbml_dom(doc)
```

SBMLProblem-class *SBMLProblem*

Description

Represents an exception thrown during SBML parsing.

Details

There are trivial subclasses for fatal errors (SBMLFatal), recoverable errors (SBMLError), warnings (SBMLWarning) and informational messages (SBMLInfo). Errors become R error conditions, warnings become R warning conditions and messages are output via message.

Slots

line: The "numeric" line number in the SBML file where the problem was detected.

column: Object of class "numeric" column number in the SBML file where the problem was detected.

msg: Object of class "character", a human-readable description of the problem.

Methods

.condition signature(object = "SBMLProblem"): constructs a condition object representing the exception.

Author(s)

Michael Lawrence

See Also

SBMLProblems, a container for instances of this class.

SBMLProblems-class *SBMLProblems*

Description

A class representing errors encountered during parsing of SBML.

Slots

`fatals`: A list of `SBMLFatal` instances.

`errors`: A list of `SBMLError` instances.

`warnings`: A list of `SBMLWarning` instances.

`infos`: A list of `SBMLInfo` instances.

Methods

.throw `signature(object = "SBMLProblems")`: Throws each `SBMLProblem` in this object.

errors `signature(object = "SBMLProblems")`: Gets the `errors` slot.

fatals `signature(object = "SBMLProblems")`: Gets the `fatals` slot.

infos `signature(object = "SBMLProblems")`: Gets the `infos` slot.

warns `signature(object = "SBMLProblems")`: Gets the `warns` slot.

Author(s)

Michael Lawrence

See Also

The `rsbml_problems` function for obtaining an instance of this class describing any problems encountered during parsing.

SimpleSpeciesReference-class *SBML type "SimpleSpeciesReference"*

Description

Base class for bindings between a `Species` and a `Reaction`.

Instantiation

Objects can be created by calls of the form `new("SimpleSpeciesReference", ...)`.

Slots

id: Object of class "character" uniquely identifying this component.

species: Object of class "character" identifying the Species being referenced.

metaId: Object of class "character" that is an XML ID "described" by an RDF resource. This links an SBML element to an RDF resource. RDF may appear anywhere in an SBML element, but is usually placed inside the annotation element.

notes: Object of class "character" containing user-readable XHTML notes about an element.

annotation: Object of class "character" containing additional machine-readable information about an element, usually as RDF, such as BioPAX. This is where application-specific data belongs.

cvTerms: Object of class "list" containing instances of CVTerm associated with this element.

sboTerm: Object of class "integer" identifying a term in the Systems Biology Ontology (SBO).

Extends

Class "SBase", directly.

Methods

id signature(object = "SpeciesGlyph"): gets the id slot

id<- signature(object = "SpeciesGlyph"): sets the id slot

species signature(object = "SpeciesGlyph"): gets the species slot

species<- signature(object = "SpeciesGlyph"): sets the species slot

Author(s)

Michael Lawrence

References

http://sbml.org/documents/

SOSDesign-class *SOSDesign*

Description

Specifies the reaction names and their parameter settings for each run in a batch experiment. It extends matrix; each column corresponds to a parameter in the model and each row should hold the parameter settings for one run of the experiment.

Details

It is often desirable to explore the state space of a model by adjusting its initial parameter settings. One could do this by modifying the model itself for each experiment, but this class aims to provide a more convenient and systematic means of running experiments in batch, over a range of parameter settings. The results of the experiment will then contain the output from each run, which may then be compared.

The design is specified as a matrix, and each column in the matrix should correspond to a parameter defined in an SBML model. The column names should identify the parameters. These are not to be confused with the simulation parameters specified in `SOSProtocol`, which control how the simulation is executed. These should be and are designed to be kept constant across the runs.

There are two different types of parameters: global and local (reaction) parameters. Global parameters may correspond to a `Species` quantity, `Compartment` size, or model-level `Parameter` value. These should be identified in the column names by the `id` of the corresponding SBML element. The element in the `reactions` slot for one of these parameters should be the empty string.

The second type of parameter specifies the value of a `Parameter` element within the `KineticLaw` of a reaction. These should be named by the `id` of the `Parameter`. They also should be namespaced by the containing `Reaction id`, which is stored in the corresponding element of the `reactions` slot.

Objects from the Class

Objects can be created by calls of the form `new("SOSDesign", data, nrow, ncol, byrow, dimnames, ...)`. This is the same as initializing a `matrix`.

Slots

`.Data`**:** Object of class `"matrix"`, holding the parameter settings.

`reactions`**:** Object of class `"character"` of length the number of columns, holding the reaction IDs for parameters local to a reaction (i.e. `KineticLaw` `Parameter`s). For global parameters, the corresponding value should be the empty string.

Extends

Class `"matrix"`, from data part. Class `"ExperimentDesign"`, directly. Class `"array"`, by class "matrix", distance 2. Class `"structure"`, by class "matrix", distance 3. Class `"vector"`, by class "matrix", distance 4, with explicit coerce.

Methods

reactions `signature(object = "SOSDesign")`: gets the `reactions` slot.

reactions<- `signature(object = "SOSDesign")`: sets the `reactions` slot.

Author(s)

Michael Lawrence

References

See http://www.tbi.univie.ac.at/~raim/odeSolver/ for more information on the SBML ODE Solver library.

See Also

SOSExperiment, the container of this class, for configuring and running a simulation.

SOSExperiment-class *SOS Experiment*

Description

Implementation of Experiment for simulating SBML models using the SOS: (S)BML (O)DE (S)olver library.

Details

The general workflow for running a simulation:

1. Create or import an SBML DOM.
2. Customize the model, for example by adding perturbation Events.
3. Wrap the SBML DOM in a SOSSubject, e.g. new("SOSSubject", dom).
4. Optionally construct a SOSDesign for running the experiment in batch over several sets of model parameter settings.
5. Optionally construct a SOSProtocol for specifying the time points and other parameters controlling the simulation.
6. Construct an instance of this class that groups the subject, design and protocol.
7. Run simulate on the SOSExperiment, optionally specifying the number of iterations and the random seed.
8. Analyze the returned SOSResult, perhaps starting by converting it to a time series with as.ts and making some plots.

Objects from the Class

Objects can be created by calls of the form new("SOSExperiment", ...).

Slots

protocol: Object of class SOSProtocol, where the simulation parameters are specified.

design: Object of class SOSDesign, specifying model parameters for each run of a batch experiment.

subject: Object of class SOSSubject, containing the Model to be simulated.

result: Object of class SOSResult containing the result of the simulation.

Extends

Class Experiment, directly.

Methods

simulate signature(object = "SOSExperiment"): simulate(object, nsim = 10, seed, ...): Simulates the SBML document in the subject slot according to the design points in design and parameters in protocol for nsim iterations, using seed as the random seed. Returns an instance of SOSExperiment, which now should include a SOSResult for analysis.

Author(s)

Michael Lawrence

References

See http://www.tbi.univie.ac.at/~raim/odeSolver/ for more information on the SBML ODE Solver library.

See Also

The simulate method on SBMLDocument is a shortcut, but most users will probably find the above approach most useful.

SOSProtocol-class *SOSProtocol*

Description

Holds the parameters controlling the execution of the simulation using the SBML ODE Solver library.

Details

Most users will probably set only the times slot, either directly or through the timeStep slot and the nsim parameter to simulate.

Objects from the Class

Objects can be created by calls of the form new("SOSProtocol", ...). Each argument in ... should correspond to one of the slots described below.

Slots

`times`: A `"numeric"` vector indicating the time points at which to evaluate the model. Defaults to `tail(seq(0, by = timeStep, length.out = nsim + 1), -1)`. The model is always evaluated at t = 0. This slot is ignored when `indefinite` (below) is `TRUE`.

`timeStep`: A scalar `"numeric"` value, giving the length in time between model evaluations. This is used when calculating the default value of `times`, above, but is otherwise only relevant when the `indefinite` slot, below, is `TRUE`. Defaults to 1.

`indefinite`: A scalar `"logical"`, indicating whether the simulation should run indefinitely, i.e. until one of the stopping conditions is met. See `haltOnEvent` and `haltOnSteadyState` below. Defaults to `FALSE`.

`atol`: Scalar `"numeric"`, the absolute tolerance in integration error. Defaults to `1e-18`.

`rtol`: Scalar `"numeric"`, the relative tolerance in integration error. Defaults to `1e-10`.

`maxStep`: Sclar `"numeric"`, the maximum number of steps for integration. Not to be confused with `timeStep`, etc, above, which control the simulation time points. Defaults to `10000`.

`odeMethod`: Scalar `"character"` naming the method for solving ODEs. Either `"bdf"` (the default) or `"adams-moulton"`.

`iterMethod`: Scalar `"character"`, naming the iteration method used by the ODE solver, either `"newton"` (the default) or `"functional"`.

`maxOrder`: Scalar `"numeric"` indicating maximum order for the ODE solver. Defaults to `5`.

`sensMethod`: Scalar `"character"` naming the method for sensitivity analysis. One of `"none"` (the default and currently the only valid option), `"simultaneous"`, `"staggered"` or `"staggered1"`.

`haltOnEvent`: Scalar `"logical"` indicating whether the simulation should halt when the model emits an `Event`. This allows the model to stop the simulation when some state is reached. Defaults to `FALSE`.

`haltOnSteadyState`: Scalar `"logical"`, indicating whether to halt when a steady state is detected. Defaults to `FALSE`.

`useJacobian`: Scalar `"logical"` indicating whether to use Jacobian ASTs (`TRUE`, the default) or the internal approximation in the CVODES library.

`storeResults`: Scalar `"logical"` indicating whether to store the entire time course (`TRUE`, the default) or just the last time point. Just for performance.

Extends

Class `"ExperimentProtocol"`, directly.

Methods

No methods defined with class "SOSProtocol" in the signature.

Author(s)

Michael Lawrence

References

See http://www.tbi.univie.ac.at/~raim/odeSolver/ for more information on the SBML ODE Solver library.

See Also

The SOSExperiment class, which contains a SOSProtocol instance, for setting up and running a simulation.

SOSResult-class *SOSResult*

Description

A result from simulating an SOSExperiment. Contains the time course for each of the model variables: the Species quantities, Compartment sizes, Parameter values, and Reaction rates.

Slots

data: A "data.frame" containing the time course data. Each row contains the value at a single time point for a single time course. Has the following columns:

- sample A factor, the run number, only exists if there were multiple runs, see SOSDesign.
- type A factor, the SBML element type for the time course, e.g. "species".
- id A factor, the id of the SBML element for the time course.
- time The numeric time value for the time point.
- value The actual numeric value for the time course at that time.

sens: A "matrix" with results from sensitivity analysis, not yet supported.

Extends

Class "ExperimentResult", directly.

Methods

as.ts signature(x = "SOSResult"): converts this object to a time course object of class ts. This allows analysis of the results with existing R infrastructure for time course analysis.

compartments signature(object = "SOSResult"): returns a subset containing only the Compartment size courses.

parameters signature(object = "SOSResult"): returns a subset containing only the global Parameter value courses.

reactions signature(object = "SOSResult"): returns a subset containing only the Reaction rate courses.

species signature(object = "SOSResult"): returns a subset containing only the Species quantity courses.

Author(s)

Michael Lawrence

References

See http://www.tbi.univie.ac.at/~raim/odeSolver/ for more information on the SBML ODE Solver library.

See Also

SOSExperiment for running a simulation and obtaining an instance of this class.

SOSSubject-class *SOSSubject*

Description

This just marks an SBML object as being a valid subject for simulation using the SBML ODE Solver library.

Objects from the Class

Normally created from a SBML with: `new("SOSSubject", model)`.

Extends

Class "ExperimentSubject", directly. Class "SBML", directly. Class "SBase", by class "SBML", distance 2. Class "Describable", by class "SBML", distance 3.

Author(s)

Michael Lawrence

References

See http://www.tbi.univie.ac.at/~raim/odeSolver/ for more information on the SBML ODE Solver library.

See Also

SOSExperiment for running a simulation on a SOSSubject.

Species-class *SBML type "Species"*

Description

A participant in an SBML model.

Instantiation

Objects can be created by calls of the form `new("Species", ...)`.

Slots

`id`: Object of class `"character"` uniquely identifying this component.

`name`: Object of class `"character"` naming this component.

`compartment`: Object of class `"character"` identifying the compartment in which this species is located.

`initialAmount`: Object of class `"numeric"` indicating the initial amount for this species (mutually exclusive with `initialConcentration`).

`initialConcentration`: Object of class `"numeric"` indicating the initial concentration for this species (mutually exclusive with `initialAmount`).

`substanceUnits`: Object of class `"character"` identifying the units for the amount of this species or the numerator of the concentration.

`spatialSizeUnits`: Object of class `"character"` identifying the units for the denominator of the species concentration.

`hasOnlySubstanceUnits`: Object of class `"logical"` indicating whether the quantity of this species is specified as an amount or a concentration.

`boundaryCondition`: Object of class `"logical"`. If `TRUE`, indicates that the quantity of this species cannot be changed by a reaction.

`charge`: Object of class `"integer"` indicating the electrical charge of this species.

`constant`: Object of class `"logical"` indicating whether the quantity of this species can change.

`units`: Object of class `"character"`, deprecated.

`metaId`: Object of class `"character"` that is an XML ID "described" by an RDF resource. This links an SBML element to an RDF resource. RDF may appear anywhere in an SBML element, but is usually placed inside the `annotation` element.

`notes`: Object of class `"character"` containing user-readable XHTML notes about an element.

`annotation`: Object of class `"character"` containing additional machine-readable information about an element, usually as RDF, such as BioPAX. This is where application-specific data belongs.

`cvTerms`: Object of class `"list"` containing instances of `CVTerm` associated with this element.

`sboTerm`: Object of class `"integer"` identifying a term in the Systems Biology Ontology (SBO).

Extends

Class "SBase", directly.

Methods

id signature(object = "Species"): gets the id slot

id<- signature(object = "Species"): sets the id slot

name signature(object = "Species"): gets the name slot

name<- signature(object = "Species"): sets the name slot

boundaryCondition signature(object = "Species"): gets the boundaryCondition slot

boundaryCondition<- signature(object = "Species"): sets the boundaryCondition slot

charge signature(object = "Species"): gets the charge slot

charge<- signature(object = "Species"): sets the charge slot

compartment signature(object = "Species"): gets the compartment slot

compartment<- signature(object = "Species"): sets the compartment slot

constant signature(object = "Species"): gets the constant slot

constant<- signature(object = "Species"): sets the constant slot

units signature(object = "Species"): gets the constant slot

units<- signature(object = "Species"): sets the constant slot

hasOnlySubstanceUnits signature(object = "Species"): gets the hasOnlySubstanceUnits slot

hasOnlySubstanceUnits<- signature(object = "Species"): sets the hasOnlySubstanceUnits slot

initialAmount signature(object = "Species"): gets the initialAmount slot

initialAmount<- signature(object = "Species"): sets the initialAmount slot

initialConcentration signature(object = "Species"): gets the initialConcentration slot

initialConcentration<- signature(object = "Species"): sets the initialConcentration slot

spatialSizeUnits signature(object = "Species"): gets the spatialSizeUnits slot

spatialSizeUnits<- signature(object = "Species"): sets the spatialSizeUnits slot

substanceUnits signature(object = "Species"): gets the substanceUnits slot

substanceUnits<- signature(object = "Species"): sets the substanceUnits slot

Author(s)

Michael Lawrence

References

http://sbml.org/documents/

SpeciesConcentrationRule-class
SBML type "SpeciesConcentrationRule"

Description

Obsolete type of rule that describes the concentration of Species.

Instantiation

Objects can be created by calls of the form `new("SpeciesConcentrationRule", ...)`.

Slots

`species`: Object of class `"character"` identifying the Species.

`variable`: Object of class `"character"`, ignored.

`type`: Object of class `"character"`, deprecated.

`math`: Object of class `"expression"` specifying the equation.

`metaId`: Object of class `"character"` that is an XML ID "described" by an RDF resource. This links an SBML element to an RDF resource. RDF may appear anywhere in an SBML element, but is usually placed inside the `annotation` element.

`notes`: Object of class `"character"` containing user-readable XHTML notes about an element.

`annotation`: Object of class `"character"` containing additional machine-readable information about an element, usually as RDF, such as BioPAX. This is where application-specific data belongs.

`cvTerms`: Object of class `"list"` containing instances of CVTerm associated with this element.

`sboTerm`: Object of class `"integer"` identifying a term in the Systems Biology Ontology (SBO).

Extends

Class "AssignmentRule", directly. Class "Rule", by class "AssignmentRule", distance 2. Class "SBase", by class "AssignmentRule", distance 3.

Methods

species `signature(object = "SpeciesConcentrationRule")`: gets the `species` slot

species<- `signature(object = "SpeciesConcentrationRule")`: sets the `species` slot

Author(s)

Michael Lawrence

References

http://sbml.org/documents/

SpeciesGlyph-class *SBML type "SpeciesGlyph"*

Description

A glyph representing a Species in an SBML layout.

Instantiation

Objects can be created by calls of the form new("SpeciesGlyph", ...).

Slots

species: Object of class "character" identifying the species this glyph represents.

id: Object of class "character" uniquely identifying this component.

boundingBox: Object of class "BoundingBox" describing the position and size of the graphical object.

metaId: Object of class "character" that is an XML ID "described" by an RDF resource. This links an SBML element to an RDF resource. RDF may appear anywhere in an SBML element, but is usually placed inside the annotation element.

notes: Object of class "character" containing user-readable XHTML notes about an element.

annotation: Object of class "character" containing additional machine-readable information about an element, usually as RDF, such as BioPAX. This is where application-specific data belongs.

cvTerms: Object of class "list" containing instances of CVTerm associated with this element.

sboTerm: Object of class "integer" identifying a term in the Systems Biology Ontology (SBO).

Extends

Class "GraphicalObject", directly. Class "SBase", by class "GraphicalObject", distance 2.

Methods

species signature(object = "SpeciesGlyph"): gets the species slot

species<- signature(object = "SpeciesGlyph"): sets the species slot

Author(s)

Michael Lawrence

References

http://projects.villa-bosch.de/bcb/sbml

SpeciesReference-class *SBML type "SpeciesReference"*

Description

Binds a reactant or product Species to a Reaction.

Instantiation

Objects can be created by calls of the form new("SpeciesReference", ...).

Slots

stoichiometry: Object of class "numeric" indicating the (static) stoichiometric coefficient.

stoichiometryMath: Object of class "StoichiometryMath" that dynamically calculates the stoichiometric coefficient.

id: Object of class "character" uniquely identifying this component.

species: Object of class "character" identifying the Species being referenced.

metaId: Object of class "character" that is an XML ID "described" by an RDF resource. This links an SBML element to an RDF resource. RDF may appear anywhere in an SBML element, but is usually placed inside the annotation element.

notes: Object of class "character" containing user-readable XHTML notes about an element.

annotation: Object of class "character" containing additional machine-readable information about an element, usually as RDF, such as BioPAX. This is where application-specific data belongs.

cvTerms: Object of class "list" containing instances of CVTerm associated with this element.

sboTerm: Object of class "integer" identifying a term in the Systems Biology Ontology (SBO).

Extends

Class "SimpleSpeciesReference", directly. Class "SBase", by class "SimpleSpeciesReference", distance 2.

Methods

stoichiometry signature(object = "SpeciesReference"): gets the stoichiometry slot

stoichiometry<- signature(object = "SpeciesReference"): sets the stoichiometry slot

stoichiometryMath signature(object = "SpeciesReference"): gets the stoichiometryMath slot

stoichiometryMath<- signature(object = "SpeciesReference"): sets the stoichiometryMath slot

Author(s)

Michael Lawrence

References

http://sbml.org/documents/

SpeciesReferenceGlyph-class

SBML type "SpeciesReferenceGlyph"

Description

A glyph representing a SpeciesReference in an SBML layout.

Instantiation

Objects can be created by calls of the form `new("SpeciesReferenceGlyph", ...)`.

Slots

speciesGlyph: Object of class "character" identifying the SpeciesGlyph representing the Species that is referenced by the underyling SpeciesReference.

speciesReference: Object of class "character" identifying the linkS4class{SpeciesReference} represented by this glyph.

role: Object of class "character" indicating how this glyph should represent the "role" of the underlying SpeciesReference.

glyphCurve: Object of class "Curve" describing this glyph as a curve (optional).

id: Object of class "character" uniquely identifying this component.

boundingBox: Object of class "BoundingBox" describing the position and size of the graphical object.

metaId: Object of class "character" that is an XML ID "described" by an RDF resource. This links an SBML element to an RDF resource. RDF may appear anywhere in an SBML element, but is usually placed inside the annotation element.

notes: Object of class "character" containing user-readable XHTML notes about an element.

annotation: Object of class "character" containing additional machine-readable information about an element, usually as RDF, such as BioPAX. This is where application-specific data belongs.

cvTerms: Object of class "list" containing instances of CVTerm associated with this element.

sboTerm: Object of class "integer" identifying a term in the Systems Biology Ontology (SBO).

Extends

Class "GraphicalObject", directly. Class "SBase", by class "GraphicalObject", distance 2.

Methods

role signature(object = "SpeciesReferenceGlyph"): gets the role slot

role<- signature(object = "SpeciesReferenceGlyph"): sets the role slot

speciesGlyph signature(object = "SpeciesReferenceGlyph"): gets the speciesGlyph slot

speciesGlyph<- signature(object = "SpeciesReferenceGlyph"): sets the speciesGlyph slot

speciesReference signature(object = "SpeciesReferenceGlyph"): gets the speciesReference slot

speciesReference<- signature(object = "SpeciesReferenceGlyph"): sets the speciesReference slot

glyphCurve signature(expr = "SpeciesReferenceGlyph"): gets the glyphCurve slot

glyphCurve<- signature(object = "SpeciesReferenceGlyph"): sets the glyphCurve slot

Author(s)

Michael Lawrence

References

http://projects.villa-bosch.de/bcb/sbml

SpeciesType-class *SBML Type "SpeciesType"*

Description

A Species represents a pool of a chemical in a particular linkS4class{Compartment}. This element specifies a type of species, that is, the chemical independent of location.

Objects from the Class

Objects can be created by calls of the form new("SpeciesType", ...).

Slots

id: Object of class "character" uniquely identifying this component.

name: Object of class "character" naming this component.

metaId: Object of class "character" that is an XML ID "described" by an RDF resource. This links an SBML element to an RDF resource. RDF may appear anywhere in an SBML element, but is usually placed inside the annotation element.

notes: Object of class "character" containing user-readable XHTML notes about an element.

annotation: Object of class "character" containing additional machine-readable information about an element, usually as RDF, such as BioPAX. This is where application-specific data belongs.

cvTerms: Object of class "list" containing instances of CVTerm associated with this element.

sboTerm: Object of class "integer" identifying a term in the Systems Biology Ontology (SBO).

Extends

Class "SBase", directly.

Methods

id signature(object = "SpeciesType"): gets the id slot

id<- signature(object = "SpeciesType"): sets the id slot

name signature(object = "SpeciesType"): gets the name slot

name<- signature(object = "SpeciesType"): sets the name slot

Note

Requires libsbml >= 3.0

Author(s)

Michael Lawrence

References

http://sbml.org/documents/

See Also

Species

StoichiometryMath-class

SBML type "StoichiometryMath"

Description

Dynamically defines the stoichiometry of a SpeciesReference.

Instantiation

Objects can be created by calls of the form new("StoichiometryMath", ...).

Slots

math: Object of class "expression" that evaluates to the stoichiometric coefficient.

metaId: Object of class "character" that is an XML ID "described" by an RDF resource. This links an SBML element to an RDF resource. RDF may appear anywhere in an SBML element, but is usually placed inside the annotation element.

notes: Object of class "character" containing user-readable XHTML notes about an element.

`annotation`: Object of class `"character"` containing additional machine-readable information about an element, usually as RDF, such as BioPAX. This is where application-specific data belongs.

`cvTerms`: Object of class `"list"` containing instances of `CVTerm` associated with this element.

`sboTerm`: Object of class `"integer"` identifying a term in the Systems Biology Ontology (SBO).

Extends

Class `"SBase"`, directly.

Methods

math `signature(object = "StoichiometryMath")`: gets the `math` slot

math<- `signature(object = "StoichiometryMath")`: sets the `math` slot

Author(s)

Michael Lawrence

References

http://sbml.org/documents/

`TextGlyph-class` *SBML type "TextGlyph"*

Description

A run of text in an SBML layout.

Instantiation

Objects can be created by calls of the form `new("TextGlyph", ...)`.

Slots

`graphicalObject`: Object of class `"character"` identifying the `GraphicalObject` that this glyph labels (optional).

`text`: Object of class `"character"` containing the text shown by the glyph (mutually exclusive with `originOfText`).

`originOfText`: Object of class `"character"` identifying an SBML component whose name is used as the text (mutually exclusive with `text`).

`id`: Object of class `"character"` uniquely identifying this component.

`boundingBox`: Object of class `"BoundingBox"` describing the position and size of the graphical object.

`metaId`: Object of class `"character"` that is an XML ID "described" by an RDF resource. This links an SBML element to an RDF resource. RDF may appear anywhere in an SBML element, but is usually placed inside the `annotation` element.

`notes`: Object of class `"character"` containing user-readable XHTML notes about an element.

`annotation`: Object of class `"character"` containing additional machine-readable information about an element, usually as RDF, such as BioPAX. This is where application-specific data belongs.

`cvTerms`: Object of class `"list"` containing instances of `CVTerm` associated with this element.

`sboTerm`: Object of class `"integer"` identifying a term in the Systems Biology Ontology (SBO).

Extends

Class `"GraphicalObject"`, directly. Class `"SBase"`, by class "GraphicalObject", distance 2.

Methods

graphicalObject `signature(object = "TextGlyph")`: gets the `graphicalObject` slot

graphicalObject<- `signature(object = "TextGlyph")`: sets the `graphicalObject` slot

originOfText `signature(object = "TextGlyph")`: gets the `originOfText` slot

originOfText<- `signature(object = "TextGlyph")`: sets the `originOfText` slot

text `signature(x = "TextGlyph")`: ...

text<- `signature(object = "TextGlyph")`: sets the `text` slot

Author(s)

Michael Lawrence

References

http://projects.villa-bosch.de/bcb/sbml

Trigger-class *SBML Type "Trigger"*

Description

Expresses when an `Event` should be fired.

Objects from the Class

Objects can be created by calls of the form `new("Trigger", ...)`.

Slots

`math`: Object of class `"expression"` that evaluates to `TRUE` when the event should be fired.

`metaId`: Object of class `"character"` that is an XML ID "described" by an RDF resource. This links an SBML element to an RDF resource. RDF may appear anywhere in an SBML element, but is usually placed inside the `annotation` element.

`notes`: Object of class `"character"` containing user-readable XHTML notes about an element.

`annotation`: Object of class `"character"` containing additional machine-readable information about an element, usually as RDF, such as BioPAX. This is where application-specific data belongs.

`cvTerms`: Object of class `"list"` containing instances of `CVTerm` associated with this element.

`sboTerm`: Object of class `"integer"` identifying a term in the Systems Biology Ontology (SBO).

Extends

Class `"SBase"`, directly.

Methods

math `signature(domain = "Trigger")`: gets the `math` slot.

math<- `signature(object = "Trigger")`: sets the `math` slot.

Note

Requires libsbml >= 3.0

Author(s)

Michael Lawrence

References

http://sbml.org/documents/

See Also

`Event`, the parent of this element.

Unit-class *SBML type "Unit"*

Description

A (possibly transformed) reference to a base UnitKind. The transformation is of the form: $multiplier * 10^scale * x^exponent + offset$.

Instantiation

Objects can be created by calls of the form new("Unit", ...).

Slots

kind: Object of class "character" identifying a an SBML UnitKind. For possible values see Table 2 in the SBML specification.

exponent: Object of class "integer" indicating the exponent to use in the transformation.

unitScale: Object of class "integer" indicating the order of magnitude of the scaling to use in the transformation.

multiplier: Object of class "numeric" indicating the factor to use for scaling in the transformation.

offset: Object of class "numeric" indicating the amount of constant shift in the transformation.

metaId: Object of class "character" that is an XML ID "described" by an RDF resource. This links an SBML element to an RDF resource. RDF may appear anywhere in an SBML element, but is usually placed inside the annotation element.

notes: Object of class "character" containing user-readable XHTML notes about an element.

annotation: Object of class "character" containing additional machine-readable information about an element, usually as RDF, such as BioPAX. This is where application-specific data belongs.

cvTerms: Object of class "list" containing instances of CVTerm associated with this element.

sboTerm: Object of class "integer" identifying a term in the Systems Biology Ontology (SBO).

Extends

Class "SBase", directly.

Methods

exponent signature(object = "Unit"): gets the exponent slot

exponent<- signature(object = "Unit"): sets the exponent slot

kind signature(object = "Unit"): gets the kind slot

kind<- signature(object = "Unit"): sets the kind slot

multiplier signature(object = "Unit"): gets the multiplier slot

multiplier<- `signature(object = "Unit")`: sets the `multiplier` slot

offset `signature(object = "Unit")`: gets the `offset` slot

offset<- `signature(object = "Unit")`: sets the `offset` slot

unitScale `signature(x = "Unit")`: ...

unitScale<- `signature(object = "Unit")`: sets the `unitScale` slot

Author(s)

Michael Lawrence

References

http://sbml.org/documents/

`UnitDefinition-class` *SBML type "UnitDefinition"*

Description

Associates one or more `Unit`s with an ID and name.

Instantiation

Objects can be created by calls of the form `new("UnitDefinition", ...)`.

Slots

`id`: Object of class `"character"` uniquely identifying this component.

`name`: Object of class `"character"` naming this component.

`units`: Object of class `"list"` containing equivalent `Unit`s that are all associated with the same ID and name.

`metaId`: Object of class `"character"` that is an XML ID "described" by an RDF resource. This links an SBML element to an RDF resource. RDF may appear anywhere in an SBML element, but is usually placed inside the `annotation` element.

`notes`: Object of class `"character"` containing user-readable XHTML notes about an element.

`annotation`: Object of class `"character"` containing additional machine-readable information about an element, usually as RDF, such as BioPAX. This is where application-specific data belongs.

`cvTerms`: Object of class `"list"` containing instances of `CVTerm` associated with this element.

`sboTerm`: Object of class `"integer"` identifying a term in the Systems Biology Ontology (SBO).

Extends

Class `"SBase"`, directly.

Methods

id `signature(object = "UnitDefinition")`: gets the `id` slot

id<- `signature(object = "UnitDefinition")`: sets the `id` slot

name `signature(object = "UnitDefinition")`: gets the `name` slot

name<- `signature(object = "UnitDefinition")`: sets the `name` slot

units `signature(object = "UnitDefinition")`: gets the `units` slot

units<- `signature(object = "UnitDefinition")`: sets the `units` slot

Author(s)

Michael Lawrence

References

http://sbml.org/documents/

Index

∗ **IO**
SBML import, 44
∗ **classes**
AlgebraicRule-class, 3
AssignmentRule-class, 4
BoundingBox-class, 5
Compartment-class, 6
CompartmentGlyph-class, 7
CompartmentType-class, 8
CompartmentVolumeRule-class, 9
Constraint-class, 10
CubicBezier-class, 11
Curve-class, 13
CVTerm-class, 14
Delay-class, 15
describe, 16
Dimensions-class, 17
Event-class, 18
EventAssignment-class, 19
Experiment-class, 20
FunctionDefinition-class, 21
GraphicalObject-class, 22
InitialAssignment-class, 23
KineticLaw-class, 24
Layout-class, 25
LineSegment-class, 27
Model-class, 29
ModelCreator-class, 31
ModelHistory-class, 32
ModifierSpeciesReference-class, 33
Parameter-class, 34
ParameterRule-class, 35
Point-class, 37
RateRule-class, 38
Reaction-class, 39
ReactionGlyph-class, 40
Rule-class, 42
SBase-class, 43
SBML-class, 45
SBMLDocument-class, 46
SBMLProblem-class, 48
SBMLProblems-class, 49
SimpleSpeciesReference-class, 49
SOSDesign-class, 50
SOSExperiment-class, 52
SOSProtocol-class, 53
SOSResult-class, 55
SOSSubject-class, 56
Species-class, 57
SpeciesConcentrationRule-class, 59
SpeciesGlyph-class, 60
SpeciesReference-class, 61
SpeciesReferenceGlyph-class, 62
SpeciesType-class, 63
StoichiometryMath-class, 64
TextGlyph-class, 65
Trigger-class, 66
Unit-class, 68
UnitDefinition-class, 69
∗ **math**
math, 28
.condition,SBMLProblem-method *(SBMLProblem-class)*, 48
.throw,SBMLError-method *(SBMLProblem-class)*, 48
.throw,SBMLFatal-method *(SBMLProblem-class)*, 48
.throw,SBMLInfo-method *(SBMLProblem-class)*, 48
.throw,SBMLProblems-method *(SBMLProblems-class)*, 49
.throw,SBMLWarning-method *(SBMLProblem-class)*, 48

acot *(math)*, 28
acoth *(math)*, 28
acsc *(math)*, 28
acsch *(math)*, 28

additionalGraphicalObjects (Layout-class), 25
additionalGraphicalObjects,Layout-method (Layout-class), 25
additionalGraphicalObjects<- (Layout-class), 25
additionalGraphicalObjects<-,Layout-method (Layout-class), 25
AlgebraicRule-class, 3
annotation (SBase-class), 43
annotation,SBase-method (SBase-class), 43
annotation<- (SBase-class), 43
annotation<-,SBase-method (SBase-class), 43
array, *51*
as.character.SBML (SBML-class), 45
as.character.SBMLDocument (SBMLDocument-class), 46
as.ts, *52*
as.ts,SOSResult-method (SOSResult-class), 55
asec (math), 28
asech (math), 28
AssignmentRule, *10*, *24*, *36*, *59*
AssignmentRule-class, 4

basePoint1 (CubicBezier-class), 11
basePoint1,CubicBezier-method (CubicBezier-class), 11
basePoint1<- (CubicBezier-class), 11
basePoint1<-,CubicBezier-method (CubicBezier-class), 11
basePoint2 (CubicBezier-class), 11
basePoint2,CubicBezier-method (CubicBezier-class), 11
basePoint2<- (CubicBezier-class), 11
basePoint2<-,CubicBezier-method (CubicBezier-class), 11
biologicalQualifierType (CVTerm-class), 14
biologicalQualifierType,CVTerm-method (CVTerm-class), 14
biologicalQualifierType<- (CVTerm-class), 14
biologicalQualifierType<-,CVTerm-method (CVTerm-class), 14
boundaryCondition (Species-class), 57
boundaryCondition,Species-method (Species-class), 57
boundaryCondition<- (Species-class), 57
boundaryCondition<-,Species-method (Species-class), 57
boundingBox (GraphicalObject-class), 22
boundingBox,GraphicalObject-method (GraphicalObject-class), 22
BoundingBox-class, 5
boundingBox<- (GraphicalObject-class), 22
boundingBox<-,GraphicalObject-method (GraphicalObject-class), 22

charge (Species-class), 57
charge,Species-method (Species-class), 57
charge<- (Species-class), 57
charge<-,Species-method (Species-class), 57
coerce (SBML-class), 45
coerce,SBML,graph-method (SBML-class), 45
coerce,SBML,SBMLDocument-method (SBML-class), 45
coerce,SBMLDocument,graph-method (SBMLDocument-class), 46
coerce,SBMLDocument,SBML-method (SBMLDocument-class), 46
Compartment, *4*, *7–9*, *19*, *29*, *38*, *51*, *55*
compartment (Species-class), 57
compartment,CompartmentGlyph-method (CompartmentGlyph-class), 7
compartment,CompartmentVolumeRule-method (CompartmentVolumeRule-class), 9
compartment,Species-method (Species-class), 57
Compartment-class, 6
compartment<- (Species-class), 57
compartment<-,CompartmentGlyph-method (CompartmentGlyph-class), 7
compartment<-,CompartmentVolumeRule-method (CompartmentVolumeRule-class), 9
compartment<-,Species-method (Species-class), 57
CompartmentGlyph, *26*
CompartmentGlyph-class, 7

compartmentGlyphs (Layout-class), 25
compartmentGlyphs,Layout-method (Layout-class), 25
compartmentGlyphs<- (Layout-class), 25
compartmentGlyphs<-,Layout-method (Layout-class), 25
compartments (Model-class), 29
compartments,Model-method (Model-class), 29
compartments,SOSResult-method (SOSResult-class), 55
compartments<- (Model-class), 29
compartments<-,Model-method (Model-class), 29
CompartmentType, *29*
CompartmentType-class, 8
compartmentTypes (Model-class), 29
compartmentTypes,Model-method (Model-class), 29
compartmentTypes<- (Model-class), 29
compartmentTypes<-,Model-method (Model-class), 29
CompartmentVolumeRule-class, 9
condition, *48*
constant (Species-class), 57
constant,Compartment-method (Compartment-class), 6
constant,Parameter-method (Parameter-class), 34
constant,Species-method (Species-class), 57
constant<- (Species-class), 57
constant<-,Compartment-method (Compartment-class), 6
constant<-,Parameter-method (Parameter-class), 34
constant<-,Species-method (Species-class), 57
Constraint, *29*
Constraint-class, 10
constraints (Model-class), 29
constraints,Model-method (Model-class), 29
constraints<- (Model-class), 29
constraints<-,Model-method (Model-class), 29
cot (math), 28
coth (math), 28
createdDate (ModelHistory-class), 32
createdDate,ModelHistory-method (ModelHistory-class), 32
createdDate<- (ModelHistory-class), 32
createdDate<-,ModelHistory,character-method (ModelHistory-class), 32
createdDate<-,ModelHistory,POSIXt-method (ModelHistory-class), 32
creators (ModelHistory-class), 32
creators,ModelHistory-method (ModelHistory-class), 32
creators<- (ModelHistory-class), 32
creators<-,ModelHistory-method (ModelHistory-class), 32
csc (math), 28
csch (math), 28
CubicBezier-class, 11
Curve-class, 13
curveSegments (Curve-class), 13
curveSegments,Curve-method (Curve-class), 13
curveSegments<- (Curve-class), 13
curveSegments<-,Curve-method (Curve-class), 13
CVTerm, *3–8*, *10–13*, *15*, *17–19*, *21–23*, *25–27*, *30*, *34–39*, *41–43*, *45*, *50*, *57*, *59–63*, *65–69*
CVTerm-class, 14
cvTerms (SBase-class), 43
cvTerms,SBase-method (SBase-class), 43
cvTerms<- (SBase-class), 43
cvTerms<-,SBase-method (SBase-class), 43

Delay-class, 15
depth (Dimensions-class), 17
depth,Dimensions-method (Dimensions-class), 17
depth<- (Dimensions-class), 17
depth<-,Dimensions-method (Dimensions-class), 17
Describable, *56*
Describable-class (describe), 16
describe, *16*, 16
describe,AlgebraicRule-method (describe), 16
describe,AssignmentRule-method (describe), 16
describe,BoundingBox-method (describe), 16

describe,Compartment-method *(describe)*, 16
describe,CompartmentGlyph-method *(describe)*, 16
describe,CompartmentType-method *(describe)*, 16
describe,CompartmentVolumeRule-method *(describe)*, 16
describe,Constraint-method *(describe)*, 16
describe,CubicBezier-method *(describe)*, 16
describe,Curve-method *(describe)*, 16
describe,CVTerm-method *(describe)*, 16
describe,Delay-method *(describe)*, 16
describe,Dimensions-method *(describe)*, 16
describe,Event-method *(describe)*, 16
describe,EventAssignment-method *(describe)*, 16
describe,FunctionDefinition-method *(describe)*, 16
describe,GraphicalObject-method *(describe)*, 16
describe,InitialAssignment-method *(describe)*, 16
describe,KineticLaw-method *(describe)*, 16
describe,Layout-method *(describe)*, 16
describe,LineSegment-method *(describe)*, 16
describe,list-method *(describe)*, 16
describe,Model-method *(describe)*, 16
describe,ModelCreator-method *(describe)*, 16
describe,ModelHistory-method *(describe)*, 16
describe,Parameter-method *(describe)*, 16
describe,ParameterRule-method *(describe)*, 16
describe,Point-method *(describe)*, 16
describe,RateRule-method *(describe)*, 16
describe,Reaction-method *(describe)*, 16
describe,ReactionGlyph-method *(describe)*, 16
describe,SBML-method *(describe)*, 16
describe,SimpleSpeciesReference-method *(describe)*, 16
describe,Species-method *(describe)*, 16
describe,SpeciesConcentrationRule-method *(describe)*, 16
describe,SpeciesGlyph-method *(describe)*, 16
describe,SpeciesReference-method *(describe)*, 16
describe,SpeciesReferenceGlyph-method *(describe)*, 16
describe,SpeciesType-method *(describe)*, 16
describe,StoichiometryMath-method *(describe)*, 16
describe,TextGlyph-method *(describe)*, 16
describe,Trigger-method *(describe)*, 16
describe,Unit-method *(describe)*, 16
describe,UnitDefinition-method *(describe)*, 16
describe-methods *(describe)*, 16
design *(Experiment-class)*, 20
design,Experiment-method *(Experiment-class)*, 20
design<- *(Experiment-class)*, 20
design<-,Experiment-method *(Experiment-class)*, 20
dimensions *(Layout-class)*, 25
dimensions,BoundingBox-method *(BoundingBox-class)*, 5
dimensions,Layout-method *(Layout-class)*, 25
Dimensions-class, 17
dimensions<- *(Layout-class)*, 25
dimensions<-,BoundingBox-method *(BoundingBox-class)*, 5
dimensions<-,Layout-method *(Layout-class)*, 25

email *(ModelCreator-class)*, 31
email,ModelCreator-method *(ModelCreator-class)*, 31
email<- *(ModelCreator-class)*, 31
email<-,ModelCreator-method *(ModelCreator-class)*, 31
end *(LineSegment-class)*, 27
end,LineSegment-method *(LineSegment-class)*, 27
end<- *(LineSegment-class)*, 27
end<-,LineSegment-method *(LineSegment-class)*, 27

errors (SBMLProblems-class), 49
errors,SBMLProblems-method (SBMLProblems-class), 49
Event, *15*, *29*, *52*, *54*, *66, 67*
Event-class, 18
EventAssignment, *15*, *18*
EventAssignment-class, 19
eventAssignments (Event-class), 18
eventAssignments,Event-method (Event-class), 18
eventAssignments<- (Event-class), 18
eventAssignments<-,Event-method (Event-class), 18
eventDelay (Event-class), 18
eventDelay,Event-method (Event-class), 18
eventDelay<- (Event-class), 18
eventDelay<-,Event-method (Event-class), 18
events (Model-class), 29
events,Model-method (Model-class), 29
events<- (Model-class), 29
events<-,Model-method (Model-class), 29
Experiment, *52, 53*
Experiment-class, 20
ExperimentDesign, *51*
ExperimentDesign-class (Experiment-class), 20
ExperimentProtocol, *54*
ExperimentProtocol-class (Experiment-class), 20
ExperimentResult, *55*
ExperimentResult-class (Experiment-class), 20
ExperimentSubject, *56*
ExperimentSubject-class (Experiment-class), 20
exponent (Unit-class), 68
exponent,Unit-method (Unit-class), 68
exponent<- (Unit-class), 68
exponent<-,Unit-method (Unit-class), 68

familyName (ModelCreator-class), 31
familyName,ModelCreator-method (ModelCreator-class), 31
familyName<- (ModelCreator-class), 31
familyName<-,ModelCreator-method (ModelCreator-class), 31
fast (Reaction-class), 39
fast,Reaction-method (Reaction-class), 39
fast<- (Reaction-class), 39
fast<-,Reaction-method (Reaction-class), 39
fatals (SBMLProblems-class), 49
fatals,SBMLProblems-method (SBMLProblems-class), 49
FunctionDefinition, *29*
FunctionDefinition-class, 21
functionDefinitions (Model-class), 29
functionDefinitions,Model-method (Model-class), 29
functionDefinitions<- (Model-class), 29
functionDefinitions<-,Model-method (Model-class), 29

givenName (ModelCreator-class), 31
givenName,ModelCreator-method (ModelCreator-class), 31
givenName<- (ModelCreator-class), 31
givenName<-,ModelCreator-method (ModelCreator-class), 31
glyphCurve (ReactionGlyph-class), 40
glyphCurve,ReactionGlyph-method (ReactionGlyph-class), 40
glyphCurve,SpeciesReferenceGlyph-method (SpeciesReferenceGlyph-class), 62
glyphCurve<- (ReactionGlyph-class), 40
glyphCurve<-,ReactionGlyph-method (ReactionGlyph-class), 40
glyphCurve<-,SpeciesReferenceGlyph-method (SpeciesReferenceGlyph-class), 62
graph, *47*
GraphicalObject, *8*, *26*, *41*, *60*, *62*, *65, 66*
graphicalObject (TextGlyph-class), 65
graphicalObject,TextGlyph-method (TextGlyph-class), 65
GraphicalObject-class, 22
graphicalObject<- (TextGlyph-class), 65
graphicalObject<-,TextGlyph-method (TextGlyph-class), 65

hasOnlySubstanceUnits (Species-class), 57
hasOnlySubstanceUnits,Species-method (Species-class), 57

hasOnlySubstanceUnits<-
(Species-class), 57
hasOnlySubstanceUnits<-,Species-method
(Species-class), 57
height (Dimensions-class), 17
height,Dimensions-method
(Dimensions-class), 17
height<- (Dimensions-class), 17
height<-,Dimensions-method
(Dimensions-class), 17

id (UnitDefinition-class), 69
id,BoundingBox-method
(BoundingBox-class), 5
id,Compartment-method
(Compartment-class), 6
id,CompartmentType-method
(CompartmentType-class), 8
id,Event-method (Event-class), 18
id,FunctionDefinition-method
(FunctionDefinition-class), 21
id,GraphicalObject-method
(GraphicalObject-class), 22
id,Layout-method (Layout-class), 25
id,Model-method (Model-class), 29
id,Parameter-method (Parameter-class),
34
id,Reaction-method (Reaction-class), 39
id,SimpleSpeciesReference-method
(SimpleSpeciesReference-class),
49
id,Species-method (Species-class), 57
id,SpeciesType-method
(SpeciesType-class), 63
id,UnitDefinition-method
(UnitDefinition-class), 69
id<- (UnitDefinition-class), 69
id<-,BoundingBox-method
(BoundingBox-class), 5
id<-,Compartment-method
(Compartment-class), 6
id<-,CompartmentType-method
(CompartmentType-class), 8
id<-,Event-method (Event-class), 18
id<-,FunctionDefinition-method
(FunctionDefinition-class), 21
id<-,GraphicalObject-method
(GraphicalObject-class), 22
id<-,Layout-method (Layout-class), 25
id<-,Model-method (Model-class), 29
id<-,Parameter-method
(Parameter-class), 34
id<-,Reaction-method (Reaction-class),
39
id<-,SimpleSpeciesReference-method
(SimpleSpeciesReference-class),
49
id<-,Species-method (Species-class), 57
id<-,SpeciesType-method
(SpeciesType-class), 63
id<-,UnitDefinition-method
(UnitDefinition-class), 69
infos (SBMLProblems-class), 49
infos,SBMLProblems-method
(SBMLProblems-class), 49
initialAmount (Species-class), 57
initialAmount,Species-method
(Species-class), 57
initialAmount<- (Species-class), 57
initialAmount<-,Species-method
(Species-class), 57
InitialAssignment, *29*
InitialAssignment-class, 23
initialAssignments (Model-class), 29
initialAssignments,Model-method
(Model-class), 29
initialAssignments<- (Model-class), 29
initialAssignments<-,Model-method
(Model-class), 29
initialConcentration (Species-class), 57
initialConcentration,Species-method
(Species-class), 57
initialConcentration<- (Species-class),
57
initialConcentration<-,Species-method
(Species-class), 57

kind (Unit-class), 68
kind,Unit-method (Unit-class), 68
kind<- (Unit-class), 68
kind<-,Unit-method (Unit-class), 68
KineticLaw, *51*
kineticLaw (Reaction-class), 39
kineticLaw,Reaction-method
(Reaction-class), 39
KineticLaw-class, 24
kineticLaw<- (Reaction-class), 39

kineticLaw<-,Reaction-method (Reaction-class), 39

Layout, *29*
Layout-class, 25
layouts (Model-class), 29
layouts,Model-method (Model-class), 29
layouts<- (Model-class), 29
layouts<-,Model-method (Model-class), 29
level (SBML-class), 45
level,SBML-method (SBML-class), 45
level<- (SBML-class), 45
level<-,SBML-method (SBML-class), 45
LineSegment, *12, 13*
LineSegment-class, 27

math, 28
math (KineticLaw-class), 24
math,Constraint-method (Constraint-class), 10
math,Delay-method (Delay-class), 15
math,EventAssignment-method (EventAssignment-class), 19
math,FunctionDefinition-method (FunctionDefinition-class), 21
math,InitialAssignment-method (InitialAssignment-class), 23
math,KineticLaw-method (KineticLaw-class), 24
math,ParameterRule-method (ParameterRule-class), 35
math,Rule-method (Rule-class), 42
math,StoichiometryMath-method (StoichiometryMath-class), 64
math,Trigger-method (Trigger-class), 66
math<- (KineticLaw-class), 24
math<-,Constraint-method (Constraint-class), 10
math<-,Delay-method (Delay-class), 15
math<-,EventAssignment-method (EventAssignment-class), 19
math<-,FunctionDefinition-method (FunctionDefinition-class), 21
math<-,InitialAssignment-method (InitialAssignment-class), 23
math<-,KineticLaw-method (KineticLaw-class), 24
math<-,ParameterRule-method (ParameterRule-class), 35
math<-,Rule-method (Rule-class), 42
math<-,StoichiometryMath-method (StoichiometryMath-class), 64
math<-,Trigger-method (Trigger-class), 66
matrix, *51*
message, *48*
metaId (SBase-class), 43
metaId,SBase-method (SBase-class), 43
metaId<- (SBase-class), 43
metaId<-,SBase-method (SBase-class), 43
Model, *45*, *52*
model (SBML-class), 45
model,SBML-method (SBML-class), 45
Model-class, 29
model<- (SBML-class), 45
model<-,SBML-method (SBML-class), 45
ModelCreator, *32*
ModelCreator-class, 31
ModelHistory, *29*
modelHistory (Model-class), 29
modelHistory,Model-method (Model-class), 29
ModelHistory-class, 32
modelHistory<- (Model-class), 29
modelHistory<-,Model-method (Model-class), 29
modelQualifierType (CVTerm-class), 14
modelQualifierType,CVTerm-method (CVTerm-class), 14
modelQualifierType<- (CVTerm-class), 14
modelQualifierType<-,CVTerm-method (CVTerm-class), 14
modifiedDate (ModelHistory-class), 32
modifiedDate,ModelHistory-method (ModelHistory-class), 32
modifiedDate<- (ModelHistory-class), 32
modifiedDate<-,ModelHistory,character-method (ModelHistory-class), 32
modifiedDate<-,ModelHistory,POSIXt-method (ModelHistory-class), 32
modifiedDate<-,ModelHistory-method (ModelHistory-class), 32
modifiers (Reaction-class), 39
modifiers,Reaction-method (Reaction-class), 39
modifiers<- (Reaction-class), 39
modifiers<-,Reaction-method

(Reaction-class), 39
ModifierSpeciesReference, *39*
ModifierSpeciesReference-class, 33
msg (Constraint-class), 10
msg,Constraint-method (Constraint-class), 10
msg<- (Constraint-class), 10
msg<-,Constraint-method (Constraint-class), 10
multiplier (Unit-class), 68
multiplier,Unit-method (Unit-class), 68
multiplier<- (Unit-class), 68
multiplier<-,Unit-method (Unit-class), 68

name (UnitDefinition-class), 69
name,Compartment-method (Compartment-class), 6
name,CompartmentType-method (CompartmentType-class), 8
name,Event-method (Event-class), 18
name,FunctionDefinition-method (FunctionDefinition-class), 21
name,Model-method (Model-class), 29
name,Parameter-method (Parameter-class), 34
name,ParameterRule-method (ParameterRule-class), 35
name,Reaction-method (Reaction-class), 39
name,Species-method (Species-class), 57
name,SpeciesType-method (SpeciesType-class), 63
name,UnitDefinition-method (UnitDefinition-class), 69
name<- (UnitDefinition-class), 69
name<-,Compartment-method (Compartment-class), 6
name<-,CompartmentType-method (CompartmentType-class), 8
name<-,Event-method (Event-class), 18
name<-,FunctionDefinition-method (FunctionDefinition-class), 21
name<-,Model-method (Model-class), 29
name<-,Parameter-method (Parameter-class), 34
name<-,ParameterRule-method (ParameterRule-class), 35
name<-,Reaction-method (Reaction-class), 39
name<-,Species-method (Species-class), 57
name<-,SpeciesType-method (SpeciesType-class), 63
name<-,UnitDefinition-method (UnitDefinition-class), 69
notes (SBase-class), 43
notes,SBase-method (SBase-class), 43
notes<- (SBase-class), 43
notes<-,SBase-method (SBase-class), 43

offset (Unit-class), 68
offset,Unit-method (Unit-class), 68
offset<- (Unit-class), 68
offset<-,Unit-method (Unit-class), 68
oldClass, *47*
OptionalCurve-class (Curve-class), 13
OptionalDelay-class (Delay-class), 15
OptionalKineticLaw-class (KineticLaw-class), 24
OptionalModelHistory-class (ModelHistory-class), 32
OptionalStoichiometryMath-class (StoichiometryMath-class), 64
organization (ModelCreator-class), 31
organization,ModelCreator-method (ModelCreator-class), 31
organization<- (ModelCreator-class), 31
organization<-,ModelCreator-method (ModelCreator-class), 31
originOfText (TextGlyph-class), 65
originOfText,TextGlyph-method (TextGlyph-class), 65
originOfText<- (TextGlyph-class), 65
originOfText<-,TextGlyph-method (TextGlyph-class), 65
outside (Compartment-class), 6
outside,Compartment-method (Compartment-class), 6
outside<- (Compartment-class), 6
outside<-,Compartment-method (Compartment-class), 6

Parameter, *4*, *19*, *24*, *29*, *35*, *38*, *51*, *55*
Parameter-class, 34
ParameterRule-class, 35
parameters (Model-class), 29

parameters,KineticLaw-method (KineticLaw-class), 24
parameters,Model-method (Model-class), 29
parameters,SOSResult-method (SOSResult-class), 55
parameters<- (Model-class), 29
parameters<-,KineticLaw-method (KineticLaw-class), 24
parameters<-,Model-method (Model-class), 29
Point-class, 37
position (BoundingBox-class), 5
position,BoundingBox-method (BoundingBox-class), 5
position<- (BoundingBox-class), 5
position<-,BoundingBox-method (BoundingBox-class), 5
POSIXt, *33*
products (Reaction-class), 39
products,Reaction-method (Reaction-class), 39
products<- (Reaction-class), 39
products<-,Reaction-method (Reaction-class), 39
protocol (Experiment-class), 20
protocol,Experiment-method (Experiment-class), 20
protocol<- (Experiment-class), 20
protocol<-,Experiment-method (Experiment-class), 20

qualifierType (CVTerm-class), 14
qualifierType,CVTerm-method (CVTerm-class), 14
qualifierType<- (CVTerm-class), 14
qualifierType<-,CVTerm-method (CVTerm-class), 14

RateRule-class, 38
reactants (Reaction-class), 39
reactants,Reaction-method (Reaction-class), 39
reactants<- (Reaction-class), 39
reactants<-,Reaction-method (Reaction-class), 39
Reaction, *24*, *29*, *33*, *40, 41*, *49*, *55*, *61*
reaction (ReactionGlyph-class), 40
reaction,ReactionGlyph-method (ReactionGlyph-class), 40
Reaction-class, 39
reaction<- (ReactionGlyph-class), 40
reaction<-,ReactionGlyph-method (ReactionGlyph-class), 40
ReactionGlyph, *26*
ReactionGlyph-class, 40
reactionGlyphs (Layout-class), 25
reactionGlyphs,Layout-method (Layout-class), 25
reactionGlyphs<- (Layout-class), 25
reactionGlyphs<-,Layout-method (Layout-class), 25
reactions (Model-class), 29
reactions,Model-method (Model-class), 29
reactions,SOSDesign-method (SOSDesign-class), 50
reactions,SOSResult-method (SOSResult-class), 55
reactions<- (Model-class), 29
reactions<-,Experiment-method (Experiment-class), 20
reactions<-,Model-method (Model-class), 29
reactions<-,SOSDesign-method (SOSDesign-class), 50
resources (CVTerm-class), 14
resources,CVTerm-method (CVTerm-class), 14
resources<- (CVTerm-class), 14
resources<-,CVTerm-method (CVTerm-class), 14
result (Experiment-class), 20
result,Experiment-method (Experiment-class), 20
result<- (Experiment-class), 20
result<-,Experiment-method (Experiment-class), 20
reversible (Reaction-class), 39
reversible,Reaction-method (Reaction-class), 39
reversible<- (Reaction-class), 39
reversible<-,Reaction-method (Reaction-class), 39
role (SpeciesReferenceGlyph-class), 62
role,SpeciesReferenceGlyph-method (SpeciesReferenceGlyph-class),

62
role<- (SpeciesReferenceGlyph-class), 62
role<-,SpeciesReferenceGlyph-method (SpeciesReferenceGlyph-class), 62
rsbml_check, *46*
rsbml_check (SBMLDocument-class), 46
rsbml_check,SBML-method (SBML-class), 45
rsbml_check,SBMLDocument-method (SBMLDocument-class), 46
rsbml_doc (SBML-class), 45
rsbml_doc,SBML-method (SBML-class), 45
rsbml_dom (SBMLDocument-class), 46
rsbml_dom,SBMLDocument-method (SBMLDocument-class), 46
rsbml_graph (SBMLDocument-class), 46
rsbml_graph,Model-method (SBMLDocument-class), 46
rsbml_graph,SBML-method (SBML-class), 45
rsbml_graph,SBMLDocument-method (SBMLDocument-class), 46
rsbml_problems, *49*
rsbml_problems (SBMLDocument-class), 46
rsbml_problems,SBMLDocument-method (SBMLDocument-class), 46
rsbml_read (SBML import), 44
rsbml_write (SBML-class), 45
rsbml_write,SBML-method (SBML-class), 45
rsbml_write,SBMLDocument-method (SBMLDocument-class), 46
rsbml_xml (SBML-class), 45
rsbml_xml,SBML-method (SBML-class), 45
rsbml_xml,SBMLDocument-method (SBMLDocument-class), 46
Rule, *3, 4*, *10*, *29*, *36*, *38*, *59*
Rule-class, 42
rules (Model-class), 29
rules,Model-method (Model-class), 29
rules<- (Model-class), 29
rules<-,Model-method (Model-class), 29

SBase, *3–6*, *8*, *10–13*, *15*, *17, 18*, *20*, *22–27*, *30*, *34–39*, *41, 42*, *45*, *50*, *56*, *58–62*, *64–69*
SBase-class, 43
SBML, *44*, *52*, *56*
SBML import, 44
SBML-class, 45
SBMLDocument, *44*, *46*, *53*
SBMLDocument-class, 46
SBMLError, *49*
SBMLError-class (SBMLProblem-class), 48
SBMLFatal, *49*
SBMLFatal-class (SBMLProblem-class), 48
SBMLInfo, *49*
SBMLInfo-class (SBMLProblem-class), 48
SBMLProblem, *49*
SBMLProblem-class, 48
SBMLProblems, *48*
SBMLProblems-class, 49
SBMLWarning, *49*
SBMLWarning-class (SBMLProblem-class), 48
sboTerm (SBase-class), 43
sboTerm,SBase-method (SBase-class), 43
sboTerm<- (SBase-class), 43
sboTerm<-,SBase-method (SBase-class), 43
sec (math), 28
sech (math), 28
show,Describable-method (describe), 16
show,SBMLProblem-method (SBMLProblem-class), 48
SimpleSpeciesReference, *34*, *61*
SimpleSpeciesReference-class, 49
simulate, *47*, *53*
simulate (SOSExperiment-class), 52
simulate,SBML-method (SBML-class), 45
simulate,SBMLDocument-method (SBMLDocument-class), 46
simulate,SOSExperiment-method (SOSExperiment-class), 52
size (Compartment-class), 6
size,Compartment-method (Compartment-class), 6
size<- (Compartment-class), 6
size<-,Compartment-method (Compartment-class), 6
SOSDesign, *52*, *55*
SOSDesign-class, 50
SOSExperiment, *21*, *52*, *55, 56*
SOSExperiment-class, 52
SOSProtocol, *47*, *51, 52*
SOSProtocol-class, 53
SOSResult, *52, 53*
SOSResult-class, 55
SOSSubject, *52*
SOSSubject-class, 56

spatialDimensions *(Compartment-class)*, 6
spatialDimensions,Compartment-method *(Compartment-class)*, 6
spatialDimensions<- *(Compartment-class)*, 6
spatialDimensions<-,Compartment-method *(Compartment-class)*, 6
spatialSizeUnits *(Species-class)*, 57
spatialSizeUnits,Species-method *(Species-class)*, 57
spatialSizeUnits<- *(Species-class)*, 57
spatialSizeUnits<-,Species-method *(Species-class)*, 57
Species, *4*, *6*, *19*, *29*, *33*, *38*, *39*, *49–51*, *55*, *59–64*
species *(SpeciesGlyph-class)*, 60
species,Model-method *(Model-class)*, 29
species,SimpleSpeciesReference-method *(SimpleSpeciesReference-class)*, 49
species,SOSResult-method *(SOSResult-class)*, 55
species,SpeciesConcentrationRule-method *(SpeciesConcentrationRule-class)*, 59
species,SpeciesGlyph-method *(SpeciesGlyph-class)*, 60
Species-class, 57
species<- *(SpeciesGlyph-class)*, 60
species<-,Model-method *(Model-class)*, 29
species<-,SimpleSpeciesReference-method *(SimpleSpeciesReference-class)*, 49
species<-,SpeciesConcentrationRule-method *(SpeciesConcentrationRule-class)*, 59
species<-,SpeciesGlyph-method *(SpeciesGlyph-class)*, 60
SpeciesConcentrationRule-class, 59
SpeciesGlyph, *26*, *62*
speciesGlyph *(SpeciesReferenceGlyph-class)*, 62
speciesGlyph,SpeciesReferenceGlyph-method *(SpeciesReferenceGlyph-class)*, 62
SpeciesGlyph-class, 60
speciesGlyph<- *(SpeciesReferenceGlyph-class)*, 62
speciesGlyph<-,SpeciesReferenceGlyph-method *(SpeciesReferenceGlyph-class)*, 62
speciesGlyphs *(Layout-class)*, 25
speciesGlyphs,Layout-method *(Layout-class)*, 25
speciesGlyphs<- *(Layout-class)*, 25
speciesGlyphs<-,Layout-method *(Layout-class)*, 25
SpeciesReference, *39*, *41*, *62*, *64*
speciesReference *(SpeciesReferenceGlyph-class)*, 62
speciesReference,SpeciesReferenceGlyph-method *(SpeciesReferenceGlyph-class)*, 62
SpeciesReference-class, 61
speciesReference<- *(SpeciesReferenceGlyph-class)*, 62
speciesReference<-,SpeciesReferenceGlyph-method *(SpeciesReferenceGlyph-class)*, 62
SpeciesReferenceGlyph, *41*
SpeciesReferenceGlyph-class, 62
speciesReferenceGlyphs *(ReactionGlyph-class)*, 40
speciesReferenceGlyphs,ReactionGlyph-method *(ReactionGlyph-class)*, 40
speciesReferenceGlyphs<- *(ReactionGlyph-class)*, 40
speciesReferenceGlyphs<-,ReactionGlyph-method *(ReactionGlyph-class)*, 40
SpeciesType, *29*
SpeciesType-class, 63
speciesTypes *(Model-class)*, 29
speciesTypes,Model-method *(Model-class)*, 29
speciesTypes<- *(Model-class)*, 29
speciesTypes<-,Model-method *(Model-class)*, 29
start *(LineSegment-class)*, 27
start,LineSegment-method *(LineSegment-class)*, 27
start<- *(LineSegment-class)*, 27
start<-,LineSegment-method

(LineSegment-class), 27
stoichiometry (SpeciesReference-class), 61
stoichiometry,SpeciesReference-method (SpeciesReference-class), 61
stoichiometry<- (SpeciesReference-class), 61
stoichiometry<-,SpeciesReference-method (SpeciesReference-class), 61
stoichiometryMath (SpeciesReference-class), 61
stoichiometryMath,SpeciesReference-method (SpeciesReference-class), 61
StoichiometryMath-class, 64
stoichiometryMath<- (SpeciesReference-class), 61
stoichiometryMath<-,SpeciesReference-method (SpeciesReference-class), 61
stoichiometryMatrix (Model-class), 29
stoichiometryMatrix,Model-method (Model-class), 29
structure, *51*
subject (Experiment-class), 20
subject,Experiment-method (Experiment-class), 20
subject<- (Experiment-class), 20
subject<-,Experiment-method (Experiment-class), 20
substanceUnits (KineticLaw-class), 24
substanceUnits,KineticLaw-method (KineticLaw-class), 24
substanceUnits,Species-method (Species-class), 57
substanceUnits<- (KineticLaw-class), 24
substanceUnits<-,KineticLaw-method (KineticLaw-class), 24
substanceUnits<-,Species-method (Species-class), 57
symbol (InitialAssignment-class), 23
symbol,InitialAssignment-method (InitialAssignment-class), 23
symbol<- (InitialAssignment-class), 23
symbol<-,InitialAssignment-method (InitialAssignment-class), 23
Sys.time, *33*

text (TextGlyph-class), 65
text,TextGlyph-method (TextGlyph-class), 65
text<- (TextGlyph-class), 65
text<-,TextGlyph-method (TextGlyph-class), 65
TextGlyph, *26*
TextGlyph-class, 65
textGlyphs (Layout-class), 25
textGlyphs,Layout-method (Layout-class), 25
textGlyphs<- (Layout-class), 25
textGlyphs<-,Layout-method (Layout-class), 25
timeUnits (KineticLaw-class), 24
timeUnits,Event-method (Event-class), 18
timeUnits,KineticLaw-method (KineticLaw-class), 24
timeUnits<- (KineticLaw-class), 24
timeUnits<-,Event-method (Event-class), 18
timeUnits<-,KineticLaw-method (KineticLaw-class), 24
Trigger, *15*
trigger (Event-class), 18
trigger,Event-method (Event-class), 18
Trigger-class, 66
trigger<- (Event-class), 18
trigger<-,Event-method (Event-class), 18
type (AssignmentRule-class), 4
type,AssignmentRule-method (AssignmentRule-class), 4
type,ParameterRule-method (ParameterRule-class), 35
type<- (AssignmentRule-class), 4
type<-,AssignmentRule-method (AssignmentRule-class), 4
type<-,ParameterRule-method (ParameterRule-class), 35

Unit, *69*
Unit-class, 68
UnitDefinition, *6*, *29*
UnitDefinition-class, 69
unitDefinitions (Model-class), 29
unitDefinitions,Model-method (Model-class), 29
unitDefinitions<- (Model-class), 29
unitDefinitions<-,Model-method (Model-class), 29
units (UnitDefinition-class), 69

units,Compartment-method
(Compartment-class), 6
units,Parameter-method
(Parameter-class), 34
units,ParameterRule-method
(ParameterRule-class), 35
units,Species-method (Species-class), 57
units,UnitDefinition-method
(UnitDefinition-class), 69
units<- (UnitDefinition-class), 69
units<-,Compartment-method
(Compartment-class), 6
units<-,Parameter-method
(Parameter-class), 34
units<-,ParameterRule-method
(ParameterRule-class), 35
units<-,Species-method (Species-class),
57
units<-,UnitDefinition-method
(UnitDefinition-class), 69
unitScale (Unit-class), 68
unitScale,Unit-method (Unit-class), 68
unitScale<- (Unit-class), 68
unitScale<-,Unit-method (Unit-class), 68

value (Parameter-class), 34
value,Parameter-method
(Parameter-class), 34
value<- (Parameter-class), 34
value<-,Parameter-method
(Parameter-class), 34
variable (RateRule-class), 38
variable,AssignmentRule-method
(AssignmentRule-class), 4
variable,EventAssignment-method
(EventAssignment-class), 19
variable,ParameterRule-method
(ParameterRule-class), 35
variable,RateRule-method
(RateRule-class), 38
variable<- (RateRule-class), 38
variable<-,AssignmentRule-method
(AssignmentRule-class), 4
variable<-,EventAssignment-method
(EventAssignment-class), 19
variable<-,ParameterRule-method
(ParameterRule-class), 35
variable<-,RateRule-method
(RateRule-class), 38

vector, *51*
ver (SBML-class), 45
ver,SBML-method (SBML-class), 45
ver<- (SBML-class), 45
ver<-,SBML-method (SBML-class), 45

warning, *48*
warns (SBMLProblems-class), 49
warns,SBMLProblems-method
(SBMLProblems-class), 49
width (Dimensions-class), 17
width,Dimensions-method
(Dimensions-class), 17
width<- (Dimensions-class), 17
width<-,Dimensions-method
(Dimensions-class), 17

x (Point-class), 37
x,Point-method (Point-class), 37
x<- (Point-class), 37
x<-,Point-method (Point-class), 37

y (Point-class), 37
y,Point-method (Point-class), 37
y<- (Point-class), 37
y<-,Point-method (Point-class), 37

z (Point-class), 37
z,Point-method (Point-class), 37
z<- (Point-class), 37
z<-,Point-method (Point-class), 37