Package 'tenXplore'

November 12, 2026

Title ontological exploration of scRNA-seq of 1.3 million mouse neurons from 10x genomics

Description
Perform ontological exploration of scRNA-seq of 1.3 million mouse neurons from 10x genomics.

Version 1.34.0

Author Vince Carey

Suggests org.Hs.eg.db, testthat, knitr, rmarkdown, BiocStyle

Depends R (>= 4.0), shiny

Imports methods, ontoProc (>= 0.99.7), SummarizedExperiment, AnnotationDbi, matrixStats, org.Mm.eg.db, stats, utils, BiocFileCache

Maintainer VJ Carey <stvjc@channing.harvard.edu>

License Artistic-2.0

LazyLoad yes

biocViews ImmunoOncology, DimensionReduction, PrincipalComponent, Transcriptomics, SingleCell

VignetteBuilder knitr

RoxygenNote 7.3.2

git_url https://git.bioconductor.org/packages/tenXplore

git_branch RELEASE_3_23

git_last_commit b583762

git_last_commit_date 2026-04-28

Repository Bioconductor 3.23

Date/Publication 2026-11-11

Contents

CellTypes 2
se1.3M 2
tenx500 3
tenXplore 3

Index 4

`CellTypes` *cellTypes: data.frame with ids and terms*

Description

cellTypes: data.frame with ids and terms

Usage

```
CellTypes
```

Format

TermSet instance

Source

efo.owl, August 2017, subclasses of http://www.ebi.ac.uk/efo/EFO_0000324

Examples

```
data(CellTypes)
head(slot(CellTypes, "cleanFrame"))
```

`se1.3M` *add/retrieve HSDS-based SE to/from cache*

Description

add/retrieve HSDS-based SE to/from cache

Usage

```
se1.3M(cache = BiocFileCache::BiocFileCache())
```

Arguments

`cache`	BiocFileCache-like cache

tenx500 *tenx500: serialized full SummarizedExperiment for demonstration*

Description

tenx500: serialized full SummarizedExperiment for demonstration

Usage

```
tenx500
```

Format

SummarizedExperiment instance

Source

restfulSE se1.3M pared down to 500 samples, assay materialized and assigned

Examples

```
data(tenx500)
tenx500
```

tenXplore *basic shiny interface to 10x data with ontological setup for cell selection*

Description

basic shiny interface to 10x data with ontological setup for cell selection

Usage

```
tenXplore()
```

Value

shiny app invocation

Note

Starts slowly as it sets up connection to HDF Server.

Examples

```
tenXplore
```

Index

∗ **datasets**
CellTypes, 2
tenx500, 3

CellTypes, 2

se1.3M, 2

tenx500, 3
tenXplore, 3