Package 'Single.mTEC.Transcriptomes'

November 10, 2026

Type Package

Title Single Cell Transcriptome Data and Analysis of Mouse mTEC cells

Version 1.40.0

Date 2025-07-28

Author Alejandro Reyes

Maintainer Alejandro Reyes <alejandro.reyes.ds@gmail.com>

Description This data package contains the code used to analyse the single-cell RNA-seq and the bulk ATAC-seq data from the manuscript titled: Single-cell transcriptome analysis reveals coordinated ectopic-gene expression patterns in medullary thymic epithelial cells. This paper was published in Nature Immunology 16,933-941(2015). The data objects provided in this package has been pre-processed: the raw data files can be downloaded from ArrayExpress under the accession identifiers E-MTAB-3346 and E-MTAB-3624. The vignette of this data package provides a documented and reproducible workflow that includes the code that was used to generate each statistic and figure from the manuscript.

License LGPL

biocViews ExperimentData

VignetteBuilder knitr

Depends R (>= 3.5.0)

Suggests DESeq2, GenomicRanges, GenomicFeatures, genefilter, statmod, gdata, RColorBrewer, ggplot2, gplots, cluster, clue, grid, gridExtra, ggbio, Gviz, geneplotter, matrixStats, pheatmap, BiocStyle, knitr, BiocParallel

RoxygenNote 5.0.1

NeedsCompilation no

git_url https://git.bioconductor.org/packages/Single.mTEC.Transcriptomes

git_branch RELEASE_3_23

git_last_commit 5e82a36

git_last_commit_date 2026-04-28

Repository Bioconductor 3.23

Date/Publication 2026-11-10

Contents

Single.mTec.Transcriptomes-package . . . 2
aireDependentSansom . . . 3
biotype . . . 3
biotypesHuman . . . 3
cea1Coexpression . . . 4
corMatsNoMarker . . . 4
deGenesNone . . . 5
deGenesSansom . . . 5
dxdATAC . . . 5
fantom . . . 6
geneNames . . . 6
geneNamesHuman . . . 6
geneRanges . . . 7
mTECdxd . . . 7
muc1Coexpression . . . 7
nomarkerCellsClustering . . . 8
percentsGG . . . 8
permutationResults . . . 8
scLVM_output . . . 9
tras . . . 9

Index **10**

`Single.mTec.Transcriptomes-package`
Single-cell transcriptome data of medullary thymic epithelial cells

---

Description

This document contains all the code used to analyse the single-cell RNA-seq and the bulk ATAC-seq data from the manuscript by Brennecke et al, 2015. The purpose of this package is to provide full reproducibility of the results presented in the manuscript. This package provides a documented and reproducible workflow of the code that was used to generate each number and figure from the manuscript.

References

Brennecke et al. Single-cell transcriptome analysis reveals coordinated ectopic gene-expression patterns in medullary thymic epithelial cells. Nature Immunology 16,933-941 (2015)

aireDependentSansom *List of Aire-dependent genes*

Description

A character vector of ensembl gene identifiers defined by Sansom et al, 2014. This list was downloaded from the supplementary material of the manuscript.

Usage

```
data(aireDependentSansom)
```

References

Sansom et al. Population and single-cell genomics reveal the Aire dependency, relief from Polycomb silencing, and distribution of self-antigen expression in thymic epithelia. Genome Res. 24, 1918–1931 (2014).

biotype *Mouse biotypes*

Description

A character vector defining biotype for each mouse ensembl gene identifier. Biotypes were queried using **biomaRt**.

Usage

```
data(biotypes)
```

biotypesHuman *Human biotypes*

Description

A character vector defining biotype for each human ensembl gene identifier. Biotypes were queried using **biomaRt**.

Usage

```
data(biotypesHuman)
```

cea1Coexpression *Cea1 co-expression group data*

Description

A data frame containing information about the Cea1 co-expression group defined in Pinto et al, 2013.

Usage

```
data(cea1Coexpression)
```

References

Pinto et al. Overlapping gene coexpression patterns in human medullary thymic epithelial cells generate self-antigen diversity. Proc. Natl. Acad. Sci. U.S.A. 110, E3497–3505, (2013).

corMatsNoMarker *Gene-gene correlation network*

Description

A matrix containing the gene-gene Spearman correlation across single unselected cells.

A matrix containing the gene-gene Spearman correlation across single unselected cells, using the data from Sansom et al, 2014.

Usage

```
data(corMatsNoMarker)

data(corMatsSansom)
```

References

Sansom et al. Population and single-cell genomics reveal the Aire dependency, relief from Polycomb silencing, and distribution of self-antigen expression in thymic epithelia. Genome Res. 24, 1918–1931 (2014).

deGenesNone *Highly variable genes.*

Description

List of highly variable genes according to the method by Brennecke et al, 2013.

Usage

```
data(deGenesNone)
```

References

Brennecke et al. Accounting for technical noise in single-cell RNA-seq experiments. Nat. Methods. 10, 1093-1095 (2013).

deGenesSansom *Highly variable genes from Sansom et al.*

Description

List of highly variable genes according to the method by Brennecke et al, 2013, using the data by Santom et al.

Usage

```
data(deGenesSansom)
```

References

Brennecke et al. Accounting for technical noise in single-cell RNA-seq experiments. Nat. Methods. 10, 1093-1095 (2013). Sansom et al. Population and single-cell genomics reveal the Aire dependency, relief from Polycomb silencing, and distribution of self-antigen expression in thymic epithelia. Genome Res. 24, 1918–1931 (2014).

dxdATAC *ATAC-seq summarized counts.*

Description

DESeqDataSet object summarizing the ATAC-seq data presented in the manuscript. This object contains the read counts of each sample over a window of 4Kb around transcription start sites.

Usage

```
data(dxdATAC)
```

fantom *FANTOM dataset*

Description

DESeqDataSet object of the read counts from selected tissues from the FANTOM dataset.

Usage

```
data(fantom)
```

References

Forrest et al. A promoter-level mammalian expression atlas. 24, 1918–1931. (2014).

geneNames *Mouse gene names*

Description

Character vector of mouse gene names. The gene names were queried using **biomaRt**.

Usage

```
data(geneNames)
```

geneNamesHuman *Human gene names*

Description

Character vector of human gene names. The gene names were queried using **biomaRt**.

Usage

```
data(geneNamesHuman)
```

geneRanges *Genomic range coordinates.*

Description

GenomicRanges object containing the coordinate ranges of mouse protein coding genes used in the manuscript.

Usage

```
data(geneRanges)
```

mTECdxd *Count data from the single-mTEC data.*

Description

DESeqDataSet object containing the read counts from the single-cell RNA-seq dataset generated by Brennecke et al, 2015.

Usage

```
data(mTECdxd)
```

References

Brennecke et al. Single-cell transcriptome analysis reveals coordinated ectopic gene-expression patterns in medullary thymic epithelial cells. Nature Immunology 16,933-941 (2015)

muc1Coexpression *Muc1 co-expression group data*

Description

A data frame containing information about the Muc1 co-expression group defined in Pinto et al, 2013.

Usage

```
data(muc1Coexpression)
```

References

Pinto et al. Overlapping gene coexpression patterns in human medullary thymic epithelial cells generate self-antigen diversity. Proc. Natl. Acad. Sci. U.S.A. 110, E3497–3505, (2013).

nomarkerCellsClustering *Clustering results*

Description

List containing the results from the clustering analysis from Figure 2 from the manuscript.

Usage

```
data(nomarkerCellsClustering)
```

percentsGG *Mapping statistics*

Description

Data frame containing the mapping statistics from the single-cell RNA-seq data.

Usage

```
data(percentsGG)
```

permutationResults *Permutation results*

Description

Result from the gene permutations from Figure 5 from the manuscript.

Usage

```
data(permutationResults)
```

scLVM_output *Output from scLVM*

Description

Objects containing the output scLVM on the single-mTEC RNA-seq data.

Usage

```
data(scLVM_output)
```

References

Buettner et al. Computational analysis of cell-to-cell heterogeneity in single-cell RNA-sequencing data reveals hidden subpopulations of cells. Nat. Biotechnol. 2015.

tras *Tissue restricted antigens lists.*

Description

Data frame containing the TRA classification from Pinto et al, 2013.

Usage

```
data(tras)
```

Index

∗ **datasets**
  aireDependentSansom, 3
  biotype, 3
  biotypesHuman, 3
  cea1Coexpression, 4
  corMatsNoMarker, 4
  deGenesNone, 5
  deGenesSansom, 5
  dxdATAC, 5
  fantom, 6
  geneNames, 6
  geneNamesHuman, 6
  geneRanges, 7
  mTECdxd, 7
  muc1Coexpression, 7
  nomarkerCellsClustering, 8
  percentsGG, 8
  permutationResults, 8
  scLVM_output, 9
  tras, 9

aireDependentSansom, 3

beta *(*scLVM_output*)*, 9
beta0 *(*scLVM_output*)*, 9
biotype, 3
biotypesHuman, 3

cea1Coexpression, 4
corMatsNoMarker, 4
corMatSp *(*corMatsNoMarker*)*, 4
corMatSpNoMarker *(*corMatsNoMarker*)*, 4

deGenesNone, 5
deGenesSansom, 5
dxd *(*mTECdxd*)*, 7
dxdATAC, 5
dxdFANTOM *(*fantom*)*, 6

fantom, 6

geneNames, 6
geneNamesHuman, 6
geneRanges, 7

h5GeneNames *(*scLVM_output*)*, 9
heter *(*scLVM_output*)*, 9

mTECdxd, 7
muc1Coexpression, 7

nomarkerCellsClustering, 8

percentsGG, 8
permsAllClusters *(*permutationResults*)*, 8
permutationResults, 8

realAllClusters *(*permutationResults*)*, 8

scLVM_output, 9
Single.mTec.Transcriptomes-package, 2

tras, 9

vars *(*scLVM_output*)*, 9

Ycorr *(*scLVM_output*)*, 9